

# JianYan Testing Group Shenzhen Co., Ltd.

Report No.: JYTSZ-R12-2301698

# **RF Exposure Evaluation Report**

**Report No.:** JYTSZ-R12-2301698

Applicant: Hangzhou Roombanker Technology Co., Ltd.

Address of Applicant: A#801 Wantong center, Hangzhou, China

**Equipment Under Test (EUT)** 

Product Name: Wall Switch

Model No.: RBAD-WS1-915, RBAD-WSx-915:(X:0~9 or X:A~Z), RBAD-

WSx-915(YY)/ZZZ:(X:0~9 or X:A~Z), (Y:0~9 or Y:A~Z)/( Z:0~9

or Z:A~Z)

Trade mark: Roombanker

FCC ID: 2AUXBRBAD-WS1915

**Applicable standards:** FCC CFR Title 47 Part 2 (§2.1091)

Date of sample receipt: 23 Nov., 2023

**Date of Test:** 24 Nov., 2023 to 22 Jan., 2024

Date of report issue: 29 Jan., 2024

Test Result: PASS

Project by: Date: 29 Jan., 2024

Reviewed by: 29 Jan., 2024

**Approved by: Date:** 29 Jan., 2024

Manager

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in above the application standard version. Test results reported herein relate only to the item(s) tested.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.





# 1 Version

Version No.	Date	Description	
00 24 Jan., 2024		Original	
01	29 Jan., 2024	Update Page 7	





# 2 Contents

		Page
Cove	r Page	1
1 V	Version	2
2 (	Contents	3
3 (	General Information	4
3.1	Client Information	4
3.2		4
3.3		4
3.4		
3.5		
3.6	S Laboratory Location	5
4	Technical Requirements Specification	6
4.1	Limits	6
4.2	Part Procedure	6
4.3	Result	7
4.4	Conclusion	7





# 3 General Information

### 3.1 Client Information

Applicant: Hangzhou Roombanker Technology Co., Ltd.		
Address: A#801 Wantong center, Hangzhou, China		
Manufacturer/ Factory:	Zhejiang dusun electron co., ltd	
Address:	No.640 Feng Qing St, DeQing Zhejiang China	

3.2 General Description of E.U.T.

Product Name:	Wall Switch			
Model No.:	RBAD-WS1-915, RBAD-WSx-915:(X:0~9 or X:A~Z), RBAD-WSx- 915(YY)/ZZZ:(X:0~9 or X:A~Z), (Y:0~9 or Y:A~Z)/( Z:0~9 or Z:A~Z)			
Operation Frequency:	SUB-G: 902MHz~928MHz			
Modulation technology:	FSK			
Antenna Type:	External Antenna			
Antenna gain:	-3.8 dBi (declare by Applicant);			
Remark?:	Model No.: RBAD-WS1-915, RBAD-WSx-915:(X:0~9 or X:A~Z), RBAD-WSx-915(YY)/ZZZ:(X:0~9 or X:A~Z), (Y:0~9 or Y:A~Z)/( Z:0~9 or Z:A~Z) were identical inside, the electrical circuit design, layout, components used and internal wiring, with only difference being model name.			
Test Sample Condition:	The test samples were provided in good working order with no visible defects.			

3.3 Operating Modes

Operating mode Detail desc		Detail description
	SUB-G mode	Keep the EUT in continuously transmitting in SUB-G mode

# 3.4 Additions to, deviations, or exclusions from the method

No



Report No.: JYTSZ-R12-2301698

# 3.5 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### FCC - Designation No.: CN1211

JianYan Testing Group Shenzhen Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

#### ● ISED - CAB identifier.: CN0021

The 3m Semi-anechoic chamber and 10m Semi-anechoic chamber of JianYan Testing Group Shenzhen Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

#### • CNAS - Registration No.: CNAS L15527

JianYan Testing Group Shenzhen Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L15527.

#### • A2LA - Registration No.: 4346.01

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: https://portal.a2la.org/scopepdf/4346-01.pdf

# 3.6 Laboratory Location

JianYan Testing Group Shenzhen Co., Ltd.

Address: No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xingiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366

Email: info-JYTee@lets.com, Website: http://jyt.lets.com

JianYan Testing Group Shenzhen Co., Ltd. Report Template No.: JYTSZ4b-177-C No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China. Tel: +86-755-23118282, Fax: +86-755-23116366



# 4 Technical Requirements Specification

### 4.1 Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)		
(A) Limits for Occupational/Controlled Exposures						
0.3–3.0 614 1.63 *(100) 6						
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6		
30–300	61.4	0.163	1.0	6		
300–1500			f/300	6		
1500–100,000			5	6		
(B) Limits for General Population/Uncontrolled Exposure						
0.3–1.34	614	1.63	*(100)	30		
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30		
30–300	27.5	0.073	0.2	30		
300–1500			f/1500	30		
1500–100,000			1.0	30		

### 4.2 Test Procedure

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna





### 4.3 Result

Frequency (MHz)	Maximum Output power (dBm)	Maximum Output power (mW)	Antenna Gain (dBi)	Antenna Gain (numeric)	Distance (cm)	Result (mW/cm²)	Limits for General Population/ Uncontrolled Exposure (mW/cm²)
SUB-G							
903	18.30	67.61	-3.8	0.42	20.00	0.0056	0.6

Note: Just the worst case mode was shown in report.

# 4.4 Conclusion

The device is exempt from the SAR test and satisfies RF exposure evaluation.

-----End of report-----