



RF Exposure Evaluation Declaration

FCC ID: DD4ULXD6X52

APPLICANT: Shure Incorporated


Application Type: Certification


Product: Wireless Boundary Transmitter

Model No.: ULXD6/C X52, ULXD6/O X52

Brand Name: SHURE

FCC Classification: Digital Transmission System (DTS)
Low Power Communication Device Transmitter (DXX)

Reviewed By : 
Manager : _____
(Robin Wu)

Approved By : 
CEO : _____
(Marlin Chen)



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
1608RSU00403	Rev. 01	Initial report	10-23-2016	Valid

1. PRODUCT INFORMATION

Product Name	Wireless Boundary Transmitter
Model No.	ULXD6/C X52, ULXD6/O X52
Frequency Range	X52 Band: 902 ~ 928 MHz
Working Mode	Normal Mode and HD Mode
Power Level	0.25mW & 10mW & 20mW
Antenna Type	PIFA
Antenna Gain	Max 0.97dBi
Components	
Rechargeable Li-ion Battery	Model: SB900A OUTPUT: 3.7Vdc, 1320mAh, 4.88Wh

Note 1: The EUT has two working modes (Normal Mode & HD Mode) and two modes can be switched from the digital wireless receiver.

Note 2: Normal mode has three power levels (0.25mW & 10mW & 20mW). Power levels are switchable among these power levels. HD mode means high density mode and it only has 0.25mW power level.

Note 3: The EUT is capable of operating with AA alkaline batteries or with the Shure SB900A rechargeable battery pack.

Note 4: The difference between ULXD6/C and ULXD6/O is that the EUT has different built-in MIC.

2. RF Exposure Evaluation

2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	f/1500	6
1500-100,000	--	--	1	30

f= Frequency in MHz

Calculation Formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2. Test Result of RF Exposure Evaluation

Product	Wireless Boundary Transmitter
Test Item	RF Exposure Evaluation

Antenna Gain: Refer to Clause 1 of antenna description.

For X52 Band:

Test Mode	Frequency Band (MHz)	Maximum Average Output Power (dBm)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)
Normal Mode HD Mode	902.4 ~ 927.6	13.35	0.0054	0.6016

CONCULISON:

Therefore, the Max Power Density at R (20 cm) = $0.0054\text{mW/cm}^2 < 0.6016\text{mW/cm}^2$.

So the EUT complies with the requirement.

_____ The End _____