

EMC TEST REPORT – 337515-2TRFWL

Applicant:

BOT Home Automation Inc.

Product name:

Ring

Model:

WL18MODGI

FCC ID:

2AEUPWL18DBMOD

IC Registration number:

20271-WL18DBMOD

Specifications:

◆ **FCC 47 CFR Part 15 Subpart E, §15.407**

Unlicensed National Information Infrastructure Devices

- §15.407(b)(1) Undesirable emission limits (Operating in the band 5.15-5.25 GHz)
- §15.407(a)(1)(ii) Power limits (Indoor access point operating in the band 5.15-5.25 GHz)

◆ **RSS-247, Issue 2, Feb 2017, Section 6**

Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices, Section 6 Technical requirements for licence-exempt local area network devices and digital transmission systems operating in the 5 GHz band

- Section 6.2.1.2 Unwanted emission limits (Operating in the band 5.15-5.25 GHz)
- Section 6.2.1.1 Power limits (Operating in the band 5.15-5.25 GHz)

Date of issue: **September 25, 2017**

Test engineer(s): **David Duchesne, Senior EMC/Wireless Specialist**

Signature:



Reviewed by: **Andrey Adelberg, Senior Wireless/EMC Specialist**

Signature:



Lab and test locations

Company name	Nemko Canada Inc.		
Facilities	Ottawa site: 303 River Road, Ottawa, ON, Canada, K1V 1H2	Montreal site: 292 Labrosse Avenue, Pointe-Claire, QC, Canada, H9R 5L8	Almonte site: 1500 Peter Robinson Road, West Carleton, ON, Canada, K0A 1L0
	Tel: +1 613 737 9680	Tel: +1 514 694 2684	Tel: +1 613 256-9117
	Fax: +1 613 737 9691	Fax: +1 514 694 3528	Fax: +1 613 256-8848
Test site registration	Organization	Recognition numbers and location	
	FCC	CA2040 (Ottawa); CA2041 (Montreal)	
	ISED	CA2040A-4 (Ottawa); CA2040G-5 (Montreal); CA2040A-3 (Almonte)	
Website	www.nemko.com		

Limits of responsibility

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contain in this report are within Nemko Canada's ISO/IEC 17025 accreditation.

Copyright notification

Nemko Canada Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties.

Nemko Canada Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

© Nemko Canada Inc.

Table of contents

Table of contents	3
Section 1. Report summary	4
1.1 Applicant and manufacturer	4
1.2 Test specifications	4
1.3 Test methods	4
1.4 Exclusions	4
1.5 Statement of compliance	4
1.6 Test report revision history	4
Section 2. Summary of test results	5
2.1 Testing period	5
2.2 FCC Part 15 Subpart E, test results	5
2.3 RSS-247, Issue 2, test results	5
Section 3. Equipment under test (EUT) details	6
3.1 Sample information	6
3.2 EUT information	6
3.3 Technical information	6
3.4 Product description and theory of operation	6
3.5 EUT exercise details	6
3.6 EUT setup diagram	7
Section 4. Engineering considerations	8
4.1 Modifications incorporated in the EUT for compliance	8
4.2 Technical judgment	8
4.3 Deviations from laboratory tests procedures	8
Section 5. Test conditions	9
5.1 Atmospheric conditions	9
5.2 Power supply range	9
Section 6. Measurement uncertainty	10
6.1 Uncertainty of measurement	10
Section 7. Test equipment	11
7.1 Test equipment list	11
Section 8. Testing data	12
8.1 FCC 15.407(b) and RSS-247 6.2.1.2 Undesirable (unwanted) emissions	12
8.2 FCC 15.407(a)(1)(ii) and RSS-247 6.2.1.1 Power limits	24
Section 9. Block diagrams of test set-ups	26
9.1 Radiated emissions set-up for frequencies below 1 GHz	26
9.2 Radiated emissions set-up for frequencies above 1 GHz	26

Section 1. Report summary

1.1 Applicant and manufacturer

Company name	BOT Home Automation Inc.
Address	1523 26 th Street, Santa Monica, California United States 90404

1.2 Test specifications

FCC 47 CFR Part 15, Subpart E, Clause 15.407	Unlicensed National Information Infrastructure Devices
RSS-247, Issue 2, Feb 2017	Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices

1.3 Test methods

789033 D02 General UNII Test Procedures New Rules v01r04 (May2, 2017)	Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices Part 15, Subpart E
662911 D01 Multiple Transmitter Output v02r01 (October 31, 2013)	Emissions Testing of Transmitters with Multiple Outputs in the Same Band
662911 D02 MIMO with Cross Polarized Antenna v01 (October 25, 2011)	Emissions testing of transmitters with multiple outputs in the same band (MIMO) with Cross Polarized Antenna
ANSI C63.10 v2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

1.4 Exclusions

As per Nemko quote Q102124338R1, the EUT was only assessed for FCC 47 CFR Part 15 Subpart E, §15.407 (b)(1), §15.407 (a)(1)(ii) and RSS-247, Issue 2, Feb 2017, Section 6.2.1.2, Section 6.2.1.1.

1.5 Statement of compliance

In the configuration tested, the EUT was found compliant.

Testing was completed against all relevant requirements of the test standard or as per detailed in the section 1.4 Exclusions above. Results obtained indicate that the product under test complies in full with the requirements tested. The test results relate only to the items tested.

See "Summary of test results" for full details.

1.6 Test report revision history

Table 1.6-1: Test report revision history

Revision #	Date of issue	Details of changes made to test report
TRF	September 25, 2017	Original report issued

Section 2. Summary of test results

2.1 Testing period

Test start date	September 14, 2017
Test end date	September 14, 2017

2.2 FCC Part 15 Subpart E, test results

Table 2.2-1: Result summary for §15.407

Part	Test description	Verdict
§15.407(a)(1)(ii)	Power limits (Indoor access point operating in the band 5.15-5.25 GHz)	Pass
§15.407(b)(1)	Undesirable emission limits (Operating in the band 5.15-5.25 GHz)	Pass
Notes:	None	

2.3 RSS-247, Issue 2, test results

Table 2.3-1: Result summary for RSS-247 Part 6.2.1.2

Section	Test description	Verdict
6.2.1.1	Power limits (Operating in the band 5.15-5.25 GHz)	Pass
6.2.1.2	Unwanted emission limits (Operating in the band 5.15-5.25 GHz)	Pass
Notes:	None	

Section 3. Equipment under test (EUT) details

3.1 Sample information

Receipt date	August 21, 2017
Nemko sample ID number	Item # 3

3.2 EUT information

Product name	Ring
Model	WL18MODGI
Serial number	BHHB11731PG000029

3.3 Technical information

Applicant IC company number	20271
IC UPN number	WL18DBMOD
All used IC test site(s) Reg. number	2040A-4
RSS number and Issue number	RSS-247 Issue 2, Section 6, February 2017
Frequency band	5.15–5.25 GHz
Type of modulation	802.11a, 802.11n HT20, 802.11n HT40
Emission classification (F1D, G1D, D1D)	W7D
Transmitter spurious, Units @ distance	66.1 dBμV/m peak and 52.9 dBμV/m average at 5.15 GHz @ 3m
Power requirements	5 V _{DC} (via external 100-240 VAC, 50/60 Hz power adapter)
Antenna information	Antenna gain: is 4.6 dBi (WI-FI Right side) and 4.6 dBi (WI-FI left side) Inverted F The EUT uses a unique antenna coupling/ non-detachable antenna to the intentional radiator.

3.4 Product description and theory of operation

Communications Hub for Home Security Products

3.5 EUT exercise details

The EUT was setup in continuous transmit state.

3.6 EUT setup diagram




Figure 3.6-1: Setup diagram

Section 4. Engineering considerations

4.1 Modifications incorporated in the EUT for compliance

There were no modifications performed to the EUT during this assessment.

4.2 Technical judgment

None

4.3 Deviations from laboratory tests procedures

No deviations were made from laboratory procedures.

Section 5. Test conditions

5.1 Atmospheric conditions

Temperature	15–30 °C
Relative humidity	20–75 %
Air pressure	86–106 kPa

When it is impracticable to carry out tests under these conditions, a note to this effect stating the ambient temperature and relative humidity during the tests shall be recorded and stated.

5.2 Power supply range

The normal test voltage for equipment to be connected to the mains shall be the nominal mains voltage. For the purpose of the present document, the nominal voltage shall be the declared voltage, or any of the declared voltages $\pm 5\%$, for which the equipment was designed.

Section 6. Measurement uncertainty

6.1 Uncertainty of measurement

UKAS Lab 34 and TIA-603-B have been used as guidance for measurement uncertainty reasonable estimations with regards to previous experience and validation of data. Nemko Canada, Inc. follows these test methods in order to satisfy ISO/IEC 17025 requirements for estimation of uncertainty of measurement for wireless products.

Measurement uncertainty budgets for the tests are detailed below. Measurement uncertainty calculations assume a coverage factor of $K = 2$ with 95% certainty.

Test name	Measurement uncertainty, dB
Radiated spurious emissions	3.78

Section 7. Test equipment

7.1 Test equipment list

Table 7.1-1: Equipment list

Equipment	Manufacturer	Model no.	Asset no.	Cal cycle	Next cal.
Receiver/spectrum analyzer	Rohde & Schwarz	ESU 26	FA002043	1 year	Jan. 31/18
Spectrum analyzer	Rohde & Schwarz	FSU	FA001877	1 year	Jul. 18/18
3 m EMI test chamber	TDK	SAC-3	FA002047	1 year	Dec. 1/17
Horn with Preamp	ETS-Lindgren	3117-PA	FA002840	1 year	Nov. 11/17
Bilog antenna (20–3000 MHz)	Sunol	JB3	FA002108	1 year	June 27/18
Horn antenna (18–40 GHz)	EMCO	3116	FA001847	1 year	June 27/18
Pre-amplifier (18–26 GHz)	Narda	BBS-1826N612	FA001550	—	VOU
Pre-amplifier (26–40 GHz)	Narda	DBL-2640N610	FA001556	—	VOU
50 Ω coax cable	Huber + Suhner	None	FA002830	1 year	May 12/18
50 Ω coax cable	C.C.A.	None	FA002555	1 year	May 2/18
Notch filter 5150–5350 MHz	Microwave Circuits	5150–5350 MHz	FA001941	—	VOU

Notes: NCR - no calibration required, VOU - verify on use

Section 8. Testing data

8.1 FCC 15.407(b) and RSS-247 6.2.1.2 Undesirable (unwanted) emissions

8.1.1 Definitions and limits

FCC §15.407 (b):

- (1) For transmitters operating in the 5.15–5.25 GHz band: all emissions outside of the 5.15–5.35 GHz band shall not exceed an EIRP of –27 dBm/MHz.
- (5) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.
- (6) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in § 15.209.
- (7) The provisions of § 15.205 apply to intentional radiators operating under this section.
- (8) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the upper and lower frequency block edges as the design of the equipment permits.

RSS-247 Section 6.2.1.2:

For transmitters operating in the band 5150–5250 MHz, all emissions outside the band 5150–5350 MHz shall not exceed –27 dBm/MHz e.i.r.p. However, any unwanted emissions that fall into the band 5250–5350 MHz must be 26 dBc, when measured using a resolution bandwidth between 1 and 5% of the occupied bandwidth, above 5.25 GHz. Otherwise, the transmission is considered as intentional and the devices shall implement dynamic frequency selection (DFS) and transmitter power control (TPC) as per the requirements for the band 5250–5350 MHz.

RSS-Gen Section 8.10:

Restricted bands, identified in table 6 of RSS-Gen Section 8.10, are designated primarily for safety-of-life services (distress calling and certain aeronautical bands), certain satellite downlinks, radio astronomy and some government uses. Except where otherwise indicated, the following restrictions apply:

- a. fundamental components of modulation of licence-exempt radio apparatus shall not fall within the restricted bands of below;
- b. unwanted emissions falling into restricted bands of below shall comply with the limits specified in RSS-Gen;
- c. unwanted emissions not falling within restricted frequency bands shall either comply with the limits specified in the applicable RSS, or with those specified in RSS-Gen.

8.1.1 Definitions and limits, continued

Table 8.1-1: FCC §15.209 and RSS-Gen – Radiated emission limits

Frequency, MHz	Field strength of emissions		Measurement distance, m
	μV/m	dBμV/m	
0.009–0.490	2400/F	$67.6 - 20 \times \log_{10}(F)$	300
0.490–1.705	24000/F	$87.6 - 20 \times \log_{10}(F)$	30
1.705–30.0	30	29.5	30
30–88	100	40.0	3
88–216	150	43.5	3
216–960	200	46.0	3
above 960	500	54.0	3

Notes: In the emission table above, the tighter limit applies at the band edges.
For frequencies above 1 GHz the limit on peak RF emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test

Table 8.1-2: ISED restricted frequency bands

MHz	MHz	MHz	GHz
0.090–0.110	12.51975–12.52025	399.9–410	5.35–5.46
2.1735–2.1905	12.57675–12.57725	608–614	7.25–7.75
3.020–3.026	13.36–13.41	960–1427	8.025–8.5
4.125–4.128	16.42–16.423	1435–1626.5	9.0–9.2
4.17725–4.17775	16.69475–16.69525	1645.5–1646.5	9.3–9.5
4.20725–4.20775	16.80425–16.80475	1660–1710	10.6–12.7
5.677–5.683	25.5–25.67	1718.8–1722.2	13.25–13.4
6.215–6.218	37.5–38.25	2200–2300	14.47–14.5
6.26775–6.26825	73–74.6	2310–2390	15.35–16.2
6.31175–6.31225	74.8–75.2	2655–2900	17.7–21.4
8.291–8.294	108–138	3260–3267	22.01–23.12
8.362–8.366	156.52475–156.52525	3332–3339	23.6–24.0
8.37625–8.38675	156.7–156.9	3345.8–3358	31.2–31.8
8.41425–8.41475	240–285	3500–4400	36.43–36.5
12.29–12.293	322–335.4	4500–5150	Above 38.6

Notes: None

Table 8.1-3: FCC restricted frequency bands

MHz	MHz	MHz	GHz
0.090–0.110	16.42–16.423	399.9–410	4.5–5.15
0.495–0.505	16.69475–16.69525	608–614	5.35–5.46
2.1735–2.1905	16.80425–16.80475	960–1240	7.25–7.75
4.125–4.128	25.5–25.67	1300–1427	8.025–8.5
4.17725–4.17775	37.5–38.25	1435–1626.5	9.0–9.2
4.20725–4.20775	73–74.6	1645.5–1646.5	9.3–9.5
6.215–6.218	74.8–75.2	1660–1710	10.6–12.7
6.26775–6.26825	108–121.94	1718.8–1722.2	13.25–13.4
6.31175–6.31225	123–138	2200–2300	14.47–14.5
8.291–8.294	149.9–150.05	2310–2390	15.35–16.2
8.362–8.366	156.52475–156.52525	2483.5–2500	17.7–21.4
8.37625–8.38675	156.7–156.9	2690–2900	22.01–23.12
8.41425–8.41475	162.0125–167.17	3260–3267	23.6–24.0
12.29–12.293	167.72–173.2	3332–3339	31.2–31.8
12.51975–12.52025	240–285	3345.8–3358	36.43–36.5
12.57675–12.57725	322–335.4	3600–4400	Above 38.6
13.36–13.41			

Notes: None

8.1.2 Test summary

Verdict	Pass		
Test date	September 14, 2017	Temperature	23.5 °C
Test engineer	David Duchesne	Air pressure	995 mbar
Test location	Ottawa	Relative humidity	53.7 %

8.1.3 Observations, settings and special notes

- The spectrum was searched from 30 MHz to 40 GHz.
- The spectral plots have been corrected with the associated transducer factors (i.e. antenna factors, cable loss, amplifier gains, and attenuators).
- Radiated measurements were performed at a distance of 3 m.
- The EUT was tested configured with 802.11a, Data rate 6 Mbps as it was deemed worst case.

Spectrum analyser settings for radiated measurements within restricted bands below 1 GHz:

Resolution bandwidth:	100 kHz
Video bandwidth:	300 kHz
Detector mode:	Peak
Trace mode:	Max Hold

Spectrum analyser settings for radiated measurements above 1 GHz:

Resolution bandwidth:	1 MHz
Video bandwidth:	3 MHz
Detector mode:	Peak
Trace mode:	Max Hold

Spectrum analyser for average radiated measurements within restricted bands above 1 GHz for frequencies where peak results were above the average limit:

Resolution bandwidth:	1 MHz
Video bandwidth:	10 MHz
Detector mode:	RMS
Trace mode:	Power average
Number of averaging traces:	100

8.1.4 Test data




Figure 8.1-1: Radiated – Undesirable (unwanted) emissions within restricted band at 5.15 GHz, peak (Channel 36 – 5180 MHz)




Figure 8.1-2: Radiated – Undesirable (unwanted) emissions within restricted band at 5.15 GHz, Average (Channel 36 – 5180 MHz)




Figure 8.1-3: Radiated – Undesirable (unwanted) emissions at upper band edge, peak (Channel 48 – 5240 MHz)

Table 8.1-4: Radiated – Undesirable (unwanted) emissions that fall within restricted band

Channel	Frequency, GHz	Peak Field strength, dBμV/m		Margin, dB	Average Field strength, dBμV/m		Margin, dB
		Measured	Limit		Measured	Limit	
36	5.15	66.1	74.0	7.9	52.9	54.0	1.1

Notes: Field strength includes correction factor of antenna, cable loss, amplifier, and attenuators where applicable.

Table 8.1-5: Radiated – Undesirable (unwanted) emissions that fall outside the band not within restricted bands for RSS

Channel	Frequency, GHz	Peak field strength, dBμV/m	Peak field strength of Tx Fund. ¹ , dBμV/m	Attenuation below Tx Fund., dB	Minimum limit, dB	Margin, dB
48	5.250	66.1	115.4	49.3	26	23.3

Notes: Field strength includes correction factor of antenna, cable loss, amplifier, and attenuators where applicable.

¹E.i.r.p. of fundamental was 20.2 dBm (See e.i.r.p. from Table 8.2-1 of this report) = 115.4 dBμV/m at 3m (20.2 dBm/MHz. +95.2 dB)

8.1.4 Test data, continued




Figure 8.1-4: Radiated – Undesirable (unwanted) emissions below 1 GHz, Channel 36 – 5180 MHz




Figure 8.1-5: Radiated – Undesirable (unwanted) emissions below 1 GHz, Channel 44 – 5220 MHz

8.1.4 Test data, continued




Figure 8.1-6: Radiated – Undesirable (unwanted) emissions below 1 GHz, Channel 48 – 5240 MHz




Figure 8.1-7: Radiated – Undesirable (unwanted) emissions 1 to 18 GHz, Channel 36 – 5180 MHz

8.1.4 Test data, continued




Figure 8.1-8: Radiated – Undesirable (unwanted) emissions 1 to 18 GHz, Channel 44 – 5220 MHz




Figure 8.1-9: Radiated – Undesirable (unwanted) emissions 1 to 18 GHz, Channel 48 – 5240 MHz

8.1.5 Test data, continued




Figure 8.1-10: Radiated – Undesirable (unwanted) emissions 18 to 26 GHz, Channel 36 – 5180 MHz




Figure 8.1-11: Radiated – Undesirable (unwanted) emissions 18 to 26 GHz, Channel 44 – 5220 MHz

8.1.4 Test data, continued




Figure 8.1-12: Radiated – Undesirable (unwanted) emissions 18 to 26 GHz, Channel 48 – 5240 MHz




Figure 8.1-13: Radiated – Undesirable (unwanted) emissions 26 to 40 GHz, Channel 36 – 5180 MHz

8.1.4 Test data, continued




Figure 8.1-14: Radiated – Undesirable (unwanted) emissions 26 to 40 GHz, Channel 44 – 5220 MHz




Figure 8.1-15: Radiated – Undesirable (unwanted) emissions 26 to 40 GHz, Channel 48 – 5240 MHz

8.1.5 Setup photos




Figure 8.1-16: Radiated – Undesirable (unwanted) emissions setup photo – below 1 GHz



Figure 8.1-17: Radiated – Undesirable (unwanted) emissions setup photo – below 1 GHz

8.1.6 Setup photos, continued



Figure 8.1-18: Radiated – Undesirable (unwanted) emissions setup photo – above 1 GHz



Figure 8.1-19: Radiated – Undesirable (unwanted) emissions setup photo – above 1 GHz

8.2 FCC 15.407(a)(1)(ii) and RSS-247 6.2.1.1 Power limits

8.2.1 Definitions and limits

FCC §15.407:

(a) *Power limits:*

- (1) For the band 5.15-5.25 GHz.
- (ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

RSS-247 Section 6.2.1.1:

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or $1.76 + 10 \log_{10} B$, dBm, whichever is less. Devices shall implement transmitter power control (TPC) in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

For other devices, the maximum e.i.r.p. shall not exceed 200 mW or $10 + 10 \log_{10} B$, dBm, whichever power is less. B is the 99% emission bandwidth in megahertz. The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.

8.2.2 Test summary

Verdict	Pass
---------	------

8.2.3 Observations, settings and special notes

Measurement data was taken from Sporton Report No.: FR4O0971D, Form FCC ID: Z64-WL18DBMOD. Client has changed the antenna; new calculations have been performed to demonstrate continued compliance.

8.2.4 Test data

Table 8.2-1: Power and EIRP results for FCC

Mod	Data rate	Chn.	Freq., MHz	Average conducted Power, dBm		Conducted power limit, dBm		Margin, dB		Antenna gain, dBi		e.i.r.p., dBm		e.i.r.p. limit, dBm		e.i.r.p. margin, dBm	
				Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2
11a	6 Mbps	36	5180	15.54	15.71	24.00	24.00	8.46	8.29	4.60	4.60	20.14	20.31	30.00	30.00	9.86	9.69
11a	6 Mbps	44	5220	15.58	15.82	24.00	24.00	8.42	8.18	4.60	4.60	20.18	20.42	30.00	30.00	9.82	9.58
11a	6 Mbps	48	5240	15.4	15.56	24.00	24.00	8.60	8.44	4.60	4.60	20.00	20.16	30.00	30.00	10.00	9.84
HT20	MCS0	36	5180	15.71	15.54	24.00	24.00	8.29	8.46	4.60	4.60	20.31	20.14	30.00	30.00	9.69	9.86
HT20	MCS0	44	5220	15.35	15.53	24.00	24.00	8.65	8.47	4.60	4.60	19.95	20.13	30.00	30.00	10.05	9.87
HT20	MCS0	48	5240	15.28	15.48	24.00	24.00	8.72	8.52	4.60	4.60	19.88	20.08	30.00	30.00	10.12	9.92
HT40	MCS0	38	5190	11.48	11.76	24.00	24.00	12.52	12.24	4.60	4.60	16.08	16.36	30.00	30.00	13.92	13.64
HT40	MCS0	46	5230	16.6	16.98	24.00	24.00	7.40	7.02	4.60	4.60	21.20	21.58	30.00	30.00	8.80	8.42

Notes: None

Table 8.2-2: Power and EIRP results for RSS

Mod	Data rate	Chn.	Freq., MHz	Average conducted Power, dBm		Antenna gain, dBi		e.i.r.p., dBm		e.i.r.p. limit ¹ , dBm		e.i.r.p. margin, dBm	
				Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2
11a	6 Mbps	36	5180	15.54	15.71	4.60	4.60	20.14	20.31	22.50	22.50	2.36	2.19
11a	6 Mbps	44	5220	15.58	15.82	4.60	4.60	20.18	20.42	22.47	22.47	2.29	2.05
11a	6 Mbps	48	5240	15.4	15.56	4.60	4.60	20.00	20.16	22.64	22.64	2.64	2.48
HT20	MCS0	36	5180	15.71	15.54	4.60	4.60	20.31	20.14	22.67	22.67	2.36	2.53
HT20	MCS0	44	5220	15.35	15.53	4.60	4.60	19.95	20.13	22.66	22.66	2.71	2.53
HT20	MCS0	48	5240	15.28	15.48	4.60	4.60	19.88	20.08	22.70	22.70	2.82	2.62
HT40	MCS0	38	5190	11.48	11.76	4.60	4.60	16.08	16.36	23.00	23.00	6.92	6.64
HT40	MCS0	46	5230	16.6	16.98	4.60	4.60	21.20	21.58	23.00	23.00	1.80	1.42

Notes: ¹ The maximum e.i.r.p. shall not exceed 200 mW or 10 + 10 log10B, dBm, whichever power is less. B is the 99% emission bandwidth in megahertz.


Table 8.2-3: EIRP PSD results for RSS

Mod	Data rate	Chn.	Freq., MHz	Average Power density, dBm/MHz (Ant 2)	Antenna gain, dBi (Ant 2)	Average PSD e.i.r.p, dBm/MHz (Ant 2)	Average PSD limit, e.i.r.p. dBm/MHz (Ant2)	margin, dB (Ant 2)
11a	6 Mbps	36	5180	5.17	4.60	9.77	10.00	0.23
11a	6 Mbps	44	5220	5.35	4.60	9.95	10.00	0.05
11a	6 Mbps	48	5240	5.18	4.60	9.78	10.00	0.22
HT20	MCS0	36	5180	4.81	4.60	9.41	10.00	0.59
HT20	MCS0	44	5220	5.36	4.60	9.96	10.00	0.04
HT20	MCS0	48	5240	4.93	4.60	9.53	10.00	0.47
HT40	MCS0	38	5190	-3.04	4.60	1.56	10.00	8.44
HT40	MCS0	46	5230	3.51	4.60	8.11	10.00	1.89

Notes: None

Section 9. Block diagrams of test set-ups

9.1 Radiated emissions set-up for frequencies below 1 GHz



9.2 Radiated emissions set-up for frequencies above 1 GHz

