

TEST REPORT

Applicant: Zhejiang Hanshow Technology Co., Ltd.

Address of Applicant: Bld. 33, No. 966 xiuyuan Rd., BeiKeJian Innovation Park,
XiuZhou District, Jiaxing, Zhejiang, China

Manufacturer/Factory: Zhejiang Hanshow Technology Co., Ltd.

**Address of
Manufacturer/Factory:** Bld. 33, No. 966 xiuyuan Rd., BeiKeJian Innovation Park,
XiuZhou District, Jiaxing, Zhejiang, China

Equipment Under Test (EUT)

Product Name: ESL Controller

Model No.: HS_C09959, HS_C09989

FCC ID: 2AHB5-C09959

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.249

Date of sample receipt: May 28, 2020

Date of Test: May 29, 2020-June 05, 2020

Date of report issued: June 05, 2020

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

A circular blue ink stamp from GTS (Global United Technology Services) is visible. The stamp contains the text "GTS", "GLOBAL UNITED TECHNOLOGY SERVICES", and "EST. 2010". Overlaid on the stamp is a handwritten signature in black ink, which appears to read "Robinson Lo". To the right of the signature, the word "June" is handwritten.

Robinson Lo
Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	June 05, 2020	Original

Prepared By:




Date:

June 05, 2020

Project Engineer

Check By:



Date:

June 05, 2020

Reviewer

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS	3
4 TEST SUMMARY	4
4.1 MEASUREMENT UNCERTAINTY	4
5 GENERAL INFORMATION.....	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	7
5.3 DESCRIPTION OF SUPPORT UNITS	7
5.4 DEVIATION FROM STANDARDS.....	7
5.5 ABNORMALITIES FROM STANDARD CONDITIONS	7
5.6 TEST FACILITY.....	8
5.7 TEST LOCATION	8
5.8 ADDITIONAL INSTRUCTIONS.....	8
6 TEST INSTRUMENTS LIST	9
7 TEST RESULTS AND MEASUREMENT DATA.....	11
7.1 ANTENNA REQUIREMENT.....	11
7.2 CONDUCTED EMISSIONS	12
7.3 RADIATED EMISSION METHOD.....	15
7.3.1 <i>Field Strength of The Fundamental Signal</i>	17
7.3.2 <i>Spurious emissions</i>	21
7.3.3 <i>Bandedge emissions</i>	47
7.4 20dB OCCUPY BANDWIDTH	63
8 TEST SETUP PHOTO.....	66
9 EUT CONSTRUCTIONAL DETAILS	66

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	Pass
Field strength of the fundamental signal	15.249 (a)	Pass
Spurious emissions	15.249 (a) (d)/15.209	Pass
Band edge	15.249 (d)/15.205	Pass
20dB Occupied Bandwidth	15.215 (c)	Pass

Remarks:

1. Test according to ANSI C63.10: 2013.
2. Pass: The EUT complies with the essential requirements in the standard.

4.1 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	30MHz-200MHz	3.8039dB	(1)
Radiated Emission	200MHz-1GHz	3.9679dB	(1)
Radiated Emission	1GHz-18GHz	4.29dB	(1)
Radiated Emission	18GHz-40GHz	3.30dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	3.44dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

5 General Information

5.1 General Description of EUT

Product Name:	ESL Controller
Model No.:	HS_C09959, HS_C09989
Test Model No:	HS_C09959
Serial No.:	907012001593871513
Hardware Version:	HS_C09959_V1_1_1
Software Version:	6.1.17
Test sample(s) ID:	GTS202005000207-1
Sample(s) Status	Engineered sample
Operation Frequency:	2402MHz~2480MHz
Channel numbers:	157
Channel separation:	0.5MHz
Modulation type:	GFSK
Antenna Type:	Omni-directional Antenna
Antenna gain:	2dBi(declare by applicant)
Power supply:	AC Adapter Model: SWI12-12-N Input: AC 100-240V, 50-60Hz, 0.31A max Output: DC 12.0V, 1.0A, 12.0W MAX

Operation Frequency each of channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2402.0	41	2422.0	81	2442.0	121	2462.0
2	2402.5	42	2422.5	82	2442.5	122	2462.5
3	2403.0	43	2423.0	83	2443.0	123	2463.0
4	2403.5	44	2423.5	84	2443.5	124	2463.5
5	2404.0	45	2424.0	85	2444.0	125	2464.0
6	2404.5	46	2424.5	86	2444.5	126	2464.5
7	2405.0	47	2425.0	87	2445.0	127	2465.0
8	2405.5	48	2425.5	88	2445.5	128	2465.5
9	2406.0	49	2426.0	89	2446.0	129	2466.0
10	2406.5	50	2426.5	90	2446.5	130	2466.5
11	2407.0	51	2427.0	91	2447.0	131	2467.0
12	2407.5	52	2427.5	92	2447.5	132	2467.5
13	2408.0	53	2428.0	93	2448.0	133	2468.0
14	2408.5	54	2428.5	94	2448.5	134	2468.5
15	2409.0	55	2429.0	95	2449.0	135	2469.0
16	2409.5	56	2429.5	96	2449.5	136	2469.5
17	2410.0	57	2430.0	97	2450.0	137	2470.0
18	2410.5	58	2430.5	98	2450.5	138	2470.5
19	2411.0	59	2431.0	99	2451.0	139	2471.0
20	2411.5	60	2431.5	100	2451.5	140	2471.5
21	2412.0	61	2432.0	101	2452.0	141	2472.0
22	2412.5	62	2432.5	102	2452.5	142	2472.5
23	2413.0	63	2433.0	103	2453.0	143	2473.0
24	2413.5	64	2433.5	104	2453.5	144	2473.5
25	2414.0	65	2434.0	105	2454.0	145	2474.0
26	2414.5	66	2434.5	106	2454.5	146	2474.5
27	2415.0	67	2435.0	107	2455.0	147	2475.0
28	2415.5	68	2435.5	108	2455.5	148	2475.5
29	2416.0	69	2436.0	109	2456.0	149	2476.0
30	2416.5	70	2436.5	110	2456.5	150	2476.5
31	2417.0	71	2437.0	111	2457.0	151	2477.0
32	2417.5	72	2437.5	112	2457.5	152	2477.5
33	2418.0	73	2438.0	113	2458.0	153	2478.0
34	2418.5	74	2438.5	114	2458.5	154	2478.5
35	2419.0	75	2439.0	115	2459.0	155	2479.0
36	2419.5	76	2439.5	116	2459.5	156	2479.5
37	2420.0	77	2440.0	117	2460.0	157	2480.0
38	2420.5	78	2440.5	118	2460.5		
39	2421.0	79	2441.0	119	2461.0		
40	2421.5	80	2441.5	120	2461.5		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
<i>Remark: During the test, the dutycycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i>	

Per-test mode.

We have verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which was shown in this test report and defined as follows:

Axis	X	Y	Z
Field Strength(dBuV/m)	96.13	97.17	96.08

5.3 Description of Support Units

None.

5.4 Deviation from Standards

None.

5.5 Abnormalities from Standard Conditions

None.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC —Registration No.: 381383**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383.

- **IC —Registration No.: 9079A**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A

- **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP). LAB CODE:600179-0

5.7 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

Address: No. 123- 128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102

Tel: 0755-27798480

Fax: 0755-27798960

5.8 Additional Instructions

Test Software	Special test command provided by manufacturer
Power level setup	Default

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 03 2015	July. 02 2020
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 26 2019	June. 25 2020
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 26 2019	June. 25 2020
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June. 26 2019	June. 25 2020
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 26 2019	June. 25 2020
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 26 2019	June. 25 2020
9	Coaxial Cable	GTS	N/A	GTS211	June. 26 2019	June. 25 2020
10	Coaxial cable	GTS	N/A	GTS210	June. 26 2019	June. 25 2020
11	Coaxial Cable	GTS	N/A	GTS212	June. 26 2019	June. 25 2020
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 26 2019	June. 25 2020
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	June. 26 2019	June. 25 2020
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 26 2019	June. 25 2020
15	Band filter	Amindeon	82346	GTS219	June. 26 2019	June. 25 2020
16	Power Meter	Anritsu	ML2495A	GTS540	June. 26 2019	June. 25 2020
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 26 2019	June. 25 2020
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	June. 26 2019	June. 25 2020
19	Splitter	Agilent	11636B	GTS237	June. 26 2019	June. 25 2020
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 26 2019	June. 25 2020
21	Breitband hornantenne	SCHWARZBECK	BBHA 9170	GTS579	Oct. 19 2019	Oct. 18 2020
22	Amplifier	TDK	PA-02-02	GTS574	Oct. 19 2019	Oct. 18 2020
23	Amplifier	TDK	PA-02-03	GTS576	Oct. 19 2019	Oct. 18 2020
24	PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	GTS578	June. 26 2019	June. 25 2020

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May.15 2019	May.14 2022
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 26 2019	June. 25 2020
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June. 26 2019	June. 25 2020
4	ENV216 2-L-V-NETZNACHB.DE	ROHDE&SCHWARZ	ENV216	GTS226	June. 26 2019	June. 25 2020
5	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	KTJ	TA328	GTS233	June. 26 2019	June. 25 2020
8	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	June. 26 2019	June. 25 2020
9	ISN	SCHWARZBECK	NTFM 8158	GTD565	June. 26 2019	June. 25 2020

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	June. 26 2019	June. 25 2020
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 26 2019	June. 25 2020
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June. 26 2019	June. 25 2020
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	June. 26 2019	June. 25 2020
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	June. 26 2019	June. 25 2020
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	June. 26 2019	June. 25 2020
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	June. 26 2019	June. 25 2020
8	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	June. 26 2019	June. 25 2020


General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Humidity/ Temperature Indicator	KTJ	TA328	GTS243	June. 26 2019	June. 25 2020
2	Barometer	ChangChun	DYM3	GTS255	June. 26 2019	June. 25 2020

7 Test results and Measurement Data

7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
EUT Antenna:	
<i>The antenna is omni-directional antenna, the best case gain of the antenna is 2dBi, reference to the appendix II for details.</i>	


7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207						
Test Method:	ANSI C63.10:2013						
Test Frequency Range:	150KHz to 30MHz						
Class / Severity:	Class B						
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto						
Limit:	Frequency range (MHz)		Limit (dBuV)				
			Quasi-peak		Average		
	0.15-0.5		66 to 56*		56 to 46*		
	0.5-5		56		46		
	5-30		60		50		
	* Decreases with the logarithm of the frequency.						
Test setup:	Reference Plane  <i>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</i>						
Test procedure:	1. The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.						
Test Instruments:	Refer to section 6.0 for details						
Test mode:	Refer to section 5.2 for details						
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar	
Test voltage:	AC 120V, 60Hz						
Test results:	Pass						

Remark: Both AC 120V and 240V were test, only the worst condition AC 120V report.


Measurement data

Line:



Freq MHz	Reading level dBuV	LISN/ISN factor dB/m	Cable loss dB	Level dBuV	Limit level dBuV	Over limit dB	Remark
0.17	14.36	20.40	0.08	34.84	65.16	-30.32	QP
0.17	-2.33	20.40	0.08	18.15	55.16	-37.01	Average
0.40	13.16	20.35	0.11	33.62	57.81	-24.19	QP
0.40	-5.01	20.35	0.11	15.45	47.81	-32.36	Average
0.63	15.52	20.28	0.12	35.92	56.00	-20.08	QP
0.63	7.26	20.28	0.12	27.66	46.00	-18.34	Average
2.18	7.68	20.20	0.18	28.06	56.00	-27.94	QP
2.18	0.14	20.20	0.18	20.52	46.00	-25.48	Average
3.55	11.47	20.20	0.18	31.85	56.00	-24.15	QP
3.55	5.60	20.20	0.18	25.98	46.00	-20.02	Average
11.93	15.37	20.20	0.20	35.77	60.00	-24.23	QP
11.93	10.96	20.20	0.20	31.36	50.00	-18.64	Average

Neutral:






Freq MHz	Reading level dBuV	LISN/ISN factor dB/m	Cable loss dB	Level dBuV	Limit level dBuV	Over limit dB	Remark
0.17	17.25	20.40	0.09	37.74	64.94	-27.20	QP
0.17	-3.23	20.40	0.09	17.26	54.94	-37.68	Average
0.24	11.57	20.40	0.11	32.08	62.26	-30.18	QP
0.24	2.02	20.40	0.11	22.53	52.26	-29.73	Average
0.63	15.51	20.28	0.12	35.91	56.00	-20.09	QP
0.63	7.22	20.28	0.12	27.62	46.00	-18.38	Average
2.18	8.52	20.20	0.18	28.90	56.00	-27.10	QP
2.18	0.58	20.20	0.18	20.96	46.00	-25.04	Average
9.01	19.03	20.20	0.20	39.43	60.00	-20.57	QP
9.01	6.20	20.20	0.20	26.60	50.00	-23.40	Average
22.06	14.83	20.32	0.23	35.38	60.00	-24.62	QP
22.06	8.76	20.32	0.23	29.31	50.00	-20.69	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

7.3 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	9kHz-150kHz	Quasi-peak	200Hz	300Hz	Quasi-peak Value
	150kHz-30MHz	Quasi-peak	9kHz	10kHz	Quasi-peak Value
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
Peak		1MHz	10Hz	Average Value	
Limit: (Field strength of the fundamental signal)	Frequency		Limit (dBuV/m @3m)		Remark
	2400MHz-2483.5MHz		94.00		Average Value
			114.00		Peak Value
Limit: (Spurious Emissions)	Frequency		Limit (uV/m)		Remark
	0.009MHz-0.490MHz		2400/F(kHz) @300m		Quasi-peak Value
	0.490MHz-1.705MHz		24000/F(kHz) @30m		Quasi-peak Value
	1.705MHz-30.0MHz		30 @30m		Quasi-peak Value
	30MHz-88MHz		100 @3m		Quasi-peak Value
	88MHz-216MHz		150 @3m		Quasi-peak Value
	216MHz-960MHz		200 @3m		Quasi-peak Value
	960MHz-1GHz		500 @3m		Quasi-peak Value
	Above 1GHz		500 @3m		Average Value
Limit: (band edge)			5000 @3m		Peak Value
	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.				
Test setup:	For radiated emissions from 9kHz to 30MHz				
					
	For radiated emissions from 30MHz to 1GHz				

	Report No.: CTS20000002017-01  For radiated emissions above 1GHz 					
Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8m for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Remark: Both AC 120V and 240V were test, only the worst condition AC 120V report.

Measurement data:
7.3.1 Field Strength of The Fundamental Signal
ANT 1:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Remark	polarization
2402.00	95.49	27.41	2.91	36.86	88.95	94.00	-5.05	Average	Horizontal
2402.00	100.68	27.41	2.91	36.86	94.14	114.00	-19.86	Peak	Horizontal
2402.00	82.35	27.41	2.91	36.86	75.81	94.00	-18.19	Average	Vertical
2402.00	88.72	27.41	2.91	36.86	82.18	114.00	-31.82	Peak	Vertical

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Remark	polarization
2441.00	97.28	27.53	2.96	36.89	90.88	94.00	-3.12	Average	Horizontal
2441.00	103.57	27.53	2.96	36.89	97.17	114.00	-16.83	Peak	Horizontal
2441.00	83.15	27.53	2.96	36.89	76.75	94.00	-17.25	Average	Vertical
2441.00	90.32	27.53	2.96	36.89	83.92	114.00	-30.08	Peak	Vertical

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Remark	polarization
2480.00	93.71	27.64	2.99	36.92	87.42	94.00	-6.58	Average	Horizontal
2480.00	101.55	27.64	2.99	36.92	95.26	114.00	-18.74	Peak	Horizontal
2480.00	83.19	27.64	2.99	36.92	76.90	94.00	-17.10	Average	Vertical
2480.00	90.94	27.64	2.99	36.92	84.65	114.00	-29.35	Peak	Vertical

ANT 2:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Remark	polarization
2402.00	89.76	27.41	2.91	36.86	83.22	94.00	-10.78	Average	Horizontal
2402.00	95.13	27.41	2.91	36.86	88.59	114.00	-25.41	Peak	Horizontal
2402.00	81.85	27.41	2.91	36.86	75.31	94.00	-18.69	Average	Vertical
2402.00	88.10	27.41	2.91	36.86	81.56	114.00	-32.44	Peak	Vertical

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Remark	polarization
2441.00	95.76	27.53	2.96	36.89	89.36	94.00	-4.64	Average	Horizontal
2441.00	102.15	27.53	2.96	36.89	95.75	114.00	-18.25	Peak	Horizontal
2441.00	86.18	27.53	2.96	36.89	79.78	94.00	-14.22	Average	Vertical
2441.00	92.84	27.53	2.96	36.89	86.44	114.00	-27.56	Peak	Vertical

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Remark	polarization
2480.00	95.35	27.64	2.99	36.92	89.06	94.00	-4.94	Average	Horizontal
2480.00	102.11	27.64	2.99	36.92	95.82	114.00	-18.18	Peak	Horizontal
2480.00	86.09	27.64	2.99	36.92	79.80	94.00	-14.20	Average	Vertical
2480.00	92.14	27.64	2.99	36.92	85.85	114.00	-28.15	Peak	Vertical

ANT 3:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Remark	polarization
2402.00	89.78	27.41	2.91	36.86	83.24	94.00	-10.76	Average	Horizontal
2402.00	95.19	27.41	2.91	36.86	88.65	114.00	-25.35	Peak	Horizontal
2402.00	82.43	27.41	2.91	36.86	75.89	94.00	-18.11	Average	Vertical
2402.00	89.17	27.41	2.91	36.86	82.63	114.00	-31.37	Peak	Vertical

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Remark	polarization
2441.00	93.43	27.53	2.96	36.89	87.03	94.00	-6.97	Average	Horizontal
2441.00	102.09	27.53	2.96	36.89	95.69	114.00	-18.31	Peak	Horizontal
2441.00	83.17	27.53	2.96	36.89	76.77	94.00	-17.23	Average	Vertical
2441.00	91.13	27.53	2.96	36.89	84.73	114.00	-29.27	Peak	Vertical

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Remark	polarization
2480.00	93.04	27.64	2.99	36.92	86.75	94.00	-7.25	Average	Horizontal
2480.00	100.31	27.64	2.99	36.92	94.02	114.00	-19.98	Peak	Horizontal
2480.00	84.86	27.64	2.99	36.92	78.57	94.00	-15.43	Average	Vertical
2480.00	91.03	27.64	2.99	36.92	84.74	114.00	-29.26	Peak	Vertical

ANT 4:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Remark	polarization
2402.00	90.98	27.41	2.91	36.86	84.44	94.00	-9.56	Average	Horizontal
2402.00	97.21	27.41	2.91	36.86	90.67	114.00	-23.33	Peak	Horizontal
2402.00	83.86	27.41	2.91	36.86	77.32	94.00	-16.68	Average	Vertical
2402.00	90.71	27.41	2.91	36.86	84.17	114.00	-29.83	Peak	Vertical

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Remark	polarization
2441.00	95.34	27.53	2.96	36.89	88.94	94.00	-5.06	Average	Horizontal
2441.00	102.54	27.53	2.96	36.89	96.14	114.00	-17.86	Peak	Horizontal
2441.00	85.09	27.53	2.96	36.89	78.69	94.00	-15.31	Average	Vertical
2441.00	91.37	27.53	2.96	36.89	84.97	114.00	-29.03	Peak	Vertical

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Remark	polarization
2480.00	86.08	27.64	2.99	36.92	79.79	94.00	-14.21	Average	Horizontal
2480.00	101.30	27.64	2.99	36.92	95.01	114.00	-18.99	Peak	Horizontal
2480.00	84.18	27.64	2.99	36.92	77.89	94.00	-16.11	Average	Vertical
2480.00	90.26	27.64	2.99	36.92	83.97	114.00	-30.03	Peak	Vertical


7.3.2 Spurious emissions

■ Below 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o), the test result no need to reported.


■ Below 1GHz

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
32.293	57.72	11.25	0.58	35.17	34.38	40.00	-5.62	QP
66.733	54.14	8.65	0.91	36.40	27.30	40.00	-12.70	QP
71.330	56.68	7.49	0.95	36.46	28.66	40.00	-11.34	QP
78.413	57.54	7.41	1.01	36.53	29.43	40.00	-10.57	QP
85.598	55.68	9.30	1.07	36.60	29.45	40.00	-10.55	QP
114.917	62.99	10.26	1.32	36.84	37.73	43.50	-5.77	QP

Vertical:




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
33.562	59.90	11.27	0.59	35.26	36.50	40.00	-3.50	QP
65.803	59.12	9.00	0.91	36.39	32.64	40.00	-7.36	QP
70.337	60.44	7.50	0.94	36.45	32.43	40.00	-7.57	QP
78.965	60.58	7.41	1.02	36.54	32.47	40.00	-7.53	QP
117.773	65.83	9.84	1.34	36.86	40.15	43.50	-3.35	QP
230.907	62.54	11.53	2.02	37.36	38.73	46.00	-7.27	QP

■ Above 1GHz

ANT 1:


Test channel:	Lowest
---------------	--------

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4804.000	26.91	31.20	4.61	37.73	24.99	54.00	-29.01	Average
4804.000	35.29	31.20	4.61	37.73	33.37	74.00	-40.63	Peak
7206.000	22.80	36.16	6.48	35.63	29.81	54.00	-24.19	Average
7206.000	32.38	36.16	6.48	35.63	39.39	74.00	-34.61	Peak
9608.000	22.76	37.93	7.97	34.94	33.72	54.00	-20.28	Average
9608.000	31.38	37.93	7.97	34.94	42.34	74.00	-31.66	Peak


Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamplifier factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4804.000	24.32	31.20	4.61	37.73	22.40	54.00	-31.60	Average
4804.000	34.83	31.20	4.61	37.73	32.91	74.00	-41.09	Peak
7206.000	20.82	36.16	6.48	35.63	27.83	54.00	-26.17	Average
7206.000	32.08	36.16	6.48	35.63	39.09	74.00	-34.91	Peak
9608.000	20.93	37.93	7.97	34.94	31.89	54.00	-22.11	Average
9608.000	31.10	37.93	7.97	34.94	42.06	74.00	-31.94	Peak


Test channel:	Middle
---------------	--------

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamplifier factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4876.000	32.28	31.31	4.69	37.75	30.53	54.00	-23.47	Average
4876.000	45.36	31.31	4.69	37.75	43.61	74.00	-30.39	Peak
7324.000	25.80	36.43	6.63	35.60	33.26	54.00	-20.74	Average
7324.000	39.88	36.43	6.63	35.60	47.34	74.00	-26.66	Peak
9772.000	19.47	38.13	8.03	35.05	30.58	54.00	-23.42	Average
9772.000	31.90	38.13	8.03	35.05	43.01	74.00	-30.99	Peak


Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamplifier factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4882.000	27.38	31.33	4.69	37.76	25.64	54.00	-28.36	Average
4882.000	42.84	31.33	4.69	37.76	41.10	74.00	-32.90	Peak
7323.000	19.10	36.43	6.63	35.60	26.56	54.00	-27.44	Average
7323.000	32.16	36.43	6.63	35.60	39.62	74.00	-34.38	Peak
9764.000	21.71	38.10	8.03	35.03	32.81	54.00	-21.19	Average
9764.000	31.82	38.10	8.03	35.03	42.92	74.00	-31.08	Peak


Test channel:	Highest
---------------	---------

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4960.000	31.99	31.44	4.79	37.78	30.44	54.00	-23.56	Average
4960.000	47.42	31.44	4.79	37.78	45.87	74.00	-28.13	Peak
7440.000	19.48	36.66	6.77	35.56	27.35	54.00	-26.65	Average
7440.000	37.11	36.66	6.77	35.56	44.98	74.00	-29.02	Peak
9920.000	18.81	38.30	8.09	35.14	30.06	54.00	-23.94	Average
9920.000	29.76	38.30	8.09	35.14	41.01	74.00	-32.99	Peak


Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4960.000	26.18	31.44	4.79	37.78	24.63	54.00	-29.37	Average
4960.000	41.53	31.44	4.79	37.78	39.98	74.00	-34.02	Peak
7440.000	16.51	36.66	6.77	35.56	24.38	54.00	-29.62	Average
7440.000	29.63	36.66	6.77	35.56	37.50	74.00	-36.50	Peak
9920.000	19.64	38.30	8.09	35.14	30.89	54.00	-23.11	Average
9920.000	30.16	38.30	8.09	35.14	41.41	74.00	-32.59	Peak


ANT 2:

Test channel:	Lowest
---------------	--------

Horizontal:


Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4804.000	23.32	31.20	4.61	37.73	21.40	54.00	-32.60	Average
4804.000	33.33	31.20	4.61	37.73	31.41	74.00	-42.59	Peak
7206.000	21.04	36.16	6.48	35.63	28.05	54.00	-25.95	Average
7206.000	31.00	36.16	6.48	35.63	38.01	74.00	-35.99	Peak
9608.000	22.25	37.93	7.97	34.94	33.21	54.00	-20.79	Average
9608.000	30.43	37.93	7.97	34.94	41.39	74.00	-32.61	Peak


Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4804.000	23.25	31.20	4.61	37.73	21.33	54.00	-32.67	Average
4804.000	33.52	31.20	4.61	37.73	31.60	74.00	-42.40	Peak
7206.000	21.73	36.16	6.48	35.63	28.74	54.00	-25.26	Average
7206.000	30.57	36.16	6.48	35.63	37.58	74.00	-36.42	Peak
9608.000	20.68	37.93	7.97	34.94	31.64	54.00	-22.36	Average
9608.000	30.07	37.93	7.97	34.94	41.03	74.00	-32.97	Peak


Test channel:	Middle
---------------	--------

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4882.000	29.79	31.33	4.69	37.76	28.05	54.00	-25.95	Average
4882.000	47.57	31.33	4.69	37.76	45.83	74.00	-28.17	Peak
7323.000	25.76	36.43	6.63	35.60	33.22	54.00	-20.78	Average
7323.000	40.66	36.43	6.63	35.60	48.12	74.00	-25.88	Peak
9764.000	21.56	38.10	8.03	35.03	32.66	54.00	-21.34	Average
9764.000	32.06	38.10	8.03	35.03	43.16	74.00	-30.84	Peak


Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamplifier factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4882.000	28.47	31.33	4.69	37.76	26.73	54.00	-27.27	Average
4882.000	45.70	31.33	4.69	37.76	43.96	74.00	-30.04	Peak
7323.000	19.22	36.43	6.63	35.60	26.68	54.00	-27.32	Average
7323.000	31.82	36.43	6.63	35.60	39.28	74.00	-34.72	Peak
9764.000	22.47	38.10	8.03	35.03	33.57	54.00	-20.43	Average
9764.000	32.07	38.10	8.03	35.03	43.17	74.00	-30.83	Peak


Test channel:	Highest
---------------	---------

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4960.000	31.91	31.44	4.79	37.78	30.36	54.00	-23.64	Average
4960.000	46.54	31.44	4.79	37.78	44.99	74.00	-29.01	Peak
7440.000	23.43	36.66	6.77	35.56	31.30	54.00	-22.70	Average
7440.000	37.94	36.66	6.77	35.56	45.81	74.00	-28.19	Peak
9920.000	21.03	38.30	8.09	35.14	32.28	54.00	-21.72	Average
9920.000	31.30	38.30	8.09	35.14	42.55	74.00	-31.45	Peak

Vertical:




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4960.000	25.04	31.44	4.79	37.78	23.49	54.00	-30.51	Average
4960.000	40.51	31.44	4.79	37.78	38.96	74.00	-35.04	Peak
7440.000	19.86	36.66	6.77	35.56	27.73	54.00	-26.27	Average
7440.000	32.11	36.66	6.77	35.56	39.98	74.00	-34.02	Peak
9920.000	22.12	38.30	8.09	35.14	33.37	54.00	-20.63	Average
9920.000	32.37	38.30	8.09	35.14	43.62	74.00	-30.38	Peak

ANT 3:


Test channel:	Lowest
---------------	--------

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4804.000	25.21	31.20	4.61	37.73	23.29	54.00	-30.71	Average
4804.000	34.42	31.20	4.61	37.73	32.50	74.00	-41.50	Peak
7206.000	21.30	36.16	6.48	35.63	28.31	54.00	-25.69	Average
7206.000	31.03	36.16	6.48	35.63	38.04	74.00	-35.96	Peak
9608.000	21.56	37.93	7.97	34.94	32.52	54.00	-21.48	Average
9608.000	30.06	37.93	7.97	34.94	41.02	74.00	-32.98	Peak


Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4804.000	23.21	31.20	4.61	37.73	21.29	54.00	-32.71	Average
4804.000	34.42	31.20	4.61	37.73	32.50	74.00	-41.50	Peak
7206.000	20.40	36.16	6.48	35.63	27.41	54.00	-26.59	Average
7206.000	32.34	36.16	6.48	35.63	39.35	74.00	-34.65	Peak
9608.000	21.20	37.93	7.97	34.94	32.16	54.00	-21.84	Average
9608.000	32.23	37.93	7.97	34.94	43.19	74.00	-30.81	Peak


Test channel:	Middle
---------------	--------

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4882.000	23.55	31.33	4.69	37.76	21.81	54.00	-32.19	Average
4882.000	48.57	31.33	4.69	37.76	46.83	74.00	-27.17	Peak
7323.000	17.76	36.43	6.63	35.60	25.22	54.00	-28.78	Average
7323.000	34.71	36.43	6.63	35.60	42.17	74.00	-31.83	Peak
9764.000	18.64	38.10	8.03	35.03	29.74	54.00	-24.26	Average
9764.000	32.30	38.10	8.03	35.03	43.40	74.00	-30.60	Peak


Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamplifier factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4882.000	23.16	31.33	4.69	37.76	21.42	54.00	-32.58	Average
4882.000	39.93	31.33	4.69	37.76	38.19	74.00	-35.81	Peak
7323.000	19.65	36.43	6.63	35.60	27.11	54.00	-26.89	Average
7323.000	32.05	36.43	6.63	35.60	39.51	74.00	-34.49	Peak
9764.000	20.96	38.10	8.03	35.03	32.06	54.00	-21.94	Average
9764.000	31.29	38.10	8.03	35.03	42.39	74.00	-31.61	Peak


Test channel:	Highest
---------------	---------

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4960.000	29.45	31.44	4.79	37.78	27.90	54.00	-26.10	Average
4960.000	46.88	31.44	4.79	37.78	45.33	74.00	-28.67	Peak
7440.000	24.24	36.66	6.77	35.56	32.11	54.00	-21.89	Average
7440.000	36.41	36.66	6.77	35.56	44.28	74.00	-29.72	Peak
9920.000	23.13	38.30	8.09	35.14	34.38	54.00	-19.62	Average
9920.000	31.73	38.30	8.09	35.14	42.98	74.00	-31.02	Peak


Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4960.000	24.62	31.44	4.79	37.78	23.07	54.00	-30.93	Average
4960.000	38.71	31.44	4.79	37.78	37.16	74.00	-36.84	Peak
7440.000	18.23	36.66	6.77	35.56	26.10	54.00	-27.90	Average
7440.000	32.12	36.66	6.77	35.56	39.99	74.00	-34.01	Peak
9920.000	22.69	38.30	8.09	35.14	33.94	54.00	-20.06	Average
9920.000	32.23	38.30	8.09	35.14	43.48	74.00	-30.52	Peak


ANT 4:

Test channel:	Lowest
---------------	--------

Horizontal:


Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4804.000	22.15	31.20	4.61	37.73	20.23	54.00	-33.77	Average
4804.000	33.12	31.20	4.61	37.73	31.20	74.00	-42.80	Peak
7206.000	17.91	36.16	6.48	35.63	24.92	54.00	-29.08	Average
7206.000	32.79	36.16	6.48	35.63	39.80	74.00	-34.20	Peak
9608.000	19.17	37.93	7.97	34.94	30.13	54.00	-23.87	Average
9608.000	31.62	37.93	7.97	34.94	42.58	74.00	-31.42	Peak


Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4804.000	20.53	31.20	4.61	37.73	18.61	54.00	-35.39	Average
4804.000	32.75	31.20	4.61	37.73	30.83	74.00	-43.17	Peak
7206.000	17.50	36.16	6.48	35.63	24.51	54.00	-29.49	Average
7206.000	31.25	36.16	6.48	35.63	38.26	74.00	-35.74	Peak
9608.000	20.79	37.93	7.97	34.94	31.75	54.00	-22.25	Average
9608.000	30.99	37.93	7.97	34.94	41.95	74.00	-32.05	Peak


Test channel:	Middle
---------------	--------

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4882.000	29.51	31.33	4.69	37.76	27.77	54.00	-26.23	Average
4882.000	46.42	31.33	4.69	37.76	44.68	74.00	-29.32	Peak
7323.000	27.96	36.43	6.63	35.60	35.42	54.00	-18.58	Average
7323.000	41.29	36.43	6.63	35.60	48.75	74.00	-25.25	Peak
9764.000	24.48	38.10	8.03	35.03	35.58	54.00	-18.42	Average
9764.000	31.32	38.10	8.03	35.03	42.42	74.00	-31.58	Peak


Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4882.000	28.32	31.33	4.69	37.76	26.58	54.00	-27.42	Average
4882.000	40.05	31.33	4.69	37.76	38.31	74.00	-35.69	Peak
7323.000	21.43	36.43	6.63	35.60	28.89	54.00	-25.11	Average
7323.000	32.43	36.43	6.63	35.60	39.89	74.00	-34.11	Peak
9764.000	22.86	38.10	8.03	35.03	33.96	54.00	-20.04	Average
9764.000	31.50	38.10	8.03	35.03	42.60	74.00	-31.40	Peak


Test channel:	Highest
---------------	---------

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamplifier factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4960.000	32.20	31.44	4.79	37.78	30.65	54.00	-23.35	Average
4960.000	47.25	31.44	4.79	37.78	45.70	74.00	-28.30	Peak
7440.000	27.13	36.66	6.77	35.56	35.00	54.00	-19.00	Average
7440.000	41.81	36.66	6.77	35.56	49.68	74.00	-24.32	Peak
9920.000	23.95	38.30	8.09	35.14	35.20	54.00	-18.80	Average
9920.000	32.53	38.30	8.09	35.14	43.78	74.00	-30.22	Peak

Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4960.000	30.07	31.44	4.79	37.78	28.52	54.00	-25.48	Average
4960.000	40.94	31.44	4.79	37.78	39.39	74.00	-34.61	Peak
7440.000	22.53	36.66	6.77	35.56	30.40	54.00	-23.60	Average
7440.000	31.21	36.66	6.77	35.56	39.08	74.00	-34.92	Peak
9920.000	23.57	38.30	8.09	35.14	34.82	54.00	-19.18	Average
9920.000	31.84	38.30	8.09	35.14	43.09	74.00	-30.91	Peak

Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. “*”, means this data is too weak instrument of signal is unable to test.


7.3.3 Bandedge emissions

All of the restriction bands were tested, and only the data of worst case was exhibited.

ANT 1:


Test channel:	Lowest
---------------	--------

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	31.35	27.14	2.81	36.79	24.51	54.00	-29.49	Average
2310.000	40.44	27.14	2.81	36.79	33.60	74.00	-40.40	Peak
2390.000	31.88	27.37	2.91	36.85	25.31	54.00	-28.69	Average
2390.000	43.19	27.37	2.91	36.85	36.62	74.00	-37.38	Peak
2400.000	53.79	27.41	2.91	36.86	47.25	54.00	-6.75	Average
2400.000	67.33	27.41	2.91	36.86	60.79	74.00	-13.21	Peak

Vertical:




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	30.61	27.14	2.81	36.79	23.77	54.00	-30.23	Average
2310.000	37.26	27.14	2.81	36.79	30.42	74.00	-43.58	Peak
2390.000	30.03	27.37	2.91	36.85	23.46	54.00	-30.54	Average
2390.000	38.00	27.37	2.91	36.85	31.43	74.00	-42.57	Peak
2400.000	52.42	27.41	2.91	36.86	45.88	54.00	-8.12	Average
2400.000	58.54	27.41	2.91	36.86	52.00	74.00	-22.00	Peak

Test channel:


Highest

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	43.66	27.66	2.99	36.93	37.38	54.00	-16.62	Average
2483.500	57.45	27.66	2.99	36.93	51.17	74.00	-22.83	Peak
2500.000	31.82	27.70	3.01	36.94	25.59	54.00	-28.41	Average
2500.000	40.88	27.70	3.01	36.94	34.65	74.00	-39.35	Peak

Vertical:




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	36.18	27.66	2.99	36.93	29.90	54.00	-24.10	Average
2483.500	42.88	27.66	2.99	36.93	36.60	74.00	-37.40	Peak
2500.000	29.74	27.70	3.01	36.94	23.51	54.00	-30.49	Average
2500.000	39.17	27.70	3.01	36.94	32.94	74.00	-41.06	Peak

ANT 2:


Test channel:	Lowest
---------------	--------

Horizontal:




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	31.33	27.14	2.81	36.79	24.49	54.00	-29.51	Average
2310.000	36.64	27.14	2.81	36.79	29.80	74.00	-44.20	Peak
2390.000	32.94	27.37	2.91	36.85	26.37	54.00	-27.63	Average
2390.000	39.29	27.37	2.91	36.85	32.72	74.00	-41.28	Peak
2400.000	53.85	27.41	2.91	36.86	47.31	54.00	-6.69	Average
2400.000	64.08	27.41	2.91	36.86	57.54	74.00	-16.46	Peak

Vertical:




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	27.47	27.14	2.81	36.79	20.63	54.00	-33.37	Average
2310.000	37.05	27.14	2.81	36.79	30.21	74.00	-43.79	Peak
2390.000	28.55	27.37	2.91	36.85	21.98	54.00	-32.02	Average
2390.000	36.85	27.37	2.91	36.85	30.28	74.00	-43.72	Peak
2400.000	44.58	27.41	2.91	36.86	38.04	54.00	-15.96	Average
2400.000	54.86	27.41	2.91	36.86	48.32	74.00	-25.68	Peak

Test channel:	Highest
Horizontal:	



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	43.22	27.66	2.99	36.93	36.94	54.00	-17.06	Average
2483.500	56.65	27.66	2.99	36.93	50.37	74.00	-23.63	Peak
2500.000	28.64	27.70	3.01	36.94	22.41	54.00	-31.59	Average
2500.000	39.21	27.70	3.01	36.94	32.98	74.00	-41.02	Peak

Vertical:




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamplifier factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	36.90	27.66	2.99	36.93	30.62	54.00	-23.38	Average
2483.500	47.29	27.66	2.99	36.93	41.01	74.00	-32.99	Peak
2500.000	27.17	27.70	3.01	36.94	20.94	54.00	-33.06	Average
2500.000	37.08	27.70	3.01	36.94	30.85	74.00	-43.15	Peak

ANT 3:


Test channel:	Lowest
---------------	--------

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamplifier factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	27.10	27.14	2.81	36.79	20.26	54.00	-33.74	Average
2310.000	36.51	27.14	2.81	36.79	29.67	74.00	-44.33	Peak
2390.000	28.26	27.37	2.91	36.85	21.69	54.00	-32.31	Average
2390.000	36.63	27.37	2.91	36.85	30.06	74.00	-43.94	Peak
2400.000	50.01	27.41	2.91	36.86	43.47	54.00	-10.53	Average
2400.000	64.40	27.41	2.91	36.86	57.86	74.00	-16.14	Peak


Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	28.04	27.14	2.81	36.79	21.20	54.00	-32.80	Average
2310.000	36.71	27.14	2.81	36.79	29.87	74.00	-44.13	Peak
2390.000	29.48	27.37	2.91	36.85	22.91	54.00	-31.09	Average
2390.000	37.15	27.37	2.91	36.85	30.58	74.00	-43.42	Peak
2400.000	44.06	27.41	2.91	36.86	37.52	54.00	-16.48	Average
2400.000	57.91	27.41	2.91	36.86	51.37	74.00	-22.63	Peak


Test channel:	Highest
---------------	---------

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	37.49	27.66	2.99	36.93	31.21	54.00	-22.79	Average
2483.500	52.90	27.66	2.99	36.93	46.62	74.00	-27.38	Peak
2500.000	26.97	27.70	3.01	36.94	20.74	54.00	-33.26	Average
2500.000	38.19	27.70	3.01	36.94	31.96	74.00	-42.04	Peak

Vertical:




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	33.95	27.66	2.99	36.93	27.67	54.00	-26.33	Average
2483.500	45.18	27.66	2.99	36.93	38.90	74.00	-35.10	Peak
2500.000	27.10	27.70	3.01	36.94	20.87	54.00	-33.13	Average
2500.000	37.37	27.70	3.01	36.94	31.14	74.00	-42.86	Peak

ANT 4:

Test channel:


Lowest

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	27.57	27.14	2.81	36.79	20.73	54.00	-33.27	Average
2310.000	37.06	27.14	2.81	36.79	30.22	74.00	-43.78	Peak
2390.000	29.77	27.37	2.91	36.85	23.20	54.00	-30.80	Average
2390.000	40.88	27.37	2.91	36.85	34.31	74.00	-39.69	Peak
2400.000	53.05	27.41	2.91	36.86	46.51	54.00	-7.49	Average
2400.000	65.50	27.41	2.91	36.86	58.96	74.00	-15.04	Peak

Vertical:




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	29.24	27.14	2.81	36.79	22.40	54.00	-31.60	Average
2310.000	39.33	27.14	2.81	36.79	32.49	74.00	-41.51	Peak
2390.000	29.83	27.37	2.91	36.85	23.26	54.00	-30.74	Average
2390.000	40.78	27.37	2.91	36.85	34.21	74.00	-39.79	Peak
2400.000	48.81	27.41	2.91	36.86	42.27	54.00	-11.73	Average
2400.000	60.68	27.41	2.91	36.86	54.14	74.00	-19.86	Peak

Test channel:


Highest

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	44.37	27.66	2.99	36.93	38.09	54.00	-15.91	Average
2483.500	55.81	27.66	2.99	36.93	49.53	74.00	-24.47	Peak
2500.000	27.92	27.70	3.01	36.94	21.69	54.00	-32.31	Average
2500.000	37.49	27.70	3.01	36.94	31.26	74.00	-42.74	Peak

Vertical:




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	36.46	27.66	2.99	36.93	30.18	54.00	-23.82	Average
2483.500	47.67	27.66	2.99	36.93	41.39	74.00	-32.61	Peak
2500.000	28.01	27.70	3.01	36.94	21.78	54.00	-32.22	Average
2500.000	37.23	27.70	3.01	36.94	31.00	74.00	-43.00	Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

7.4 20dB Occupy Bandwidth


Test Requirement:	FCC Part15 C Section 15.249/15.215
Test Method:	ANSI C63.10:2013
Limit:	Operation Frequency range 2400MHz~2483.5MHz
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data


Test channel	20dB bandwidth(MHz)				Result
	ANT 1	ANT 2	ANT 3	ANT 4	
Lowest	1.031	1.026	1.011	1.028	Pass
Middle	1.031	1.029	1.030	1.031	Pass
Highest	1.035	1.032	1.034	1.032	Pass

Test plot as follows:



ANT 1





ANT 2



Lowest channel




Middle channel




Highest channel



ANT 3





ANT 4



Lowest channel



Middle channel



Highest channel

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----