

	1	2	3	4	5	6						
A						制作公差容许范围表						
						單位:mm						
						指定公差	◆	◇	◇			
						公差等级	A级	B级	C级			
						图面尺寸	≥200	±0.25	±0.40	±0.80		
							≥150-<200	±0.20	±0.35	±0.70		
							≥100<150	±0.16	±0.30	±0.60		
							≥60-<100	±0.13	±0.25	±0.50		
							≥30-<60	±0.10	±0.20	±0.40		
							≥10-<30	±0.07	±0.15	±0.30		
≥1-<10	±0.05	±0.10	±0.20									
<1	±0.03	±0.05	±0.10									
ANGLES	±0.5°	±1°	±1°									
B												
C												
D	技术要求: 1. 环保要求: 符合RoHS2.0, REACH, CP65, POPs 2. 外观要求: 缩水、变形、披锋、顶白、溶结线、杂色、脏污、等不良外观注塑缺陷; 3. “”为重点检测尺寸;					COSONIC						
						产品型号:	CH-5181B	零件名称:	产品镭雕示意图			
						零件料号:	2201025181B0100					
						文件编号:						
						绘图:	唐均均	2022/12/1	投影方向:			
						审核:			单位:	mm	比例:	1/1
						核准:			页数:	1/1	版本:	A/0
						NO	变更内容	变更者	日期			
						1	2	3	4	5	6	