

PCTEST Engineering Laboratory, Inc. 6660-B Dobbin Road • Columbia, MD 21045 • U.S.A. TEL (410) 290-6652 • FAX (410) 290-6654 http://www.pctestlab.com



CERTIFICATE OF COMPLIANCE FCC Part 22 Certification

NOKIA MOBILE PHONES INC. 12278 Scripps Summit Drive San Diego, CA 92131

Dates of Tests: March 29-31, 2004 Test Report S/N: 22.240329215.QMN Test Site: PCTEST Lab, Columbia MD

FCC ID

QMNRM-20

APPLICANT

NOKIA MOBILE PHONES INC.

| Classification | Liconsod Portable Transmitter Hold to Ear (PCE) |
|-------------------------|---|
| Classification. | |
| FCC Rule Part(s): | §22(H); §2 |
| EUT Type: | Dual-Mode Single-Band Phone (AMPS/CDMA) |
| Model: | 6012 |
| Tx Frequency Range: | 824.04MHz – 848.97MHz (AMPS) / 824.70 – 848.31MHz (CDMA) |
| Rx Frequency Range: | 869.04MHz – 893.97MHz (AMPS) / 869.70 – 893.31MHz (CDMA) |
| Max. RF Output Power: | 0.374 W ERP AMPS (25.729 dBm) / 0.370 W ERP CDMA (25.683 dBm) |
| Emission Designator(s): | 40K0F8W / 40K0F1D (AMPS), 1M25F9W (CDMA) |
| Test Device Serial No. | Identical Prototype [S/N: #3] |

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Grant conditions: Power output listed is ERP for Part 22. SAR compliance for body- worn operating configuration is limited to the specific belt-clip/holster tested for this filing. End-users must be informed of the body-worn operating requirements for satisfying RF exposure compliance

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.

Alfred Cirwithian Vice President Engineering



| PCTESTÔ PT. 22 REPORT | FCC MEASUREMENT REPORT | | | Reviewed By: Quality Manager |
|-----------------------|------------------------|-----------------------|----------|--|
| Test Report S/N: | Test Dates: | Phone Type: | FCC ID: | Page 1 of 26 |
| 22.240329215.QMN | March 29-31, 2004 | Dual-Mode Single-Band | QMNRM-20 | |



TABLE OF CONTENTS

| 1.1 SCOPE | 3 |
|---|-------|
| 2.1 INTRODUCTION | 4 |
| 3.1 INSERTS | 5 |
| 4.1 DESCRIPTION OF TESTS | 6-9 |
| 5.1 EQUIVALENT ISOTROPIC RADIATED POWER | 10-12 |
| 6.1 RADIATED MEASUREMENTS | 13-18 |
| 7.1 FREQUENCY STABILITY | 19-22 |
| 8.1 PLOTS OF EMISSIONS | 23 |
| 9.1 LIST OF TEST EQUIPMENT | 24 |
| 10.1 SAMPLE CALCULATIONS | 25 |
| 11.1 CONCLUSION | 26 |
| ATTACHMENT A: TEST PLOTS | |
| ATTACHMENT B: TEST SETUP PHOTOGRAPHS | |
| ATTACHMENT C: EXTERNAL PHOTOGRAPHS | |

ATTACHMENT D: INTERNAL PHOTOGRAPHS

| | PCTESTÔ PT. 22 REPORT | FC | C MEASUREMENT REP | ORT NOKIA | Reviewed By: Quality Manager |
|---|--------------------------------------|---|--------------------------------------|---------------------|---------------------------------|
| | Test Report S/N: 22.240329215.QMN | Test Dates: March 29-31, 2004 | Phone Type: Dual-Mode Single-Band | FCC ID: QMNRM-20 | Page 2 of 26 |
| ļ | 22.240329215.QMIN | March 29-31, 2004 | Dual-Wode Single-Band | QIVINRIVI-20 | 5 |



| PCTESTÔ PT. 22 REPORT | FC | C MEASUREMENT REP | | Reviewed By: Quality Manager |
|--------------------------------------|---|---|---------------------|---------------------------------|
| Test Report S/N: 22.240329215.QMN | Test Dates: March 29-31, 2004 | Phone Type : Dual-Mode Single - Band | FCC ID: QMNRM-20 | Page 3 of 26 |
| CARAL DOTEOT ENGLISEDING LABORA | | | | |



MEASUREMENT REPORT

1.1 Scope



Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

§2.1033 General Information

Applicant Name: NOKIA MOBILE PHONES INC. Address: 12278 Scripps Summit Drive San Diego, CA 92131

• FCC ID:

•

QMNRM-20

- Quantity: Quantity production is planned
 Emission Designators: 40K0F8W / 40K0F1D (AMPS), 1M25F9W (CDMA)
- Tx Freq. Range: 824.04 848.97 MHz (AMPS)
 - 824.70 848.31 MHz (CDMA)
- Rx Freq. Range: 869.04 893.97 MHz (AMPS)
- 869.70 893.31 MHz (CDMA)
- Max. Power Rating: 0.374 W ERP AMPS (25.729 dBm) / 0.370 W ERP CDMA (25.683 dBm)
- FCC Classification(s): Licensed Portable Tx Held to Ear (PCE)
- Equipment (EUT) Type: Dual-Mode Single-Band Phone
- Modulation(s): AMPS / CDMA
- Frequency Tolerance: ± 0.00025% (2.5 ppm)
- FCC Rule Part(s): §22(H)
- Dates of Tests: March 29-31, 2004
- Place of Tests: PCTEST Lab, Columbia, MD U.S.A.
- Test Report S/N: 22.240329215.QMN

| PCTESTÔ PT. 22 REPORT | FC | CC MEASUREMENT REP | | Reviewed By: Quality Manager |
|-----------------------|--------------------|-----------------------|----------|---------------------------------|
| Test Report S/N: | Test Dates: | Phone Type: | FCC ID: | Page 4 of 26 |
| 22.240329215.QMN | March 29-31, 2004 | Dual-Mode Single-Band | QMNRM-20 | |





Figure 1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area.



Open Area Test Site

Figure 2. Diagram of 3-meter outdoor test range

| PCTESTÔ PT. 22 REPORT | FC | C MEASUREMENT REP | | Reviewed By: Quality Manager |
|--------------------------------------|---|---|---------------------|--|
| Test Report S/N: 22.240329215.QMN | Test Dates: March 29-31, 2004 | Phone Type : Dual-Mode Single - Band | FCC ID: QMNRM-20 | Page 5 of 26 |
| | | | | |

These measurement tests were conducted at *PCTEST Engineering Laboratory, Inc.* facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4 on October 19, 1992.

Measurement Procedure

The radiated and spurious measurements were made outdoors at a 3-meter test range (see Figure2). The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.



3.1 INSERTS

Function of Active Devices (Confidential)

The Function of active devices are shown in Attachment K.

Block & Schematic Diagrams (Confidential)

The block diagrams are shown in Attachment I, and the schematic diagrams are shown in Attachment J.

Operating Instructions

The instruction manual is shown in Attachment M.

Parts List & Tune-Up Procedure (Confidential)

The parts list & tune-up procedure is shown in Attachment L.

Description of Freq. Stabilization Circuit (Confidential)

The description of frequency stabilization circuit is shown in Attachment K.

Description for Suppression of Spurious Radiation, for Limiting Modulation, and Harmonic Suppression Circuits (Confidential)

The description of suppression stabilization circuits is shown in Attachment K.

| PCTESTÔ PT. 22 REPORT | FC | C MEASUREMENT REP | ORT NOKIA | Reviewed By: Quality Manager |
|--------------------------------------|---|--------------------------------------|---------------------|--|
| Test Report S/N: 22.240329215.QMN | Test Dates: March 29-31, 2004 | Phone Type: Dual-Mode Single-Band | FCC ID: QMNRM-20 | Page 6 of 26 |
| | | | | |



4.1 DESCRIPTION OF TESTS

4.2 Transmitter Audio Frequency Response

The frequency response of the audio modulating circuit over the frequency range 100 – 5000 Hz is measured. The audio signal generator is connected to the audio input circuit/microphone of the EUT. The audio signal input is adjusted to obtain 50% modulation at 1kHz and this point is taken as the 0dB reference. With the input held constant and below the limit at all frequencies, the audio signal generator is varied from 100 to 50 kHz.

4.3 Audio Low Pass Filter Frequency Response

The response in dB relative to 1kHz is measured using the HP8901 a Modulation Analyzer. For the frequency response of the audio low-pass filter, the audio input is connected at the input to the modulation limiter and the modulated stage. The audio output is connected at the output of the modulated stage. The corresponding plots are shown herein.

4.4 Modulation Limiting

The audio signal generator is connected to the audio input circuit/microphone of the EUT. The modulation response is measured for each of the three modulating frequencies (300Hz, 1000 Hz, and 3000Hz), and the input voltage is varied from 30% modulation (±3.6kHz deviation) to at least 20dB higher than the saturation point. Measurements of modulation and the plots are attached herein. Measurements were performed for ST, SAT, and wide-band data modulations. The corresponding results are shown herein.



| PCTESTÔ PT. 22 REPORT | FCC MEASUREMENT REPORT | | | Reviewed By: Quality Manager |
|-----------------------|------------------------|-------------------------|----------|---------------------------------|
| Test Report S/N: | Test Dates: | Phone Type : | FCC ID: | Page 7 of 26 |
| 22.240329215.QMN | March 29-31, 2004 | Dual-Mode Single - Band | QMNRM-20 | |



4.5 Occupied Bandwidth Emission Limits

- (a) On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least 43 + 10 log(P) dB.
- (b) Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.
- (c) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.
- (d) The measurement of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.



4.6 Cellular - Base Frequency Blocks

4.7 Cellular - Mobile Frequency Blocks



| PCTESTÔ PT. 22 REPORT | FCC MEASUREMENT REPORT | | | Reviewed By: Quality Manager |
|-----------------------|------------------------|-----------------------|----------|--|
| Test Report S/N: | Test Dates: | Phone Type : | FCC ID: | Page 8 of 26 |
| 22.240329215.QMN | March 29-31, 2004 | Dual-Mode Single-Band | QMNRM-20 | |



4.1 DESCRIPTION OF TESTS (CONTINUED)





4.9 PCS - Mobile Frequency Blocks



| PCTESTÔ PT. 22 REPORT | FC | C MEASUREMENT REP | | Reviewed By: Quality Manager |
|--------------------------------------|---|---|---------------------|---------------------------------|
| Test Report S/N: 22.240329215.QMN | Test Dates: March 29-31, 2004 | Phone Type : Dual-Mode Single - Band | FCC ID: QMNRM-20 | Page 9 of 26 |
| © 2004 DOTEST ENCINEEDING LABORA | | | | |

4.1 DESCRIPTION OF TESTS (CONTINUED)

4.10 Occupied Bandwidth

The audio signal generator is adjusted to 1kHz. The output level is set to ± 6 kHz deviation. With the level constant, the frequency is set to 2500Hz. Then the audio signal level is increased by 16dB. The occupied bandwidth data is obtained for the SAT (Supervisory Audio Tone), ST (Signaling Tone), WBD (Wideband data), and DTMF (Dual Tone Multi Frequencies). The results are shown on the attached graphs.

Specified Limits:

- a. On any frequency removed from the assigned carrier frequency by more than 20 kHz, up to and including 45kHz, the sideband is at least 26dB below the carrier.
- b. On any frequency removed from the assigned carrier frequency by more than 45 kHz, up to and including 90kHz, the sideband is at least 45dB below the carrier.
- c. On any frequency removed from the assigned carrier frequency by more than 90 kHz, up to the first multiple of the carrier frequency, the sideband is at least 60dB below the carrier or $40 + \log_{10}$ (mean power output in Watts) dB, whichever is the smaller attenuation.

4.11 Spurious and Harmonic Emissions at Antenna Terminal

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to 10 GHz. The transmitter is modulated with a 2500Hz tone at a level of 16dB greater than that required to provided 50% modulation.

At the input terminals of the spectrum analyzer, an isolator (RF circulator with on port terminated with 50 ohms) and an 870 MHz to 890 MHz bandpass filter is connected between the test transceiver (for conducted tests) or the receive antenna (for radiated tests) and the analyzer. The rejection of the bandpass filter to signals in the 825 – 845 MHz range is adequate to limit the transmit energy from the test transceiver which appears to a level which will allow the analyzer to measure signals less than –90dBm. Calibration of the test receiver is performed in the 870 – 890 MHz range to insure accuracy to allow variation in the bandpass filter insertion loss to be calibrated.

4.12 Frequencies

At the input terminals of the spectrum analyzer, an isolator (RF pad) and an high-pass filter are connected between the test transceiver (for conducted tests) or the receive antenna (for radiated tests) and the analyzer. The high-pass filter (signals below 1.6 GHz) is to limit the fundamental frequency from interfering with the measurement of low-level spurious and harmonic emissions and to ensure that the preamplifier is not saturated.

4.13 Radiation Spurious and Harmonic Emissions

Radiation and harmonic emissions are measured outdoors at our 3-meter test range. The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

| PCTESTÔ PT. 22 REPORT | FCC MEASUREMENT REPORT | | | Reviewed By: Quality Manager |
|-----------------------|------------------------|-----------------------|----------|--|
| Test Report S/N: | Test Dates: | Phone Type : | FCC ID: | Page 10 of 26 |
| 22.240329215.QMN | March 29-31, 2004 | Dual-Mode Single-Band | QMNRM-20 | |



The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +60°C using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ± 0.00025 (± 2.5 ppm) of the center frequency.

Time Period and Procedure:

- 1. The carrier frequency of the transmitter and the individual oscillators is measured at room temperature (22°C to 25°C to provide a reference).
- 2. The equipment is subjected to an overnight "soak" at -30°C without any power applied.
- 3. After the overnight "soak" at -30°C (usually 14-16 hours), the equipment is turned on in a "standby" condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter and the individual oscillators is made within a three minute interval after applying power to the transmitter.
- 4. Frequency measurements are made at 10°C interval up to room temperature. At least a period of one and one half-hour is provided to allow stabilization of the equipment at each temperature level.
- 5. Again the transmitter carrier frequency and the individual oscillators is measured at room temperature to begin measurement of the upper temperature levels.
- 6. Frequency measurements are at 10 intervals starting at -30°C up to +50°C allowing at least two hours at each temperature for stabilization. In all measurements the frequency is measured within three minutes after re-applying power to the transmitter.
- 7. The artificial load is mounted external to the temperature chamber.

NOTE: The EUT is tested down to the battery endpoint.

| PCTESTÔ PT. 22 REPORT | FC | C MEASUREMENT REP | ORT NOKIA | Reviewed By: Quality Manager |
|-----------------------|--------------------|-------------------------|-----------|--|
| Test Report S/N: | Test Dates: | Phone Type : | FCC ID: | Page 11 of 26 |
| 22.240329215.QMN | March 29-31, 2004 | Dual-Mode Single - Band | QMNRM-20 | |



5.1 Test Data

5.2 Effective Radiated Power Output

A. POWER: Low (Analog Mode)

| Freq. Tuned (MHz) | REF. LEVEL (dBm) | POL (H/V) | ERP (W) | ERP (dBm) |
|----------------------|------------------------|---------------------|------------|---------------------|
| 824.04 | -36.200 | Н | 0.003 | 5.073 |
| 836.52 | -35.700 | Н | 0.004 | 5.729 |
| 848.97 | -35.900 | Н | 0.004 | 5.685 |

B. POWER: High (Analog Mode)

| Freq. Tuned (MHz) | REF. LEVEL (dBm) | POL (H/V) | ERP (W) | ERP (dBm) | BATTERY |
|----------------------|------------------------|--------------|------------|---------------------|----------|
| 824.04 | -16.200 | Н | 0.322 | 25.073 | Standard |
| 836.52 | -15.700 | Н | 0.374 | 25.729 | Standard |
| 848.97 | -15.900 | Н | 0.370 | 25.685 | Standard |

Note: Standard batteries are the only options for this phone

NOTES:

Effective Radiated Power Output Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

| PCTESTÔ PT. 22 REPORT | FC | C MEASUREMENT REP | | Reviewed By: Quality Manager |
|-----------------------|--------------------|-----------------------|----------|--|
| Test Report S/N: | Test Dates: | Phone Type: | FCC ID: | Page 12 of 26 |
| 22.240329215.QMN | March 29-31, 2004 | Dual-Mode Single-Band | QMNRM-20 | |



5.3 Effective Radiated Power Output

A. POWER: High (CDMA Mode)

| Freq. Tuned (MHz) | REF. LEVEL (dBm) | POL (H/V) | ERP (W) | ERP (dBm) | BATTERY |
|----------------------|------------------------|---------------------|------------|--------------|----------|
| 824.70 | -16.100 | Н | 0.329 | 25.173 | Standard |
| 836.52 | -16.100 | Н | 0.341 | 25.333 | Standard |
| 848.31 | -15.900 | Н | 0.370 | 25.683 | Standard |

Note: Standard batteries are the only options for this phone

NOTES:

Effective Radiated Power Output Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

| PCTESTÔ PT. 22 REPORT | FC | C MEASUREMENT REP | | Reviewed By: Quality Manager |
|--------------------------------------|----------------------------------|--------------------------------------|---------------------|---------------------------------|
| Test Report S/N: 22.240329215.QMN | Test Dates: March 29-31, 2004 | Phone Type: Dual-Mode Single-Band | FCC ID: QMNRM-20 | Page 13 of 26 |
| @ 0004 DOTEOT ENOINEEDINO LADODA | | | | |



6.1 Test Data

6.2 AMPS Radiated Measurements

Field Strength of SPURIOUS Radiation

| OPERATING FREQUENCY: | 824 | MHz | |
|------------------------|---------------------------|--------|----------------|
| CHANNEL: | 0991 (| (Low) | _ |
| MEASURED OUTPUT POWER: | 25.729 | dBm = | <u>0.374</u> W |
| MODULATION SIGNAL: | FM (Internal) | | |
| DISTANCE: | 3 | meters | |
| LIMIT: | $43 + 10 \log_{10} (W) =$ | 38.73 | dBc |

| FREQ. | LEVEL @ ANTENNA | SUBSTITUTE ANTENNA | CORRECT GENERATOR | POL | |
|---------|--------------------|-----------------------|----------------------|-------|-------|
| (MHz) | TERMINALS | GAIN | LEVEL | (H/V) | (dBc) |
| | (ubiii) | (ubu) | (ubili) | | |
| 1648.08 | -42.18 | 6.10 | -36.08 | V | 61.8 |
| 2472.12 | -60.68 | 6.70 | -53.98 | V | 79.7 |
| 3296.16 | -55.68 | 6.80 | -48.88 | V | 74.6 |
| 4120.20 | -63.48 | 6.50 | -56.98 | V | 82.7 |
| 4944.24 | -68.18 | 7.00 | -61.18 | V | 86.9 |

NOTES:

Radiated Spurious Emission Measurements by Substitution Method

according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

| PCTESTÔ PT. 22 REPORT | FC | CC MEASUREMENT REP | | Reviewed By: Quality Manager |
|-----------------------|--------------------|-----------------------|----------|---------------------------------|
| Test Report S/N: | Test Dates: | Phone Type: | FCC ID: | Page 14 of 26 |
| 22.240329215.QMN | March 29-31, 2004 | Dual-Mode Single-Band | QMNRM-20 | |



6.3 AMPS Radiated Measurements

Field Strength of SPURIOUS Radiation

| OPERATING FREQUENCY: | 836 | .52 | MHz |
|------------------------|---------------------------|--------|----------------|
| CHANNEL: | 38 | 4 | _ |
| MEASURED OUTPUT POWER: | 25.729 | dBm = | <u>0.374</u> W |
| MODULATION SIGNAL: | FM (Internal) | | |
| DISTANCE: | 3 | meters | |
| LIMIT: | $43 + 10 \log_{10} (W) =$ | 38.73 | dBc |
| | | | |

| FREQ. | LEVEL @ ANTENNA | SUBSTITUTE ANTENNA | CORRECT GENERATOR | POL | |
|---------|--------------------|-----------------------|-----------------------|-------|-------|
| (MHz) | TERMINALS (dBm) | GAIN (dBd) | LEVEL (dBm) | (H/V) | (dBc) |
| 1673.04 | -38.68 | 6.10 | -32.58 | V | 58.3 |
| 2509.56 | -59.28 | 6.70 | -52.58 | V | 78.3 |
| 3346.08 | -52.18 | 6.80 | -45.38 | V | 71.1 |
| 4182.60 | -68.38 | 6.50 | -61.88 | V | 87.6 |
| 5019.12 | -57.78 | 7.00 | -50.78 | V | 76.5 |

NOTES:

Radiated Spurious Emission Measurements by Substitution Method

according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

| | PCTESTÔ PT. 22 REPORT | POTEST FO | CC MEASUREMENT REP | | Reviewed By: Quality Manager |
|---|--------------------------------------|----------------------------------|--------------------------------------|---------------------|---------------------------------|
| Test Report S/N: 22.240329215.QMNTest Dates: March 29-31, 2004Phone Type: Dual-Mode Single-BandFCC ID: | Test Report S/N: 22.240329215.QMN | Test Dates: March 29-31, 2004 | Phone Type: Dual-Mode Single-Band | FCC ID: QMNRM-20 | Page 15 of 26 |



6.4 AMPS Radiated Measurements

Field Strength of SPURIOUS Radiation

| OPERATING FREQUENCY: | 848 | .97 | MHz |
|------------------------|---------------------------|--------|----------------|
| CHANNEL: | 0799 (| High) | _ |
| MEASURED OUTPUT POWER: | 25.729 | dBm = | <u>0.374</u> W |
| MODULATION SIGNAL: | FM (Internal) | | |
| DISTANCE: | 3 | meters | |
| LIMIT: | $43 + 10 \log_{10} (W) =$ | 38.73 | dBc |

| FREQ. | LEVEL @ ANTENNA | SUBSTITUTE ANTENNA | CORRECT GENERATOR | POL | |
|---------|--------------------|-----------------------|----------------------|-------|-------|
| (MHz) | TERMINALS | GAIN (dBd) | LEVEL (dBm) | (H/V) | (dBc) |
| | (abiii) | (dDd) | (dBiii) | | |
| 1697.94 | -41.48 | 6.10 | -35.38 | V | 61.1 |
| 2546.91 | -60.78 | 6.70 | -54.08 | V | 79.8 |
| 3395.88 | -54.48 | 6.80 | -47.68 | V | 73.4 |
| 4244.85 | -60.88 | 6.50 | -54.38 | V | 80.1 |
| 5093.82 | -64.58 | 7.00 | -57.58 | V | 83.3 |

NOTES:

Radiated Spurious Emission Measurements by Substitution Method

according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

| PCTESTÔ PT. 22 REPORT | FC | CC MEASUREMENT REP | | Reviewed By: Quality Manager |
|-----------------------|--------------------|-----------------------|----------|---------------------------------|
| Test Report S/N: | Test Dates: | Phone Type: | FCC ID: | Page 16 of 26 |
| 22.240329215.QMN | March 29-31, 2004 | Dual-Mode Single-Band | QMNRM-20 | |



6.5 CELLULAR CDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

| OPERATING FREQUENCY: | | 70 | MHz |
|------------------------|---------------------------|--------|----------------|
| CHANNEL: | 1013 (| Low) | - |
| MEASURED OUTPUT POWER: | 25.683 | dBm = | <u>0.370</u> W |
| MODULATION SIGNAL: | CDMA (Internal) | | |
| DISTANCE: | 3 | meters | |
| LIMIT: | $43 + 10 \log_{10} (W) =$ | 38.68 | dBc |
| | | | |

| FREQ. | LEVEL @ ANTENNA | SUBSTITUTE ANTENNA | CORRECT GENERATOR | POL | |
|---------|--------------------|-----------------------|----------------------|-------|-------|
| (MHz) | TERMINALS | GAIN (dBd) | LEVEL (dBm) | (H/∨) | (dBc) |
| | (abiii) | | (dDill) | | |
| 1649.40 | -56.38 | 6.10 | -50.28 | Н | 76.0 |
| 2474.10 | -73.28 | 6.70 | -66.58 | н | 92.3 |
| 3298.80 | -60.28 | 6.80 | -53.48 | Н | 79.2 |
| 4123.50 | -66.68 | 6.50 | -60.18 | Н | 85.9 |
| 4948.20 | -84.38 | 7.00 | -77.38 | Н | 103.1 |

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

| PCTESTÔ PT. 22 REPORT | POTEST FO | CC MEASUREMENT REP | | Reviewed By: Quality Manager |
|-----------------------|--------------------|-----------------------|----------|---------------------------------|
| Test Report S/N: | Test Dates: | Phone Type: | FCC ID: | Page 17 of 26 |
| 22.240329215.QMN | March 29-31, 2004 | Dual-Mode Single-Band | QMNRM-20 | |



6.6 CELLULAR CDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

| OPERATING FREQUENCY: | 836. | 52 | MHz |
|------------------------|---------------------------|--------|----------------|
| CHANNEL: | 384 | 4 | _ |
| MEASURED OUTPUT POWER: | 25.683 | dBm = | <u>0.370</u> W |
| MODULATION SIGNAL: | CDMA (Internal) | | |
| DISTANCE: | 3 | meters | |
| LIMIT: | $43 + 10 \log_{10} (W) =$ | 38.68 | dBc |
| | | | |

| FREQ. | LEVEL @ ANTENNA | SUBSTITUTE ANTENNA | CORRECT GENERATOR | POL | |
|---------|--------------------|-----------------------|----------------------|-------|-------|
| (MHz) | TERMINALS (dBm) | GAIN (dBd) | LEVEL (dBm) | (H/V) | (dBc) |
| 1673.04 | -45.08 | 6.10 | -38.98 | Н | 64.7 |
| 2509.56 | -62.58 | 6.70 | -55.88 | Н | 81.6 |
| 3346.08 | -53.18 | 6.80 | -46.38 | Н | 72.1 |
| 4182.60 | -56.18 | 6.50 | -49.68 | н | 75.4 |
| 5019.12 | -83.78 | 7.00 | -76.78 | н | 102.5 |

NOTES:

Radiated Spurious Emission Measurements by Substitution Method

according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

| PCTESTÔ PT. 22 REPORT | FC | CC MEASUREMENT REP | | Reviewed By: Quality Manager |
|-----------------------|--------------------|-----------------------|----------|---------------------------------|
| Test Report S/N: | Test Dates: | Phone Type: | FCC ID: | Page 18 of 26 |
| 22.240329215.QMN | March 29-31, 2004 | Dual-Mode Single-Band | QMNRM-20 | |



6.7 CELLULAR CDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

| OPERATING FREQUENCY: | | .31 | MHz | |
|------------------------|---------------------------|--------|----------------|---|
| CHANNEL: | 0777 (| High) | _ | |
| MEASURED OUTPUT POWER: | 25.683 | dBm = | <u>0.370</u> V | V |
| MODULATION SIGNAL: | CDMA (Internal) | | | |
| DISTANCE: | 3 | meters | | |
| LIMIT: | $43 + 10 \log_{10} (W) =$ | 38.68 | dBc | |
| | | | | |

| FREQ. | LEVEL @ ANTENNA | SUBSTITUTE ANTENNA | CORRECT GENERATOR | POL | |
|---------|---------------------------|-----------------------|-----------------------|-------|-------|
| (MHz) | TERMINALS (dBm) | GAIN (dBd) | LEVEL (dBm) | (H/V) | (dBc) |
| 1696.62 | -52.78 | 6.10 | -46.68 | н | 72.4 |
| 2544.93 | -72.48 | 6.70 | -65.78 | Н | 91.5 |
| 3393.24 | -58.88 | 6.80 | -52.08 | Н | 77.8 |
| 4241.55 | -68.58 | 6.50 | -62.08 | Н | 87.8 |
| 5089.86 | -65.58 | 7.00 | -58.58 | Н | 84.3 |

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

| PCTESTÔ PT. 22 REPORT | POTEST FO | CC MEASUREMENT REP | | Reviewed By: Quality Manager |
|-----------------------|--------------------|-----------------------|----------|---------------------------------|
| Test Report S/N: | Test Dates: | Phone Type: | FCC ID: | Page 19 of 26 |
| 22.240329215.QMN | March 29-31, 2004 | Dual-Mode Single-Band | QMNRM-20 | |



7.2 FREQUENCY STABILITY (AMPS)

OPERATING FREQUENCY: <u>836,520,003</u> Hz CHANNEL: <u>384</u> REFERENCE VOLTAGE: <u>3.7</u> VDC

DEVIATION LIMIT: <u>± 0.00025</u>% or 2.5 ppm

| VOLTAGE | POWER | TEMP | FREQ. | Deviation |
|----------------|-------|------------|-------------|-----------|
| (%) | (VDC) | (°C) | (Hz) | (%) |
| 100 % | 3.70 | + 20 (Ref) | 836,520,003 | 0.000000 |
| 100 % | | - 30 | 836,519,852 | 0.000018 |
| 100 % | | - 20 | 836,519,794 | 0.000025 |
| 100 % | | - 10 | 836,519,760 | 0.000029 |
| 100 % | | 0 | 836,519,744 | 0.000031 |
| 100 % | | + 10 | 836,519,685 | 0.000038 |
| 100 % | | + 20 | 836,520,003 | 0.000000 |
| 100 % | | + 25 | 836,519,936 | 0.00008 |
| 100 % | | + 30 | 836,519,844 | 0.000019 |
| 100 % | | + 40 | 836,519,786 | 0.000026 |
| 100 % | | + 50 | 836,519,760 | 0.000029 |
| 100 % | | + 60 | 836,519,693 | 0.000037 |
| 85 % | 3.15 | + 20 | 836,520,003 | 0.000000 |
| 115 % | 4.26 | + 20 | 836,520,003 | 0.000000 |
| BATT. ENDPOINT | 2.90 | + 20 | 836,520,003 | 0.000000 |

| PCTESTÔ PT. 22 REPORT | FCC MEASUREMENT REPORT | | | Reviewed By: Quality Manager |
|-----------------------|------------------------|-----------------------|----------|--|
| Test Report S/N: | Test Dates: | Phone Type: | FCC ID: | Page 20 of 26 |
| 22.240329215.QMN | March 29-31, 2004 | Dual-Mode Single-Band | QMNRM-20 | |



7.3 FREQUENCY STABILITY (AMPS)



| PCTESTÔ PT. 22 REPORT | FC | C MEASUREMENT REP | ORT NOKIA | Reviewed By: Quality Manager |
|--------------------------------------|---|--------------------------------------|---------------------|---------------------------------|
| Test Report S/N: 22.240329215.QMN | Test Dates: March 29-31, 2004 | Phone Type: Dual-Mode Single-Band | FCC ID: QMNRM-20 | Page 21 of 26 |
| © 2004 DOTEST ENCINEEDING LADODA | | | | |



7.1 Test Data

7.4 FREQUENCY STABILITY (CDMA 800 MHz)

OPERATING FREQUENCY: <u>836,520,002</u> Hz CHANNEL: <u>384</u>

REFERENCE VOLTAGE: ______ 3.7 VDC

DEVIATION LIMIT: <u>± 0.00025</u>% or 2.5 ppm

| VOLTAGE | POWER | ТЕМР | FREQ. | Deviation |
|----------------|-------|------------|-------------|-----------|
| (%) | (VDC) | (°C) | (Hz) | (%) |
| 100 % | 3.70 | + 20 (Ref) | 836,520,002 | 0.000000 |
| 100 % | | - 30 | 836,519,885 | 0.000014 |
| 100 % | | - 20 | 836,519,759 | 0.000029 |
| 100 % | | - 10 | 836,519,684 | 0.000038 |
| 100 % | | 0 | 836,519,718 | 0.000034 |
| 100 % | | + 10 | 836,519,759 | 0.000029 |
| 100 % | | + 20 | 836,520,002 | 0.000000 |
| 100 % | | + 25 | 836,519,877 | 0.000015 |
| 100 % | | + 30 | 836,519,776 | 0.000027 |
| 100 % | | + 40 | 836,519,743 | 0.000031 |
| 100 % | | + 50 | 836,519,701 | 0.000036 |
| 100 % | | + 60 | 836,519,726 | 0.000033 |
| 85 % | 3.15 | + 20 | 836,520,002 | 0.000000 |
| 115 % | 4.26 | + 20 | 836,520,002 | 0.000000 |
| BATT. ENDPOINT | 2.95 | + 20 | 836,520,002 | 0.000000 |

| PCTESTÔ PT. 22 REPORT | FC | C MEASUREMENT REPO | | Reviewed By: Quality Manager |
|-----------------------|--------------------|-----------------------|----------|--|
| Test Report S/N: | Test Dates: | Phone Type: | FCC ID: | Page 22 of 26 |
| 22.240329215.QMN | March 29-31, 2004 | Dual-Mode Single-Band | QMNRM-20 | |



7.5 FREQUENCY STABILITY (AMPS)



| PCTESTÔ PT. 22 REPORT | FC | C MEASUREMENT REP | | Reviewed By: Quality Manager |
|-----------------------|--------------------|-------------------------|----------|---------------------------------|
| Test Report S/N: | Test Dates: | Phone Type : | FCC ID: | Page 23 of 26 |
| 22.240329215.QMN | March 29-31, 2004 | Dual-Mode Single - Band | QMNRM-20 | |



(SEE ATTACHMENT D)

| PCTESTÔ PT. 22 REPORT | FC | C MEASUREMENT REPO | ORT NOKIA | Reviewed By: Quality Manager |
|--------------------------------------|---|--------------------------------------|---------------------|---------------------------------|
| Test Report S/N: 22.240329215.QMN | Test Dates: March 29-31, 2004 | Phone Type: Dual-Mode Single-Band | FCC ID: QMNRM-20 | Page 24 of 26 |
| © 2004 DOTEST ENCINEEDING LADODA | | | | |



9.1 TEST EQUIPMENT

| Туре | Model | Cal. Due Date S/N | | |
|-----------------------------------|---|-----------------------------|------------------------|--|
| Microwave Spectrum Analyzer | 8566B (100Hz-22GHz) HP | 08/15/04 | 3638A08713 | |
| Microwave Spectrum Analyzer | HP 8566B (100Hz-22GHz) | 04/17/04 | 2542A11898 | |
| Spectrum Analyzer/Tracking Gen. | HP 8591A (100Hz-1.8GHz) | 08/10/04 | 3144A02458 | |
| Signal Generator* | HP 8640B (500Hz-1GHz) | 06/03/04 | 2232A19558 | |
| Signal Generator* | HP 8640B (500Hz-1GHz) | 06/03/04 | 1851A09816 | |
| Signal Generator* | Rohde & Schwarz (0.1-1000MHz) | 09/11/04 | 894215/012 | |
| Ailtech/Eaton Receiver | NM 37/57A-SL (30-1000MHz) | 04/12/04 | 0792-032 | |
| Ailtech/Eaton Receiver | NM 37/57A (30-1000MHz) | 03/11/05 | 0805-03334 | |
| Ailtech/Eaton Receiver | NM17/27A (0.1-32MHz) | 09/17/04 | 0608-03241 | |
| Quasi-Peak Adapter | HP 85650A | 08/15/04 | 2043A00301 | |
| Ailtech/Eaton Adapter | CCA-7 CISPR/ANSI OP Adapter | 03/11/05 | 0194-04082 | |
| Gigatronics Universal Power Meter | 8657A | | 1835256 | |
| Gigatronics Power Sensor | 80701A (0.05-18GHz) | | 1833460 | |
| Signal Generator | HP 8648D (9kHz-4GHz) | | 3613A00315 | |
| Amplifier Research | 5S1G4 (5W, 800MHz-4.2GHz) | | 22322 | |
| Network Analyzer | HP 8753E (30kHz-3GHz) | | JP38020182 | |
| Audio Analyzer | HP 8903B | | 3011A09025 | |
| Modulation Analyzer | HP 8901A | | 2432A03467 | |
| PowerMeter | HP 437B | | 3125U24437 | |
| Power Sensor | HP 8482H (3QuW-3W) | | 2237A02084 | |
| Harmonic/Flicker | Test System HP 6841A (IEC 555-2/3) | | 3531A00115 | |
| Broadband Amplifier (2) | HP 8447D | | 1145A00470, 1937A03348 | |
| Broadband Amplifier | HP 8447F | | 2443A03784 | |
| Hom Antenna ' | EMCO Model 3115 (1-18GHz) | | 9704-5182 | |
| Hom Antenna | EMCO Model 3115 (1-18GHz) | | 9205-3874 | |
| Hom Antenna | EMCO Model 3116 (18-40GHz) | | 9203-2178 | |
| Biconical Antenna (4) | Eaton94455/Eaton94455-1/Singer94455-1/0 | amplanceDesign | 1295, 1332, 0355 | |
| Log-Spiral Antenna (3) | Ailtech/Eaton 93490-1 | 1 5 | 0608, 1103, 1104 | |
| Roberts Dipoles | Compliance Design (1 set) | | | |
| Ailtech Dipoles | DM-105A (1 set) | | 33448-111 | |
| EMCOLIŚN (6) | 3816/2 | | 1079 | |
| Microwave Preamplifier 40dB | Gain HP 83017A (0.5-26.5GHz) | | 3123A00181 | |
| Microwave Cables | MicroCoax (1.0-26.5GHz) | | | |
| Ailtech/Eaton Receiver | NM37/57A-SL | | 0792-03271 | |
| Spectrum Analyzer | HP 8594A | | 3051A00187 | |
| Spectrum Analyzer (2) | HP 8591A | | 3034A01395, 3108A02053 | |
| Microwave Survey Meter | Holaday Model 1501 (2.450GHz) | | 80931 | |
| Digital Thermometer | Extech Instruments 421305 | | 426966 | |
| Attenuator | HP 8495A (0-70dB) DC-4GHz | | | |
| Bi-Directional Coax Coupler | Narda 3020A (50-1000MHz) | | | |
| Shielded Screen Room | RF Lindgren Model 26-2/2-0 | | 6710 (PCT270) | |
| Shielded Semi-Anechoic Chamber | Ray Proof Model S81 | | R2437 (PCT278) | |
| Enviromental Chamber | Associated Systems Model 1025 (Tem | nperature/Humidity) | PCT285 | |
| * Calibra | tion traceable to the National Institute of S | Standards and Technology (1 | VIST). | |

| PCTESTÔ PT. 22 REPORT | FC | C MEASUREMENT REPO | | Reviewed By: Quality Manager |
|-----------------------|--------------------|-----------------------|----------|--|
| Test Report S/N: | Test Dates: | Phone Type: | FCC ID: | Page 25 of 26 |
| 22.240329215.QMN | March 29-31, 2004 | Dual-Mode Single-Band | QMNRM-20 | |



10.1 SAMPLE CALCULATIONS

A. Emission Designator

Emission Designator = 1M25F9W

CDMA BW = 1.25 MHz F = Frequency Modulation 9 = Composite Digital Info W = Combination (Audio/Data) (Measured at the 99.75% power bandwidth)

Emission Designator = 40K0F8W

| Calculation: | Voice + SAT |
|--------------|---|
| Modulation: | Voice is 2.5 kHz and SAT is 6 kHz – Maximum modulation is M = 6 kHz |
| Deviation: | Voice is 12 kHz and SAT is 2 kHz – Maximum deviation is D = 12 + 2 = 14 kHz |
| Bn = | 2xM + 2xDK with K = 1 |
| Bn = | 40 kHz |
| Calculation: | Signaling Tone (ST) + SAT |
| Modulation: | ST is 10 kHz and SAT is 6 kHz – Maximum modulation is M = 10 kHz |
| Deviation: | ST is 8 kHz and SAT is 2 kHz – Maximum deviation is D = 8 + 2 = 10 kHz |
| Bn = | 2xM + 2xDK with K = 1 |
| Bn = | 40 kHz |

Emission Designator = 40K0F1D

Calculation:Voice + SATModulation:Wideband Data is 10 kHz and SAT is 6 kHz – Maximum modulation is M = 10 kHzDeviation:Wideband Data is 8 kHz and SAT is 2 kHz – Maximum deviation is D = 8 + 2 = 10 kHzBn =2xM + 2xDK with K = 1Bn =40 kHz

B. Spurious Radiated Emission - PCS Band

Example: Channel 25 PCS Mode 2nd Harmonic (3702.50 MHz)

The receive analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the receive analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3702.50 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm -(-24.80) = 50.3 dBc

| PCTESTÔ PT. 22 REPORT | | | | Reviewed By: Quality Manager |
|-----------------------|--------------------|-----------------------|----------|---------------------------------|
| Test Report S/N: | Test Dates: | Phone Type: | FCC ID: | Page 26 of 26 |
| 22.240329215.QMN | March 29-31, 2004 | Dual-Mode Single-Band | QMNRM-20 | |



11.1 CONCLUSION

The data collected shows that the **NOKIA MOBILE PHONES INC. Dual-Mode Single-Band Phone (AMPS/CDMA)** FCC ID: QMNRM-20 complies with all the requirements of Parts 2 and 22 of the FCC rules.

| PCTESTÔ PT. 22 REPORT | FC | C MEASUREMENT REP | ORT NOKIA | Reviewed By: Quality Manager |
|--------------------------------------|---|--------------------------------------|---------------------|---------------------------------|
| Test Report S/N: 22.240329215.QMN | Test Dates: March 29-31, 2004 | Phone Type: Dual-Mode Single-Band | FCC ID: QMNRM-20 | Page 27 of 26 |
| @ 2004 DOTEST ENCINEEDING LADODA | TODY INC | | | |

| | Freq/Channel | | | |
|--|--|--|--|--|
| FCC ID: QMNRM-20 Cond Spurs FM Ch. 0991 Mkr1 1.649 G Ref 25.29 dBm #Atten 30 dB -34.29 dB #Peak | Center Freq 1.25500000 GHz | | | |
| Log 10 dB/ Offst | Start Freq 10.0000000 MHz | | | |
| 16.3 dB DI | Stop Freq 2.5000000 GHz | | | |
| -13.0 dBm LgAv | CF Step 249.000000 MHz <u>Auto Man</u> | | | |
| V1 S2 Million of the second of | Freq Offset 0.00000000 Hz | | | |
| ¤(f): FTun Swp | Signal Track On <u>Off</u> | | | |
| Start 10 MHz Stop 2.500 G #Res BW 1 MHz #VBW 1 MHz Sweep 4.192 ms (999 pts) | Hz | | | |
| Copyright 2000-2002 Agilent Technologies | | | | |



| 🔆 Agilent L | Freq/Channel | | | |
|--|--|--|--|--|
| FCC ID: QMNRM-20 Cond Spurs FM Ch. 0384 Mkr1 1.649 G Ref 25.31 dBm #Atten 30 dB -34.02 dB #Peak | m Center Freq 1.25500000 GHz | | | |
| Log 10 dB/ | Start Freq 10.0000000 MHz | | | |
| 16.3 dB DI | Stop Freq 2.5000000 GHz | | | |
| -13.0 dBm LgAv | CF Step 249.000000 MHz <u>Auto Mar</u> | | | |
| V1 S2 Washington washington and the state of | Freq Offset 0.00000000 Hz | | | |
| ¤(f): FTun Swp | Signal Track On <u>Off</u> | | | |
| Start 10 MHz Stop 2.500 G #Res BW 1 MHz #VBW 1 MHz Sweep 4.192 ms (999 pts | Hz) | | | |
| Copyright 2000-2002 Agilent Technologies | | | | |



| 🔆 Agilent | L Freq/Channel | | | | |
|---|--|--|--|--|--|
| FCC ID: QMNRM-20 Cond Spurs FM Ch. 0799 Mkr1 1.649 Ref 25.22 dBm #Atten 30 dB -33.67 #Peak | GHz dBm 1.25500000 GHz | | | | |
| Log 10 dB/ | Start Freq 10.0000000 MHz | | | | |
| 16.3 dB DI | Stop Freq 2.5000000 GHz | | | | |
| -13.0 dBm LgAv <u>1</u> | CF Step 249.000000 MHz <u>Auto Mar</u> | | | | |
| V1 S2 Windowson and a state of the state of | Freq Offset 0.00000000 Hz | | | | |
| ¤(f): FTun Swp | Signal Track On <u>Off</u> | | | | |
| Start 10 MHz Stop 2.500 #Res BW 1 MHz #VBW 1 MHz Sweep 4.192 ms (999 p | I GHz pts) | | | | |
| Copyright 2000-2002 Agilent Technologies | | | | | |



| 🔆 Agilent | | L | Freq/Channel | |
|--|---|--|--|--|
| FCC ID: QMNRM-20 Cond Spurs CDMA (Ref 24.83 dBm Atten 20 dB #Peak | Ch. 1013 | Mkr1 1.649 GHz -39.70 dBm | Center Freq 1.25500000 GHz | |
| Log 10 dB/ | | | Start Freq 10.0000000 MHz | |
| 16.3 dB DI | | | Stop Freq 2.5000000 GHz | |
| -13.0 dBm LgAv | | | CF Step 249.000000 MHz <u>Auto Mar</u> | |
| V1 S2 S3 FC | 1 10-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1 | ويعافدون والمنافع المعالية والمعالية والمعالية والمعالية والمعالية | Freq Offset 0.00000000 Hz | |
| ¤(f): FTun Swp | | | Signal Track ^{On <u>Off</u>} | |
| Start 10 MHz #Res BW 1 MHz #VB | W 1 MHz Sweep | Stop 2.500 GHz 4.192 ms (999 pts) | | |
| Copyright 2000-2002 Agilent Technologies | | | | |



| 🔆 Agilent | | L | Freq/Channel | |
|--|--|---|--|--|
| FCC ID: QMNRM-20 Cond Spurs Ref 24.88 dBm Atten 20 #Peak | : CDMA Ch. 0384) dB | Mkr1 1.672 GHz -32.44 dBm | Center Freq 1.25500000 GHz | |
| Log 10 dB/ | | | Start Freq 10.0000000 MHz | |
| 16.3 dB DI | | | Stop Freq 2.5000000 GHz | |
| -13.0 dBm LgAv | | 1 \$ | CF Step 249.000000 MHz <u>Auto Mar</u> | |
| V1 S2 S3 FC | ฟ้า เป็นข้อเป็นผู้ได้รับมีรายหรือนรู้ในสูงเหลือเป็นเสียง | 44444 | Freq Offset 0.00000000 Hz | |
| ¤(f): FTun Swp | | | Signal Track ^{On <u>Off</u>} | |
| Start 10 MHz #Res BW 1 MHz | #VBW 1 MHz Sv | Stop 2.500 GHz veep 4.192 ms (999 pts) | | |
| Copyright 2000-2002 Agilent Technologies | | | | |



| 🔆 Agilent L | Freq/Channel | | | |
|--|--|--|--|--|
| FCC ID: QMNRM-20 Cond Spurs CDMA Ch. 0777 Mkr1 1.697 (Ref 24.85 dBm Atten 20 dB -35.63 dB #Peak | GHz Bm 1.25500000 GHz | | | |
| Log 10 dB/ | Start Freq 10.0000000 MHz | | | |
| 16.3 dB DI | Stop Freq 2.5000000 GHz | | | |
| -13.0 dBm LgAv | CF Step 249.000000 MHz <u>Auto Mar</u> | | | |
| | Freq Offset 0.00000000 Hz | | | |
| #(f): FTun Swp | Signal Track On <u>Off</u> | | | |
| Start 10 MHz Stop 2.500 (#Res BW 1 MHz #VBW 1 MHz Sweep 4.192 ms (999 pt | GHz s) | | | |
| Copyright 2000-2002 Agilent Technologies | | | | |















| 🔆 Agilent | RL | Freq/Channel | | | |
|---|--|--|--|--|--|
| FCC ID: QMNRM-20 Band Edge CDMA Ch. 1013 Ref 24.83 dBm #Atten 30 dB #Peak | Mkr1 824.000 MHz -17.537 dBm | Center Freq 824.000000 MHz | | | |
| Log 10 dB/ Offst | Non-on- provincing to a per- | Start Freq 823.000000 MHz | | | |
| DI | | Stop Freq 825.00000 MHz | | | |
| -13.0 dBm LgAv | | CF Step 200.000000 kHz Auto Mar | | | |
| 100 W1 S2 S3 FS | | Freq Offset 0.00000000 Hz | | | |
| ¤(f): f>50k Swp | | Signal Track ^{On <u>Off</u>} | | | |
| Start 823.000 MHz #Res BW 13 kHz #VBW 13 kHz Swe | Stop 825.000 MHz ep 14.3 ms (999 pts) | | | | |
| Copyright 2000-2002 Agilent Technologies | | | | | |



| 🔆 Agilent | | | | | | F | R L | Freq/Channel |
|--|------------------|--------------------------------|--------------------------|-----|-----------------|--------------------------|---------------|--|
| FCC ID: QMI Ref 24.83 dl #Peak | NRM-2041 3m 7 | MHz Span #Atten 30 (| CDMA Ch. 1 1 B | 013 | M | kr1 822.91 -32.982 | 2 MHz dBm | Center Freq 821.000000 MHz |
| Log 10 dB/ | | | | | | | | Start Freq 819.00000 MHz |
| 16.3 dB | | | | | | | | Stop Freq 823.00000 MHz |
| -13.0 dBm LgAv | | | | | | | 1 | CF Step 400.000000 kHz <u>Auto Mar</u> |
| 100 V1 S2 S3 FS | | | | (| the part of the | ~~~~~ | - AND | Freq Offset 0.00000000 Hz |
| ¤(f): f>50k Swp | h-p-campa | 100 mm | | | | | | Signal Track ^{On <u>Off</u>} |
| Start 819.00 #Res BW 10 | 0 MHz 0 kHz | | #VBW 100 | kHz | S Sweep 1.0 | top 823.00 65 ms (999 | 0 MHz pts) | |
| Copyright 2000-2002 Agilent Technologies | | | | | | | | |







SPECTRUM ANALYZER PRESENTATION

FCC ID:QMNRM-20 NOKIA Dual-Mode Phone FM Channel 384 Operating Frequency: 836.520 MHz Output Power : 25.3 dBm

Test Mode:SAT + Voice



SPECTRUM ANALYZER PRESENTATION

FCC ID:QMNRM-20 NOKIA Dual-Mode Phone FM Channel 384 Operating Frequency: 836.520 MHz Output Power : 25.3 dBm

Test Mode:SAT + DTMF



SPECTRUM ANALYZER PRESENTATION

FCC ID:QMNRM-20 NOKIA Dual-Mode Phone FM Channel 384 Operating Frequency: 836.520 MHz Output Power : 25.3 dBm



Test Mode:SAT + ST

SPECTRUM ANALYZER PRESENTATION

FCC ID:QMNRM-20 NOKIA Dual-Mode Phone FM Channel 384 Operating Frequency: 836.520 MHz Output Power : 25.3 dBm





SPECTRUM ANALYZER PRESENTATION

FCC ID:QMNRM-20 NOKIA Dual-Mode Phone FM Channel 384 Operating Frequency: 836.520 MHz Output Power : 25.3 dBm





SPECTRUM ANALYZER PRESENTATION

FCC ID:QMNRM-20 NOKIA Dual-Mode Phone FM Channel 384 Operating Frequency: 836.520 MHz Output Power : 25.3 dBm



Test Mode:Wide Band Data

SPECTRUM ANALYZER PRESENTATION

FCC ID:QMNRM-20 NOKIA Dual-Mode Phone FM Channel 384 Operating Frequency: 836.520 MHz Output Power : 25.3 dBm

Test Mode:Voice



SPECTRUM ANALYZER PRESENTATION

FCC ID:QMNRM-20 NOKIA Dual-Mode Phone FM Channel 384 Operating Frequency: 836.520 MHz Output Power : 25.3 dBm



Test Mode:Unmodulated Signal





PCTEST Engineering Lab., Inc.

SUBJECT: Modulation Characteristics FCC Part 22
 Test Report No.:
 22.240329215.QMN

 Test Date:
 03.29-31.2004

EUT: Dual-Mode Single-Band Phone (AMPS/CDMA)

Model: 6012

FCC ID: QMNRH-20

REFERENCE: 1 kHz = 0 dB



NOKIA Dual-Mode Single-Band Phone (AMPS/CDMA) FCC ID: QMNRH-20

PCTEST Engineering Lab., Inc.

SUBJECT: Modulation Characteristics FCC Part 22

Test Date:

Test Report No.: 22.240329215.QMN 03.29-31.2004

EUT: Dual-Mode Single-Band Phone (AMPS/CDMA) Model: 6012 FCC ID: QMNRH-20

REFERENCE: 1 kHz = 0 dB

