



Test Report No.: SA161212W008



RF EXPOSURE REPORT

Product: BT Remote

Model Name: BTRP

FCC ID: IKQBTRP

Applicant: Scosche Industries Inc

Address: 1550 Pacific Avenue, Oxnard, CA 93033, United States

Manufacturer: Scosche Industries Inc

Address: 1550 Pacific Avenue, Oxnard, CA 93033, United States

Prepared by: Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch

Lab Location: No. 34, Chenwulu Section, Guantai Rd., Houjie Town,
Dongguan City, Guangdong 523942, China

TEL: +86 769 8593 5656

FAX: +86 769 8593 1080

E-MAIL: customerservice.dg@cn.bureauveritas.com

Report No.: SA161212W008

Received Date: Dec. 12, 2016

Test Date: Feb. 07, 2017 ~ Feb. 17, 2017

Issued Date: Feb. 20, 2017

This report should not be used by the client to claim product certification, approval, or endorsement by A2LA or any government agencies.

Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



Test Report No.: SA161212W008

TABLE OF CONTENTS

RF EXPOSURE REPORT	1
RELEASE CONTROL RECORD	3
1 CERTIFICATION	4
2 GENERAL INFORMATI.....	5
2.1 GENERAL DESCRIPTION OF EUT	5
3 RF EXPOSURE	6
3.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)	6
3.2 MPE CALCULATION FORMULA.....	6
3.4 CONDUCTED POWER	7
3.5 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	7



Test Report No.: SA161212W008

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA161212W008	Original release	Feb. 20, 2017



Test Report No.: SA161212W008

1 CERTIFICATION

PRODUCT: BT Remote
BRAND NAME: *SCOSCHE*
MODEL NAME: BTRP
APPLICANT: Scosche Industries Inc
TESTED: Feb. 07, 2017 ~ Feb. 17, 2017
TEST SAMPLE: Identical Prototype
STANDARDS: **FCC Part 2 (Section 2.1091)**
FCC OET Bulletin 65, Supplement C (01-01)
IEEE C95.1

The above equipment has been tested by **Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch** and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Harry, **DATE:** Feb. 20, 2017
(Harry Li/ Engineer)

APPROVED BY : Sam Tung, **DATE:** Feb. 20, 2017
(Sam Tung / Manager)

2 GENERAL INFORMATI

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	BT Remote
MODEL NAME	BTRP
FCC ID	IKQBTRP
NOMINAL VOLTAGE	DC 3.0V
MODULATION TECHNOLOGY	DTS
MODULATION TYPE	BT-LE(GFSK) for DTS
TRANSMISSION RATE	BT_LE: 1Mbps
OPERATING FREQUENCY	2402-2480MHz
MAX. OUTPUT POWER	BT-LE: 0.302mW (Maximum)
ANTENNA TYPE	PCB Antenna with 0dBi gain
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	N/A

NOTE:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- The EUT incorporates a SISO function. Physically, the EUT provides one transmitter and one receiver.

MODULATION MODE	TX/RX FUNCTION
BT_LE	1TX /1RX

- For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

3 RF EXPOSURE

3.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

3.2 MPE CALCULATION FORMULA

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

3.4 CONDUCTED POWER

BT-LE (GFSK)

PEAK OUTPUT POWER

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
0	2402	-5.20	0.302	1	PASS
19	2440	-5.91	0.256	1	PASS
39	2480	-6.61	0.218	1	PASS

AVERAGE OUTPUT POWER

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
0	2402	-5.27	N/A
19	2440	-5.95	N/A
39	2480	-6.66	N/A

3.5 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

BT-LE (GFSK)

OPERATING BAND(MHz)	Output Power E.I.R.P. (dBm)	Output Power E.I.R.P. (mW)	Power Density (mW/cm ²)	limit (mW/cm ²)	Evaluation Result
2402~2480	-5.0	0.316	0	1	N/A

Remark: The "N/A" means that, this device complies with FCC's RF radiation exposure limits for general population without SAR evaluation.