

Smart Protective Film Plotter ZC1 Max (V1.0)

Model: ZC1-A(V1.0)


Product Manual

(This equipment is also called film cutting machine, protective film cutting machine)






Product List



Appearance And Function



1 Driver

Control the lateral movement of the Blade Kit

Blade Kit

Cutting protective film See details 10, 11, 12, 13

- Platen Roller
 Fixes protecive film
- 4 Lateral Panel
 Set limit of position and movement for protective film

- 6 Operation Display
 Touch to control device operation
- 6 Power Switch Starting device
- Power Interface
- Link power


 Pressing Bar
 - Press to control the platen roller to lift or fall
- Blade Kit Clamp Lock the knife handle to secure the blade kit






Instructions

1. Install Blade Kit



2. Power On



Connect the power cord to the adapter and then connect the power cord to the power socket. To ensure the normal operation of the device, please use 100-240 volts AC power; Connect the adapter to the power interface of the device; Install the blade kit on the knife holder to ensure it is fixed correctly. After connecting, press [Power Switch] to start the device.



3. Cut Film

When using it for the first time, you need to click [select language] to complete the language setting, then you need to click [set WIFI] to complete WIFI connection.






 Please prepare a protective film to be cut as shown in the figure. Confirm that the protective film is flat and complete, without bending, folding or missing layer.






(2) Press down the pressing bar to lift the platen roller, and place the protective film in the dotted area as shown.





(3) Slowly lift the pressing bar so that the platen roller presses the protective film.



(4) After the system starting normally, enter the home page.



(5) Enter keywords in the search box, search for the product model you need to cut and select the film code of the corresponding specification according to the recommended guidelines on the screen.






(6) After confirming the relevant information, click [OK] to start cutting the film.



(7) After cutting, the protective film will be pushed out automatically. Take out the protective film and finish cutting.



4. Activate Film Code

Enter [Consumable identification code] found on the protective film package box, and then click [ADD].



Product Specification		
Control Panel	5.5 inch color LCD capacitive screen	
Network Interface	2.4G/5G Wireless LAN	
Input	100-240V 1.5A 50-60Hz	
Output	24V 2.7A	
Power	64.8w	
Size	613*220*174mm	
Net Weight	7.1kg	

ivet weight		7.1Kg
Cautions		
	Don't touch the tip of the blade with your finger. It may hurt your finger.	
	Liquid or metal objects are not allowed to enter into the machine. These objects may cause fires.	
	Do not destroy or arbitrarily replace the original power cord. Do not bend, pull or bind the power cord excessively or place the power cord under heavy object. This may cause damage to the power supply, resulting in an electric shock or fire.	
	If you do not use the device for a long time, remove the power cord from the socket. Otherwise, it may cause a fire.	
		device should be placed on a firm surface erwise, the device may fall down and get damaged
EE	When the power cord is unplugged from the socket, the plug should be unplugged instead of the cable. Pulling a cable strongly may cause an electric shock or fire.	
[(Anne)	It is forbidden to use in thunderstorm and lightning weather Lest the machine be damaged by electric shocks.	



5. How to Install the Film





Wipe the screen with the cleaning kit





Tear off the outer frame of the film from the tearing position at the upper right corner of the front of the film:





Place the film flat y and remove the white release film;





Remove the hole film and tear off the middle aux 'ary strip; (Please fix the film with your index and middle fingers);





Place the film flatly on the screen and ho e of the phone precisely and press the auxiliary strip (Be careful not to touch either end of the aux ary strip);





Lift the upper part of the film and pull back 2cm, then push forward slowly with a scratch card from the middle of the auxiliary strip;





Then lift the lower part of the film and pull back 2cm, then push forward forcefully with a scratch card;





Use a cleaning c oth to smooth the curved surface if necessary;





Finally uncover the surface PET film and finish installing the film



Precautions





Please don't move the driver manually when powered on to avoid damage to the machine.



Please don't touch or bump the blade against anything hard for it is sharp and fragile.



In order to ensure perfect cutting effect, it is suggested to replace the blade and the rubber strip every 500 times of cutting or 3 months of use.



Please shut down the machine normally through the App, and please don't unplug the power cable directly, for it may cause irreversible damage to the machine.



If you are a user beyond China, please scan the QR code to follow us on Facebook for more information.

FCC Warning Statement

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment. This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However. there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception. which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- - Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

FCC Radiation Exposure Statement

The antennas used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co - located for operating in conjunction with any other antenna or transmitter.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1)This device may not cause harmful interference, and (2)This device must accept any interference received, including interference that may cause undesired operation.