

RF Exposure Report

Report No.: SA150407E02A

Compliance ID: ADBA-SX14015A

Product Name*: ADB-1761W

*For any other product variant refer to above Compliance ID

FCC ID: MCLADB1761W

Received Date: Feb. 11, 2015

Test Date: May 09, 2015

Issued Date: May 28, 2015

Applicant: HON HAI PRECISION IND. CO., LTD.

Address: 5F-1,5 Hsin-An Road Hsinchu, Science-Based Industrial Park Taiwan,

R.O.C.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Hsin Chu Laboratory

Lab Address: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin

Chu Hsien 307, Taiwan R.O.C.

Test Location (1): No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin

Chu Hsien 307, Taiwan R.O.C.

Test Location (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin

Chu Hsien 307, Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

Report No.: SA150407E02A Page No. 1 / 5 Report Format Version: 6.1.1 Reference No.: 150408E06



Table of Contents

Relea	ase Control Record	3
1	Certificate of Conformity	4
2	RF Exposure	5
	Limits for Maximum Permissible Exposure (MPE)	
	MPE Calculation Formula	
_	Classification	_
2.4	Antenna Gain	5
3	Calculation Result Of Maximum Conducted Power	5



Release Control Record

Issue No.	Description	Date Issued
SA150407E02A	Original release.	May 28, 2015

Page No. 3 / 5 Report Format Version: 6.1.1

Report No.: SA150407E02A Reference No.: 150408E06



1 Certificate of Conformity

Compliance ID: ADBA-SX14015A

Product Name*: ADB-1761W

Product Description: IP Set-Top Box

*For any other product variant refer to above Compliance ID

Brand: ADB

Sample Status: ENGINEERING SAMPLE

Applicant: HON HAI PRECISION IND. CO., LTD.

7,118

Test Date: May 09, 2015

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D03

IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by:	Com	,Date:	May 28, 2015	
	Elsie Hsu / Specialist			

Approved by: ______, Date: ______, May 28, 2015

Report No.: SA150407E02A Reference No.: 150408E06



2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range Electric Field Magnetic F (MHz) Strength (V/m) Strength (A			Power Density (mW/cm ²)	Average Time (minutes)			
	Limits For General Population / Uncontrolled Exposure						
300-1500 F/1500 30							
1500-100,000			1.0	30			

F = Frequency in MHz

2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

The antennas provided to the EUT, please refer to the following table:

	Antenna No.	Transmitter Circuit	Brand	Model	Ant. Gain(dBi) <including cable="" loss=""></including>	Frequency range (GHz to GHz)	Antenna Type	Connecter Type
-	1	Chain (0)	INIDAO	NA	2.78	2.4~2.5	DIEA	71
	2	Chain (1)	INPAQ	NA	2.45	2.4~2.5	PIFA	NA

3 Calculation Result Of Maximum Conducted Power

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm²)
2405-2480	1.959	2.78	20	0.00074	1

--- END ---

Report No.: SA150407E02A Page No. 5 / 5 Report Format Version: 6.1.1 Reference No.: 150408E06