

FCC TEST REPORT

FCC ID: 2BOQV-M11

Report No. : SSP25040239-1E

Applicant : Gesheng Intelligent Technology (Shenzhen) Co., Ltd

Product Name : Headphones

Model Name : M11

Test Standard : FCC Part 15.247

Date of Issue : 2025-04-27




Shenzhen CCUT Quality Technology Co., Ltd.

1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen,
Guangdong, China; (Tel.:+86-755-23406590 website: www.ccuttest.com)

This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.

Test Report Basic Information

Applicant:	Gesheng Intelligent Technology (Shenzhen) Co., Ltd 1811, Block B, Zhantao Technology Building, Minzhi Street, Longhua District, Shenzhen, China
Manufacturer:	Gesheng Intelligent Technology (Shenzhen) Co., Ltd 1811, Block B, Zhantao Technology Building, Minzhi Street, Longhua District, Shenzhen, China
Product Name:	Headphones
Brand Name:	-
Main Model:	M11
Series Models:	-
Test Standard:	FCC Part 15 Subpart C ANSI C63.4-2014 ANSI C63.10-2013
Date of Test	2025-04-16 to 2025-04-27
Test Result:	PASS
Tested By	<u>Coke Huang</u> (Coke Huang)
Reviewed By:	<u>Lieber Ouyang</u> (Lieber Ouyang)
Authorized Signatory:	<u>Lahm Peng</u> (Lahm Peng)



Note : This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.. All test data presented in this test report is only applicable to presented test sample.

CONTENTS

1. General Information.....	5
1.1 Product Information	5
1.2 Test Setup Information.....	6
1.3 Compliance Standards.....	7
1.4 Test Facilities.....	7
1.5 List of Measurement Instruments	8
1.6 Measurement Uncertainty	9
2. Summary of Test Results	10
3. Antenna Requirement.....	11
3.1 Standard and Limit.....	11
3.2 Test Result	11
4. Conducted Emissions	12
4.1 Standard and Limit.....	12
4.2 Test Procedure.....	12
4.3 Test Data and Results	13
5. Radiated Emissions	16
5.1 Standard and Limit.....	16
5.2 Test Procedure.....	16
5.3 Test Data and Results	18
6. Band-edge Emissions(Radiated)	22
6.1 Standard and Limit.....	22
6.2 Test Procedure.....	22
6.3 Test Data and Results	22
7. Frequency Hopping System.....	24
7.1 Standard and Limit.....	24
7.2 Test Procedure.....	24
7.3 Test Data and Results	25
8. Dwell Time.....	26
8.1 Standard and Limit.....	26
8.2 Test Procedure.....	26
8.3 Test Data and Results	27
9. Maximum Peak Conducted Output Power	31
9.1 Standard and Limit.....	31
9.2 Test Procedure.....	31
9.3 Test Data and Results	31
10. Occupied Bandwidth(-20dB)	34
10.1 Standard and Limit.....	34
10.2 Test Procedure.....	34
10.3 Test Data and Results	34
11. Carrier Frequencies Separation.....	38
11.1 Standard and Limit.....	38
11.2 Test Procedure.....	38
11.3 Test Data and Results	38
12. Number of Hopping Channel.....	41
12.1 Standard and Limit.....	41
12.2 Test Procedure.....	41
12.3 Test Data and Results	41
13. Band-edge Emission(Conducted).....	43
13.1 Standard and Limit.....	43
13.2 Test Procedure.....	43
13.3 Test Data and Results	43
14. Conducted RF Spurious Emissions.....	49
14.1 Standard and Limit.....	49
14.2 Test Procedure.....	49
14.3 Test Data and Results	49

Revision History

Revision	Issue Date	Description	Revised By
V1.0	2025-04-27	Initial Release	Lahm Peng

1. General Information

1.1 Product Information

Product Name:	Headphones
Trade Name:	-
Main Model:	M11
Series Models:	-
Rated Voltage:	DC 3.8V by battery, USB 5V Charging
Power Adapter:	-
Battery:	DC 3.8V, 100mAh
Test Sample No:	SSP25040239-1
Hardware Version:	V1.0
Software Version:	V230
Note 1: The test data is gathered from a production sample, provided by the manufacturer.	

Wireless Specification	
Wireless Standard:	Bluetooth BR/EDR
Operating Frequency:	2402MHz ~ 2480MHz
RF Output Power:	-2.68dBm
Number of Channel:	79
Channel Separation:	1MHz
Modulation:	GFSK, Pi/4 DQPSK, 8DPSK
Antenna Gain:	2.7dBi
Type of Antenna:	SMD Antenna
Type of Device:	<input checked="" type="checkbox"/> Portable Device <input type="checkbox"/> Mobile Device <input type="checkbox"/> Modular Device

1.2 Test Setup Information

List of Test Modes			
Test Mode	Description	Remark	
TM1	Lowest Channel	2402MHz(DH5/2DH5/3DH5)	
TM2	Middle Channel	2441MHz(DH5/2DH5/3DH5)	
TM3	Highest Channel	2480MHz(DH5/2DH5/3DH5)	
TM4	Hopping	2402MHz~2480MHz	
TM5	Charging	AC 120V/60Hz	
List and Details of Auxiliary Cable			
Description	Length (cm)	Shielded/Unshielded	With/Without Ferrite
-	-	-	-
-	-	-	-
List and Details of Auxiliary Equipment			
Description	Manufacturer	Model	Serial Number
Adapter	HUAWEI	HW-110600C02	JL28L4P2D06114
-	-	-	-

List of Channels							
No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)
01	2402	21	2422	41	2442	61	2462
02	2403	22	2423	42	2443	62	2463
03	2404	23	2424	43	2444	63	2464
04	2405	24	2425	44	2445	64	2465
05	2406	25	2426	45	2446	65	2466
~	~	~	~	~	~	~	~
16	2417	36	2437	56	2457	76	2477
17	2418	37	2438	57	2458	77	2478
18	2419	38	2439	58	2459	78	2479
19	2420	39	2440	59	2460	79	2480
20	2421	40	2441	60	2461		

1.3 Compliance Standards

Compliance Standards	
FCC Part 15 Subpart C	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Intentional Radiators
All measurements contained in this report were conducted with all above standards	
According to standards for test methodology	
FCC Part 15 Subpart C	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Intentional Radiators
ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.
ANSI C63.10-2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
Maintenance of compliance is the responsibility of the manufacturer or applicant. Any modification of the product, which result is lowering the emission, should be checked to ensure compliance has been maintained.	

1.4 Test Facilities

Laboratory Name:	Shenzhen CCUT Quality Technology Co., Ltd. 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China
CNAS Laboratory No.:	L18863
A2LA Certificate No.:	6893.01
FCC Registration No:	583813
ISED Registration No.:	CN0164
All measurement facilities used to collect the measurement data are located at 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China.	

1.5 List of Measurement Instruments

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Conducted Emissions					
AMN	ROHDE&SCHWARZ	ENV216	101097	2024-08-07	2025-08-06
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100242	2024-08-07	2025-08-06
Test Cable	N/A	Cable 5	N/A	2024-08-07	2025-08-06
EMI Test Software	FARA	EZ-EMC	EMEC-3A1+	N/A	N/A
Radiated Emissions					
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100154	2024-08-07	2025-08-06
Spectrum Analyzer	KEYSIGHT	N9020A	MY48030972	2024-08-07	2025-08-06
Spectrum Analyzer	ROHDE&SCHWARZ	FSV40-N	101692	2024-08-07	2025-08-06
Amplifier	SCHWARZBECK	BBV 9743B	00251	2024-08-07	2025-08-06
Amplifier	HUABO	YXL0518-2.5-45	--	2024-08-07	2025-08-06
Amplifier	COM-MW	DLAN-18G-4G-02	10229104	2024-08-07	2025-08-06
Loop Antenna	DAZE	ZN30900C	21104	2024-08-03	2025-08-02
Broadband Antenna	SCHWARZBECK	VULB 9168	01320	2024-08-03	2025-08-02
Horn Antenna	SCHWARZBECK	BBHA 9120D	02553	2024-08-03	2025-08-02
Horn Antenna	COM-MW	ZLB7-18-40G-950	12221225	2024-08-03	2025-08-02
Attenuator	QUANJUDA	6dB	220731	2024-08-07	2025-08-06
Test Cable	N/A	Cable 1	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 2	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 3	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 4	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 8	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 9	N/A	2024-08-07	2025-08-06
EMI Test Software	FARA	EZ-EMC	FA-03A2 RE+	N/A	N/A
Conducted RF Testing					
RF Test System	MWRFTTest	MW100-RFCB	220418SQS-37	2024-08-07	2025-08-06
Spectrum Analyzer	KEYSIGHT	N9020A	ATO-90521	2024-08-07	2025-08-06
RF Test Software	MWRFTTest	MTS 8310	N/A	N/A	N/A
Laptop	Lenovo	ThlnkPad E15 Gen 3	SPPOZ22485	N/A	N/A

1.6 Measurement Uncertainty

Test Item	Conditions	Uncertainty
Conducted Emissions	9kHz ~ 30MHz	±1.64 dB
Radiated Emissions	9kHz ~ 30MHz	±2.88 dB
	30MHz ~ 1GHz	±3.32 dB
	1GHz ~ 18GHz	±3.50 dB
	18GHz ~ 40GHz	±3.66 dB
Conducted Output Power	9kHz ~ 26GHz	±0.50 dB
Occupied Bandwidth	9kHz ~ 26GHz	±4.0 %
Conducted Spurious Emission	9kHz ~ 26GHz	±1.32 dB

2. Summary of Test Results

FCC Rule	Description of Test Item	Result
FCC Part 15.203	Antenna Requirement	Passed
FCC Part 15.247(i)	RF Exposure(see the RF exposure report)	Passed
FCC Part 15.207	Conducted Emissions	Passed
FCC Part 15.209, 15.247(d)	Radiated Emissions	Passed
FCC Part 15.247(d)	Band-edge Emissions(Radiated)	Passed
FCC Part 15.247(a)(1), (g), (h)	Frequency Hopping System	Passed
FCC Part 15.247(a)(1)(iii)	Dwell Time	Passed
FCC Part 15.247(b)(1)	Maximum Peak Conducted Output Power	Passed
FCC Part 15.215(c)	Occupied Bandwidth(-20dB)	Passed
FCC Part 15.247(a)(1)	Carrier Frequencies Separation	Passed
FCC Part 15.247(a)(1)(iii)	Number of Hopping Channel	Passed
FCC Part 15.247(d)	Band-edge Emissions(Conducted)	Passed
FCC Part 15.247(d)	Conducted RF Spurious Emissions	Passed
Passed: The EUT complies with the essential requirements in the standard Failed: The EUT does not comply with the essential requirements in the standard N/A: Not applicable		

3. Antenna Requirement

3.1 Standard and Limit

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has an SMD antenna, fulfill the requirement of this section.

4. Conducted Emissions

4.1 Standard and Limit

According to the rule FCC Part 15.207, Conducted emissions limit, the limit for a wireless device as below:

Frequency of Emission (MHz)	Conducted emissions (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Note 1: Decreases with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz
 Note 2: The lower limit applies at the band edges

4.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.2.



Test Setup Block Diagram

a) The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

b) The following is the setting of the receiver

Attenuation: 10dB

Start Frequency: 0.15MHz

Stop Frequency: 30MHz

IF Bandwidth: 9kHz

c) The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

d) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

e) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

f) LISN is at least 80 cm from nearest part of EUT chassis.

g) For the actual test configuration, please refer to the related Item - photographs of the test setup.

4.3 Test Data and Results

All of the modes have been tested, the EUT complied with the FCC Part 15.207 standard limit for a wireless device, and with the worst case as below:

Remark: Level = Reading + Factor, Margin = Level - Limit


Test Plots and Data of Conducted Emissions

Tested Mode: TM5

Test Voltage: AC 120V/60Hz

Test Power Line: Neutral

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1770	24.38	9.23	33.61	64.63	-31.02	QP	P	
2	0.1770	12.36	9.23	21.59	54.63	-33.04	AVG	P	
3	0.4065	23.48	9.38	32.86	57.72	-24.86	QP	P	
4	0.4065	10.09	9.38	19.47	47.72	-28.25	AVG	P	
5 *	0.8385	26.81	9.40	36.21	56.00	-19.79	QP	P	
6	0.8385	10.88	9.40	20.28	46.00	-25.72	AVG	P	
7	1.1670	22.36	9.43	31.79	56.00	-24.21	QP	P	
8	1.1670	10.90	9.43	20.33	46.00	-25.67	AVG	P	
9	1.6440	19.82	9.45	29.27	56.00	-26.73	QP	P	
10	1.6440	7.48	9.45	16.93	46.00	-29.07	AVG	P	
11	2.1480	16.82	9.47	26.29	56.00	-29.71	QP	P	
12	2.1480	4.46	9.47	13.93	46.00	-32.07	AVG	P	


Test Plots and Data of Conducted Emissions

Tested Mode: TM5

Test Voltage: AC 120V/60Hz

Test Power Line: Live

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.2670	23.73	9.52	33.25	61.21	-27.96	QP	P	
2	0.2670	11.62	9.52	21.14	51.21	-30.07	AVG	P	
3	0.4965	22.13	9.58	31.71	56.06	-24.35	QP	P	
4	0.4965	10.18	9.58	19.76	46.06	-26.30	AVG	P	
5 *	0.8475	28.33	9.59	37.92	56.00	-18.08	QP	P	
6	0.8475	11.55	9.59	21.14	46.00	-24.86	AVG	P	
7	1.2075	22.38	9.63	32.01	56.00	-23.99	QP	P	
8	1.2075	11.03	9.63	20.66	46.00	-25.34	AVG	P	
9	1.9455	19.09	9.65	28.74	56.00	-27.26	QP	P	
10	1.9455	5.81	9.65	15.46	46.00	-30.54	AVG	P	
11	2.4720	17.23	9.68	26.91	56.00	-29.09	QP	P	
12	2.4720	2.58	9.68	12.26	46.00	-33.74	AVG	P	

5. Radiated Emissions

5.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

According to the rule FCC Part 15.209, Radiated emission limit for a wireless device as below:


Frequency of emission (MHz)	Radiated emissions (3m)
	Quasi-peak (dBuV/m)
30-88	40
88-216	43.5
216-960	46
Above 960	54
Note: The more stringent limit applies at transition frequencies.	

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.


Note: Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

5.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.3 to 6.6.



Block Diagram of Radiated Emission Below 30MHz



Block Diagram of Radiated Emission From 30MHz to 1GHz



Block Diagram of Radiated Emission Above 1GHz

- a) The EUT is placed on a turntable, which is 0.8m above ground plane for test frequency range below 1GHz, and 1.5m above ground plane for test frequency range above 1GHz.
- b) EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- c) Use the following spectrum analyzer settings:
Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 kHz for $f < 1\text{GHz}$, 10kHz for $f < 30\text{MHz}$
VBW \geq RBW, Sweep = auto
Detector function = peak
Trace = max hold
- d) Follow the guidelines in ANSI C63.4-2014 with respect to maximizing the emission by rotating the EUT, adjusting the measurement antenna height and polarization, etc. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, submit this data. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- e) The peak level, once corrected, must comply with the limit specified in Section 15.209. Set the RBW = 1MHz, VBW = 10Hz, Detector = PK for AV value, while maintaining all of the other instrument settings.
- f) For the actual test configuration, please refer to the related item - EUT test photos.


5.3 Test Data and Results

All of the GFSK, $\pi/4$ DQPSK and 8DPSK modes have been tested, the EUT complied with the FCC Part 15.247 standard limit for a wireless device, and with the worst case GFSK_2402MHz as below:

Remark: Level = Reading + Factor, Margin = Level - Limit

Radiated Emission Test Data (30MHz to 1GHz)

Tested Mode:	TM1
Test Antenna Polarization:	Horizontal
Remark:	




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	33.3279	26.60	-9.03	17.57	40.00	-22.43	QP	100	10	P	
2	62.6507	26.74	-10.43	16.31	40.00	-23.69	QP	100	228	P	
3	152.1297	26.76	-7.75	19.01	43.50	-24.49	QP	100	329	P	
4	314.3765	27.13	-7.48	19.65	46.00	-26.35	QP	100	195	P	
5	407.5145	27.31	-5.42	21.89	46.00	-24.11	QP	100	354	P	
6 *	656.5300	26.30	-0.69	25.61	46.00	-20.39	QP	100	165	P	

Radiated Emission Test Data (30MHz to 1GHz)

Tested Mode: TM1

Test Antenna Polarization: Vertical

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	36.5092	26.80	-8.87	17.93	40.00	-22.07	QP	100	236	P	
2	55.4147	26.49	-9.23	17.26	40.00	-22.74	QP	100	124	P	
3	140.8351	27.68	-8.19	19.49	43.50	-24.01	QP	100	348	P	
4	317.7011	26.33	-7.35	18.98	46.00	-27.02	QP	100	348	P	
5	499.4247	26.81	-3.27	23.54	46.00	-22.46	QP	100	6	P	
6 *	813.1115	26.58	1.53	28.11	46.00	-17.89	QP	100	115	P	

Radiated Emission Test Data (Above 1GHz)							
Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	PK/AV
Lowest Channel (GFSK_2402MHz)							
4804	79.1	-14.72	64.38	74	-9.62	H	PK
4804	62.14	-14.72	47.42	54	-6.58	H	AV
7206	65.31	-8.41	56.9	74	-17.1	H	PK
7206	45.67	-8.41	37.26	54	-16.74	H	AV
4804	74.86	-14.72	60.14	74	-13.86	V	PK
4804	58.18	-14.72	43.46	54	-10.54	V	AV
7206	65.85	-8.41	57.44	74	-16.56	V	PK
7206	48.77	-8.41	40.36	54	-13.64	V	AV
Lowest Channel (GFSK_2441MHz)							
4882	77.58	-14.64	62.94	74	-11.06	H	PK
4882	61.21	-14.64	46.57	54	-7.43	H	AV
7323	63.12	-8.28	54.84	74	-19.16	H	PK
7323	49.55	-8.28	41.27	54	-12.73	H	AV
4882	73.8	-14.64	59.16	74	-14.84	V	PK
4882	58.4	-14.64	43.76	54	-10.24	V	AV
7323	65.51	-8.28	57.23	74	-16.77	V	PK
7323	50.17	-8.28	41.89	54	-12.11	V	AV
Lowest Channel (GFSK_2480MHz)							
4960	77.12	-14.53	62.59	74	-11.41	H	PK
4960	59.95	-14.53	45.42	54	-8.58	H	AV
7440	63.94	-8.13	55.81	74	-18.19	H	PK
7440	47.96	-8.13	39.83	54	-14.17	H	AV
4960	73.29	-14.53	58.76	74	-15.24	V	PK
4960	57.21	-14.53	42.68	54	-11.32	V	AV
7440	63.15	-8.13	55.02	74	-18.98	V	PK
7440	45.82	-8.13	37.69	54	-16.31	V	AV

Note 1: All of the GFSK, $\pi/4$ DQPSK and 8DPSK modes have been tested. This EUT was tested in 3 orthogonal positions and the worst case position data of GFSK was reported.

Note 2: Testing is carried out with frequency rang 9kHz to the tenth harmonics. The measurements greater than 20dB below the limit from 9kHz to 30MHz.

Note 3: Other emissions are attenuated 20dB below the limits from 9kHz to 30MHz, so it does not recorded report, 18GHz-26GHz not recorded for no spurious point have a margin of less than 6 dB with respect to the limits.


6. Band-edge Emissions(Radiated)

6.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

6.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.3 to 6.6 and section 6.10.



Test Setup Block Diagram

As the radiated emissions testing, set the Lowest and Highest Transmitting Channel, observed the outside band of 2310MHz to 2400MHz and 2483.5MHz to 2500MHz, than mark the higher-level emission for comparing with the FCC rules.

6.3 Test Data and Results

All of the GFSK, $\pi/4$ DQPSK and 8DPSK modes have been tested, the EUT complied with the FCC Part 15.247 standard limit, and with the worst case GFSK as below:

Test Mode	Frequency	Limit	Result
	MHz	dBuV/dBc	
Lowest	2310.00	<54 dBuV	Pass
	2390.00	<54 dBuV	Pass
Highest	2483.50	<54 dBuV	Pass
	2500.00	<54 dBuV	Pass

Radiated Emission Test Data (Band edge emissions)							
Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	PK/AV
Lowest Channel (GFSK_2402MHz)							
2310	69.64	-21.34	48.3	74	-25.7	H	PK
2310	51.88	-21.34	30.54	54	-23.46	H	AV
2390	69.08	-20.96	48.12	74	-25.88	H	PK
2390	52.94	-20.96	31.98	54	-22.02	H	AV
2400	68.31	-20.91	47.4	74	-26.6	H	PK
2400	54.07	-20.91	33.16	54	-20.84	H	AV
2310	65.41	-21.34	44.07	74	-29.93	V	PK
2310	51.48	-21.34	30.14	54	-23.86	V	AV
2390	68.44	-20.96	47.48	74	-26.52	V	PK
2390	50.7	-20.96	29.74	54	-24.26	V	AV
2400	68.4	-20.91	47.49	74	-26.51	V	PK
2400	56.07	-20.91	35.16	54	-18.84	V	AV
Highest Channel (GFSK_2480MHz)							
2483.50	71.21	-20.51	50.7	74	-23.3	H	PK
2483.50	54.66	-20.51	34.15	54	-19.85	H	AV
2500	64.11	-20.43	43.68	74	-30.32	H	PK
2500	52.08	-20.43	31.65	54	-22.35	H	AV
2483.50	70.09	-20.51	49.58	74	-24.42	V	PK
2483.50	54.25	-20.51	33.74	54	-20.26	V	AV
2500	64.5	-20.43	44.07	74	-29.93	V	PK
2500	52.34	-20.43	31.91	54	-22.09	V	AV

Remark: Level = Reading + Factor, Margin = Level - Limit

7. Frequency Hopping System

7.1 Standard and Limit

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

7.2 Test Procedure

This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH-enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

This device was tested with an bluetooth system receiver to check that the device maintained hopping synchronization, and the device complied with these requirements for DA 00-705 and FCC Part 15.247 rule.

7.3 Test Data and Results

Pseudorandom Frequency Hopping Sequence Table as below:

Channel: 08, 24, 40, 56, 40, 56, 72, 09, 01, 09, 33, 41, 33, 41, 65, 73, 53, 69, 06, 22, 04, 20, 36, 52, 38, 46, 70, 78, 68, 76, 21, 29, 10, 26, 42, 58, 44, 60, 76, 13, 03, 11, 35, 43, 37, 45, 69, 77, 55, 71, 08, 24, 08, 24, 40, 56, 40, 48, 72, 01, 72, 01, 25, 33, 12, 28, 44, 60, 42, 58, 74, 11, 05, 13, 37, 45 etc.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

8. Dwell Time

8.1 Standard and Limit

According to 15.247 (a)(1)(iii), Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed..

8.2 Test Procedure

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Spectrum Setting: RBW=1MHz, VBW=3MHz, Span=0Hz, Detector=Peak
- 3) Use video trigger with the trigger level set to enable triggering only on full pulses.
- 4) Sweep Time is more than once pulse time.
- 5) Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- 6) Measure the maximum time duration of one single pulse.
- 7) Set the EUT for packet transmitting.
- 8) Measure the maximum time duration of one single pulse.
- 9) The EUT was set to the Hopping Mode for Dwell Time Test.



Test Setup Block Diagram

8.3 Test Data and Results


Test Mode	Data Packet	Channel (MHz)	Pulse Duration (ms)	Burst Count	Dwell Time (ms)	Limit (ms)	Result
GFSK	DH1	2441	0.382	317	121.094	<400	Pass
	DH3	2441	1.638	155	253.89	<400	Pass
	DH5	2441	2.886	100	288.6	<400	Pass
Pi/4 DQPSK	2DH1	2441	0.392	317	124.264	<400	Pass
	2DH3	2441	1.644	164	269.616	<400	Pass
	2DH5	2441	2.886	99	285.714	<400	Pass
8DPSK	3DH1	2441	0.392	314	123.088	<400	Pass
	3DH3	2441	1.642	161	264.362	<400	Pass
	3DH5	2441	2.894	113	327.022	<400	Pass

Note:


1. Pulse Duration*Burst Count= Dwell Time

GFSK (2441MHz)


Burst(DH1)




Accumulate(DH1)




Burst(DH3)




Accumulate(DH3)





Burst(DH5)





Accumulate(DH5)





Accumulate(2DH1)



Accumulate(2DH3)




Accumulate(2DH5)




8DPSK (2441MHz)


Burst(3DH1)




Accumulate(3DH1)




Burst(3DH3)




Accumulate(3DH3)



Burst(3DH5)



Accumulate(3DH5)



9. Maximum Peak Conducted Output Power

9.1 Standard and Limit

According to 15.247(b)(1). For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

9.2 Test Procedure

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 2MHz, VBW = 6MHz, Sweep = Auto, Detector = Peak.
- 4) Measure the highest amplitude appearing on spectral display and mark the value.
- 5) Repeat the above procedures until all frequencies measured were complete.




Test Setup Block Diagram

9.3 Test Data and Results

Test Mode	Test Channel MHz	Conducted Output Power (dBm)	Limit (dBm)	Test Result
GFSK	2402	-4.22	21	Pass
	2441	-4.55	21	Pass
	2480	-3.89	21	Pass
Pi/4 DQPSK	2402	-3.39	21	Pass
	2441	-3.78	21	Pass
	2480	-3.08	21	Pass
8DPSK	2402	-2.98	21	Pass
	2441	-3.36	21	Pass
	2480	-2.68	21	Pass


GFSK

2402MHz



Pi/4 DQPSK

2402MHz



2441MHz



2441MHz



2480MHz



2480MHz



8DPSK

2402MHz



2441MHz



2480MHz



10. Occupied Bandwidth(-20dB)

10.1 Standard and Limit

According to 15.215 (c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

10.2 Test Procedure

According to the ANSI 63.10-2013, section 6.9, the emission bandwidth test method as follows.

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 30kHz, VBW = 100kHz, Sweep = Auto.
- 4) Set a reference level on the measuring instrument equal to the highest peak value.
- 5) Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- 6) Repeat the above procedures until all frequencies measured were complete.



Test Setup Block Diagram

10.3 Test Data and Results

Test Mode	Test Channel (MHz)	20dB Bandwidth (MHz)	99% Bandwidth (kHz)
GFSK	2402	0.956	891.21
	2441	0.996	884.24
	2480	1.016	899.68
Pi/4 DQPSK	2402	1.312	1187
	2441	1.285	1175.6
	2480	1.309	1184.9
8DPSK	2402	1.284	1170.8
	2441	1.282	1176.4
	2480	1.295	1178.6

GFSK

2402MHz



Pi/4 DQPSK

2402MHz



2441MHz



2441MHz



2480MHz



2480MHz



8DPSK

2402MHz



2441MHz



2480MHz



11. Carrier Frequencies Separation

11.1 Standard and Limit

According to FCC 15.247(a)(1), frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, and frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

11.2 Test Procedure

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 30kHz, VBW = 100kHz, Sweep = Auto, Detector = Peak.
- 4) By using the Max Hold function, record the separation of two adjacent channels.
- 5) Measure the frequency difference of these two adjacent channels by spectrum analyzer mark function. and then plot the result on the screen of the spectrum analyzer.
- 6) Repeat above procedures until all frequencies measured were complete.



11.3 Test Data and Results


Test Mode	Test Channel	Test Freq. 1 (MHz)	Test Freq. 2 (MHz)	CFS (MHz)	Limit (MHz)
GFSK	Lowest	2401.988	2402.986	0.998	0.637
	Middle	2440.97	2441.972	1.002	0.664
	Highest	2478.968	2479.974	1.006	0.677
Pi/4 DQPSK	Lowest	2401.986	2402.982	0.996	0.875
	Middle	2440.974	2441.994	1.02	0.857
	Highest	2478.966	2479.994	1.028	0.873
8DPSK	Lowest	2401.826	2402.838	1.012	0.856
	Middle	2440.834	2441.98	1.146	0.855
	Highest	2479.154	2480.162	1.008	0.863

Note: CFS(Channel Frequency Separation) = Test Freq. 2 - Test Freq. 1




8DPSK


Lowest



Middle



Highest



12. Number of Hopping Channel

12.1 Standard and Limit

According to FCC 15.247(a)(1), frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, and frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

12.2 Test Procedure

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 100kHz, VBW = 300kHz, Sweep = Auto, Detector = Peak.
- 4) Set the spectrum analyzer on Max hold mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- 5) Set the spectrum analyzer on View mode and then plot the result on the screen of the spectrum analyzer.
- 6) Repeat the above procedures until all frequencies measured were complete.




Test Setup Block Diagram

12.3 Test Data and Results

Test Mode	Number of Hopping Channel	Limit	Test Result
GFSK	79	15	Pass
Pi/4 DQPSK	79	15	Pass
8DPSK	79	15	Pass

GFSK



Center Freq 2.441750000 GHz
 Ref Offset 1.68 dB
 Ref 20.00 dBm
 Span 30 dB
 Start 2.400000 GHz
 Stop 2.483500 GHz
 Res BW 100 kHz
 Sweep 2.000 ms (1001 pts)
 #VBW 300 kHz
 Mkr1 2.4018370 GHz
 -4.816 dBm
 Mkr2 2.4835000 GHz
 -4.816 dBm

Knight Spectrum Analyzer - Setup OK
 10:15:57 PM Apr 25, 2015
 Center Freq 2.441750000 GHz
 Span 300 kHz
 Ref Offset 1.68 dB
 Ref 20.00 dBm
 PNC: Fast
 IF Gain: Low
 Trip: Free Run
 #Att: 30 dB
 #Avg Type: RMS
 Avg/Hold: >100/100
 TRACE 0 2.44175
 TYPE BW Noise
 DET PNMN
 Frequency
 Auto Tun
 Center Freq
 2.441750000 GHz
 Start Freq
 2.400000000 GHz
 Stop Freq
 2.483500000 GHz
 CF Step
 8.350000000 MHz
 Auto
 Freq Offset
 0 Hz
 Scale Type
 Log
 Span
 300 kHz
 Resolution Bandwidth
 100 kHz
 Sweep
 8.000 ms (1001 pts)
 #VBW 300 kHz
 Start 2.400000 GHz
 Stop 2.483500 GHz
 #Res BW 100 kHz
 -4.678 dBm
 -9.198 dBm
 2.4026649 GHz
 2.4404195 GHz
 2.4417500 GHz
 2.4430000 GHz
 2.4442500 GHz
 2.4455000 GHz
 2.4467500 GHz
 2.4480000 GHz
 2.4492500 GHz
 2.4505000 GHz
 2.4517500 GHz
 2.4530000 GHz
 2.4542500 GHz
 2.4555000 GHz
 2.4567500 GHz
 2.4580000 GHz
 2.4592500 GHz
 2.4605000 GHz
 2.4617500 GHz
 2.4630000 GHz
 2.4642500 GHz
 2.4655000 GHz
 2.4667500 GHz
 2.4680000 GHz
 2.4692500 GHz
 2.4705000 GHz
 2.4717500 GHz
 2.4730000 GHz
 2.4742500 GHz
 2.4755000 GHz
 2.4767500 GHz
 2.4780000 GHz
 2.4792500 GHz
 2.4805000 GHz
 2.4817500 GHz
 2.4830000 GHz
 2.4842500 GHz
 2.4855000 GHz
 2.4867500 GHz
 2.4880000 GHz
 2.4892500 GHz
 2.4905000 GHz
 2.4917500 GHz
 2.4930000 GHz
 2.4942500 GHz
 2.4955000 GHz
 2.4967500 GHz
 2.4980000 GHz
 2.4992500 GHz
 2.5005000 GHz
 2.5017500 GHz
 2.5030000 GHz
 2.5042500 GHz
 2.5055000 GHz
 2.5067500 GHz
 2.5080000 GHz
 2.5092500 GHz
 2.5105000 GHz
 2.5117500 GHz
 2.5130000 GHz
 2.5142500 GHz
 2.5155000 GHz
 2.5167500 GHz
 2.5180000 GHz
 2.5192500 GHz
 2.5205000 GHz
 2.5217500 GHz
 2.5230000 GHz
 2.5242500 GHz
 2.5255000 GHz
 2.5267500 GHz
 2.5280000 GHz
 2.5292500 GHz
 2.5305000 GHz
 2.5317500 GHz
 2.5330000 GHz
 2.5342500 GHz
 2.5355000 GHz
 2.5367500 GHz
 2.5380000 GHz
 2.5392500 GHz
 2.5405000 GHz
 2.5417500 GHz
 2.5430000 GHz
 2.5442500 GHz
 2.5455000 GHz
 2.5467500 GHz
 2.5480000 GHz
 2.5492500 GHz
 2.5505000 GHz
 2.5517500 GHz
 2.5530000 GHz
 2.5542500 GHz
 2.5555000 GHz
 2.5567500 GHz
 2.5580000 GHz
 2.5592500 GHz
 2.5605000 GHz
 2.5617500 GHz
 2.5630000 GHz
 2.5642500 GHz
 2.5655000 GHz
 2.5667500 GHz
 2.5680000 GHz
 2.5692500 GHz
 2.5705000 GHz
 2.5717500 GHz
 2.5730000 GHz
 2.5742500 GHz
 2.5755000 GHz
 2.5767500 GHz
 2.5780000 GHz
 2.5792500 GHz
 2.5805000 GHz
 2.5817500 GHz
 2.5830000 GHz
 2.5842500 GHz
 2.5855000 GHz
 2.5867500 GHz
 2.5880000 GHz
 2.5892500 GHz
 2.5905000 GHz
 2.5917500 GHz
 2.5930000 GHz
 2.5942500 GHz
 2.5955000 GHz
 2.5967500 GHz
 2.5980000 GHz
 2.5992500 GHz
 2.6005000 GHz
 2.6017500 GHz
 2.6030000 GHz
 2.6042500 GHz
 2.6055000 GHz
 2.6067500 GHz
 2.6080000 GHz
 2.6092500 GHz
 2.6105000 GHz
 2.6117500 GHz
 2.6130000 GHz
 2.6142500 GHz
 2.6155000 GHz
 2.6167500 GHz
 2.6180000 GHz
 2.6192500 GHz
 2.6205000 GHz
 2.6217500 GHz
 2.6230000 GHz
 2.6242500 GHz
 2.6255000 GHz
 2.6267500 GHz
 2.6280000 GHz
 2.6292500 GHz
 2.6305000 GHz
 2.6317500 GHz
 2.6330000 GHz
 2.6342500 GHz
 2.6355000 GHz
 2.6367500 GHz
 2.6380000 GHz
 2.6392500 GHz
 2.6405000 GHz
 2.6417500 GHz
 2.6430000 GHz
 2.6442500 GHz
 2.6455000 GHz
 2.6467500 GHz
 2.6480000 GHz
 2.6492500 GHz
 2.6505000 GHz
 2.6517500 GHz
 2.6530000 GHz
 2.6542500 GHz
 2.6555000 GHz
 2.6567500 GHz
 2.6580000 GHz
 2.6592500 GHz
 2.6605000 GHz
 2.6617500 GHz
 2.6630000 GHz
 2.6642500 GHz
 2.6655000 GHz
 2.6667500 GHz
 2.6680000 GHz
 2.6692500 GHz
 2.6705000 GHz
 2.6717500 GHz
 2.6730000 GHz
 2.6742500 GHz
 2.6755000 GHz
 2.6767500 GHz
 2.6780000 GHz
 2.6792500 GHz
 2.6805000 GHz
 2.6817500 GHz
 2.6830000 GHz
 2.6842500 GHz
 2.6855000 GHz
 2.6867500 GHz
 2.6880000 GHz
 2.6892500 GHz
 2.6905000 GHz
 2.6917500 GHz
 2.6930000 GHz
 2.6942500 GHz
 2.6955000 GHz
 2.6967500 GHz
 2.6980000 GHz
 2.6992500 GHz
 2.7005000 GHz
 2.7017500 GHz
 2.7030000 GHz
 2.7042500 GHz
 2.7055000 GHz
 2.7067500 GHz
 2.7080000 GHz
 2.7092500 GHz
 2.7105000 GHz
 2.7117500 GHz
 2.7130000 GHz
 2.7142500 GHz
 2.7155000 GHz
 2.7167500 GHz
 2.7180000 GHz
 2.7192500 GHz
 2.7205000 GHz
 2.7217500 GHz
 2.7230000 GHz
 2.7242500 GHz
 2.7255000 GHz
 2.7267500 GHz
 2.7280000 GHz
 2.7292500 GHz
 2.7305000 GHz
 2.7317500 GHz
 2.7330000 GHz
 2.7342500 GHz
 2.73

13. Band-edge Emission(Conducted)

13.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

13.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.10.

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 100kHz, VBW = 300kHz, Sweep = Auto, Detector = Peak.
- 4) Measure the highest amplitude appearing on spectral display and set it as a reference level.
- 5) Set a convenient frequency span including 100 kHz bandwidth from band edge.
- 6) Measure the emission and marking the edge frequency.
- 7) Repeat above procedures until all frequencies measured were complete.




Test Setup Block Diagram

13.3 Test Data and Results


Test Mode	Band-edge	Test Channel (MHz)	Max. Value (dBc)	Limit (dBc)	Test Result
No-Hopping					
GFSK	Lowest	2402	-49.82	-20	Pass
	Highest	2480	-50.54	-20	Pass
Pi/4 DQPSK	Lowest	2402	-49.51	-20	Pass
	Highest	2480	-50.91	-20	Pass
8DPSK	Lowest	2402	-49.95	-20	Pass
	Highest	2480	-51.06	-20	Pass
Hopping					
GFSK	Lowest	2402	-49.5	-20	Pass
	Highest	2480	-49.72	-20	Pass
Pi/4 DQPSK	Lowest	2402	-49.49	-20	Pass
	Highest	2480	-46.92	-20	Pass
8DPSK	Lowest	2402	-49.81	-20	Pass
	Highest	2480	-50.1	-20	Pass

No-Hopping Pi/4 DQPSK Highest

Reference Power




Band-edge Emission




No-Hopping 8DPSK Lowest

Reference Power




Band-edge Emission




No-Hopping 8DPSK Highest

Reference Power




Band-edge Emission




Hopping GFSK Lowest

Reference Power



Band-edge Emission




Hopping GFSK Highest

Reference Power




Band-edge Emission




Hopping Pi/4 DQPSK Lowest

Reference Power




Band-edge Emission




Hopping Pi/4 DQPSK Highest

Reference Power




Band-edge Emission




Hopping 8DPSK Lowest

Reference Power




Band-edge Emission




Hopping 8DPSK Highest

Reference Power



Band-edge Emission



14. Conducted RF Spurious Emissions


14.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

14.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.7.

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 100kHz, VBW = 300kHz, Sweep = Auto, Detector = Peak.
- 4) Measure the highest amplitude appearing on spectral display and set it as a reference level.
- 5) Measure the spurious emissions with frequency range from 9kHz to 26.5GHz.
- 6) Repeat above procedures until all measured frequencies were complete.




Test Setup Block Diagram

14.3 Test Data and Results


Note: The measurement frequency range is from 9kHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions measurement data.

GFSK Middle


Spurious Emissions



Spurious Emissions



Spurious Emissions




Pi/4 DQPSK Lowest

Reference Power



Spurious Emissions




Pi/4 DQPSK Middle

Reference Power



Spurious Emissions




Pi/4 DQPSK Highest

Reference Power



Spurious Emissions




8DPSK Lowest

Reference Power



Spurious Emissions




8DPSK Middle

Reference Power




Spurious Emissions




8DPSK Highest

Reference Power



Spurious Emissions



***** END OF REPORT *****