Acceptance Letter

SPECIFICATION FOR APPROVAL

(CUSTOMER):		Bingdi Technology Co., LT	'D						
(CHOTOMED DAI)									
(CUSTOMER P/N)	:								
(DESCRIPTION):		Wireless charging coil		DATE: 2025/3/12					
(SPECIFICATION)	: G43.5 slotted + b	pack adhesive 50 lengths	REV.NO.:A0						
Hongri Shengwei Technology acknowledges the signature and seal									
department	Confirmation/D ate	Review/Date	Approval/Date	(Stamped with the company's official seal)					
quality	Dong Wanhong	Lu Hui	Wei Hanman	□ ★ □ □					
project	He Weihua	Wei Lihong	Wei Lihong						
remark:			•						
	. 1			the signature and seal					
department	Confirmation/D	Review/Date	Approval/Date	(Stamped with the company's official seal)					
development engineering									
purchase									
quality									
备注:									
	海加手。	地口目的的 计方图公司							

深圳市鸿日昇威科技有限公司


HRSW ELECTRONICS CO.,LTD

Address: 2nd Floor, Building 1, No. 48, Huanguan Middle Road, Guanlan, Longhua New District, Shenzhen City


TEL: +86-15112254520 FAX: +86-0755-28015170

SPECIFICATION FOR APPROVAL

1.MECHANICAL DIMENSION (UNIT:mm)



2. SCHEMATICS:



1. The coil is attached to the magnetic sheet, and the size of the magnetic sheet

43.5mm, with a thickness of 0.8 ± 0.05 mm

Open an L-line groove.

- 2. Coil lead-out position Adhesive tape 1-2Ts;
- 3. Stick back adhesive on the back

A	В	С	D2	Е	Н	备注	I
43.5 \pm 1.0	20 ± 1.0	0.8 ± 0.5	50 ± 3	3±1.5	1.8MAX		

3.WINDING:

ST EP	START-FINISH	WIRE TYPE	TURNS	TAPE	REMAR K
N1	S-F	thermoanalysis 0.08*24 2UEW	10TS (Ref)		

4. ELECTRICAL SPECIFICATION:

ITEM	L	DCR	L	Q value	HI-POT
TES	l with magnetic sh	S-F	Individual coil		
CON	100KHz, 0.25V	AT 25℃	100KHz, 0.25V		
SPEC	6. $5uH \pm 10\%$	80mΩ Max	3.8uH±15%		

5.BILF OF MATERIAL:

NO.	ITEM	MATERIAL SPECIFICATION			MA	NUFACTURER	SGS NO.
1	silk-covered wire		0.08*24*2P		NANJI	NGJINNINGCO,LTD	
2	Lead-free tin bar		Lead-free tin bar			QIAODO	
3	magnetic sheet	43. 5*0.	8 manganese-zinc hard	_	7	TAIYI CO.,LTD	
4	glue	Yellow glue 9999			LIA	NCHENG CO.,LTD	
5	high-temperature adhesive tape	8mm w	8mm wide high-temperature adhesive tape		C	UDAK CO.,LTD	
6	gum		41.8*0.1		C	UDAK CO.,LTD	
HRSW ELECTRONICS CO.,LTD		PART	NO				
		TITL	LE G43.5 slotting		+ 50mm ac		
DRAWN BY CHECKE		ED BY	Al		PPROVED B		
	He Weihua Wei Liho		hong		W	ei Lihong	
							maga, 0 /0

page: 2/2