

ABOUT TIMES-7

Pushing the boundaries of RFID technology worldwide Times-7 are leaders in RFID antenna design and manufacture. Our patented award winning UHF antennas meet the needs of virtually any industry application; providing customers with fast accurate tracking of products, assets & people; empowering organisations to transform processes & reduce costs.

Our SlimLine range of antennas are unique in the RFID industry; offering high levels of performance & durability in an aesthetically superior form. Proven in a diverse & growing range of markets, applications include: retail & customer interaction, conference & people tracking, race timing, baggage handling, and logistic & supply chain asset management.



The SlimLine A4030L

Up to 9 m / 29 ft. read range

Just 12mm / 0.5 in. thick

Versatile & compact with superb aesthetics

Seamless installation using rear connector

Part of the SlimLine range of multi-purpose antennas, the A4030L is a rugged high performance linear polarised UHF antenna suitable for a wide range of RFID deployments. With a read range of up to 9m / 29ft., and dimensions of only 280 mm / 11 in. square, the A4030L is an extremely versatile and compact antenna. A rear connector provides for ease of seamless installation with no visible cable.

Specifications


Physical / Environmental Specifications

Dimensions (LxWxD):	280 mm x 280 mm x 12 mm 11 in. x 11 in. x 0.5 in.
Weight:	0.75kg / 1.6 lbs.
Radome Material:	Fire retardant Kydex
Environmental Rating:	IP65
Operating / Storage Temperature:	-20° to +55°C / -30° to +65°C -4° to +131°F / -22° to +149°F
Connector type / position:	SMA female / Rear connector
Cable:	2m SMA to RPTNC (included)


Electrical Specifications

Frequency Range:	864 – 869 MHz / 902 – 928 MHz
Polarisation:	Linear
Far-field Gain:	7.5dBi
Far-field 3dB beamwidth:	62° in both planes
Typical VSWR across frequency range:	< 1.4:1
Front to back ratio:	22dB
Nominal Impedance:	50 Ω
Anti-static protection:	Yes
Maximum Input Power:	6 W

E-field elevation & Azimuth Patterns



Vertical




Horizontal

Ordering Information (please quote both product code & part no.)

Product Code	Band	Part No.
A4030L	ETSI 864-869 MHz	71271
A4030L	FCC 902-928 MHz	71272
Cable 4m, SMA to RPTNC		71437
Cable 8m, SMA to RPTNC		71438

Applications

- Inventory Management
- Logistics & Supply Chain
- Healthcare (asset & people tracking)
- Retail / POS self service



OUR GLOBAL NETWORK

Constantly increasing market reach and influence in the global RFID industry, Times-7's international support spans The Americas, Europe, and Asia Pacific regions through our distributor, authorized reseller and integrated solutions provider network.

The technical data contained in this publication is not a guarantee for which Times-7 Research Ltd assumes legal accountability. It is indicative of typical performance, and if required should be relied on for specific applications only after due verification.

All technical data, specifications and other information contained herein are deemed to be the proprietary intellectual property of Times-7 Research Ltd. No reproduction, copy or use thereof may be made without the express written consent of Times-7 Research Ltd.