

86-471-001N



## mcmurdo SEARCH AND RESCUE TRANSPONDER

MOUNTING



11.5/5.5V LITHIUM BATTERY

> MANU DATE: REPLACE BY





SPECIALIST DISPOSAL

Compass safe distance: 1.5m



TEST ROTATE SWITCH

POSITION

ACTIVATE

RING ANTICLOCKWISE HOLD TO SECONDS WAIT FOR RED LED



86-471-005N

## SAILOR SEARCH AND RESCUE TRANSPONDER

MOUNTING



11.5/5.5V LITHIUM BATTERY

> MANU DATE: REPLACE BY:



CHARGE, SHORT CIRCUIT, PUNCTURE, DEFORM OR INCINERATE

SPECIALIST DISPOSAL

Compass safe distance: 1.5m

ACTIVATE PULL OFF RED TAB ROTATE SWITCH RING CLOCKWISE TO ON

POSITION



TEST ROTATE SWITCH ANTICLOCKWISE HOLD 10 SECONDS WAIT FOR RED LED



VARIANT TABLE							
	PART No.	ARTWORK					
McMURDO	86-471-001	86-471-001N					
SAILOR	86-471-005	86-471-005N					

					2	C2755	12/12/2003	BOS
						C2686	24/10/2003	BOS
	ISSUE	CHG.No.	DATE	APPD	ISSUE	CHG.N⋄.	DATE	APPD
DRA	WN JBY:	APPROVED BOS	TITLE.					

USED ON

TOLERANCES UNLESS OTHERWISE STATED WHOLE No. ±0.5 ANGULAR DIMS± I DEC PLACE ±0.1

2 DEC PLACE ±0.05 DRILLED HOLFS+

HIS DOCUMENTIS MCMURDO LIMITED COPYRIGHT AND CONTAINS PROPRIETARY OWNED INTELLECTUAL PROPERTY RIGHTS AND CONFIDENTIAL DATA. ALL RIGHTS ARE STRICTLY RESERVED. THE INFORMATION MUST NOT BE USED EXCEPT FOR THE AGREED PURPOSE. UNAUTHORISED USE, REPRODUCTION, OR ISSUE TO ANY THIRD PARTY IS NOT PERMITTED WITHOUT THE PRIOR WRITTEN AUTHORITY OF MCMURDO LIMITED. THIS DOCUMENT IS TO BE RETURNED TO MCMURDO LIMITED WHEN THE AGREED PURPOSE IS FULFILLED.

FINISH :-DIMENSIONS IN :-3RD ANGLE PROJECTION THIS DOCUMENT IS UNCONTROLLED, UNLESS OTHERWISE STATED

B.S.8888

MATERIAL :-

mm **⊕**  $\Box$ 

RELEASED

McMURDO LIMITED PORTSMOUTH - HAMPSHIRE - ENGLAND

SCALE

86-47 I - XXXD

BATTERY PACK LABEL