

MFA **M. Flom Associates, Inc. - Global Compliance Center**
3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176
www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

Transmitter Certification

of

FCC ID: P7QNP-7
Model: MMII

to

Federal Communications Commission

Rule Part(s) 24E, Confidentiality
Class II Permissive Change

Date Of Report: July 17, 2003

On the Behalf of the Applicant:

Vertu Ltd.

At the Request of:

P.O. E68-4622933

Vertu Ltd.
Beacon Hill Road
Church Crookham, Hampshire GU52 8DY UK

Attention of:

Mark Pope, Certification and Compliance Manager
+44 1252 611135; FAX: -611302
Mobile: +44 7774 8158594
mark.pope@vertu.com

Supervised By:


Morton Flom, P. Eng.

List of Exhibits
(FCC **Certification** (PCS Transmitters) - Revised 9/28/98)

Applicant: Vertu Ltd.

FCC ID: P7QNP-7

By Applicant:

- | | |
|---|---|
| 1. Letter of Authorization | x |
| 2. Identification Drawings, 2.1033(c)(11) | |
| <u>x</u> Id Label | |
| <u>x</u> Location of Label | |
| <u>x</u> Compliance Statement | |
| <u>x</u> Location of Compliance Statement | |
| 3. Photographs, 2.1033(c)(12) | x |
| 4. Confidentiality Request: 0.457 And 0.459 | x |
| 5. Documentation: 2.1033(c) | |
| (3) User Manual | x |
| (9) Tune Up Info | x |
| (10) Schematic Diagram | x |
| (10) Theory Of Operation | x |
| Block Diagram | x |
| Parts List | x |
| Active Devices | x |
| 6. GSM Statement | x |
| 7. ESN Statement | x |
| 8. SAR Report by Nokia (Finland) | x |

By M.F.A. Inc.

- A. Testimonial & Statement of Certification
- B. Statement of Qualifications

The applicant has been cautioned as to the following:

15.21 Information to User.

The users manual or instruction manual for an intentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.27(a) Special Accessories.

Equipment marketed to a consumer must be capable of complying with the necessary regulations in the configuration in which the equipment is marketed. Where special accessories, such as shielded cables and/or special connectors are required to enable an unintentional or intentional radiator to comply with the emission limits in this part, the equipment must be marketed with, i.e. shipped and sold with, those special accessories. However, in lieu of shipping or packaging the special accessories with the unintentional or intentional radiator, the responsible party may employ other methods of ensuring that the special accessories are provided to the consumer, without additional charge.

Information detailing any alternative method used to supply the special accessories for a grant of equipment authorization or retained in the verification records, as appropriate. The party responsible for the equipment, as detailed in § 2.909 of this chapter, shall ensure that these special accessories are provided with the equipment. The instruction manual for such devices shall include appropriate instructions on the first page of text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.

Table of Contents

Rule	Description	Page
	Test Report	1
	Expository Statement for Permissive Changes	2
2.1033(c)	General Information Required	3
2.1033(c)(14)	Rule Summary	6
	Standard Test Conditions and Engineering Practices	7
2.1046(a)	ERP Carrier Power (Radiated)	8
2.1051, 2.1049(c), 24, 24.238(b)		9
	Transmitter Conducted Measurements	9
2.1053(a)	Field Strength of Spurious Radiation	16
2.202(g)	Necessary Bandwidth and Emission Bandwidth	20

Page Number 1 of 20.

Required information per ISO/IEC Guide 25-1990, paragraph 13.2:

a)

Test Report

b) Laboratory:
(FCC: 31040/SIT)
(Canada: IC 2044)

M. Flom Associates, Inc.
3356 N. San Marcos Place, Suite 107
Chandler, AZ 85225

c) Report Number:

d0370016

d) Client:

Vertu Ltd.
Beacon Hill Road
Church Crookham, Hampshire GU52 8DY UK

e) Identification:

MMII
FCC ID: P7QNP-7
Serial Numbers of Units Tested:
MFA00785 IMEI 004400/06/178570/3
MFA00786 IMEI 004400/06/178569/5
PCS 1900 GSM

Description:

f) EUT Condition:

Not required unless specified in individual tests.

g) Report Date:
EUT Received:

July 17, 2003
June 30, 2003

h, j, k):

As indicated in individual tests.

i) Sampling method:

No sampling procedure used.

l) Uncertainty:

In accordance with MFA internal quality manual.

m) Supervised by:



Morton Flom, P. Eng.

n) Results:

The results presented in this report relate only to the item tested.

o) Reproduction:

This report must not be reproduced, except in full, without written permission from this laboratory.

Page Number 2 of 20.

Expository Statement
Permissive Change

Applicant: Vertu Ltd.

FCC ID: P7QNPM-7

The purpose of this report is to provide verification evidence for continued compliance of the Vertu Model: MMII, Type NPM-7, FCCID: P7QNPM-7 GSM Mobile Phone.

The recent changes made are an improvement to the integral antenna, such that an external antenna is no longer necessary.

Prior to this revision a combined internal/external antenna was fitted, the external antenna has now been removed and the improved internal antenna will be fitted as standard in future production.

There are NO changes to the basic frequency determining and stabilization circuitry, basic modulator circuit, Transmitter active devices, or tuning targets, which remain the same.

Areas verified are those, which might be affected by the change. These are:

- 1) Transmit Power, Maximum, Low/Mid/High Channel.*
- 2) Spurious Emissions.*

The test results show continued compliance to the standards.

This change will be implemented to the P7QNPM-7 GSM Mobile Phone tested here and to the cosmetic variants previously verified through testing.

Page Number 3 of 20.

List of General Information Required for Certification

In Accordance with FCC Rules and Regulations,
Volume II, Part 2 and to

24E, Confidentiality

Sub-Part 2.1033

(c)(1): Name and Address of Applicant:

Vertu Ltd.
Beacon Hill Road
Church Crookham, Hampshire GU52 8DY UK

Manufacturer:

Applicant

(c)(2): **FCC ID:** P7QNP-7

Model Number: MMII

(c)(3): Instruction Manual(s):

Please See Attached Exhibits

(c)(4): TYPE OF EMISSION: 256KGXW

(c)(5): FREQUENCY RANGE, MHz: 1850.2 to 1909.8

(c)(6): POWER RATING, Watts: 1.0715 EIRP to 0.0017
 ___ Switchable ___ x Variable ___ N/A

FCC GRANT NOTE:

BC - The output power is continuously variable from the value listed in this entry to 5%-10% of the value listed.

(c)(7): MAXIMUM POWER RATING, Watts: 1

Page Number 4 of 20.

Subpart 2.1033 (continued)



(c)(8): Voltages & Currents in All Elements in Final RF Stage, Including Final Transistor or Solid State Device:

Collector Current, A	=	per manual
Collector Voltage, Vdc	=	per manual
Supply Voltage, Vdc	=	3.6

(c)(14): **Test and Measurement Data:**

Follows

M. Flom Associates, Inc. is accredited by the American Association for Laboratory Accreditation (A2LA) as shown in the scope below.



"This laboratory is accredited by the American Association for Laboratory Accreditation (A2LA) and the results shown in this report have been determined in accordance with the laboratory's terms of accreditation unless stated otherwise in the report."

Should this report contain any data for tests for which we are not accredited, or which have been undertaken by a subcontractor that is not A2LA accredited, such data would not covered by this laboratory's A2LA accreditation.

Page Number

6 of 20.

Sub-part

2.1033(c)(14):**Test and Measurement Data**

All tests and measurement data shown were performed in accordance with FCC Rules and Regulations, Volume II; Part 2, Sub-part J, Sections 2.947, 2.1033(c), 2.1041, 2.1046, 2.1047, 2.1079, 2.1051, 2.1053, 2.1055, 2.1057 and the following individual Parts:

- ☐ 21 – Domestic Public Fixed Radio Services
- ☐ 22 – Public Mobile Services
- ☐ 22 Subpart H - Cellular Radiotelephone Service
- ☐ 22.901(d) - Alternative technologies and auxiliary services
- ☐ 23 – International Fixed Public Radiocommunication services
- ☒ 24 – Personal Communications Services
- ☐ 74 Subpart H - Low Power Auxiliary Stations
- ☐ 80 – Stations in the Maritime Services
- ☐ 80 Subpart E - General Technical Standards
- ☐ 80 Subpart F - Equipment Authorization for Compulsory Ships
- ☐ 80 Subpart K - Private Coast Stations and Marine Utility Stations
- ☐ 80 Subpart S - Compulsory Radiotelephone Installations for Small Passenger Boats
- ☐ 80 Subpart T - Radiotelephone Installation Required for Vessels on the Great Lakes
- ☐ 80 Subpart U - Radiotelephone Installations Required by the Bridge-to-Bridge Act
- ☐ 80 Subpart V - Emergency Position Indicating Radiobeacons (EPIRB'S)
- ☐ 80 Subpart W - Global Maritime Distress and Safety System (GMDSS)
- ☐ 80 Subpart X - Voluntary Radio Installations
- ☐ 87 – Aviation Services
- ☐ 90 – Private Land Mobile Radio Services
- ☐ 94 – Private Operational-Fixed Microwave Service
- ☐ 95 Subpart A - General Mobile Radio Service (GMRS)
- ☐ 95 Subpart C - Radio Control (R/C) Radio Service
- ☐ 95 Subpart D - Citizens Band (CB) Radio Service
- ☐ 95 Subpart E - Family Radio Service
- ☐ 95 Subpart F - Interactive Video and Data Service (IVDS)
- ☐ 97 - Amateur Radio Service
- ☐ 101 – Fixed Microwave Services

Standard Test Conditions
and
Engineering Practices

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-1992/2000 Draft, section 6.1.9, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst case measurements.

For PCS Equipment:

Pursuant to Section 24.51(d), the EUT complies with IEEE C95.1-1991, "IEEE Standards for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz."

The EUT uses digital modulation, as such, measurements of the modulation characteristics are not applicable. The applicant has provided a description of the modulation particular to the EUT.

Pursuant to Section 24.238(c), the EUT was tested at it's lowest and highest possible tuned frequencies.

Page Number


8 of 20.

Name of Test: ERP Carrier Power (Radiated)**Specification:** TIA/EIA 603A (Substitution Method)

2.2.17.1 Definition: The average radiated power of a licensed device is the equivalent power required, when delivered to a half-wave dipole or horn antenna, to produce at a distant point the same average received power as produced by the licensed device.

2.2.17.2 Method of Measurement:

a) Connect the equipment as illustrated. Place the transmitter to be tested on the turntable in the standard test site.



b) Raise and lower the test antenna from 1m to 6 m with the transmitter facing the antenna and record the highest received signal in dB as LVL.

c) Repeat step b) for seven additional readings at 45° interval positions of the turntable.

d) Replace the transmitter under test with a half-wave or horn vertically polarized antenna. The center of the antenna should be at the same location as the transmitter under test. Connect the antenna to a signal generator with a known output power and record the path loss in dB or LOSS.

e) Calculate the average radiated output power from the readings in step c) and d) by the following:

$$\text{average radiated power} = 10 \log_{10} \sum 10(\text{LVL} - \text{LOSS})/10 \text{ (dBm)}$$

Results

	1850.2 MHz		1880 MHz		1909.8 MHz	
	LVL, dbm	Path Loss, db	LVL, dbm	Path Loss, db	LVL, dbm	Path Loss, db
0°	28.1	0.8	18.4	-0.1	24.0	0.1
45°	13.8	0.8	29.4	-0.1	22.6	0.1
90°	24.5	0.8	23.2	-0.1	29.9	0.1
135°	21.4	0.8	21.9	-0.1	21.2	0.1
180°	23.4	0.8	21.2	-0.1	21.8	0.1
225°	15.3	0.8	24.1	-0.1	24.7	0.1
270°	22.8	0.8	20.5	-0.1	20.8	0.1
315°	24.4	0.8	23.4	-0.1	18.6	0.1
Av. Radiated Power:		1850.2 MHz	1880.0 MHz	1909.8 MHz		
		22.51 dbm	22.66 dbm	23.05 dbm		

Page Number 9 of 20.

Name of Test: Transmitter Conducted Measurements

Specification: 47 CFR 2.1051: Unwanted (spurious) Emissions
2.1049(c), 24.238(b): Occupied Bandwidth
24: Emissions at Band Edges

Guide: As indicated on page **Error! Bookmark not defined.**

Test Equipment: As per attached page

Measurement Procedure

1. The EUT and test equipment were set up as shown on the following page with the Spectrum Analyzer connected.
2. The low and high channels for all RF powers within the designated frequency block(s) were measured.
3. Measurement Results: Attached




Performed By:

David Lee

Transmitter Spurious Emission

Test A. Occupied Bandwidth (In-Band Spurious)


Test B. Out-of-Band Spurious



Asset	Description (as applicable)	s/n
(1)	Audio Oscillator/Generator	
i00010	HP 204D	1105A04683
i00017	HP 8903A	2216A01753
i00012	HP 3312A	1432A11250
(2)	Coaxial Attenuator	
i00122	Narda 766-10	7802
i00123	Narda 766-10	7802A
i00069	Bird 8329 (30 dB)	1006
i00113	Sierra 661A-3D	1059
(3)	Filters; Notch, HP, LP, BP	
i00126	Eagle TNF-1	100-250
i00125	Eagle TNF-1	50-60
i00124	Eagle TNF-1	250-850
(4)	Spectrum Analyzer	
i00048	HP 8566B	2511A01467
i00029	HP 8563E	3213A00104

Page Number 11 of 20.

Name of Test: Emission Masks (Occupied Bandwidth)
g0370050: 2003-Jul-01 Tue 13:38:00
State: 2:High Power



Power:
Modulation:


HIGH
NONE
MASK: FCC, 24, BROADBAND GSM
PCS

Performed By:

David Lee

Page Number 12 of 20.

Name of Test: Emission Masks (Occupied Bandwidth)
g0370051: 2003-Jul-01 Tue 13:44:00
State: 2:High Power



Power:
Modulation:


HIGH
GMSK
MASK: FCC, 24, BROADBAND GSM
PCS

Performed By:

David Lee

Page Number 13 of 20.

Name of Test: Emission Masks (Occupied Bandwidth)
g0370052: 2003-Jul-01 Tue 13:46:00
State: 2:High Power




Power: HIGH
Modulation: GSMK
99% POWER BANDWIDTH

Performed By:

David Lee

Page Number 14 of 20.

Name of Test: Emission Masks (Occupied Bandwidth)
g0370054: 2003-Jul-01 Tue 15:49:00
State: 2:High Power



Power:
Modulation:


HIGH
GMSK
UPPER EDGE

Performed By:

David Lee

Page Number 15 of 20.

Name of Test: Emission Masks (Occupied Bandwidth)
g0370055: 2003-Jul-01 Tue 15:55:00
State: 2:High Power



Power:
Modulation:

HIGH
GMSK
LOWER EDGE

Performed By:

David Lee

Page Number 16 of 20.

Name of Test: Field Strength of Spurious Radiation

Specification: 47 CFR 2.1053(a)


Guide: ANSI/TIA/EIA-603-1992/2001, Paragraph 1.2.12 and Table 16, 47 CFR 22.917

Measurement Procedure

1.2.12.1 Definition: Radiated spurious emissions are emissions from the equipment when transmitting into a non-radiating load on a frequency or frequencies which are outside an occupied band sufficient to ensure transmission of information of required quality for the class of communications desired.


1.2.12.2 Method of Measurement

- A) Connect the equipment as illustrated
- B) Adjust the spectrum analyzer for the following settings:
 - 1) Resolution Bandwidth 100 kHz (<1 GHz), 1 MHz (> 1GHz).
 - 2) Video Bandwidth ≥ 3 times Resolution Bandwidth, or 30 kHz (22.917)
 - 3) Sweep Speed ≤ 2000 Hz/second
 - 4) Detector Mode = Mean or Average Power
- C) Place the transmitter to be tested on the turntable in the standard test site. The transmitter is transmitting into a non-radiating load which is placed on the turntable. The RF cable to this load should be of minimum length.



Name of Test: Field Strength of Spurious Radiation (Cont.)

- D) For each spurious measurement the test antenna should be adjusted to the correct length for the frequency involved. This length may be determined from a calibration ruler supplied with the equipment. Measurements shall be made from the lowest radio frequency generated in the equipment to the tenth harmonic of the carrier, except for the region close to the carrier equal to \pm the test bandwidth (see section 1.3.4.4).
- E) For each spurious frequency, raise and lower the test antenna from 1 m to 4 m to obtain a maximum reading on the spectrum analyzer with the test antenna at horizontal polarity. Repeat this procedure to obtain the highest possible reading. Record this maximum reading.
- F) Repeat step E) for each spurious frequency with the test antenna polarized vertically.



- G) Reconnect the equipment as illustrated.
- H) Keep the spectrum analyzer adjusted as in step B).
- I) Remove the transmitter and replace it with a substitution antenna (the antenna should be half-wavelength for each frequency involved). The center of the substitution antenna should be approximately at the same location as the center of the transmitter. At lower frequencies, where the substitution antenna is very long, this will be impossible to achieve when the antenna is polarized vertically. In such case the lower end of the antenna should be 0.3 m above the ground.

Page Number 18 of 20.

Name of Test: Field Strength of Spurious Radiation (Cont.)

- J) Feed the substitution antenna at the transmitter end with a signal generator connected to the antenna by means of a non-radiating cable. With the antennas at both ends horizontally polarized and with the signal generator tuned to a particular spurious frequency, raise and lower the test antenna to obtain a maximum reading at the spectrum analyzer. Adjust the level of the signal generator output until the previously recorded maximum reading for this set of conditions is obtained. This should be done carefully repeating the adjustment of the test antenna and generator output.
- K) Repeat step J) with both antennas vertically polarized for each spurious frequency.
- L) Calculate power in dBm into a reference ideal half-wave dipole antenna by reducing the readings obtained in steps J) and K) by the power loss in the cable between the generator and the antenna and further corrected for the gain of the substitution antenna used relative to an ideal half-wave dipole antenna.
- M) The levels recorded in step L) are absolute levels of radiated spurious emissions in dBm. The radiated spurious emissions in dB can be calculated by the following:

$$\text{Radiated spurious emissions dB} = 10\log_{10}(\text{TX power in watts}/0.001) - \text{the levels in step I)}$$

NOTE: It is permissible that other antennas provided can be referenced to a dipole.

Test Equipment:

Asset (as applicable)	Description	s/n	Cycle	Last Cal
<small>Per ANSI C63.4-1992/2000 Draft, 10.1.4</small>				
Transducer				
i00088	EMCO 3109-B 25MHz-300MHz	2336	12 mo.	Sep-02
i00065	EMCO 3301-B Active Monopole	2635	12 mo.	Sep-02
i00089	Apriel 2001 200MHz-1GHz	001500	12 mo.	Sep-02
i00103	EMCO 3115 1GHz-18GHz	9208-3925	12 mo.	Sep-02
Amplifier				
i00028	HP 8449A	2749A00121	12 mo.	Mar-03
Spectrum Analyzer				
i00029	HP 8563E	3213A00104	12 mo.	Jan-03
i00033	HP 85462A	3625A00357	12 mo.	Jan-03
i00048	HP 8566B	2511AD1467	6 mo.	Jun-03

Page Number 19 of 20.

Name of Test: Field Strength of Spurious Radiation
g0370044: 2003-Jul-01 Tue 07:59:00
State: 1:Low Power

Frequency Tuned, MHz	Frequency Emission, MHz	EIRP, dBm	EIRP, dbc
1850.200000	3700.260834	-48.9	≤ -65.25
1880.000000	3759.853333	-45.5	≤ -65.25
1909.800000	3819.465000	-50.4	≤ -65.25
1850.200000	5550.390834	-47.5	≤ -65.25
1880.000000	5639.783333	-44.9	≤ -65.25
1909.800000	5729.197500	-52.6	≤ -65.25
1850.200000	7400.520834	-41.9	≤ -65.25
1880.000000	7519.716667	-44.7	≤ -65.25
1909.800000	7638.930000	-43.7	≤ -65.25
1850.200000	9250.650834	-45.1	≤ -65.25
1880.000000	9399.646667	-43	≤ -65.25
1909.800000	9548.662500	-42.3	≤ -65.25
1850.200000	11100.780834	-39	≤ -65.25
1880.000000	11279.596667	-42.8	≤ -65.25
1909.800000	11458.395000	-39.4	≤ -65.25

Page Number 20 of 20.

Name of Test: Necessary Bandwidth and Emission Bandwidth

Specification: 47 CFR 2.202(g)

Modulation = 256KGXW

Necessary Bandwidth:

Necessary Bandwidth (B_N), kHz = 256
(measured at the 99.75% power bandwidth)



Performed By:
END

OF

David Lee
TEST

REPORT

**Testimonial
and
Statement of Certification**

This is to certify that:

1. **That** the application was prepared either by, or under the direct supervision of, the undersigned.
2. **That** the technical data supplied with the application was taken under my direction and supervision.
3. **That** the data was obtained on representative units, randomly selected.
4. **That**, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

Certifying Engineer:

A handwritten signature in black ink, appearing to read "M. Flom P. Eng.", with a horizontal line drawn underneath the signature.

Morton Flom, P. Eng.