

## Exhibit 17

### SECTION 2.995

#### MEASUREMENT OF FREQUENCY STABILITY

##### RESPONSE:

The frequency stabilization and accuracy of the CDMA signal amplified by the ICLA is a function of the input signal which it is provided from the CBR (FCC ID: AS5CMP-26). The Time Frequency Unit (TFU) provides the time and frequency reference used by the CBR (FCC ID: AS5CMP-26). The TFU is highly accurate time and frequency unit which relies upon a signal lock of GPS satellite signals to provide the primary discipline of system timing. In the event of loss of GPS lock the Oscillator Module (OM) can provides up to eight hours of freewheel operation. The system provides for automatic timing synchronization upon reacquisition of GPS lock. These units are powered by an AC-DC power converter with battery backup to provide immunity to power fluctuations and failures.

This system exceeds the frequency stability requirements necessary for **FLEXENT**® system compliance with FCC Rules for frequency stability. These devices are compliant with FCC Part 15 rules when powered by and installed in a Lucent Technologies Inc. **FLEXENT**® MicroCell. The MicroCell's small size and circuit integration precluded individual testing outside the cabinet.

The following frequency stability test data for the TFU, CBR and OM was measured as installed and tested in a **FLEXENT**® MicroCell. The entire MicroCell was subjected to the FCC specified environments while operating at full rated power. Both carrier center frequency and reference oscillator deviations were measured.

##### Results:

**The frequency stability performance for the ICLA / FCC ID: AS5CMP-27 was presented in the original filing and has not changed. The data provided at that time documented that the worst case frequency stability over temperature and voltage was 0.015 ppm. The average stability was 0.0056 ppm.**