

FCC ID: 2AB4KMETYH823
Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

We use 5mm as separation distance to calculate.

Maximum measured transmitter power:

BT DSS:

Transmit Frequency (GHz)	Mode	peak conducted output power (dBm)	EIRP (dBm)	tune up maximum power	Result calculation	1-g SAR
2.402	GFSK	-1.076	1.224	2	0.49	3.0
2.441	GFSK	-0.281	2.019	3	0.62	3.0
2.480	GFSK	0.948	3.248	4	0.79	3.0
2.402	pi/4-DQPSK	-0.360	1.94	2	0.49	3.0
2.441	pi/4-DQPSK	0.366	2.666	3	0.62	3.0
2.480	pi/4-DQPSK	1.592	3.892	4	0.79	3.0

Conclusion:
For the max result : $0.79 \leq 3.0$ for 1-g SAR, No SAR is required.

Signature: 

Date: 2017-09-28

NAME AND TITLE (Please print or type): David Lee/Manager
COMPANY (Please print or type): EMTEK (Shenzhen) Co.,Ltd./Building 69, Majialong Industry Zone, Nanshan District, Shenzhen,Guangdong,China