

# LABORATORY TEST REPORT

## RADIO PERFORMANCE MEASUREMENTS

for the  
TPDC0B Handportable Transceiver

Tested in accordance with:  
FCC 47 CFR Parts 80 and 90

Report Revision: 1  
Issue Date: 5 April 2019

PREPARED BY: L. M. White

  
Test Technician

CHECKED & APPROVED BY: M. C. James

  
Laboratory Technical Manager



FCC REGISTRATION: 838288

All tests reported herein have been performed in accordance with the laboratory's scope of accreditation.

This document must not be reproduced except in full, without the written permission of the Compliance Laboratory Manager

TELTEST Laboratories (A Division of Tait International Ltd)  
PO Box 1645, 558 Wairakei Road, Christchurch, New Zealand.

Telephone: 64 3 358 3399  
FAX: 64 3 359 4632

## TABLE OF CONTENTS

REVISION .....	3
INTRODUCTION .....	4
STATEMENT OF COMPLIANCE .....	5
MODULATION TYPES, NECESSARY BANDWIDTH & EMISSION DESIGNATORS .....	6
TEST RESULTS.....	8
TRANSMITTER OUTPUT POWER (CONDUCTED) .....	8
TRANSMITTER AUDIO FREQUENCY RESPONSE - PRE-EMPHASIS.....	9
TRANSMITTER MODULATION LIMITING .....	13
TRANSMITTER OCCUPIED BANDWIDTH AND SPECTRUM MASKS .....	17
TRANSMITTER SPURIOUS EMISSIONS (CONDUCTED).....	48
TRANSMITTER SPURIOUS EMISSIONS (RADIATED).....	58
TRANSIENT FREQUENCY BEHAVIOR.....	62
TRANSMITTER FREQUENCY STABILITY - TEMPERATURE .....	65
TRANSMITTER FREQUENCY STABILITY - VOLTAGE .....	67
TEST EQUIPMENT LIST.....	68
ANNEX A – TEST SETUP DETAILS.....	70

## REVISION

Date	Revision	Comments
5 April 2019	1	Initial test report

## INTRODUCTION

Type approval testing of the TPDC0B, 5 Watt, Handportable transceiver in order to demonstrate compliance with FCC 47 Parts 80 & 90. This radio supports analogue, digital FFSK, Digital Mobile Radio (DMR), APCO P25 phase-1 and APCO P25 phase-2 modulations.

### REPORT PREPARED FOR

Tait International Ltd  
245 Wooldridge Road  
Harewood  
Christchurch 8051  
New Zealand

### DESCRIPTION OF SAMPLE

Manufacturer: Tait International Limited  
Equipment: Handportable Transceiver  
Type: TPDC0B  
Product Code: T03-22112-CBEA  
Serial Number(s): 26126441  
Frequency range: 173.3 → 225.0 MHz  
Transmit Power: 5 W

Modulation		Channel Spacing	Speech Channels	Symbol Rate (symbols/sec)	Data Rate (bps)
Analogue FM		12.5 kHz & 25 kHz	1	-	-
FFSK	Fast Frequency Shift Keying	12.5 kHz & 25 kHz	-	1200	1200
		12.5 kHz & 25 kHz	-	2400	2400
Digital Mobile Radio (DMR)	4 Level FSK (2 slot TDMA) (ETSI TS102 361-1)	12.5 kHz	2	4800	9600
APCO P25 Phase 1	C4FM (TIA 102)	12.5 kHz	1	4800	9600
APCO P25 Phase 2	H-CPM (2 slot TDMA) (TIA 102)	12.5 kHz	2	6000	12000

### HARDWARE & SOFTWARE

Quantity: 1

	Analogue, FFSK and DMR tests	P25 tests
Hardware ID	TPDB5X-C002_0002	TPDB5X-C002_0002
Boot Code	QPD5B_S00_3.05.11.0001	QPD5B_S00_3.05.11.0001
DSP	QPD5A_E00_2.19.05.0054	QPD5A_A02_2.13.03.0039
Radio Application	QPD5F_E00_2.19.05.0054	QPD5F_A00_2.13.03.0039
Firmware Package	QI93P_E00_2.19.05.0054	QI94P_A02_2.13.03.0039
FPGA Image	QPD5G_S00_1.12.14.0001	QPD5G_S00_1.12.14.0001

### TEST CONDITIONS

All testing was performed between 28 March → 3 April 2019, and under the following conditions:

Ambient temperature: 15°C → 30°C  
Relative Humidity: 20% → 75%  
Standard Test Voltage: 7.5 V<sub>DC</sub>

## STATEMENT OF COMPLIANCE

We, TELTEST LABORATORIES of 558 Wairakei Road, Christchurch, New Zealand, declare under our sole responsibility that the product:

Equipment: Handportable Transceiver  
Type: TPDC0B  
Product Code: T03-22112-CBEA  
Serial Number(s): 26126441  
Quantity: 1

to which this declaration relates, is in conformity with the following standards:


FCC 47 CFR Parts 80 and 90

**Signature:**



M. C. James  
Laboratory Technical Manager

**Date:**



## MODULATION TYPES, NECESSARY BANDWIDTH & EMISSION DESIGNATORS

### MODULATION TYPES:

F3E	Analogue Frequency Modulation (FM)	
G3E	Analogue Phase Modulation (PM)	
F2D	FFSK	1200 bps and 2400 bps
FXW	DMR Digital Voice	9600 bps
FXD	DMR Digital Data	9600 bps
F1E, F7E	P25 phase 1 Digital Voice	9600 bps
F1D, F7D	P25 phase 1 Digital Data	9600 bps
F1W	P25 phase 2 Digital Voice / Data	12000 bps

CHANNEL SPACINGS: 12.5 kHz                      25.0 kHz

### EMISSION DESIGNATORS:

	12.5 kHz	25.0 kHz
Analog FM	11K0F3E 11K0G3E	16K0F3E 16K0G3E
FFSK Data 1200 bps	6K60F2D	9K60F2D
FFSK Data 2400 bps	7K80F2D	10K8F2D
Digital Voice DMR	7K60FXW	
Digital Data DMR	7K60FXD	
Digital Voice P25 phase 1	8K10F1E	
Digital Data P25 phase 1	8K10F1D	
Digital Voice P25 phase 2	8K10F1W	
Digital Data P25 phase 2	8K10F1W	

### CALCULATIONS

Equation:  $B_n = 2M + 2Dk$

(M is highest modulating frequency; D is peak allowable deviation; k is a constant of 1 for FM)

#### Analog Voice 12.5 kHz Bandwidth

Necessary bandwidth

M = 3.0 kHz

D = 2.5 kHz

$$B_n = (2 \times 3.0) + (2 \times 2.5) \times 1 \\ = 11.0 \text{ kHz}$$

Emission Designator

**11K0F3E**

F3E represents an FM voice transmission

**11K0G3E**

G3E represents a PM Voice transmission

#### Analog Voice 25.0 kHz Bandwidth

Necessary bandwidth

M = 3.0 kHz

D = 5.0 kHz

$$B_n = (2 \times 3.0) + (2 \times 5.0) \times 1 \\ = 16.0 \text{ kHz}$$

Emission Designator

**16K0F3E**

F3E represents an FM voice transmission

**16K0G3E**

G3E represents a PM voice transmission

#### Fast Frequency Shift Keying (FFSK – 1200 bps) 12.5 kHz Bandwidth

Necessary bandwidth

M = 1.8 kHz

D = 1.5 kHz (60% of peak deviation)

$$B_n = (2 \times 1.8) + (2 \times 1.5) \times 1 \\ = 6.6 \text{ kHz}$$

Emission Designator

**6K60F2D**

F2D represents a FM data transmission with the use of a modulating sub carrier

#### Fast Frequency Shift Keying (FFSK – 1200 bps) 25.0 kHz Bandwidth

Necessary bandwidth

M = 1.8 kHz

D = 3.0 kHz (60% of peak deviation)

$$B_n = (2 \times 1.8) + (2 \times 3.0) \times 1 \\ = 9.6 \text{ kHz}$$

Emission Designator

**9K60F2D**

F2D represents a FM data transmission with the use of a modulating sub carrier

## Emission Designators – Continued

### Fast Frequency Shift Keying (FFSK – 2400 bps) 12.5 kHz Bandwidth

Necessary bandwidth

M = 2.4 kHz

D = 1.5 kHz (60% of peak deviation)

$$B_n = (2 \times 2.4) + (2 \times 1.5) \times 1 \\ = 7.8 \text{ kHz}$$

Emission Designator

**7K80F2D**

F2D represents a FM data transmission with the use of a modulating sub carrier

### Fast Frequency Shift Keying (FFSK – 2400 bps) 25.0 kHz Bandwidth

Necessary bandwidth

M = 2.4 kHz

D = 3.0 kHz (60% of peak deviation)

$$B_n = (2 \times 2.4) + (2 \times 3.0) \times 1 \\ = 10.8 \text{ kHz}$$

Emission Designator

**10K8F2D**

F2D represents a FM data transmission with the use of a modulating sub carrier

### Digital Voice 12.5 kHz Bandwidth DMR

99% bandwidth

= 7.6 kHz

Emission Designator

**7K60FXW**

FXW represents a FM Time Division Multiple Access (TDMA) combination of data and telephony

### Digital Data 12.5 kHz Bandwidth DMR

99% bandwidth

= 7.6 kHz

Emission Designator

**7K60FXD**

FXD represents FM Time Division Multiple Access (TDMA) data only

### Digital Voice 12.5 kHz Bandwidth P25 phase 1

99% bandwidth

= 8.1 kHz

Emission Designator

**8K10F1E**

F1E represents a digital FM voice transmission

### Digital Data 12.5 kHz Bandwidth P25 phase 1

99% bandwidth

= 8.1 kHz

Emission Designator

**8K10F1D**

F1D represents an digital FM data transmission

### Digital Voice 12.5 kHz Bandwidth P25 phase 2

99% bandwidth

= 8.1 kHz

Emission Designator

**8K10F1W**

F1W represents a single FM telephony channel

### Digital Data 12.5 kHz Bandwidth P25 phase 2

99% bandwidth

= 8.1 kHz

Emission Designator

**8K10F1W**

F1W represents digital FM data transmission

## TEST RESULTS

### TRANSMITTER OUTPUT POWER (CONDUCTED)

SPECIFICATION: FCC 47 CFR 2.1046

GUIDE: TIA/EIA-603D 2.2.1

#### MEASUREMENT PROCEDURE:

1. Refer Annex A for Equipment set up.
2. The coaxial attenuator has an impedance of 50 Ohms.
3. The unmodulated output power was measured with an RF Power meter.

#### MEASUREMENT RESULTS:

Manufacturer's Rated Output Power:

Switchable: 5 W and 1 W

Nominal 5 W	173.3 MHz	216.5 MHz	219.5 MHz	221.5 MHz
Measured	5.2	5.2	5.2	5.2
Variation (%)	3.9	4.7	4.7	4.6
Nominal 1 W	173.3 MHz	216.5 MHz	219.5 MHz	221.5 MHz
Measured	1.1	1.1	1.1	1.1
Variation (%)	5.0	5.6	6.0	6.2
Measurement Uncertainty	$\pm 0.6$ dB			

#### LIMIT CLAUSE:

FCC 47 CFR 90.205 (s)

The output power shall not exceed by more than 20%... the manufacturer's rated output power for the particular transmitter specifically listed on the authorization.



## TRANSMITTER AUDIO FREQUENCY RESPONSE - PRE-EMPHASIS

SPECIFICATION: FCC 47 CFR 2.1047 (a)

GUIDE: TIA/EIA-603D 2.2.6

### MEASUREMENT PROCEDURE:

1. Refer Annex A for Equipment set up.
2. An audio input tone of 1000 Hz was applied with the level set to obtain 20% of maximum deviation. This was used as the 0 dB reference point.
3. The AF was varied while the audio level was held constant.
4. The response in dB relative to 1000 Hz was measured.

### MEASUREMENT RESULTS:

See the plots on the following pages for 12.5 kHz & 25.0 kHz channel spacings tested at 5 W transmit power.


LIMIT CLAUSE: TIA/EIA-603D 3.2.6

MEASUREMENT UNCERTAINTY:  $\pm 1.5 \%$

SPECIFICATION: FCC 47 CFR 2.1047 (a)

Tx FREQUENCY: 173.3 MHz

12.5 kHz Channel Spacing




## Transmitter Audio Frequency Response – Pre-emphasis

SPECIFICATION: FCC 47 CFR 2.1047 (a)


Tx FREQUENCY: 216.5 MHz

12.5 kHz Channel Spacing



Tx FREQUENCY: 216.5 MHz

25.0 kHz Channel Spacing




## Transmitter Audio Frequency Response – Pre-emphasis

SPECIFICATION: FCC 47 CFR 2.1047 (a)


Tx FREQUENCY: 219.5 MHz

12.5 kHz Channel Spacing



Tx FREQUENCY: 219.5 MHz


25.0 kHz Channel Spacing



Transmitter Audio Frequency Response – Pre-emphasis

SPECIFICATION: FCC 47 CFR 2.1047 (a)

Tx FREQUENCY: 221.5 MHz 12.5 kHz Channel Spacing



## TRANSMITTER MODULATION LIMITING

SPECIFICATION: FCC 47 CFR 2.1047 (b)

GUIDE: TIA/EIA-603D 2.2.3

### MEASUREMENT PROCEDURE:

1. Refer Annex A for Equipment set up.
2. The modulation response was measured at three audio frequencies while varying the input level.
3. Measurements were made for both Positive and Negative Deviation.

### MEASUREMENT RESULTS:


See the plots on the following pages for 12.5 kHz & 25.0 kHz channel spacings.

LIMIT CLAUSE: TIA/EIA-603D 1.3.4.4

MEASUREMENT UNCERTAINTY:  $\pm 1.5 \%$

Tx FREQUENCY: 173.3 MHz

12.5 kHz Channel Spacing




## Transmitter Modulation Limiting

SPECIFICATION: FCC 47 CFR 2.1047 (b)


Tx FREQUENCY: 216.5 MHz

12.5 kHz Channel Spacing



Tx FREQUENCY: 216.5 MHz

25.0 kHz Channel Spacing




## Transmitter Modulation Limiting

SPECIFICATION: FCC 47 CFR 2.1047 (b)


Tx FREQUENCY: 219.5 MHz

12.5 kHz Channel Spacing



Tx FREQUENCY: 219.5 MHz

25.0 kHz Channel Spacing




## Transmitter Modulation Limiting

SPECIFICATION: FCC 47 CFR 2.1047 (b)

Tx FREQUENCY: 221.5 MHz

12.5 kHz Channel Spacing





## TRANSMITTER OCCUPIED BANDWIDTH AND SPECTRUM MASKS

SPECIFICATION: FCC 47 CFR 2.1049 (c)

GUIDE: TIA/EIA-603D 2.2.11 (Analog)  
TIA-102.CAAA-C 2.2.5 (Digital)

### MEASUREMENT PROCEDURE:

1. Refer Annex A for Equipment Set up.
2. For analog measurements: The EUT was modulated by a 2500 Hz tone at an input level 16 dB above a level that produced 50% deviation. The input level was established at the frequency of maximum response of the audio modulating circuit.  
For Data measurements: The EUT was modulated with an internally generated pseudo random bit sequence at the appropriate Baud rates.
3. The Occupied Bandwidth was measured on the Spectrum Analyser, with bandwidth settings as follows.

Emission Mask D – Resolution Bandwidth = 100 Hz, Video Bandwidth = 1 kHz

Emission Mask B, and F – Resolution bandwidth = 300 Hz, Video Bandwidth = 3 kHz

Please note: frequencies in the 216-220 MHz band are to be tested with emission mask found in part 80.211 (f). This mask is the same as Mask B found in Part 90.210

### MEASUREMENT RESULTS:

See the plots on the following pages for 12.5 kHz & 25.0 kHz channel spacings.

MEASUREMENT UNCERTAINTY 95%  $\pm 0.65\text{dB}$

LIMIT CLAUSE: FCC 47 CFR 90.210

### EMISSION MASKS

Emission Mask D	12.5 kHz Channel Spacing	Analog, FFSK, Digital Voice/Data
Emission Mask B	12.5 kHz & 25.0 kHz Channel Spacing	Analog, FFSK, Digital Voice/Data
Emission Mask F	12.5 kHz Channel Spacing	Analog, FFSK, Digital Voice/Data

### DATA SPEED


Digital Voice/Data	12.5 kHz Channel Spacing	9600 bps
FFSK	12.5 kHz Channel Spacing	1200 bps & 2400 bps
FFSK	25.0 kHz Channel Spacing	1200 bps & 2400 bps

## Occupied Bandwidth and Spectrum Masks


ANALOG VOICE

SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 173.3 MHz 5 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 173.3 MHz 1 W 12.5 kHz Channel Spacing




## Occupied Bandwidth and Spectrum Masks


ANALOG VOICE

SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 216.5 MHz 5 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 216.5 MHz 1 W 12.5 kHz Channel Spacing




## Occupied Bandwidth and Spectrum Masks


ANALOG VOICE

SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 219.5 MHz 5 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 219.5 MHz 1 W 12.5 kHz Channel Spacing




## Occupied Bandwidth and Spectrum Masks


ANALOG VOICE

SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 221.5 MHz 5 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 221.5 MHz 1 W 12.5 kHz Channel Spacing




## Occupied Bandwidth and Spectrum Masks


ANALOG VOICE

SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 216.5 MHz 5 W 25 kHz Channel Spacing



Tx FREQUENCY: 216.5 MHz 1 W 25 kHz Channel Spacing




## Occupied Bandwidth and Spectrum Masks


ANALOG VOICE

SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 219.5 MHz 5 W 25 kHz Channel Spacing



Tx FREQUENCY: 219.5 MHz 1 W 25 kHz Channel Spacing




## Occupied Bandwidth and Spectrum Masks


FFSK 1200 bps

SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 173.3 MHz 5 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 173.3 MHz 1 W 12.5 kHz Channel Spacing






## Occupied Bandwidth and Spectrum Masks


FFSK 1200 bps

SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 216.5 MHz 5 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 216.5 MHz 1 W 12.5 kHz Channel Spacing




## Occupied Bandwidth and Spectrum Masks


FFSK 1200 bps

SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 219.5 MHz 5 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 219.5 MHz 1 W 12.5 kHz Channel Spacing




## Occupied Bandwidth and Spectrum Masks


FFSK 1200 bps

SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 221.5 MHz 5 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 221.5 MHz 1 W 12.5 kHz Channel Spacing




## Occupied Bandwidth and Spectrum Masks


FFSK 1200 bps

SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 216.5 MHz 5 W 25 kHz Channel Spacing



Tx FREQUENCY: 216.5 MHz 1 W 25 kHz Channel Spacing




## Occupied Bandwidth and Spectrum Masks


FFSK 1200 bps

SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 219.5 MHz 5 W 25 kHz Channel Spacing



Tx FREQUENCY: 219.5 MHz 1 W 25 kHz Channel Spacing




## Occupied Bandwidth and Spectrum Masks


FFSK 2400 bps

SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 173.3 MHz 5 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 173.3 MHz 1 W 12.5 kHz Channel Spacing




## Occupied Bandwidth and Spectrum Masks


FFSK 2400 bps

SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 216.5 MHz 5 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 216.5 MHz 1 W 12.5 kHz Channel Spacing




## Occupied Bandwidth and Spectrum Masks


FFSK 2400 bps

SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 219.5 MHz 5 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 219.5 MHz 1 W 12.5 kHz Channel Spacing






## Occupied Bandwidth and Spectrum Masks


FFSK 2400 bps

SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 221.5 MHz 5 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 221.5 MHz 1 W 12.5 kHz Channel Spacing




## Occupied Bandwidth and Spectrum Masks


FFSK 2400 bps

SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 216.5 MHz 5 W 25 kHz Channel Spacing



Tx FREQUENCY: 216.5 MHz 1 W 25 kHz Channel Spacing




## Occupied Bandwidth and Spectrum Masks


FFSK 2400 bps

SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 219.5 MHz 5 W 25 kHz Channel Spacing



Tx FREQUENCY: 219.5 MHz 1 W 25 kHz Channel Spacing




## Occupied Bandwidth and Spectrum Masks

DMR


SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 173.3 MHz 5 W 12.5 kHz Channel Spacing



**DMR 173.3000MHz Mask D 5W**  
**RBW=100Hz, VBW=1000Hz, Detector Mode=Peak**  
**Result=Pass**

Tx FREQUENCY: 173.3 MHz 1 W 12.5 kHz Channel Spacing




**DMR 173.3000MHz Mask D 1W**  
**RBW=100Hz, VBW=1000Hz, Detector Mode=Peak**  
**Result=Pass**

## Occupied Bandwidth and Spectrum Masks

DMR


SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 216.5 MHz 5 W 12.5 kHz Channel Spacing



**DMR 216.5000MHz Mask B 5W**  
**RBW=300Hz, VBW=3000Hz, Detector Mode=Peak**  
**Result=Pass**

Tx FREQUENCY: 216.5 MHz 1 W 12.5 kHz Channel Spacing




**DMR 216.5000MHz Mask B 1W**  
**RBW=300Hz, VBW=3000Hz, Detector Mode=Peak**  
**Result=Pass**

## Occupied Bandwidth and Spectrum Masks

DMR


SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 219.5 MHz 5 W 12.5 kHz Channel Spacing



**DMR 219.5000MHz Mask B 5W**  
**RBW=300Hz, VBW=3000Hz, Detector Mode=Peak**  
**Result=Pass**

Tx FREQUENCY: 219.5 MHz 1 W 12.5 kHz Channel Spacing




**DMR 219.5000MHz Mask B 1W**  
**RBW=300Hz, VBW=3000Hz, Detector Mode=Peak**  
**Result=Pass**

## Occupied Bandwidth and Spectrum Masks


DMR

SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 221.5 MHz 5 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 221.5 MHz 1 W 12.5 kHz Channel Spacing




## Occupied Bandwidth and Spectrum Masks


P25 Phase I

SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 173.3 MHz 5 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 173.3 MHz 1 W 12.5 kHz Channel Spacing






## Occupied Bandwidth and Spectrum Masks


P25 Phase I

SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 216.5 MHz 5 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 216.5 MHz 1 W 12.5 kHz Channel Spacing




## Occupied Bandwidth and Spectrum Masks


P25 Phase I

SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 219.5 MHz 5 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 219.5 MHz 1 W 12.5 kHz Channel Spacing




## Occupied Bandwidth and Spectrum Masks


P25 Phase I

SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 221.5 MHz 5 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 221.5 MHz 1 W 12.5 kHz Channel Spacing




## Occupied Bandwidth and Spectrum Masks


P25 Phase II

SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 173.3 MHz 5 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 173.3 MHz 1 W 12.5 kHz Channel Spacing




## Occupied Bandwidth and Spectrum Masks


P25 Phase II

SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 216.5 MHz 5 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 216.5 MHz 1 W 12.5 kHz Channel Spacing




## Occupied Bandwidth and Spectrum Masks


P25 Phase II

SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 219.5 MHz 5 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 219.5 MHz 1 W 12.5 kHz Channel Spacing




## Occupied Bandwidth and Spectrum Masks


P25 Phase II

SPECIFICATION: FCC 47 CFR 2.1049 (c)

Tx FREQUENCY: 221.5 MHz 5 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 221.5 MHz 1 W 12.5 kHz Channel Spacing





## TRANSMITTER SPURIOUS EMISSIONS (CONDUCTED)

SPECIFICATIONS: FCC 47 CFR 2.1051

GUIDE: TIA/EIA-603D 2.2.13

### MEASUREMENT PROCEDURE:

1. Refer Annex A for equipment set up.
2. The frequency range examined was from the lowest frequency generated within the EUT, to a frequency higher than the 10<sup>th</sup> Harmonic:  
100 kHz to Fc-BW  
Fc+ BW to 10Fc (2.22 GHz)
3. The EUT was set to transmit high or low power, modulated with DMR. A scan is performed with a resolution bandwidth of 10 kHz and a video bandwidth of 30 kHz for frequencies up to 1 GHz, and a resolution bandwidth of 1 MHz and a video bandwidth of 3 MHz for frequencies above 1 GHz. A filter was used for frequencies just below the second harmonic to 1 GHz.
4. The spectrum analyser was loaded with the appropriate calibration figures to compensate for the cables, attenuator and filter losses.

Spurious emissions which were attenuated by more than 20 dB below the limit were not recorded.


A photograph of the test set-up is included below.

### MEASUREMENT RESULTS:

See the tables and plots on the following pages for 12.5 kHz & 25.0 kHz channel spacings.

LIMIT CLAUSE: FCC 47 CFR 90.210

Photo: Conducted Emissions Test Setup





### Spurious Emissions (Tx Conducted)

SPECIFICATION: FCC 47 CFR 2.1051

12.5 kHz Channel Spacing

173.3 MHz @ 5 W

Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
346.6	-38.92	-75.92


12.5 kHz Channel Spacing

173.3 MHz @ 1 W

Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
~	~	~
Measurement Uncertainty:	≤12.75 GHz ± 3.0 dB	
No other emissions were detected at a level greater than 20 dB below the limit.		

Spurious Emissions (Tx Conducted)



### Spurious Emissions (Tx Conducted)

SPECIFICATION: FCC 47 CFR 2.1051


12.5 kHz Channel Spacing                      216.5 MHz @ 5 W                      Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
~	~	~

12.5 kHz Channel Spacing                      216.5 MHz @ 1 W                      Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
~	~	~
Measurement Uncertainty:	≤12.75 GHz ± 3.0 dB	
No emissions were detected at a level greater than 20 dB below the limit.		

Spurious Emissions (Tx Conducted)



### Spurious Emissions (Tx Conducted)

SPECIFICATION: FCC 47 CFR 2.1051

12.5 kHz Channel Spacing

219.5 MHz @ 5 W

Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
~	~	~


12.5 kHz Channel Spacing

219.5 MHz @ 1 W

Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
~	~	~
Measurement Uncertainty:	≤12.75 GHz ± 3.0 dB	
No emissions were detected at a level greater than 20 dB below the limit.		

Spurious Emissions (Tx Conducted)



### Spurious Emissions (Tx Conducted)

SPECIFICATION: FCC 47 CFR 2.1051

12.5 kHz Channel Spacing

221.5 MHz @ 5 W

Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
~	~	~


12.5 kHz Channel Spacing

221.5 MHz @ 1 W

Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
~	~	~
Measurement Uncertainty:	≤12.75 GHz ± 3.0 dB	
No emissions were detected at a level greater than 20 dB below the limit.		

Spurious Emissions (Tx Conducted)





Spurious Emissions (Tx Conducted)

SPECIFICATION: FCC 47 CFR 2.1051

LIMIT CLAUSE: FCC 47 CFR 90.210

Carrier Output Power	Emission Mask D 12.5 kHz Channel Spacing $50 + 10 \log_{10} (P_{\text{Watts}})$	
	-20 dBm	-57 dBc
5 W	-20 dBm	-57 dBc
1 W	-20 dBm	-50 dBc

## TRANSMITTER SPURIOUS EMISSIONS (RADIATED)

SPECIFICATION: FCC 47 CFR 2.1053

GUIDE: TIA/EIA-603D 2.2.12

### MEASUREMENT PROCEDURE:

#### Initial Scan:

1. The EUT is placed in the S-Line TEM cell and emissions are measured from 30 MHz to 800 MHz. Any emission within 20 dB of the limit is then re-tested on the OATS.
2. The EUT is placed in the reverberation chamber and emissions are measured from 800 MHz to the upper frequency required. Any emission within 20 dB of the limit is then re-tested on the OATS.
3. The harmonics emissions up to the 6<sup>th</sup> harmonic of the fundamental frequency are measured on the OATS

#### OATS Measurement:

1. The EUT is placed on a wooden turntable at a distance of three metres from the test antenna. The output terminal is connected to an RF dummy load.
2. The test antenna is raised from 1 m to 4 m to obtain a maximum reading; the turntable is then rotated through 360° to obtain the maximum response of each spurious emission. Valid emissions are determined by switching the EUT on and off.
3. The EUT is then replaced by a signal generator and substitution antenna to make measurements by the substitution method.

### MEASUREMENT RESULTS:

See the tables on the following pages

LIMIT CLAUSE: FCC 47 CFR 90.210

## Spurious Emissions (Tx Radiated)

SPECIFICATION: FCC 47 CFR 2.1053

12.5 kHz Channel Spacing

173.3 MHz @ 5 W

Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
~	~	~

12.5 kHz Channel Spacing

173.3 MHz @ 1 W

Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
~	~	~
Measurement Uncertainty	± 4.6 dB	
No emissions were detected at a level greater than 20 dB below the limit.		

12.5 kHz Channel Spacing

216.5 MHz @ 5 W

Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
~	~	~

12.5 kHz Channel Spacing

216.5 MHz @ 1 W

Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
~	~	~
Measurement Uncertainty	± 4.6 dB	
No emissions were detected at a level greater than 20 dB below the limit.		

12.5 kHz Channel Spacing

219.5 MHz @ 5 W

Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
~	~	~

12.5 kHz Channel Spacing

219.5 MHz @ 1 W

Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
~	~	~
Measurement Uncertainty	± 4.6 dB	
No emissions were detected at a level greater than 20 dB below the limit.		

Spurious Emissions (Tx Radiated)

12.5 kHz Channel Spacing

221.5 MHz @ 5 W

Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
~	~	~

12.5 kHz Channel Spacing

221.5 MHz @ 1 W

Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
~	~	~
Measurement Uncertainty	± 4.6 dB	
No emissions were detected at a level greater than 20 dB below the limit.		

LIMIT CLAUSE: FCC 47 CFR 2.1053

Carrier Output Power	Emission Mask D 12.5 kHz Channel Spacing $50 + 10 \log_{10} (P_{\text{Watts}})$	
5 W	-20 dBm	-57 dBc
1 W	-20 dBm	-50 dBc

## Spurious Emissions (Tx Radiated)

### Open Area Test Site Results:

12.5 kHz Channel Spacing

216.5 MHz @ 5 W

Emission Mask D

Harmonics Emission Frequency (MHz)	Level (dBm)	Level (dBc)
433.0	-54.43	-91.43
649.5	-63.34	-100.34
866.0	-76.89	-113.89
1082.5	-66.37	-103.37
1299.0	-75.63	-112.63
1515.5	-67.45	-104.45
Measurement Uncertainty	$\pm 4.6$ dB	

Sample Calculation	Measurement					Result	
	Reference	Substitution					
Emission Frequency (MHz)	Reference Level (dBm)	Sig-gen Level	Cable and Attenuator Gain	Antenna Gain (dBd)	Path and Boresight corrections	dBm	nW
433.0	-82.43	-39.58	-14.69	-0.35	0.18	-54.43	3.60
		A	B	C	D	E	

Result (E) = A+B+C+D

Photo: OATS Setup



## TRANSIENT FREQUENCY BEHAVIOR

SPECIFICATION: FCC 47 CFR 90.214

GUIDE: TIA/EIA-603D 2.2.19

### MEASUREMENT PROCEDURE:

1. Refer Annex A for equipment set up.
2. Measurements and plots were made following the TIA/EIA procedure.

### MEASUREMENT RESULTS:

See the tables and plots on the following pages for 12.5 kHz channel spacing.

LIMIT CLAUSE: FCC 47 CFR 90.214

## Transient Frequency Behaviour

SPECIFICATION: FCC 47 CFR 90.214

Tx FREQUENCY: 173.3 MHz      5 W      12.5 kHz Channel Spacing

TRANSIENT RESPONSE PERIOD	CARRIER PEAK VARIATION FROM NORMAL	
	Key ON (kHz)	Key OFF (kHz)
t1	1.2	N/A
t2	0.5	N/A
t3	N/A	3.0

Confirm that during periods t1 and t3 the frequency difference does not exceed the value of one channel separation.	YES	NO
	<input type="checkbox"/>	<input type="checkbox"/>
Confirm that during the period t2 the frequency difference does not exceed half a channel separation.	YES	NO
	<input type="checkbox"/>	<input type="checkbox"/>
Confirm that during the period t2 to t3 the frequency difference does not exceed the frequency error limit.	YES	NO
	<input type="checkbox"/>	<input type="checkbox"/>

Measurement Uncertainty: Frequency  $\pm 130$  Hz; Time  $\pm 0.2\%$



LIMIT: FCC 47 CFR 90.214

TRANSIENT PERIODS	FREQUENCY RANGE	
	150 MHz – 174 MHz	421 MHz – 512 MHz
t1 (ms)	5 ms	10 ms
t2 (ms)	20 ms	25 ms
t3 (ms)	5 ms	10 ms

## Transient Frequency Behaviour

SPECIFICATION: FCC 47 CFR 90.214

Tx FREQUENCY: 173.3 MHz      5 W      12.5 kHz Channel Spacing





## TRANSMITTER FREQUENCY STABILITY - TEMPERATURE

SPECIFICATION: FCC 47 CFR 2.1055 (a) (1)

GUIDE: TIA/EIA-603D 2.2.2

### MEASUREMENT PROCEDURE:

1. Refer Annex A for equipment set up.
2. The EUT was tested for frequency error from -30° C to +50° C in 10° C increments
3. The frequency error was recorded in parts per million (ppm).

### MEASUREMENT RESULTS:

See the plots on the following pages for 12.5 kHz channel spacing.

173.3 MHz

Temperature (°C)	Error (ppm)			
	173.3 MHz	216.5 MHz	219.5 MHz	221.5 MHz
-30	0.65	0.52	0.52	0.61
-20	0.38	0.38	0.46	0.45
-10	0.66	0.40	0.53	0.59
0	0.40	0.27	0.30	0.33
10	0.44	0.31	0.27	0.31
20	0.28	0.30	0.23	0.36
30	0.32	0.29	0.42	0.29
40	0.43	0.04	0.35	0.39
50	0.40	0.35	0.42	0.42
Measurement	$\pm 7 \times 10^{-8}$			





LIMIT CLAUSE: FCC 47 CFR 90.213

Frequency range	Frequency Error (ppm)
150-174	5
220-222	1.5

LIMIT CLAUSE: FCC 47 CFR 80.209(a)

Frequency range	Frequency Error (ppm)
216-220	5

## Transmitter Frequency Stability – Temperature



## TRANSMITTER FREQUENCY STABILITY - VOLTAGE

SPECIFICATION: FCC 47 CFR 2.1055 (d) (1)

GUIDE: TIA/EIA-603D 2.2.2

### MEASUREMENT PROCEDURE:

1. Refer Annex A for equipment set up.
2. The EUT was tested for frequency error at an input voltage to the radio of nominal battery voltage and battery end point.
3. The frequency error was recorded in parts per million (ppm).

### MEASUREMENT RESULTS:

	FREQUENCY ERROR (ppm) for 12.5 kHz	
	7.5 V <sub>DC</sub>	6.375 V <sub>DC</sub>
173.3 MHz	0.05	0.05
216.5 MHz	0.04	0.05
219.5 MHz	0.05	0.03
221.5 MHz	0.03	0.03
Measurement Uncertainty		$\pm 7 \times 10^{-8}$

LIMIT CLAUSE: FCC 47 CFR 90.213

Frequency range	Frequency Error (ppm)
150-174	5
220-222	1.5

LIMIT CLAUSE: FCC 47 CFR 80.209(a)

Frequency range	Frequency Error (ppm)
216-220	5

## TEST EQUIPMENT LIST

Equipment Type	Information	Manufacturer	Model No	Serial No#	Tait ID	Cal Due
Antenna	Reference Dipoles	Emco	3121C DB1	9510-1164	E3559	14-Apr-19
Antenna	18GHz DRG	Emco	DRG3115	9512-4638	E3560	15-May-20
Antenna	Log Periodic	Schwarzbeck	VUSLP	9111-219	E4617	
Antenna	Reverb - 1-18GHz DRG	Schwarzbeck	BBHA 9120 D	9120D-885	E4857	
Antenna	Reverb - 1-18GHz DRG	Schwarzbeck	BBHA 9120 D	9120D-884	E4858	
Audio Analyser	TREVA1	Hewlett Packard	HP8903A	2437A04625	E4986	4-Oct-19
Audio Analyser	TREVA2	Hewlett Packard	HP8903B	2818A04275	E3710	28-Sep-19
Coax Cable	OATS Turntable Cable 1	Intelcom	RG214	OATS1	E4621	15-Nov-19
Coax Cable	OATS Tower Cable	Intelcom	RG214	OATS2	E4622	14-Nov-19
Coax Cable	2m Black	Suhner	RG214HF/Nm/Nm/2000	TeltestBlack2	E4623	17-Oct-19
Coax Cable	2m Black	Suhner	RG214HF/Nm/Nm/2000	TeltestBlack3	E4624	17-Oct-19
Coax Cable	2m Black	Suhner	RG214HF/Nm/Nm/2000	TeltestBlack4	E4653	18-Oct-19
Coax Cable	Reverb - 4.5m Multiflex 141	TeltestBlue6	MF 141	TeltestBlue6	E4843	18-Oct-19
Coax Cable	Reverb - 2m Multiflex 141	TeltestBlue5	MF 141	TeltestBlue5	E4844	18-Oct-19
Coax Cable	Reverb - 2m Multiflex 141	TeltestBlue4	MF 141	TeltestBlue4	E4845	18-Oct-19
Coax Cable	Reverb - 1m Multiflex 141	TeltestBlue3	MF 141	TeltestBlue3	E4846	18-Oct-19
Coax Cable	Reverb - 1m Multiflex 141	TeltestBlue2	MF 141	TeltestBlue2	E4847	18-Oct-19
Coax Cable	Reverb - 1m Multiflex 141	TeltestBlue1	MF 141	TeltestBlue1	E4848	18-Oct-19
Coax Cable	OATS Turntable Cable 2	Intelcom	RG215	OATS3	E4995	14-Nov-19
Coax Cable	2m Black	Suhner	RG214HF/Nm/Nm/2000	TeltestBlack8	E5005	17-Oct-19
Coax Cable	2m Black	Suhner	RG214HF/Nm/Nm/2000	TeltestBlack7	E5004	17-Oct-19
Environ. Chamber	Upright	Contherm	5400 RHSLT.M	1416	E4051	7-Aug-23
Environ. Chamber	Upright	Contherm	5400 RHSLT.M	1416	E4051	23-Apr-19
Filter High Pass/ Notch	135 to 175MHz	Tait		N/A	E3382	25-Sep-19
Filter High Pass/ Notch	175 to 220MHz	Tait		N/A	E3383	25-Sep-19
Modulation Analyser	TREVA1	Hewlett Packard	HP8901B (Opt 002)	2441A00393	E3073	4-Oct-19
Modulation Analyser	TREVA2	Hewlett Packard	HP8901B (Opt 002)	3704A05837	E3786	28-Sep-19
Multimeter		Fluke	77	35069359	E3237	25-Oct-19
OATS	Controller	Electrometrics	EM-4700	119	E4445	
OATS	Turntable	Electrometrics	EM-4704A	105	E4446	
OATS	Antenna Tower	Electrometrics	EM-4720-2	112	E4447	
OATS	FCC Listing Registration			837095		8-May-19
Power Meter	TREVA1 Power Head for HP8901	Hewlett Packard	HP11722A	3111A05573	E7054	28-Sep-19
Power Meter	TREVA2 Power Head for HP8901	Hewlett Packard	HP11722A	2716A02037	1575	28-Sep-19
Power Supply	60V/50A/1000W	Hewlett Packard	HP6012B	2524A00616	E3712	30-Sep-19
Power Supply	TREVA1	Agilent	HP6032A	MY41000319	E4045	24-Sep-20

TELTEST Laboratories  
Tait International Ltd  
Report Number 3977

Power Supply	TREVA2 60V/25A	Agilent	N5767A	US09F4901H	E4656	7-Oct-19
Power Supply	60V/25A	Agilent	N5767A	3111A05573	E4979	2-Oct-20
RF Amplifier	+21.7 dB 1GHz	Tait	ZFL-1000LN	E3660	E3360	17-Apr-19
RF Amplifier	0.8 - 2 GHz	Ophir	5803012A	1006	E4448	
RF Amplifier	Pre-amplifier	Agilent	87405C	MY47010688	E4941	2-Oct-19
RF Attenuator	10dB 50W	Weinschel	24-10-34	AZ0401	E3388	17-Oct-19
RF Attenuator	20dB 25W	Weinschel	33-20-33	BD5871	E3673	18-Oct-19
RF Attenuator	TREVA2 20dB 150W	Weinschel	40-20-33	CJ405	E3733	17-Oct-19
RF Attenuator	10dB 50W	Weinschel	24-10-34	BC3293	E4364	17-Oct-19
RF Attenuator	TREVA2 3dB	Weinschel	Model 1	BL9950	E4080	17-Oct-19
RF Attenuator	TREVA1 3dB	Weinschel	Model 1	BL9958	E4081	17-Oct-19
RF Attenuator	TREVA 1 20dB 150W	Weinschel	40-20-23	MF817	E4082	17-Oct-19
RF Attenuator	3dB 0.5W	Weinschel	Model 2	CH6857	E5012	17-Oct-19
RF Chamber	S-LINE TEM CELL	Rohde & Schwarz	1089.9296.02	338232/003	E3636	12-Sep-20
RF Chamber	Reverb - Stirrer controller for reverb chamber	Teseq	Stirrer Controller	29765.1	E4854	
RF Chamber	Reverb - 0.5 - 18GHz Reverberation Chamber	Teseq	RVC XS	29765	E4855	
RF Combiner	TREVA1	Minicircuits	ZFSC-4-1	-	E4083	
RF Combiner	TREVA2	Minicircuits	ZFSC-4-1	-	E4084	
RF Load	50W	Weinschel	F1426	BF0487	E3675	18-Oct-19
Signal Generator	Analog 3.2GHz	Hewlett Packard	HP8648C	3443U00543	E3558	2-Oct-19
Signal Generator	Analog 4GHz	Agilent	E4422B	GB40050320	E3788	27-Sep-19
Signal Generator	TREVA2 Analog 3.3GHz	Rohde & Schwarz	SML03 1090.3000.13	100597	E4050	29-Sep-19
Signal Generator	Digital 3GHz	Agilent	E4438C	MY45093154	E4600	3-Oct-20
Signal Generator	Digital 3GHz	Agilent	E4438C	MY49070242	E4657	9-Oct-19
Signal Generator	TREVA1 Analog 3.2GHz	Agilent	E8663D	MY50420224	E4908	2-Oct-20
Spectrum Analyser	13.2GHz	Agilent	E4445A	MY42510072	E4139	19-Jul-20
Temp & Humidity datalogger		Hobo	U21-011	10134276	E4981	22-Apr-19
TREVA 1		Teltest	-	1	-	2-May-19
TREVA 2		Teltest	-	2	-	3-May-19
Testware	Frequency Vs Temperature		April 2018	-	-	
Testware	Radiated Emissions		April 2018	-	-	
Testware	Reverb Emissions		June 2018	-	-	
Testware	Sideband Spectrum		February 2017	-	-	
Testware	S-Line Radiated Emissions		April 2018	-	-	
Testware	TREVA		7 February 2019	-	-	

NOTE: Items without calibration dates are calibrated immediately before use, or set using calibrated instruments.

