

Hong Kong Standards and Testing Centre

Applicant: J P Products Co., Ltd.

Rm 1303 Grandmark, No. 8A-10 Granville Road,

Tsimshatsui, Kowloon, Hong Kong

Description of Samples: Model name: WALKIE TALKIE

Model no.: JP-65668 Brand name: N/A

FCC ID: SVDJP-65668

Date Samples Received: 2004-12-23

Date Tested: 2005-01-06

Investigation Requested: FCC Part 15 Subpart C

Conclusions: The submitted product <u>COMPLIED</u> with the

requirements of Federal Communications Commission [FCC] Rules and Regulations Part 15. The tests were performed in accordance with the standards described above and on

Section 2.2 in this Test Report.

Remarks: ----

K C Lee, EMC for Chief Executive

This report shall not be reproduced unless with prior written approval from the Hong Kong Standards and Testing Centre.



Hong Kong Standards and Testing Centre

Date : 2005-01-20 **TEST REPORT** Page 2 of 17

No.: HM153147

CONTENT:

	Cover Content	Page 1 of 17 Page 2-3 of 17
<u>1.0</u>	General Details	
1.1	Test Laboratory	Page 4 of 17
1.2	Applicant Details Applicant HKSTC Code Number for Applicant Manufacturer	Page 4 of 17
1.3	Equipment Under Test [EUT] Description of EUT operation	Page 5 of 17
1.4	Date of Order	Page 5 of 17
1.5	Submitted Samples	Page 5 of 17
1.6	Test Duration	Page 5 of 17
1.7	Country of Origin	Page 5 of 17
1.8	Additional Information of EUT	Page 6 of 17
<u>2.0</u>	Technical Details	
2.1	Investigations Requested	Page 7 of 17
2.2	Test Standards and Results Summary	Page 7 of 17
<u>3.0</u>	<u>Test Results</u>	
3.1	Emission	Page 8-12 of 17
3.2	Bandwidth Measurement	Page 13-14 of 17



Hong Kong Standards and Testing Centre

Date : 2005-01-20 **TEST REPORT** Page 3 of 17

No.: HM153147

Appendix A

List of Measurement Equipment Page 15 of 17

Appendix B

Photographs Page 16-17 of 17

香港新界大埔工業村大宏街 10 號



Hong Kong Standards and Testing Centre

No.: HM153147

1.0 General Details

1.1 Test Laboratory

The Hong Kong Standards and Testing Centre Ltd. EMC Laboratory 10 Dai Wang Street, Taipo Industrial Estate New Territories, Hong Kong

Telephone: 852 2666 1888 Fax: 852 2664 4353

1.2 Applicant Details Applicant

J P Products Co., Ltd. Rm 1303 Grandmark, No. 8A-10 Granville Road, Tsimshatsui, Kowloon, Hong Kong

HKSTC Code Number for Applicant

MII001

Manufacturer

J P Products Co., Ltd. Rm 1303 Grandmark, No. 8A-10 Granville Road, Tsimshatsui, Kowloon, Hong Kong



Hong Kong Standards and Testing Centre

No.: HM153147

1.3 Equipment Under Test [EUT] Description of Sample

Model Name: WALKIE TALKIE
Manufacturer: J P Products Co., Ltd.

Brand Name: N/A Model Number: JP-65668

Input Voltage: 9Vd.c ("6F22" size battery x 1)

1.3.1 Description of EUT Operation

The Equipment Under Test (EUT) is an J P Products Co., Ltd., Walkie Talkies. The transmitter is a 2 button transmitter. The EUT continues to transmit while button is being pressed. It is voice transmission, Modulation by Mic and type is frequency modulation.

1.4 Date of Order

2004-12-23

1.5 Submitted Sample(s):

3 Samples per model

1.6 Test Duration

2005-01-06

1.7 Country of Origin

China



Hong Kong Standards and Testing Centre

Date : 2005-01-20 **TEST REPORT** Page 6 of 17

No.: HM153147

1.8 Additional Information of EUT

	Submitted	Not Available
User Manual		
Part List		
Circuit Diagram		
Printed Circuit Board [PCB] Layout		
Block diagram		
FCC ID Label	\boxtimes	

香港新界大埔工業村大宏街 10 號



Hong Kong Standards and Testing Centre

No.: HM153147

2.0 Technical Details

2.1 Investigations Requested

Perform ElectroMagnetic Interference measurement in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15 and ANSI C63.4:2003 for FCC Certification.

2.2 Test Standards and Results Summary Tables

	EMISSION									
Results Summary										
Test Condition Test Requirement Test Method Class / Test Result										
			Severity	Pass	Failed	N/A				
Field Strength of Fundamental Emissions & Spurious Emissions	FCC 47CFR 15.235	ANSI C63.4:2003	N/A	\boxtimes						
Radiated Emissions, 30MHz to 1GHz	FCC 47CFR 15.209	ANSI C63.4:2003	Class B			/10				
Conducted Emissions on AC, 0.15MHz to 30MHz	FCC 47CFR 15.207	ANSI C63.4:2003	Class B							

Note: N/A - Not Applicable



Hong Kong Standards and Testing Centre

Date : 2005-01-20 **TEST REPORT** Page 8 of 17

No.: HM153147

3.0 Test Results

3.1 Emission

3.1.1 Radiated Emissions (30 – 1000MHz)


Test Requirement: FCC 47CFR 15.235
Test Method: ANSI C63.4:2003
Test Date: 2005-01-06
Mode of Operation: Tx mode

Test Method:

The sample was placed 0.8m above the ground plane on the OATS *. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

*: OATS [Open Area Test Site] located at HKSTC with a metal ground plane filed with the FCC pursuant to section 2.948 of the FCC rules, with Registration Number: 607756.

Test Setup:





Hong Kong Standards and Testing Centre

No.: HM153147

Limits for Field Strength of Fundamental Emissions [FCC 47CFR 15.135]:

Frequency Range of	Field Strength of	Field Strength of
Fundamental	Fundamental Emission	Spurious Emission
	[Peak]	[Average]
[MHz]	[µV/m]	[µV/m]
49.82-49.90	100.000	10.000

Results: Transmitter

Field Strength of Fundamental Emissions									
	Peak Value								
Frequency	Measured	Correction	Field	Field	Limit @3m	E-Field			
	Level @3m	Factor	Strength	Strength		Polarity			
MHz	dBμV/m	dBμV/m	dBµV/m	μV/m	μV/m				
49.86	47.3	10.2	57.5	749.9	100,000	Vertical			

Field Strength of Fundamental Emissions								
	Average							
Frequency	Measured	Correction	Field	Field	Limit @3m	E-Field		
	Level @3m	Factor	Strength	Strength		Polarity		
MHz	dBμV/m	dBμV/m	dBµV/m	μV/m	μV/m			
49.86	47.1	10.2	57.3	732.8	10,000	Vertical		

Remarks

According to FCC 47CFR15.35, the limit on the radio frequency emissions as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

For effective averaging, the bandwidth of the video filter must be smaller than the resolution bandwidth. The higher the ratio of resolution bandwidth to video bandwidth, the greater the averaging will be recorded. Below setting for HP8572A EMI Receiver.

Resolution Bandwidth =3MHz Video Bandwidth =1Hz

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty : 30MHz to 1GHz ±4.1dB



Hong Kong Standards and Testing Centre

No.: HM153147

Limits for Radiated Emissions [FCC 47 CFR 15.209 Class B]:

Frequency Range [MHz]	Quasi-Peak Limits [μV/m]		
30-88	100		
88-216	150		
216-960	200		
Above960	500		

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

Results: Transmitter

Radiated Emissions Quasi-Peak									
Frequency	Me	asured	Correction		Field		Field	Limit @3m	E-Field
	Lev	el @3m	Factor	s	trength	S	trength		Polarity
MHz	dE	3μV/m	dΒμV/m	d	BµV/m		μV/m	μV/m	
99.72	<	1.0	11.0	<	12.0	<	4.0	150	Vertical
149.58	<	1.0	9.8	<	10.8	<	3.5	150	Vertical
199.44	<	1.0	11.5	<	12.5	<	4.2	150	Vertical
249.30	<	1.0	15.2	<	16.2	<	6.5	200	Vertical
299.16	<	1.0	16.9	<	17.9	<	7.9	200	Vertical
349.02	<	1.0	19.0	<	20.0	<	10.0	200	Vertical
398.88	<	1.0	20.6	<	21.6	<	12.0	200	Vertical
448.74	<	1.0	19.7	<	20.7	<	10.8	200	Vertical
498.60	<	1.0	20.6	<	21.6	<	12.0	200	Vertical

Remarks:

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty : 30MHz to 1GHz ±4.1dB



Hong Kong Standards and Testing Centre

Date : 2005-01-20 **TEST REPORT** Page 11 of 17

No.: HM153147

Limits for Radiated Emissions [FCC 47 CFR 15.235 Class B]:

Frequency Range	Quasi-Peak Limits		
[MHz]	[μV/m]		
30-88	100		
88-216	150		
216-960	200		
Above960	500		

The emission limits shown in the above table are based on measurement employing a CISPR quasipeak detector and above 1000MHz are based on measurements employing an average detector.

Results: Receiver

	Radiated Emissions									
	Quasi-Peak									
Frequency	Measured	Correction	Field	Field	Limit @3m	E-Field				
	Level @3m	Factor	Strength	Strength		Polarity				
MHz	dBµV/m	dΒμV/m	dBµV/m	μV/m	μV/m					
49.86	25.1	10.2	35.3	58.2	100	Vertical				
99.72	< 1.0	12.5	< 13.5	< 4.7	150	Vertical				
149.58	< 1.0	9.8	< 10.8	< 3.5	150	Vertical				
199.44	< 1.0	11.5	< 12.5	< 4.2	150	Vertical				
249.30	< 1.0	15.9	< 16.9	< 7.0	200	Vertical				
299.16	< 1.0	17.4	< 18.4	< 8.3	200	Vertical				
349.02	< 1.0	17.2	< 18.2	< 8.1	200	Vertical				
398.88	< 1.0	18.8	< 19.8	< 9.8	200	Vertical				
448.74	< 1.0	19.7	< 20.7	< 10.8	200	Vertical				
498.60	< 1.0	20.6	< 21.6	< 12.0	200	Vertical				

Calculated measurement uncertainty : 30MHz to 1GHz ±4.1dB



Hong Kong Standards and Testing Centre

Date : 2005-01-20 **TEST REPORT** Page 12 of 17

No.: HM153147

3.1.1 Conducted Emissions (0.15MHz to 30MHz)

Test Requirement: FCC 47CFR 15.207
Test Method: ANSI C63.4:2003

Test Date: N/A
Mode of Operation: N/A

Results: N/A

The EUT is operated by a single source of internal battery power [located in the battery compartment], therefore power line conducted emission was deemed unnecessary.



香港標準及檢定中心 Hong Kong Standards and Testing Centre

nong Rong Gtandardo and reoting Gentre

TEST REPORT

Page 13 of 17

Date: 2005-01-20 No.: HM153147

3.2 20dB Bandwidth of Fundamental Emission

Test Requirement: FCC 47 CFR 15.235

Test Method: ANSI C63.4:2003 (Section 13.1.7)

Test Date: 2005-01-06 Mode of Operation: On mode

Test Method:

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

Test Setup:

As Test Setup of clause 3.1.1 in this test report.



港 準 香 檢 定 心

Hong Kong **Standards** and Testing

TEST REPORT Date: 2005-01-20 Page 14 of 17

No.: HM153147


Limits for 20dB Bandwidth of Fundamental Emission:

Frequency Range [MHz]	20B Bandwidth [KHz]	FCC Limits [MHz]
		within 49.82-49.90
49.86	39.6	Within 49.82-49.90

20B Bandwidth of Fundamental Emission

/40 MARKER A 50.8 kHz -36.99 dB

ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKRA 50.8 kHz
-36.99 dB





Hong Kong Standards and Testing Centre

Date : 2005-01-20 **TEST REPORT** Page 15 of 17

No.: HM153147

Appendix A

List of Measurement Equipment

Radiated Emission

		1		1	
EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL
EM007	SPECTRUM ANALYZER	HEWLETT PACKARD	HP85660B	3144A21192	15/06/04
EM008	SPECTRUM ANALYZER DISPLAY	HEWLETT PACKARD	HP85662A	3144A20514	15/06/04
EM009	QUASI PEAK ADAPTOR	HEWLETT PACKARD	HP85650A	3303A01702	15/06/04
EM010	RF PRESELECTOR	HEWLETT PACKARD	HP85685A	3221A01410	15/06/04
EM011	ATTENNUATOR/SWITCH	HEWLETT PACKARD	HP11713A	2508A10595	15/06/04
EM012	PRE-AMPLIFIER	HEWLETT PACKARD	HP8449B	3008A00262	15/06/04
EM013	CONTROLLER (COMPUTER), COLOR MONITOR, KEYBOARD & MOUSE FLOPPY DRIVE	HEWLETT PACKARD HEWLETT PACKARD HEWLETT PACKARD	HP9000 HP A1097C HP9133L	6226A60314 3151J39517 2623A02468	15/06/04
EM020	HORN ANTENNA	EMCO	3115	4032	30/07/03
EM022	LOOP ANTENNA	EMCO	6502	1189-2424	30/07/03
EM072	SIGNAL GENERATOR	HEWLETT PACKARD	8640B	1948A11892	N/A
EM083	HKSTC OPEN AREA TEST SITE	HKSTC	N/A	N/A	08/02/03
EM131	PORTABLE SPECTRUM ANALYSER	HEWLETT PACKARD	8595EM	3710A00155	13/01/04
EM145	EMI TEST RECEIVER	R&S	ESCS 30	830245/021	04/10/04
EM219	BICONILOG ANTENNA	EMCO	3142C	00029071	28/10/03
EM195	ANTENNA POSITIONING MAST	EMCO	2075	2368	N/A
EM196	MULTI-DEVICE CONTROLLER	EMCO	2090	1662	N/A

Line Conducted

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL
EM078	VARIAC	SHANGHAI VOLTAGE	TDGC-3/0.5	N/A	CM
EM081	SMALL SCREENED ROOM	MIKO INST HK	N/A	N/A	17/10/03
EM119	LISN	R&S	ESH3-Z5	0831.5518.52	14/10/04
EM127	ISOLATION TRANSFORMER 220 TO 300	WING SUN	N/A	N/A	СМ
EM142	PULES LIMITER	R&S	ESH3Z2	357.8810.52	04/08/04
EM181	EMI TEST RECEIVER	R&S	ESIB7	100072	06/01/04
EM154	SHIELDING ROOM	SIEMENA MATSUSHITA COMPONENTS	N/A	803-740-057- 99A	17/10/03
EM197	LISN	EMCO	4825/2	1193	05/06/04

Remarks:-

CM Corrective Maintenance N/A Not Applicable or Not Available

TBD To Be Determined



Hong Kong Standards and Testing Centre

Date : 2005-01-20 **TEST REPORT** Page 16 of 17

No.: HM153147

Appendix B

Photographs of EUT


Front View of the product




Rear View of the product



Inner Circuit Top View



Inner Circuit Bottom View





Hong Kong Standards and Testing Centre

Date : 2005-01-20 **TEST REPORT** Page 17 of 17

No.: HM153147

Photographs of EUT



***** End of Test Report *****