



SAR TEST REPORT

Test Report No.: 10258271S-A

Applicant : Canon Inc.
Type of Equipment : Wireless Module
Model No. : WM229 (*. Wireless module for the single platform.)
FCC ID : AZD229
Test Standard : FCC 47CFR §2.1093
Test Result : Complied

Highest Reported SAR(1g) Value	Platform #	Platform type	Platform model	Remarks
0.74 W/kg	Single platform	Digital camera	PC2201	(DTS) 2412MHz, IEEE 802.11b (1Mbps, DBPSK/DSSS) *. This was a highest measured SAR(1g) value: 0.595 W/kg (output power: 14.08dBm).

*. **The highest reported SAR (1g) value for body-touch condition is "0.74 W/kg".**

*. Since highest reported SAR (1g): 0.74 W/kg of this platform which obtained in accordance with KDB447498 (v05) was kept under 1.2 W/kg, this EUT was approved to operate single platform (which were tested in above.).

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the limits of the above regulation.
4. The test results in this test report are traceable to the national or international standards.
5. This test report must not be used by the customer to claim product certification, approval, or endorsement by any agency of the Federal Government.
6. The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan has been accredited.

Date of test: April 3, 2014

Test engineer: *H. Naka*

Hiroshi Naka
Engineer, Consumer Technology Division

Approved by: *T. Imamura*

Toyokazu Imamura
Leader, Consumer Technology Division

- ☐ The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan.
☒ There is no testing item of "Non-accreditation".



REVISION HISTORY

Revision	Test report No.	Date	Page revised	Contents
Original	10258271S-A	April 23, 2014	-	
-r01	10258271S-A	May 15, 2014	1,2,3	(p3) The operation temperature range was corrected.

*. By issue of new revision report, the report of an old revision becomes invalid.

CONTENTS

PAGE

REVISION HISTORY	2
CONTENTS	2
SECTION 1: Customer information	3
SECTION 2: Equipment under test (EUT).....	3
2.1 Identification of EUT	3
2.2 Product Description.....	3
2.3 Tx output power specification (antenna port terminal conducted)	4
2.4 Maximum output power which may possible.....	4
SECTION 3: Test specification, procedures and results	5
3.1 Test specification.....	5
3.2 Exposure limit	5
3.3 Procedure and result	5
3.4 Test location	5
3.5 Confirmation before SAR testing	6
3.6 Confirmation after SAR testing	6
3.7 Test setup of EUT and SAR measurement procedure	7
SECTION 4: Operation of EUT during testing.....	7
SECTION 5: Uncertainty assessment (SAR measurement).....	8
SECTION 6: Confirmation before testing	9
6.1 SAR reference power measurement (antenna terminal conducted average power of EUT)	9
6.2 Comparison of power of EMC sample.....	9
SECTION 7: Measurement results	10
7.1 SAR test results	10

Contents of appendixes

APPENDIX 1: Photographs of test setup	11
Appendix 1-1 Photograph of Platform and antenna position	11
Appendix 1-2 EUT and support equipment.....	12
Appendix 1-3 Photograph of test setup / Platform-Digital camera.....	13
APPENDIX 2: SAR Measurement data.....	16
Appendix 2-1 Evaluation procedure.....	16
Appendix 2-2 SAR measurement data	17
APPENDIX 3: Test instruments	30
Appendix 3-1 Equipment used	30
Appendix 3-2 Configuration and peripherals	31
Appendix 3-3 Test system specification.....	32
Appendix 3-4 Simulated tissues composition and parameter confirmation	33
Appendix 3-5 System check results.....	34
Appendix 3-6 System check measurement data	34
Appendix 3-7 System check uncertainty	35
Appendix 3-8 Calibration certificate: E-Field Probe (EX3DV4)	36
Appendix 3-9 Calibration certificate: Dipole (D2450V2).....	47

SECTION 1: Customer information

Company Name	Canon Inc.
Brand Name	Canon
Address	30-2, Shimomaruko 3-chome, Ohta-ku, Tokyo 146-8501 Japan
Telephone Number	+81-3-5482-8070
Facsimile Number	+81-3-3757-8431
Contact Person	Hironobu Saida

SECTION 2: Equipment under test (EUT)

2.1 Identification of EUT

Type of Equipment	Wireless Module	(* The EUT was installed into the platform: digital camera
Model Number	WM229	(* Platform model: PC2201)
Serial Number	E4813949ECC8	(* Platform serial number: 57)
Condition of EUT	WM229: Production model	(* Platform: Engineering prototype)
	(* Not for sale: This sample is equivalent to mass-produced items.)	
Receipt Date of Sample	February 3, 2014 (* EUT for power measurement.) * No modification by the Lab. March 29, 2014(* EUT for SAR test.) * No modification by the Lab. (* The EUT that had been measured the power of SAR test reference, was installed into the platform-digital camera (model: PC2201) from the beginning. After power measurement, the EUT was returned to the customer, and the RF wiring was changed to the original antenna line form the antenna conducted power measurement line of the SAR test. The EUT was installed into a platform which SAR tested, by the customer.)	
Country of Mass-production	WM229: Philippines	(* Platform: Japan)
Category Identified	Portable device * Since EUT may contact and/or very close to a human body during Wi-Fi operation, the partial-body SAR (1g) shall be observed.	
Rating	DC3.3V and DC1.8V supplied form the platform * The EUT is installed into the specified the platform that was operated by the re-chargeable Li-ion battery. Therefore, each SAR test, the platform which had built-in EUT was operated with full-charged battery.	
Feature of EUT	The EUT is a Wireless Module which installs into the single platform (digital camera, model: PC2201).	
SAR Accessory	None	

2.2 Product Description (Wireless module: WM229)

Equipment type	Transceiver	
Frequency of operation	2412-2462MHz (11b, 11g, 11n(20HT)), 2422-2452MHz (11n(40HT))	
Channel spacing	5MHz	
Bandwidth	20MHz(11b, 11g, 11n(20HT)), 40MHz(11n(40HT))	
Type of modulation	DSSS(11b): CCK, DQPSK, DBPSK OFDM(11g, 11n(20HT), 11n(40HT)): 64QAM, 16QAM, QPSK, BPSK	
Q'ty of Antenna	1 pc.	
Antenna type	Monopole type chip antenna	
Antenna gain (peak)	-3.30dBi (2442MHz)	
Transmit power and tolerance (Manufacture variation)	11b: 13dBm +2dBm/-2.5dB	11g: 10.7dBm +2dBm/-2.5dB
	11n(20HT): 10.7dBm +2dBm/-2.5dB	11n(40HT): 10.7dBm +2dBm/-2.5dB
	* Refer to clause 2.3 for more detail.	
Maximum output power which may possible	* The measured Tx output power (conducted) refers to section 6 in this report.	
	11b: 15dBm	11g: 12.7dBm
	11n(20HT): 12.7dBm	11n(40HT): 12.7dBm
	* Refer to clause 2.4 for more detail.	
Power supply	DC 3.3V, DC1.8V (* The power of DC3.3V and DC1.8V are supplied from the platform via constant voltage circuit.)	
Operation temperature range	-20 to +85 deg.C.	

*. The EUT do not use the special transmitting technique such as "beam-forming" and "time-space code diversity."

2.3 Tx output power specification (antenna port terminal conducted)

		Target Power [dBm] (average)																											
		11b					11g								11n(20HT)														
[MHz]	CH	1	2	5.5	11	6	9	12	18	24	36	48	54	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15
2412	1	13	13	13	13	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	-	-	-	-	-	-	-	-
2417	2	13	13	13	13	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	-	-	-	-	-	-	-	-
2422	3	13	13	13	13	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	-	-	-	-	-	-	-	-
2427	4	13	13	13	13	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	-	-	-	-	-	-	-	-
2432	5	13	13	13	13	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	-	-	-	-	-	-	-	-
2437	6	13	13	13	13	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	-	-	-	-	-	-	-	-
2442	7	13	13	13	13	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	-	-	-	-	-	-	-	-
2447	8	13	13	13	13	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	-	-	-	-	-	-	-	-
2452	9	13	13	13	13	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	-	-	-	-	-	-	-	-
2457	10	13	13	13	13	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	-	-	-	-	-	-	-	-
2462	11	13	13	13	13	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	-	-	-	-	-	-	-	-

		Target Power [dBm] (average)															
		11n(40HT)															
[MHz]	CH	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15
2422	3	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	-	-	-	-	-	-	-	-
2427	4	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	-	-	-	-	-	-	-	-
2432	5	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	-	-	-	-	-	-	-	-
2437	6	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	-	-	-	-	-	-	-	-
2442	7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	-	-	-	-	-	-	-	-
2447	8	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	-	-	-	-	-	-	-	-
2452	9	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	-	-	-	-	-	-	-	-

2.4. Maximum output power which may possible

		Target Power [dBm] (average)																											
		11b				11g								11n(20HT)															
[MHz]	CH	1	2	5.5	11	6	9	12	18	24	36	48	54	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15
2412	1	15	15	15	15	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	-	-	-	-	-	-	-	-
2417	2	15	15	15	15	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	-	-	-	-	-	-	-	-
2422	3	15	15	15	15	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	-	-	-	-	-	-	-	-
2427	4	15	15	15	15	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	-	-	-	-	-	-	-	-
2432	5	15	15	15	15	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	-	-	-	-	-	-	-	-
2437	6	15	15	15	15	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	-	-	-	-	-	-	-	-
2442	7	15	15	15	15	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	-	-	-	-	-	-	-	-
2447	8	15	15	15	15	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	-	-	-	-	-	-	-	-
2452	9	15	15	15	15	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	-	-	-	-	-	-	-	-
2457	10	15	15	15	15	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	-	-	-	-	-	-	-	-
2462	11	15	15	15	15	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	-	-	-	-	-	-	-	-

		Target Power [dBm] (average)															
		11n(40HT)															
[MHz]	CH	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15
2422	3	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	-	-	-	-	-	-	-	-
2427	4	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	-	-	-	-	-	-	-	-
2432	5	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	-	-	-	-	-	-	-	-
2437	6	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	-	-	-	-	-	-	-	-
2442	7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	-	-	-	-	-	-	-	-
2447	8	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	-	-	-	-	-	-	-	-
2452	9	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	-	-	-	-	-	-	-	-

SECTION 3: Test specification, procedures and results

3.1 Test specification

The US Federal Communications Commission has released the report and order "Guidelines for Evaluating the Environmental Effects of RF Radiation", ET Docket No. 93-62 in August 1996. The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g for an uncontrolled environment and 8.0 mW/g for an occupational/controlled environment as recommended by the ANSI/IEEE standard C95.1-1992. The device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling in accordance with the following measurement procedures..

- KDB 447498 D01 (v05r02):** General RF exposure guidance
KDB 248227 D01 (v01r02): SAR Measurement Procedures for 802.11a/b/g Transmitters
KDB 865664 D01 (v01r03): SAR measurement 100MHz to 6GHz
IEEE Std. 1528-2003: IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
IEEE Std. 1528-2013: IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
(*. The reference for Uncertainty in SAR correction for deviations in permittivity and conductivity, in clause E.3.2.)

3.2 Exposure limit

Environments of exposure limit	Whole-Body (averaged over the entire body)	Partial-Body (averaged over any 1g of tissue)	Hands, Wrists, Feet and Ankles (averaged over any 10g of tissue)
(A) Limits for Occupational /Controlled Exposure (W/kg)	0.4	8.0	20.0
(B) Limits for General population /Uncontrolled Exposure (W/kg)	0.08	1.6	4.0

- *. **Occupational/Controlled Environments:** are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).
*. **General Population/Uncontrolled Environments:** are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

The limit applied in this test report is;

General population / uncontrolled exposure, Partial-Body (averaged over any 1g of tissue) limit: 1.6 W/kg

3.3 Procedures and Results

	Wi-Fi (DTS) / in Platform (digital camera)
Test Procedure	SAR measurement; KDB 447498, KDB 248227, KDB 865664, IEEE Std.1528
Category	FCC 47CFR §2.1093 (Portable device)
Results (SAR(1g))	Complied
Reported SAR value (*. Scaled)	0.74 W/kg
Measured SAR value	0.595 W/kg
Operation mode, channel	11b, 1Mbps, 2412MHz (1ch)
Power measured/max. (scaled factor)	14.08 dBm/15dBm (×1.24)

Note: UL Japan's SAR Work Procedures No.13-EM-W0429 and 13-EM-W0430. No addition, deviation nor exclusion has been made from standards

Test outline: Where this product is built into a new platform, it was verified whether multiplatform conditions can be suited in according with section 2) of 5.2.2.2 in KDB447498 D01 (v05).

Consideration of the test results: **The highest reported SAR (1g) of EUT in a platform was kept; ≤ 1.2 W/kg.**
Since highest reported SAR (1g) on a EUT's platform obtained in accordance with KDB447498 (v05) was kept under 1.2 W/kg, this EUT was approved to operate single-platform.

3.4 Test Location

No.7 shielded room (2.76m (Width) × 3.76m (Depth) × 2.4m (Height)) for SAR testing.

UL Japan, Inc., Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken 259-1220 JAPAN
Telephone number: +81 463 50 6400 / Facsimile number: +81 463 50 6401

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN
Telephone: +81 463 50 6400 / Facsimile: +81 463 50 6401

3.5 Confirmation before SAR testing

3.5.1 Average power for SAR tests

Before SAR test, the RF wiring for the sample had been switched to the antenna conducted power measurement line from the antenna line and the average power was measured. The result is shown in Section 6.

*. The EUT transmission power was verified that it was within 2dB lower than the maximum tune-up tolerance limit when it was set the rated power. (Clause 4.1, KDB447498 D01(v05))

Step.1 Check the power by data rate and operation channel

The data rate check was measured for all modes in one of default channel. For the SAR test reference, the average output power was measured on the low/middle/high channels with the worst data rate condition in.

11b		11g		11n(20HT)		11n(40HT)			
Modulation	Data rate [Mbps]	Modulation	Data rate [Mbps]	MCS Index	Spatial Stream	Modulation	MCS Index	Spatial Stream	Modulation
DBPSK/DSSS	1	BPSK/OFDM	6	MCS0	1	BPSK/OFDM	MCS0	1	BPSK/OFDM
DQPSK/DSSS	2	BPSK/OFDM	9	MCS1	1	QPSK/OFDM	MCS1	1	QPSK/OFDM
CCK/DSSS	5.5	QPSK/OFDM	12	MCS2	1	QPSK/OFDM	MCS2	1	QPSK/OFDM
CCK/DSSS	11	QPSK/OFDM	18	MCS3	1	16QAM/OFDM	MCS3	1	16QAM/OFDM
		16QAM/OFDM	24	MCS4	1	16QAM/OFDM	MCS4	1	16QAM/OFDM
		16QAM/OFDM	36	MCS5	1	64QAM/OFDM	MCS5	1	64QAM/OFDM
		64QAM/OFDM	48	MCS6	1	64QAM/OFDM	MCS6	1	64QAM/OFDM
		64QAM/OFDM	54	MCS7	1	64QAM/OFDM	MCS7	1	64QAM/OFDM

Step.2 Consideration of SAR test channel

The following operation mode, data rate and channels were determined to apply SAR test by SAR reference power measured.

Mode	MHz	Channel	default	SAR Tested/Reduced				Remarks
			11b/g/n(20HT)	11b	11g	11n(20HT)	11n(40HT)	
802.11 b/g/n	2412	1 (*1)	√	Tested	Reduced (*2)	Reduced (*2)		SAR test were applied to 11b and 11n(40HT) mode, in lowest data rate. (*3)
	2422	3					Tested	
	2437	6	√	Tested	Reduced (*2)	Reduced (*2)	Reduced (*4)	
	2452	9					Reduced (*4)	
	2462	11 (*1)	√	Tested	Reduced (*2)	Reduced (*2)		

√ = "default test channels of requested by KDB248227"

- *1. Any output power reducing for channel 1 and 11 to meet restricted band requirements was not observed. Therefore channel 1 and 11 was selected for the default channels of power measurement and SAR test plan.
- *2. (KDB248227) Since the target average power of 11g and 11n(20HT) were more than 2dB lower than the corresponded 11b power, SAR test was only applied to the 11b mode for 20MHz BW operation.. (Refer to Section 6.)
- *3. (KDB248227) In 11b and 11n(40HT) mode, since the average power of higher data rate were less than 0.25dB higher than the lowest data rate, SAR test were only applied to the lowest data rate. (Refer to Section 6.)
- *4. (KDB248227) During SAR test, since the extrapolated maximum peak SAR for the maximum output channel was $\leq 1.6\text{W/kg}$ and the 1g averaged SAR was $\leq 0.8\text{W/kg}$, the testing for other channels were omitted.

3.6 Confirmation after SAR testing

It was checked that the power drift [W] is within $\pm 5\%$ in the evaluation procedure of SAR testing. The verification of power drift during the SAR test is that DASY5 system calculates the power drift by measuring the e-filed at the same location at beginning and the end of the scan measurement for each test position.

The result is shown in APPENDIX 2.

- *. DASY5 system calculation Power drift value[dB] = $20\log(E_a)/(E_b)$ (where, Before SAR testing: $E_b[\text{V/m}]$ / After SAR testing: $E_a[\text{V/m}]$)

Limit of power drift[W] = $\pm 5\%$

Power drift limit (X) [dB] = $10\log(P_{\text{drift}}) = 10\log(1.05/1) = 10\log(1.05) - 10\log(1) = 0.21\text{dB}$

from E-filed relations with power.

$S = E \times H = E^2 / \eta = P / (4 \times \pi \times r^2)$ (η : Space impedance) $\rightarrow P = (E^2 \times 4 \times \pi \times r^2) / \eta$

Therefore, The correlation of power and the E-filed

Power drift limit (X) dB = $10\log(P_{\text{drift}}) = 10\log(E_{\text{drift}})^2 = 20\log(E_{\text{drift}})$

From the above mentioned, **the calculated power drift of DASY5 system must be the less than $\pm 0.21\text{dB}$.**

3.7 Test setup of EUT and SAR measurement procedure

After considering the outline of EUT, the SAR test was carried out on the following setup conditions.

Setup	Explanation of EUT setup position (* Refer to Appendix 1 for test setup photographs.)	Antenna distance [mm]	(*1) SAR Tested /Reduced	SAR type
Left	The left-hand surface of platform was touched to the Flat phantom.	≈3.6	Tested	Body (touch)
Left-rear	The back part on the left-hand side of a platform was touched to the Flat phantom.	≈3.3	Tested	
Rear(1)	The rear section (LCD side) of platform was touched to the Flat phantom. (with LCD close)	≈10	Tested	
Rear(2)	The rear section (LCD side) of platform was touched to the Flat phantom. (with LCD open)	≈4.7	Tested	
Front-left	Near the antenna of the front of a platform was touched to the Flat phantom.	≈13	Tested	
Front	The front side (Lens) of a platform was touched to the Flat phantom.	≈25	Tested (*2)	
Right	The right-hand surface of platform was touched to the Flat phantom.	≈99	Tested (*2)	
Top	The top surface of platform was touched to the Flat phantom.	≈39	Tested (*2)	
Bottom	The bottom flat surface of platform was touched to the Flat phantom.	≈20	Tested (*2)	

*. Antenna distance: this means the distance from the EUT antenna inside a platform to the outer surface of platform which an operator may touch.

*. Size of EUT: 22.5mm (width) × 11.5mm (depth) × 2.05mm max (height)

. Size of platform: 103mm (width) × 40.3mm (depth) × 60.4mm (height) (This size is when the LCD is in closed position. The convex portion is not contained in size.)

*1. SAR test reduction consideration

KDB 447498 D01 (v05) was taken into consideration as other approaches to reduce SAR test.

Parenthesis 1), Clause 4.3.1, KDB 447498 D01 (v05) gives the following formula to calculate the SAR(1g) test exclusion thresholds for 100MHz-6GHz at test separation distance ≤50mm.

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \times [\sqrt{f} (\text{GHz})] \leq 3.0$ (for SAR(1g)) (formula (1))

If power is calculated from the upper formula (1);

$[\text{SAR(1g) test exclusion thresholds, mW}] = 3 \times [\text{test separation distance, mm}] / [\sqrt{f} (\text{GHz})]$ (formula (2))

Parenthesis 2), Clause 4.3.1, KDB 447498 D01 (v05) gives the following formula to calculate the SAR(1g) test exclusion thresholds for 1.5-6GHz at test separation distance >50mm.

$[\text{test exclusion thresholds, mW}] = [(\text{Power allowed at numeric threshold for 50mm in formula (1)}) + [(\text{test separation distance, mm}) - (50\text{mm})] \times 10]$ (formula (3))

According to this formula, the calculated results in typical antenna distance of platform are shown in the following table.

SAR(1g) test exclusion thresholds [mW]		
Frequency [GHz]	Antenna separation distance [mm]	
	5	20
2.462	10 (10dBm)	38 (15.8dBm)

*. The measured average power of EUT was shown in Section 6: Confirmation before SAR testing.

2. Although SAR(1g) test exclusion threshold power was satisfied (maximum output power of EUT was 15dBm), since the platform was small at the compact digital camera, the SAR test was carried out in all setup surfaces.

By the determined test setup shown above, the SAR test was applied in the following procedures.

Step 1	Change the setup positions and channels (at worst setup).
Step 2	Change the operation mode. (at the worst setup)

*. During SAR test, the radiated power is always monitored by Spectrum Analyzer.

SECTION 4: Operation of EUT during testing

4.1 Operating modes for SAR testing

This EUT has IEEE.802.11b, 11g, 11n(20HT) and 11n(40HT) continuous transmitting modes.

The frequency and the modulation used in the SAR testing are shown as a following.

Operation mode	11b	11g	11n(20HT)	11n(40HT)
Tx frequency band	2412-2462MHz			2422-2452MHz
Tested frequency	2412, 2437, 2462MHz	Reduced (*2)	Reduced (*2)	2422MHz (*1)
Modulation	DBPSK/DSSS	-	-	BPSK/OFDM
Data rate	1Mbps (*3)	-	-	MCS0
Crest factor	1.0 (100% duty cycle)	-	-	1.0 (100% duty cycle)
Controlled software	"RF TEST" mode. (* Power setting (for power measurement and SAR test): 14(11b), 12(11g, 11n(20HT), 11n(40HT))			

*1. SAR test was only applied to a highest output channels of 11n(40HT), because the reported SAR (1g) value of highest output power channel was small enough to 0.8W/kg and the peak-SAR was small enough to 1.6W/kg. (KDB248227)

*2. Since the target average power of 11g and 11n(20HT) were more than 2dB lower than the corresponded 11b power, SAR test was only applied to the 11b mode for 20MHz BW operation.. (KDB248227)

*3. Since the average powers of higher data rate were less than 0.25dB higher than the lowest data rate, SAR test was only applied to the lowest data rate. (KDB248227)

SECTION 5: Uncertainty Assessment (SAR measurement)

Uncertainty of SAR measurement (2.4-6GHz) (*.ε&σ: ≤±5%, DAK3.5, Tx: ≈100% duty cycle) (v08)							1g SAR	10g SAR	
Combined measurement uncertainty of the measurement system (k=1)							± 13.7%	± 13.6%	
Expanded uncertainty (k=2)							± 27.4%	± 27.2%	
	Error Description (2.4-6GHz) (v08)	Uncertainty Value	Probability distribution	Divisor	ci (1g)	ci (10g)	ui (1g)	ui (10g)	Vi, veff
A	Measurement System (DASY5)						(std. uncertainty)	(std. uncertainty)	
1	Probe Calibration Error	±6.55 %	Normal	1	1	1	±6.55 %	±6.55 %	∞
2	Axial isotropy Error	±4.7 %	Rectangular	√3	√0.5	√0.5	±1.9 %	±1.9 %	∞
3	Hemispherical isotropy Error	±9.6 %	Rectangular	√3	√0.5	√0.5	±3.9 %	±3.9 %	∞
4	Linearity Error	±4.7 %	Rectangular	√3	1	1	±2.7 %	±2.7 %	∞
5	Probe modulation response	±2.4 %	Rectangular	√3	1	1	±1.4 %	±1.4 %	∞
6	Sensitivity Error (detection limit)	±1.0 %	Rectangular	√3	1	1	±0.6 %	±0.6 %	∞
7	Boundary effects Error	±4.3 %	Rectangular	√3	1	1	±2.5 %	±2.5 %	∞
8	Readout Electronics Error(DAE)	±0.3 %	Rectangular	√3	1	1	±0.3 %	±0.3 %	∞
9	Response Time Error	±0.8 %	Normal	1	1	1	±0.8 %	±0.8 %	∞
10	Integration Time Error (≈100% duty cycle)	±0 %	Rectangular	√3	1	1	0 %	0 %	∞
11	RF ambient conditions-noise	±3.0 %	Rectangular	√3	1	1	±1.7 %	±1.7 %	∞
12	RF ambient conditions-reflections	±3.0 %	Rectangular	√3	1	1	±1.7 %	±1.7 %	∞
13	Probe positioner mechanical tolerance	±3.3 %	Rectangular	√3	1	1	±1.9 %	±1.9 %	∞
14	Probe Positioning with respect to phantom shell	±6.7 %	Rectangular	√3	1	1	±3.9 %	±3.9 %	∞
15	Max. SAR evaluation (Post-processing)	±4.0 %	Rectangular	√3	1	1	±2.3 %	±2.3 %	∞
B	Test Sample Related								
16	Device Holder or Positioner Tolerance	±3.6 %	Normal	1	1	1	±3.6 %	±3.6 %	5
17	Test Sample Positioning Error	±5.0 %	Normal	1	1	1	±5.0 %	±5.0 %	145
18	Power scaling	±0%	Rectangular	√3	1	1	±0 %	±0 %	∞
19	Drift of output power (measured, <0.2dB)	±2.3%	Rectangular	√3	1	1	±2.9 %	±2.9 %	∞
C	Phantom and Setup								
20	Phantom uncertainty (shape, thickness tolerances)	±7.5 %	Rectangular	√3	1	1	±4.3 %	±4.3 %	∞
21	Algorithm for correcting SAR (ε,σ: ≤5%)	±1.2 %	Normal	1	1	0.84	±1.2 %	±0.97 %	∞
22	Measurement Liquid Conductivity Error (DAK3.5)	±3.0 %	Normal	1	0.78	0.71	±2.3 %	±2.1 %	7
23	Measurement Liquid Permittivity Error (DAK3.5)	±3.1 %	Normal	1	0.23	0.26	±0.7 %	±0.8 %	7
24	Liquid Conductivity-temp.uncertainty (≤2deg.C.)	±5.3 %	Rectangular	√3	0.78	0.71	±2.4 %	±2.2 %	∞
25	Liquid Permittivity-temp.uncertainty (≤2deg.C.)	±0.9 %	Rectangular	√3	0.23	0.26	±0.1 %	±0.1 %	∞
	Combined Standard Uncertainty						±13.7 %	±13.6 %	733
	Expanded Uncertainty (k=2)						±27.4 %	±27.2 %	

*. Table of uncertainties are listed for ISO/IEC 17025.

*. This measurement uncertainty budget is suggested by IEEE Std.1528(2013) and determined by Schmid & Partner Engineering AG (DASY5 Uncertainty Budget). Per KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r01 Section 2.8.1., when the highest measured SAR(1g) within a frequency band is < 1.5W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std.1528 (2013) is not required in SAR reports submitted for equipment approval.

SECTION 6: Confirmation before testing

6.1 SAR reference power measurement (antenna terminal conducted average power of EUT) - Worst data rate/channel determination

Mode	Frequency [MHz]	Data rate [Mbps]	Cable Loss [dB]	Attenuator [dB]	Duty factor [dB]	Average power			PAR [dB]	Power tolerance & correction				SAR Tested/ Reduced	Remarks
						P/M Reading [dBm]	Result			Target & (+)tolerance [dBm]	Deviation from max. [dB]	Scaled Factor [-]	≤ 2 dB from max.?		
							[dBm]	[mW]							
11b	2412	1	0.50	10.02	0.00	3.56	14.08	25.6	2.55	13.0+2	-0.92	x1.24	Yes	Tested	Highest in Ch(11b)
	2412	2	0.50	10.02	0.00	3.55	14.07	25.5	2.55	13.0+2	-0.93	x1.24	Yes	-	-
	2412	5.5	0.50	10.02	0.00	3.58	14.10	25.7	1.94	13.0+2	-0.90	x1.23	Yes	(*1)	Highest in D/R.(11b)
	2412	11	0.50	10.02	0.00	3.56	14.08	25.6	2.55	13.0+2	-0.92	x1.24	Yes	-	-
	2437	1	0.50	10.02	0.00	3.01	13.53	22.5	2.60	13.0+2	-1.47	x1.40	Yes	Tested	-
	2462	1	0.50	10.02	0.00	3.18	13.70	23.4	2.58	13.0+2	-1.30	x1.35	Yes	Tested	-
11g	2412	6	0.50	10.02	0.00	1.20	11.72	14.9	9.47	10.7±2	-0.98	x1.25	Yes	Reduced(*2)	Highest in Ch(11g)
	2412	9	0.50	10.02	0.00	1.19	11.71	14.8	8.96	10.7±2	-0.99	x1.26	Yes	-	-
	2412	12	0.50	10.02	0.00	1.18	11.70	14.8	9.33	10.7±2	-1.00	x1.26	Yes	-	-
	2412	18	0.50	10.02	0.00	1.21	11.73	14.9	8.81	10.7±2	-0.97	x1.25	Yes	(*1)	Highest in D/R.(11g)
	2412	24	0.50	10.02	0.00	1.14	11.66	14.7	9.57	10.7±2	-1.04	x1.27	Yes	-	-
	2412	36	0.50	10.02	0.00	1.07	11.59	14.4	9.45	10.7±2	-1.11	x1.29	No	-	-
	2412	48	0.50	10.02	0.00	1.17	11.69	14.8	9.12	10.7±2	-1.01	x1.26	No	-	-
	2412	56	0.50	10.02	0.00	1.09	11.61	14.5	9.46	10.7±2	-1.09	x1.29	No	-	-
	2437	6	0.50	10.02	0.00	0.84	11.36	13.7	9.40	10.7±2	-1.34	x1.36	Yes	Reduced(*2)	-
11n (20HT)	2462	6	0.50	10.02	0.00	0.81	11.33	13.6	9.55	10.7±2	-1.37	x1.37	Yes	Reduced(*2)	-
	2412	MCS0	0.50	10.02	0.00	1.18	11.70	14.8	8.87	10.7±2	-1.00	x1.26	Yes	Reduced(*2)	Highest in D/R&Ch.(n20)
	2412	MCS1	0.50	10.02	0.00	1.16	11.68	14.7	8.81	10.7±2	-1.02	x1.26	Yes	-	-
	2412	MCS2	0.50	10.02	0.00	1.17	11.69	14.8	8.83	10.7±2	-1.01	x1.26	Yes	-	-
	2412	MCS3	0.50	10.02	0.00	1.16	11.68	14.7	8.65	10.7±2	-1.02	x1.26	Yes	-	-
	2412	MCS4	0.50	10.02	0.00	1.16	11.68	14.7	8.83	10.7±2	-1.02	x1.26	Yes	-	-
	2412	MCS5	0.50	10.02	0.00	1.16	11.68	14.7	8.84	10.7±2	-1.02	x1.26	Yes	-	-
	2412	MCS6	0.50	10.02	0.00	1.16	11.68	14.7	8.84	10.7±2	-1.02	x1.26	Yes	-	-
	2412	MCS7	0.50	10.02	0.00	1.16	11.68	14.7	8.78	10.7±2	-1.02	x1.26	Yes	-	-
11n (40HT)	2437	MCS0	0.50	10.02	0.00	0.83	11.35	13.6	8.60	10.7±2	-1.35	x1.36	Yes	Reduced(*2)	-
	2462	MCS0	0.50	10.02	0.00	0.85	11.37	13.7	8.80	10.7±2	-1.33	x1.36	Yes	Reduced(*2)	-
	2422	MCS0	0.50	10.02	0.00	1.20	11.72	14.9	8.86	10.7±2	-0.98	x1.25	Yes	Tested	Highest in D/R&Ch.(n40)
	2422	MCS1	0.50	10.02	0.00	1.16	11.68	14.7	8.86	10.7±2	-1.02	x1.26	Yes	-	-
	2422	MCS2	0.50	10.02	0.00	1.17	11.69	14.8	8.93	10.7±2	-1.01	x1.26	Yes	-	-
	2422	MCS3	0.50	10.02	0.00	1.10	11.62	14.5	9.55	10.7±2	-1.08	x1.28	Yes	-	-
	2422	MCS4	0.50	10.02	0.00	1.13	11.65	14.6	9.43	10.7±2	-1.05	x1.27	Yes	-	-
	2422	MCS5	0.50	10.02	0.00	1.11	11.63	14.6	9.65	10.7±2	-1.07	x1.28	Yes	-	-
	2422	MCS6	0.50	10.02	0.00	1.17	11.69	14.8	9.20	10.7±2	-1.01	x1.26	Yes	-	-
	2422	MCS7	0.50	10.02	0.00	1.15	11.67	14.7	8.98	10.7±2	-1.03	x1.27	Yes	-	-
	2437	MCS0	0.50	10.02	0.00	1.16	11.68	14.7	8.97	10.7±2	-1.02	x1.26	Yes	Reduced(*3)	-
	2452	MCS0	0.50	10.02	0.00	0.66	11.18	13.1	8.92	10.7±2	-1.52	x1.42	Yes	Reduced(*3)	-

- *1. (KDB248227) Since the average power of higher data rate was less than 0.25dB higher than lowest data rate, SAR test was considered at lowest data rate.
*2. (KDB248227) Since the target average power of 11g and 11n(20HT) were more than 2dB lower than the corresponded 11b power, SAR test was only applied to 11b mode for 20MHz BW mode.
*3. (KDB248227) Since the extrapolated maximum peak SAR for the maximum output channel was ≤1.6W/kg and the 1g averaged SAR was ≤0.8W/kg, the testing for other channels were omitted.

- *. Duty Factor: 0dB=100% duty cycle, P/M: Power Meter, PAR: Peak average ratio ("Peak power"/"Average power", in dBm), Ch: channel, D/R: Data Rate.
*. Calculating formula: Results (Ave, dBm) = (P/M Reading)+(Cable loss)+(Attenuator)+(duty factor), where (duty factor, dBm)=10 × log (100/(duty cycle, %))
Deviation from max.: (Power deviation, dB) = (results power (average, dBm)) - (Max.-specification output power (average, dBm))
Scaled Factor: Power scaled factor for obtained SAR value, Scaled Factor [-] = 1 / (10 ^ ("Deviation from max." / 10))
*. SAR reference; Date measured February 10, 2014 / measured by: Hiroshi Naka / 21deg.C/32%RH (at preparation room of No.7 shielded room)
*. Uncertainty of antenna port conducted test; Power measurement uncertainty above 1GHz for this test was: (±) 1.5dB

6.2 Comparison of power of EMC sample

	EMC test	SAR test
	-	single platform
Platform model No.	-	PC2201
Serial No.	2C9EFCFF E915	E4813949E CC8
Date power measured	Aug. 14, 2013	Feb. 10, 2014
Reference report#	10048647S-K	This report.
Tx operation mode	11b	11b
Data rate [Mbps]	1	1
Average power [dBm]	2412 13.59	14.08
	2437 13.91	13.53
	2462 14.02	13.70

- *. Since the deviation of the maximum output average power between EMC sample and SAR sample was less than 0.5dB, it was judged that the EUT was equivalent.

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN
Telephone: +81 463 50 6400 / Facsimile: +81 463 50 6401

SECTION 7: Measurement results

7.1 SAR test results of platform-Digital camera (model: PC2201)

Measurement date: April 3, 2014

Measurement by: Hiroshi Naka

[Liquid measurement]

Target Frequency [MHz]	Liquid type	Liquid parameters (Body liquid) (*a)								ASAR Coefficients (*c)		Date measured		
		Permittivity (εr) [-]				Conductivity [S/m]				Temp. [deg.C.]	Depth [mm]			
		Target	Measured		Limit (*b)	Target	Measured		Limit (*b)					
			Meas.	Δεr			Meas.	Δσ						
2412	Body	52.75	50.62	-4.0%	-5% ≤ εr-meas. ≤ 0%	1.914	1.928	+0.7%	0% ≤ σ-meas. ≤ +5%	22.2	155	+1.26	not required.	April 3, 2014 before SAR test (ambient; 22.5 deg.C., 52%RH)
2422		52.74	50.59	-4.1%		1.923	1.943	+1.0%				+1.41	not required.	
2437		52.72	50.49	-4.2%		1.938	1.971	+1.7%				+1.79	not required.	
2462		52.68	50.43	-4.3%		1.967	1.994	+1.4%				+1.62	not required.	

*. Liquid parameters measurement range: 2350-2550MHz (200MHz), by 1MHz step.

[SAR measurement results (Partial-Body)]

SAR measurement results (Body simulated tissue)														Reported SAR(1g) [W/kg]		Remarks	
Mode	[MHz] (CH)	Modulation /Data rate	EUT setup conditions				Liquid temp. [deg.C.]		Power drift [dB]	SAR (1g) [W/kg]			Data# in Appendix 2-2				
			Position	LCD position	Gap [mm]	Battery ID	Before	After		maximum value of multi-peak							
										Observed	ASAR [%]	ΔSAR corrected					
SAR measurement results (Body simulated tissue)																	
Step 1: Change the setup positions and channels																	
11b (*2)	2412(1)	DBPSK-DSSS /1Mbps	Left-rear	Left	CL(nml)	0	#1	22.1	22.1	0.06	0.429	+1.26	-(*c)	Plot 1-1	×1.24	0.53	-
					CL(nml)	0	#1	22.1	22.1	-0.04	0.595	+1.26	-(*c)	Plot 1-2	×1.24	0.74	→Highest SAR.
					OP(180)	0	#1	22.1	22.1	0.05	0.556	+1.26	-(*c)	Plot 1-3	×1.24	0.69	-
					CL(nml)	0	#2	22.1	22.1	-0.07	0.508	+1.79	-(*c)	Plot 1-4	×1.40	0.71	-
	2437(7)		Left-rear		CL(nml)	0	#2	22.1	22.1	-0.01	0.534	+1.62	-(*c)	Plot 1-5	×1.35	0.72	-
					CL(nml)	0	#2	22.1	22.1	-0.01	0.534	+1.62	-(*c)	Plot 1-5	×1.35	0.72	-
					CL(nml)	0	#2	22.1	22.1	-0.01	0.534	+1.62	-(*c)	Plot 1-5	×1.35	0.72	-
					CL(nml)	0	#2	22.1	22.1	-0.01	0.534	+1.62	-(*c)	Plot 1-5	×1.35	0.72	-
	2462(11)		Left-rear		CL(nml)	0	#2	22.1	22.1	-0.01	0.534	+1.62	-(*c)	Plot 1-5	×1.35	0.72	-
					CL(nml)	0	#2	22.1	22.1	-0.01	0.534	+1.62	-(*c)	Plot 1-5	×1.35	0.72	-
					CL(nml)	0	#2	22.1	22.1	-0.01	0.534	+1.62	-(*c)	Plot 1-5	×1.35	0.72	-
					CL(nml)	0	#2	22.1	22.1	-0.01	0.534	+1.62	-(*c)	Plot 1-5	×1.35	0.72	-
2412(1)	Left-rear	Rear (1)	CL(nml)	0	#1	22.1	22.1	-0.06	0.012	+1.26	-(*c)	Plot 1-6	×1.24	<0.10	-		
		Rear (2)	OP(180)	0	#1	22.1	22.1	-0.12	0.014	+1.26	-(*c)	Plot 1-7	×1.24	<0.10	-		
		Front-left	CL(nml)	0	#2	22.2	22.2	-0.2	0.140	+1.26	-(*c)	Plot 1-8	×1.24	0.17	-		
		Front	CL(nml)	0	#2	22.2	22.2	-0.19	0.015	+1.26	-(*c)	Plot 1-9	×1.24	<0.10	-		
	Right	CL(nml)	0	#1	22.2	22.2	-0.2	0.00158	+1.26	-(*c)	Plot 1-10	×1.24	<0.10	-			
	Top	CL(nml)	0	#1	22.2	22.3	-0.09	0.082	+1.26	-(*c)	Plot 1-11	×1.24	0.10	-			
	Bottom	CL(nml)	0	#2	22.3	22.3	0.07	0.019	+1.26	-(*c)	Plot 1-12	×1.24	<0.10	-			
Step 2: Change the operation mode																	
11n (40HT)	2422(3)	BPSK-OFDM /MCS0	Left-rear	CL(nml)	0	#2	22.1	22.1	0.10	0.368	+1.41	-(*c)	Plot 2-1	×1.25	0.46	(*1)	

Notes:

- At the highest output power channel, since the extrapolated maximum peak SAR for the maximum output channel was ≤1.6W/kg and the 1g averaged SAR was ≤0.8W/kg, the testing for other channels were omitted. (KDB248227)
- Since the target average power of 11g and 11n(20HT) were more than 2dB lower than the corresponded 11b power, SAR test were not applied to the 11g and 11n(20HT) mode for 20MHz BW operation. (KDB248227)

*. Gap: It is the separation distance between the nearest position of platform outer surface and the bottom outer surface of phantom; n/a: not applied.

*. Battery No.#1 and #2 was same model. Refer to Appendix 1 for more details.

*. LCD position; CL(nml):Close(normal), OP(180): Open(180degrees). More detail of LCD position is shown in Appendix 1 in this report.

*. During test, the EUT was operated with full-charged battery and without all signal interface cables.

*. Calibration frequency of the SAR measurement probe (and used conversion factors)

SAR test frequency	Probe calibration frequency	Validity	Conversion factor	Uncertainty
2412, 2422, 2437, 2462MHz	2450MHz	within ±50MHz of calibration frequency	6.82	±12.0%

*. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

*a. The target value is a parameter defined in Appendix A of KDB865664 D01, the dielectric parameters suggested for head and body tissue simulating liquid are given at 2000, 2450 and 3000MHz. (*The parameters of the head liquid are the same value as IEEE Std 1528-2013.) Parameters for the frequencies 2000-3000MHz were obtained using linear interpolation. (Refer to appendix 3-4.)

*b. Refer to KDB865664 D01, item 2), Clause 2.6; "When nominal tissue dielectric parameters are recorded in the probe calibration data; for example, only target values and tolerance are reported, the measured εr and σ of the liquid used in routine measurements must be: ≤ the target εr and ≥ the target σ values and also within 5% of the required target dielectric parameters."

c. The coefficients are parameters defined in clause E.3.3.2, IEEE Std 1528(2013). Since the measured liquid parameters were ≤ the target εr and ≥ the target σ values and also within 5% of the required target dielectric parameters, the measured SAR was not compensated by ΔSAR coefficients (. Clause 2) of 2.6, KDB865664 D01).

$$\Delta SAR(1g) = C_{\epsilon r} \times \Delta \epsilon r + C_{\sigma} \times \Delta \sigma, C_{\epsilon r} = 7.854E-4 \times f^3 + 9.402E-3 \times f^2 - 2.742E-2 \times f - 0.2026 / C_{\sigma} = 9.804E-3 \times f^3 - 8.661E-2 \times f^2 + 2.981E-2 \times f - 0.7829$$

*d. Tuned-up SAR by scaled factor: Accordance with KDB 447498 D01; "When SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance (clause 4, 4.1, 4)." (Refer to section 6 in this report for "Scaled factor" of channels, each operation mode.)

*. Calculating formula: $\Delta SAR \text{ corrected SAR (1g) (W/kg)} = (\text{Observed SAR (1g) (W/kg)}) \times (100 - (\Delta SAR(\%) / 100)$
 $\text{Reported SAR (1g) (=Tuned-up SAR) (W/kg)} = (\text{Observed SAR (1g) (W/kg)}) \times (\text{Scaled factor})$