

FCC TEST REPORT

CATEGORY	:	Portable
PRODUCT NAME	:	Desktop Wireless 9000 Pro
FCC ID.	:	IBA-WCUT0D-MS
FILING TYPE	:	Certification
BRAND NAME	:	Creative
MODEL NAME	:	WCUT0D
APPLICANT	:	Creative Technology Ltd. 31 International Business Park, Creative Resource, Singapore 609921
MANUFACTURER	:	Paten Wireless Technology Co., Ltd.
		Da-Ning Industrial Zone, Humen, Dongguan, Guangdong, China
ISSUED BY	:	SPORTON INTERNATIONAL INC. 6F, No. 106, Sec. 1, Hsin Tai Wu Rd., His Chih, Taipei Hsien, Taiwan, R.O.C.

Statements:

The test result in this report refers exclusively to the presented test model / sample. Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

Certificate or Test Report could not be used by the applicant to claim the product endorsement by CNLA and any agency of U.S. government.

The test equipments used to perform the test are calibrated and traceable to NML/ROC or NIST/USA.



1190 ILAC MRA



Table of Contents

HISTORY OF THIS TEST REPORT	II
CERTIFICATE OF COMPLIANCE	
 GENERAL DESCRIPTION OF EQUIPMENT UNDER TEST. 1.1. Applicant	1 1 1 1 1 1
2. TEST CONFIGURATION OF THE EQUIPMENT UNDER TEST 2.1. Connection Diagram of Test System 2.2. The Test Mode Description 2.3. Description of Test Supporting Units	2
 3. GENERAL INFORMATION OF TEST 3.1. Test Facility. 3.2. Standards for Methods of Measurement. 3.3. DoC Statement 3.4. Frequency Range Investigated 3.5. Test Distance 	
4. LIST OF MEASUREMENTS 4.1. Summary of the Test Results.	4
 5. TEST RESULT 5.1. Test of Maximum Field Strength of Fundamental 5.2. Test of Spurious Radiated Emission 5.3. Antenna Requirements 	5 5 7 20
6. LIST OF MEASURING EQUIPMENTS USED	21
7. COMPANY PROFILE. 7.1. Certificate of Accreditation 7.2. Test Location	22 22 22
8. CNLA CERTIFICATE OF ACCREDITATION	23
APPENDIX A. PHOTOGRAPHS OF EUT	A1 ~ A13



HISTORY OF THIS TEST REPORT

Received Date: Dec. 24, 2004 Test Date: Feb. 01, 2005 Original Report Issue Date: Feb. 04, 2005 Report No.: FR4D2418

No additional attachment.

Additional attachment were issued as following record:

Attachment No.	Issue Date	Description



CERTIFICATE OF COMPLIANCE

with

47 CFR FCC Part 15 Subpart C

PRODUCT NAME	:	Desktop Wireless 9000 Pro
BRAND NAME	:	Creative
MODEL NAME	:	WCUT0D
APPLICANT	:	Creative Technology Ltd. 31 International Business Park, Creative Resource, Singapore 609921
MANUFACTURER	:	Paten Wireless Technology Co., Ltd.
		Da-Ning Industrial Zone, Humen, Dongguan, Guangdong, China

I HEREBY CERTIFY THAT:

The measurements shown in this test report were made in accordance with the procedures given in ANSI

C63.4-2003 and all test are performed according to 47 CFR FCC Part 15 Subpart C. Testing was carried

out on Feb. 01, 2005 at SPORTON International Inc. LAB.

Dr. Alan Lane Vice General Manager Sporton International Inc.



1. General Description of Equipment under Test

1.1. Applicant

Creative Technology Ltd.

31 International Business Park, Creative Resource, Singapore 609921

1.2. Manufacturer

Paten Wireless Technology Co., Ltd. Da-Ning Industrial Zone, Humen, Dongguan, Guangdong, China

1.3. Basic Description of Equipment under Test

This product is a 2.4GHz wireless mouse. The radio technical data has been listed on section "Features of Equipment under Test". The interface of the receiver is USB.

1.4. Features of Equipment under Test

Items	Description
Type of Modulation	FSK
Number of Channels	8
Frequency Band	2403MHz ~ 2430MHz
Carrier Frequency	See section 1.5 for details
Channel Bandwidth	4 MHz
Antenna Type	Printed Antenna
Testing Duty Cycle	100.00%
Test Power Source	3 VDC (battery)
Temperature Range (Operating)	-10 ~ 55 °C

1.5. Table for Carrier Frequencies

Channel	Frequency	Channel	Frequency
01	2403 MHz	05	2419 MHz
02	2407 MHz	06	2422 MHz
03	2411 MHz	07	2426 MHz
04	2415 MHz	08	2430 MHz



2. Test Configuration of the Equipment under Test

2.1. Connection Diagram of Test System



2.2. The Test Mode Description

- 1. Spurious emission below 1GHz is independent of channel selection, so only channel 08 was tested.
- 2. AC conduction emission is independent of channel selection, so only channel 08 was tested.

2.3. Description of Test Supporting Units

The EUT was tested alone.



3. General Information of Test

3.1. Test Facility

: No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiag, Tao
Yuan Hsien, Taiwan, R.O.C.
: TEL 886-3-327-3456
: FAX 886-3-318-0055
: 03CH03-HY / CO04-HY

3.2. Standards for Methods of Measurement

Here is the list of the standards followed in this test report. ANSI C63.4-2003 47 CFR FCC Part 15 Subpart C

3.3. DoC Statement

This EUT is also classified as a device of computer peripheral Class B which DoC has to be followed. It has been verified according to the rule of 47 CFR part 15 Subpart B, and found that all the requirements has been fulfilled.

3.4. Frequency Range Investigated

Radiated emission test: from 30 MHz to 10th carrier harmonic.

3.5. Test Distance

The test distance of radiated emission (30MHz~1GHz) test from antenna to EUT is 3 M. The test distance of radiated emission (1GHz~10th carrier harmonic) test from antenna to EUT is 3 M.



4. List of Measurements

4.1. Summary of the Test Results

Applied Standard: 47 CFR FCC Part 15 Subpart C					
Paragraph	FCC Rule	Description of Test	Result		
5.1	15.249(a)	Maximum Field Strength of Fundamental	Pass		
5.2	15.249(d)	Spurious Radiated Emission	Pass		
5.3	15.203	Antenna Requirement	Pass		



5. Test Result

5.1. Test of Maximum Field Strength of Fundamental

5.1.1. Applicable Standard

Section 15.249(a): The field strength of emissions within these bands specified at a distance of 3 meters (measurement instrumentation employing an average detector) shall comply with the following table. The peak field strength of any emission shall not exceed the maximum permitted average limits specified in the table by more than 20 dB under any condition of modulation

Fundamental Frequency (MHz)	Field Strength of Fundamental (millivolts/meter)	Unwanted Emission (microvolts/meter)
2400-2483.5	50	500
5725-5875	50	500

5.1.2. Measuring Instruments

Item 6~17 of the table is on section 6.

5.1.3. Description of Major Test Instruments Setting

•	Spectrum Analyzer	:	R&S FSP40 (Radiated Measurement)
	Attenuation	:	Auto
	Center Frequency	:	Carrier Frequency
	Span Frequency	:	Suitable for observe
	RB	:	1 MHz for PK value / 1 MHz for AV value
	VB	:	1 MHz for PK value / 10 Hz for AV value
	Detector	:	Peak
	Trace	:	Max Hold
	Sweep Time	:	Auto

5.1.4. Test Procedures

- 1. Configure the EUT according to ANSI C63.4.
- 2. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emission field strength of both horizontal and vertical polarization.
- 4. For carrier field strength emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. For carrier field strength emission, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.



5.1.5. Test Setup Layout



5.1.6. Test Criteria

All test results complied with in Section 15.249(a) requirements. Measurement Uncertainty is 2.26dB.

5.1.7. Test Result

- Temperature: 21.9°C
- Relative Humidity: 40%
- Duty Cycle of the Equipment During the Test: 100.00%
- Test Engineer: Sun Chen

Channel	Frequency	Level	Over	Limit	Read	Detector
			Limit	Line	Level	
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	
01	2403 MHz	70.34	-23.66	94.00	40.11	Average
01	2403 MHz	71.23	-42.77	114.00	41.00	Peak
05	2419 MHz	69.39	-24.61	94.00	39.12	Average
05	2419 MHz	70.48	-43.52	114.00	40.21	Peak
08	2430 MHz	69.33	-24.67	94.00	39.03	Average
08	2430 MHz	70.24	-43.76	114.00	39.94	Peak

Note:

Correct Factor = Antenna Factor + Cable Loss - Preamp Factor.

Read Level = Level of Receiver or Spectrum.

Level = Read Level + Correct Factor.



5.2. Test of Spurious Radiated Emission

5.2.1. Applicable Standard

Section 15.249(d): Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

5.2.2. Measuring Instruments

Please reference item 1~17 in chapter 6 for the instruments used for testing.

5.2.3. Description of Major Test Instruments Setting

Amplifier RF Gain	(HP 8447D) 25 dB
Signal Input	0.1 MHz -1.3 GHz
Spectrum Analyzer	(R&S FSP40)
Attenuation	10 dB
Start Frequency	1 GHz
Stop Frequency	18 GHz
Resolution Bandwidth	1 MHz
Video Bandwidth	1 MHz
Signal Input	9 KHz to 40 GHz
Amplifier	(MITEQ AFS44)
RF Gain	40 dB
Signal Input	100 MHz -26.5 GHz

5.2.4. Test Procedures

- 1. Configure the EUT according to ANSI C63.4.
- 2. The EUT was placed on the top of the turntable 0.8 meter above ground.
- 3. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 4. Power on the EUT and all the supporting units.
- 5. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 6. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emission field strength of both horizontal and vertical polarization.
- 7. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 8. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.



- 9. For emission above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
- 10. If the emission level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz and average method for above the 1GHz. the reported.
- 11.For testing above 1GHz, the emission level of the EUT in peak mode was 20dB higher than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 5.2.5. Test Setup Layout



5.2.6. Test Criteria

All test results complied with in Section 15.249(d) requirements. Measurement Uncertainty is 2.26dB.



5.2.7. Test Results for CH 08 / 2430 MHz (for emission below 1GHz)

- Temperature: 21.9°C
- Relative Humidity: 40%
- Duty Cycle of the Equipment During the Test: 100.00%
- Test Engineer: Sun Chen

(A) Polarization: Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
5	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB	8 	cm	deg
1	129.620	18.15	-25.35	43.50	32.97	12.32	0.00	27.14	Peak		
2	153.420	21.33	-22.17	43.50	36.27	12.15	0.00	27.09	Peak		
з	170.420	20.76	-22.74	43.50	34.10	13.72	0.00	27.06	Peak	1000	ಂದರ





	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
5	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB	S	cm	deg
1	339.200	20.76	-25.24	46.00	32.75	14.98	0.00	26.97	Peak		
2	663.200	19.87	-26.13	46.00	27.49	20.59	0.00	28.21	Peak		
з	861.600	22.26	-23.74	46.00	27.87	21.78	0.00	27.39	Peak	1.000	10000



(B) Polarization: Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB	. <u> </u>	cm	deg
1	36.460	15.59	-24.41	40.00	30.95	12.11	0.00	27.47	Peak		
2	92.900	11.37	-32.13	43.50	29.97	8.65	0.00	27.25	Peak		
3	166.340	13.41	-30.09	43.50	27.19	13.29	0.00	27.07	Peak	100000	





	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
3	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB	. <u> </u>	CM	deg
1	557.600	18.58	-27.42	46.00	28.31	18.54	0.00	28.27	Peak		
2	800.000	22.46	-23.54	46.00	28.26	21.90	0.00	27.70	Peak		
з	957.600	23.78	-22.22	46.00	28.14	22.96	0.00	27.32	Peak		

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m) Corrected Reading: Probe Factor + Cable Loss + Read Level - Preamp Factor = Level



5.2.8. Test Results for CH 01 / 2403 MHz (for emission above 1GHz)

- Temperature: 21.9°C
- Relative Humidity: 40%
- Duty Cycle of the Equipment During the Test: 100.00%
- Test Engineer: Sun Chen

(A) Polarization: Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB	·2	cm	deg
1	1080.000	39.39	-34.61	74.00	53.04	24.32	1.26	39.23	Peak		
2	3968.000	45.82	-28.18	74.00	50.29	32.46	2.49	39.42	Peak		
3	6728.000	49.14	-24.86	74.00	50.64	34.66	3.47	39.63	Peak	1 0.00 1	19 70-0 19



(B) Polarization: Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB	·	cm	deg
1	2604.000	40.97	-33.03	74.00	49.62	28.87	2.02	39.54	Peak		
2	3908.000	44.71	-29.29	74.00	49.31	32.28	2.46	39.34	Peak		
3	6448.000	48.02	-25.98	74.00	50.07	34.27	3.39	39.71	Peak	10000	्र ाजन ः ।

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m) Corrected Reading: Probe Factor + Cable Loss + Read Level - Preamp Factor = Level



5.2.9. Test Results for CH 05 / 2419 MHz (for emission above 1GHz)

- Temperature: 21.9°C
- Relative Humidity: 40%
- Duty Cycle of the Equipment During the Test: 100.00%
- Test Engineer: Sun Chen

(A) Polarization: Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB	. <u> </u>	CM	deg
1	1723.000	37.88	-36.12	74.00	49.58	26.10	1.58	39.38	Peak		
2	3932.000	46.12	-27.88	74.00	50.69	32.32	2.47	39.36	Peak		
з	6416.000	48.71	-25.29	74.00	50.78	34.27	3.38	39.72	Peak		10000



(B) Polarization: Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB		cm	deg
1	1688.000	38.18	-35.82	74.00	49.96	26.02	1.56	39.36	Peak		
2	5860.000	47.95	-26.05	74.00	50.57	34.07	3.21	39.90	Peak		
3	6672.000	48.78	-25.22	74.00	50.43	34.55	3.45	39.65	Peak	3 11 11 11 12	19 05.5 19

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m) Corrected Reading: Probe Factor + Cable Loss + Read Level - Preamp Factor = Level



- 5.2.10. Test Results for CH 08 / 2430 MHz (for emission above 1GHz)
 - Temperature: 21.9°C
 - Relative Humidity: 40%
 - Duty Cycle of the Equipment During the Test: 100.00%
 - Test Engineer: Sun Chen

(A) Polarization: Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB	. <u> </u>	cm	deg
1	2388.000	39.88	-34.12	74.00	49.30	28.27	1.91	39.60	Peak		
2	5916.000	48.25	-25.75	74.00	50.80	34.08	3.24	39.87	Peak		
3	6384.000	49.27	-24.73	74.00	51.39	34.25	3.37	39.74	Peak		



(B) Polarization: Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB	. <u> </u>	CM	deg
1	1416.000	36.28	-37.72	74.00	49.10	24.94	1.43	39.19	Peak		
2	4864.000	45.69	-28.31	74.00	49.88	33.08	2.87	40.14	Peak		
3	5788.000	47.73	-26.27	74.00	50.38	34.06	3.20	39.91	Peak	1 -	20 10-01 0

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m) Corrected Reading: Probe Factor + Cable Loss + Read Level - Preamp Factor = Level



5.2.11. Photographs of Radiated Emission Test Configuration



FRONT VIEW



REAR VIEW



5.3. Antenna Requirements

5.3.1. Standard Applicable

47 CFR Part15 Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

5.3.2. Antenna Connected Construction

There is no antenna connector for printed antenna.



6. List of Measuring Equipments Used

Items	Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
1	3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30MHz~1GHz 3m	Jun. 21, 2004	Radiation (03CH03-HY)
2	Spectrum analyzer	R&S	FSP40	100004	9KHZ~40GHz	Aug. 31, 2004	Radiation (03CH03-HY)
3	Amplifier	HP	8447D	2944A09072	100KHz – 1.3GHz	Nov. 10, 2004	Radiation (03CH03-HY)
4	Biconical Antenna	SCHWARZBECK	VHBB 9124	301	30MHz –200MHz	Jul. 28, 2004	Radiation (03CH03-HY)
5	Log Antenna	SCHWARZBECK	VUSLP 9111	221	200MHz -1GHz	Jul. 28, 2004	Radiation (03CH03-HY)
6	RF Cable-R03m	Jye Bao	RG142	CB021	30MHz~1GHz	Dec. 02, 2004	Radiation (03CH03-HY)
7	Amplifier	MITEQ	AFS44	849984	100MHz~26.5GHz	Mar. 26, 2004	Radiation (03CH03-HY)
8	Horn Antenna	EMCO	3115	6741	1GHz – 18GHz	Apr. 07, 2004	Radiation (03CH03-HY)
9	Turn Table	HD	DS 420	420/650/00	0 ~ 360 degree	N/A	Radiation (03CH03-HY)
10	Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)
11	Horn Antenna	Schwarzbeck	BBHA9170	154	18GHz~40GHz	Jun. 09, 2004	Radiation (03CH03-HY)
12	RF Cable-HIGH	Jye Bao	RG142	CB030-HIGH	1GHz~29.5GHz	Dec. 04, 2004	Radiation (03CH03-HY)

※ Calibration Interval of instruments listed above is one year.



7. Company Profile

SPORTON Lab. was established in 1986 with one shielded room: the first private EMI test facility, offering local manufacturers an alternative EMI test familial apart from ERSO. In 1988, one 3M and 10M/3M open area test site were setup and also obtained official accreditation from FCC, VCCI and NEMKO. In 1993, a Safety laboratory was founded and obtained accreditation from UL of USA, CSA of Canada and TUV (Rhineland & PS) of Germany. In 1995, one EMC lab, including EMI and EMS test facilities was setup. In 1997, SPORTON Group has provided financial expense to relocate the headquarter to Orient Scientific Park in Taipei Hsien to offer more comprehensive, more qualified and better service to local suppliers and manufactures. In 1999, Safety Group and Component Group were setup. In 2001, SPORTON has established 3M/10M chamber in Hwa Ya Technology Park.

7.1. Certificate of Accreditation

Taiwan	BSMI, CNLA, DGT
USA	FCC, NVLAP, UL
EU	Nemko, TUV
Japan	VCCI
Canada	Industry Canada

7.2. Test Location

SHIJR	ADD:	6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shiir City, Taipei, Taiwan 221, R.O.C.		
	TEL :	02-2696-2468		
	FAX :	02-2696-2255		
HWA YA	ADD :	No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Y Hsien, Taiwan, R.O.C.		
	TEL :	03-327-3456		
	FAX :	03-318-0055		
LINKOU	ADD :	No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C		
	TEL :	02-2601-1640		
	FAX :	02-2601-1695		
DUNGHU	ADD:	No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C.		
	TEL :	02-2631-4739		
	FAX :	02-2631-9740		
JUNGHE	ADD :	7FI., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C.		
	TEL :	02-8227-2020		
	FAX :	02-8227-2626		
NEIHU	ADD :	4FI., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C.		
	TEL :	02-2794-8886		
	FAX :	02-2794-9777		



8. CNLA Certificate of Accreditation

Test Lab.	:	Sporton International Inc.
Accreditation Number	:	1190
Originally Accredited	:	2003/12/15
Effective Period	:	2003/12/15~2006/12/14
Accredited Scope	:	47 CFR FCC Part 15 Subpart C (9kHz~40GHz)



Taiwan Accreditation Foundation Chinese National Laboratory Accreditation Certificate of Accreditation

Accreditation Criteria: Accreditation Number: Organization/Laboratory: Originally Accredited: Effective Period: Accredited Scope: Specific Accreditation Program:

ISO 17025 1190 EMC & Wireless Communications Laboratory,Sporton International Inc. December 15, 2003 December 15, 2003 To December 14, 2006 Electrical Testing Field, 7 items, details shown in the following pages. Recognition and Approval of Designated Laboratory for Commodities Inspection

Ľφ

President, Taiwan Accreditation Foundation Date:July 19, 2004

(This document is invalid unless accompanied by all 4 pages)

CNLA-ZL03191E Page 1 of 4