



REPORT No.: SZ22030285W04

TEST REPORT

APPLICANT : Thundercomm Technology Co., Ltd

PRODUCT NAME : Smart Module Development Kit

MODEL NAME : C865C-DK

BRAND NAME : TurboX

FCC ID : 2AOHHTURBOXC865CDK

STANDARD(S) : 47 CFR Part 15 Subpart E

RECEIPT DATE : 2022-03-29

TEST DATE : 2022-03-30 to 2022-04-27

ISSUE DATE : 2022-05-20

Edited by:

Zeng Xiaoying
Zeng Xiaoying (Rapporteur)

Approved by:

Shen Junsheng
Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, Guangdong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





DIRECTORY

1. Technical Information	3
1.1. Applicant and Manufacturer Information	3
1.2. Equipment Under Test (EUT) Description	3
1.3. Modulation Type and Data Rate of EUT	5
1.4. The Channel Number and Frequency	6
1.5. Test Standards and Results	7
1.6. Environmental Conditions	8
2. 47 CFR Part 15E Requirements	9
2.1. Antenna Requirement	9
2.2. Duty Cycle of the Test Signal	10
2.3. Maximum Conducted Output Power	18
2.4. Emission Bandwidth	29
2.5. Peak Power Spectral Density	106
2.6. Frequency Stability	189
2.7. Conducted Emission	192
2.8. Restricted Frequency Bands	196
2.9. Radiated Emission	225
Annex A Test Uncertainty	280
Annex B Testing Laboratory Information	281

Change History		
Version	Date	Reason for change
1.0	2022-05-20	First edition



1. Technical Information

Note: Provide by applicant.

1.1. Applicant and Manufacturer Information

Applicant:	Thundercomm Technology Co., Ltd
Applicant Address:	Building 4, No. 99, Data Valley Middle Road,Xiantao District, Yubei District Chongqing, China
Manufacturer:	Thundercomm Technology Co., Ltd
Manufacturer Address:	Building 4, No. 99, Data Valley Middle Road,Xiantao District, Yubei District Chongqing, China

1.2. Equipment Under Test (EUT) Description

Product Name:	Smart Module Development Kit
Sample No.:	2#
Hardware Version:	DT865_DEq_LA-IOB V03
Software Version:	FlatBuild_Turbox-QCS8250_xx.xx_la1.0.D.userdebug
Modulation Technology:	OFDM
Modulation Mode:	802.11a, 802.11n (HT20), 802.11n (HT40) 802.11ac (VHT20), 802.11ac (VHT40),802.11ac (VHT80) 802.11ax (HEW20), 802.11ax (HEW40),802.11ax (HEW80)
Operating Frequency Range:	5180MHz-5240MHz; 5260MHz-5320MHz; 5500MHz-5720MHz; 5745MHz-5825MHz
Channel Number:	Refer to 1.3
Antenna Type:	Dipole Antenna
Antenna Gain:	ANT0: 2.7dBi; ANT1: 2.7dBi
Directional Gain:	5.71dBi _{Note 2}

Note 1: The EUT supports a MIMO function. Physically, the EUT provides two completed transmitters and two receivers for 802.11n, 802.11ac and 802.11ax modulation mode.

Modulation Mode:	TX Function
802.11a	1TX
802.11n	2TX
802.11ac	2TX
802.11ax	2TX



Note 2: According to KDB 662911 D01, the directional gain = $G_{ANT} + 10\log(N_{ANT})$ dBi, where G_{ANT} is the maximum antenna gain in dBi, N_{ANT} is the number of outputs.

Note 3: For conducted test item Conducted Output Power and Peak Power Spectral Density of each modulation mode, we recorded the test result of two antennas separately, for other conducted test items both of the two antennas were tested separately, we only recorded the worst test result (ANT0) in this report.

Note 4: All radiation test items for 802.11n, 802.11ac and 802.11ax modulation mode operate at MIMO mode during the test. Other modulation mode operate at SISO mode, both of the two antennas were tested separately, we only recorded the worst test result(ANT0) in this report.

Note 5: We use the dedicated software to control the EUT continuous transmission.

Note 6: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



1.3. Modulation Type and Data Rate of EUT

Mode	Bandwidth (MHz)	Modulation Technology	Modulation Type	Data Rate	RU Size
802.11a	20	OFDM	DBPSK	1/2/5.5/11Mbps	N/A
			DQPSK		
			CCK		
802.11n	20/40 (HT20/40)	OFDM	BPSK	MCS0~MCS7	N/A
			QPSK		
			16QAM		
			64QAM		
802.11ac	20/40/80 (VHT20/40/80)	OFDM	BPSK	MCS0~MCS9	N/A
			QPSK		
			16QAM		
			64QAM		
			256QAM		
802.11ax	20/40/80 (HEW20/40/80)	OFDMA	BPSK	MCS0~MCS11	26/52/106/242/484/996
			QPSK		
			16QAM		
			64QAM		
			256QAM		
			1024QAM		

Note1: The worst-case mode(black bold) in all data rates has been determined during the pre-scan, only the test data of the worst-case were recorded in this report.

1.4. The Channel Number and Frequency

(U-NII-1) 5180MHz-5240MHz				
Bandwidth	Channel	Frequency (MHz)	Channel	Frequency (MHz)
20MHz	36	5180	40	5200
	44	5220	48	5240
40MHz	38	5190	46	5230
80MHz	42	5210		
(U-NII-2A) 5260MHz-5320MHz				
Bandwidth	Channel	Frequency (MHz)	Channel	Frequency (MHz)
20MHz	52	5260	56	5280
	60	5300	64	5320
40MHz	54	5270	62	5310
80MHz	58	5290		
(U-NII-2C) 5500MHz-5720MHz				
Bandwidth	Channel	Frequency (MHz)	Channel	Frequency (MHz)
20MHz	100	5500	105	5520
	108	5540	112	5560
	116	5580	120	5600
	124	5620	128	5640
	132	5660	136	5680
	140	5700	144	5720
40MHz	102	5510	110	5550
	118	5590	126	5630
	134	5670	142	5710
80MHz	106	5530	122	5610
	138	5690		
(U-NII-3) 5745MHz-5825MHz				
Bandwidth	Channel	Frequency (MHz)	Channel	Frequency (MHz)
20MHz	149	5745	153	5765
	157	5785	161	5805
	165	5825		
40MHz	151	5775	159	5795
80MHz	155	5775		

Note 1: The black bold channels were selected for test.



1.5. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart E (U-NII band) for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15(5-1-14 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result	Method Determination /Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	No deviation
2	ANSI C63.10	Duty Cycle of the Test Signal	Mar. 31, 2022	Su Xiaoxian	PASS	No deviation
3	15.407(a)	Maximum Conducted Output Power	Apr. 27, 2022	Su Xiaoxian	PASS	No deviation
4	15.407(a) (e)	Emission Bandwidth	Apr. 19, 2022	Su Xiaoxian	PASS	No deviation
5	15.407(a)	Peak Power Spectral Density	Apr. 19, 2022	Su Xiaoxian	PASS	No deviation
6	15.407(g)	Frequency Stability	Apr. 20, 2022	Su Xiaoxian	PASS	No deviation
7	15.207	Conducted Emission	Apr. 27, 2022	Wu Zhaoling	PASS	No deviation
8	15.407(b)	Restricted Frequency Bands	Apr. 20, 2022	Lin Jiayong	PASS	No deviation
9	15.407(b)	Radiated Emission	Apr. 22&26, 2022	Lin Jiayong	PASS	No deviation

Note 1: The DFS test report was documented in a separate report (Report No.: SZ22030285W05).

Note 2: The tests of Conducted Emission and Radiated Emission were performed according to the method of measurements prescribed in ANSI C63.102013.

Note 3: These RF tests were performed according to the method of measurements prescribed in KDB789033 D02 v02r01 and KDB662911 D01 v02r01.



Note 4: The path loss during the RF test is calibrated to correct the results by the offset setting in the test equipments. The ref offset 12.0dB contains two parts that cable loss 2.0dB and Attenuator 10dB.

Note 5: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

Note 6: When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.

1.6. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106



2. 47 CFR Part 15E Requirements

2.1. Antenna Requirement

2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

2.1.2. Test Result: Compliant

Inside of the EUT has a permanently attached Dipole antenna fixed to PCB with solder. Please refer to the EUT internal photos.

2.2. Duty Cycle of the Test Signal


2.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than $\pm 2\%$; otherwise, the duty cycle is considered to be nonconstant.

2.2.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

2.2.3. Test Procedure

KDB 789033 Section B was used in order to prove compliance.




2.2.4. Test Result


A. Test Verdict:

Test Mode	Duty Cycle (%) (D)	Duty Factor (10*log[1/D])
802.11a	99.00	0.04
802.11n(HT20)	99.63	0.02
802.11n(HT40)	99.63	0.02
802.11ac(VHT20)	99.63	0.02
802.11ac(VHT40)	99.63	0.02
802.11ac(VHT80)	100.00	0.00
802.11ax(HEW20)	99.63	0.02
802.11ax(HEW40)	99.63	0.02
802.11ax(HEW80)	100.00	0.00
802.11ax(HEW20) RU26	100.00	0.00
802.11ax(HEW20) RU52	100.00	0.00
802.11ax(HEW20) RU106	100.00	0.00


B. Test Plot:




(Channel 36, 5180MHz, 802.11a)




(Channel 36, 5180MHz, 802.11n (HT20))




(Channel 38, 5190MHz, 802.11n (HT40))




(Channel 36, 5180MHz, 802.11ac (VHT20))




(Channel 38, 5190MHz, 802.11ac (VHT40))




(Channel 42, 5210MHz, 802.11ac (VHT80))




(CH36, 5180MHz, 802.11ax (HEW20))




(CH38, 5190MHz, 802.11ax (HEW40))




(CH42, 5210MHz, 802.11ax (HEW80))



(CH36, 5180MHz, 802.11ax (HEW20) RU26)



(CH36, 5180MHz, 802.11ax (HEW20) RU52)



(CH36, 5180MHz, 802.11ax (HEW20) RU106)

2.3. Maximum Conducted Output Power

2.3.1. Requirement

(1) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6dBi.

(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or $11\text{dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz.

(3) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.


(4) According to KDB662911D01 Measure-and-sum technique, the conducted emission level (e.g., transmit power or power in specified bandwidth) is measured at each antenna port. The measured results at the various antenna ports are then summed mathematically to determine the total emission level from the device. Summing is performed in units that are directly proportional to power.

(5) According to KDB 662911 D01, the directional gain = $G_{\text{ANT}} + 10\log(N_{\text{ANT}})\text{dBi}$, where G_{ANT} is the antenna gain in dBi, N_{ANT} is the number of outputs.


2.3.2. Test Description

Section E) 3) of KDB 789033 defines a methodology using a USB Wideband Power Sensor.

Test Setup:



The EUT (Equipment under the test) which is coupled to the USB Wideband Power Sensor; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading, all test result in USB Wideband Power Sensor.

For ac (VHT80) mode power

The EUT (Equipment under the test) is coupled to the Spectrum analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading, all test result in Spectrum analyzer.

2.3.3. Limits

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz.

Mode	Band	Channel (MHz)	26dB BW (MHz)	$10+10\log(26\text{dB BW})$	Limits (dBm)
a	UNII-2a	5260	18.55	23.68	23.68
		5300	18.55	23.68	23.68
		5320	18.80	23.74	23.74
	UNII-2c	5500	18.48	23.67	23.67
		5600	18.86	23.76	23.76
		5720	18.61	23.70	23.70
n20	UNII-2a	5260	19.55	23.91	23.91
		5300	19.82	23.97	23.97
		5320	19.85	23.98	23.98
	UNII-2c	5500	19.77	23.96	23.96
		5600	20.21	24.06	24.00
		5720	19.86	23.98	23.98
ac20	UNII-2a	5260	19.98	24.01	24.00
		5300	19.97	24.00	24.00
		5320	20.06	24.02	24.00
	UNII-2c	5500	19.70	23.94	23.94
		5600	20.05	24.02	24.00
		5720	19.92	23.99	23.99
ax20	UNII-2a	5260	20.72	24.16	24.00
		5300	20.63	24.14	24.00
		5320	20.36	24.09	24.00
	UNII-2c	5500	20.45	24.11	24.00
		5600	20.76	24.17	24.00
		5720	20.84	24.19	24.00
ax_RU26	UNII-2a	5260	19.81	23.97	23.97
		5300	20.01	24.01	24.00
		5320	19.80	23.97	23.97
	UNII-2c	5500	19.84	23.98	23.98
		5600	20.12	24.04	24.00
		5720	19.95	24.00	24.00



2.3.4. Test Result

Maximum Average Conducted Output Power

802.11a Mode

Frequency (MHz)	Average Power							Limit		Verdict
	Measured		Duty Factor	Duty Factor Calculated						
	ANT0	ANT1		ANT0		ANT1				
	dBm	dBm		dBm	W	dBm	W	dBm	W	
5180	16.26	15.89	0.04	16.30	0.043	15.93	0.039	24	0.25	PASS
5220	16.31	16.11		16.35	0.043	16.15	0.041			
5240	16.23	15.96		16.27	0.042	16.00	0.040			
5260	16.25	16.13		16.29	0.043	16.17	0.041	23.68	0.23	
5300	16.39	16.28		16.43	0.044	16.32	0.043	23.68	0.23	
5320	16.35	16.21		16.39	0.044	16.25	0.042	23.74	0.24	
5500	14.74	15.27		14.78	0.030	15.31	0.034	23.67	0.23	
5600	15.43	14.93		15.47	0.035	14.97	0.031	23.76	0.24	
5720	16.27	15.79		16.31	0.043	15.83	0.038	23.70	0.23	
5745	16.45	16.07		16.49	0.045	16.11	0.041	30	1	
5785	16.42	16.05		16.46	0.044	16.09	0.041			
5825	16.02	16.15		16.06	0.040	16.19	0.042			

**802.11n (HT20) Mode**

Frequency (MHz)	Average Power					Limit		Verdict
	Measured		Duty Factor	Total Power with Duty Factor				
	ANT0	ANT1						
	dBm	dBm		dBm	W	dBm	W	
5180	16.26	15.71	0.02	19.03	0.080	24	0.25	PASS
5220	16.28	15.85		19.08	0.081			
5240	16.20	15.74		19.03	0.080			
5260	16.22	15.98		19.14	0.082	23.91	0.25	
5300	16.37	16.27		19.34	0.086	23.97	0.25	
5320	16.33	15.88		19.14	0.082	23.98	0.25	
5500	14.59	14.31		17.48	0.056	23.96	0.25	
5600	15.35	15.07		18.26	0.067	24.00	0.25	
5720	16.13	16.07		19.14	0.082	23.98	0.25	
5745	16.39	16.33		19.40	0.087	30	1	
5785	16.23	16.14		19.19	0.083			
5825	16.01	15.55		18.81	0.076			

Note: Directional gain = 2.7dBi + 10log(2) = 5.71dBi < 6dBi, so the power limit shall be 24dBm for 5.18-5.24 GHz band and 30dBm for 5.745-5.825 GHz band.

802.11n (HT40) Mode

Frequency (MHz)	Average Power					Limit		Verdict
	Measured		Duty Factor	Total Power with Duty Factor				
	ANT0	ANT1						
	dBm	dBm		dBm	W	dBm	W	
5190	15.17	15.11	0.02	18.20	0.066	24	0.25	PASS
5230	15.35	15.24		18.33	0.068			
5270	15.69	15.48		18.63	0.073			
5310	15.56	15.52		18.57	0.072			
5510	14.39	14.33		17.40	0.055			
5630	14.67	14.59		17.63	0.058			
5710	14.61	14.50		17.56	0.057			
5755	16.95	16.86		19.96	0.099	30	1	
5795	16.67	16.25		19.49	0.089			

Note: Directional gain = 2.7dBi + 10log(2) = 5.71dBi < 6dBi, so the power limit shall be 24dBm for 5.18-5.24 GHz band and 30dBm for 5.745-5.825 GHz band.

**802.11ac (VHT20) Mode**

Frequency (MHz)	Average Power					Limit		Verdict
	Measured		Duty Factor	Total Power with Duty Factor				
	ANT0	ANT1						
	dBm	dBm		dBm	W			
5180	15.34	15.09	0.02	18.26	0.067	24	0.25	PASS
5220	15.41	15.22		18.33	0.068			
5240	15.22	15.15		18.20	0.066			
5260	15.13	15.02		18.13	0.065	24.00	0.25	
5300	15.25	15.23		18.26	0.067	24.00	0.25	
5320	15.23	15.16		18.20	0.066	24.00	0.25	
5500	13.64	13.25		16.43	0.044	23.94	0.25	
5600	14.30	14.24		17.32	0.054	24.00	0.25	
5720	15.25	14.89		18.13	0.065	23.99	0.25	
5745	15.44	14.95		18.26	0.067	30	1	
5785	15.37	15.37		18.39	0.069			
5825	15.09	15.06		18.13	0.065			

Note: Directional gain = 2.7dBi + 10log(2) = 5.71dBi < 6dBi, so the power limit shall be 24dBm for 5.18-5.24 GHz band and 30dBm for 5.745-5.825 GHz band.

802.11ac (VHT40) Mode

Frequency (MHz)	Average Power					Limit		Verdict
	Measured		Duty Factor	Total Power with Duty Factor				
	ANT0	ANT1						
	dBm	dBm		dBm	W	dBm	W	
5190	15.66	15.52	0.02	18.63	0.073	24	0.25	PASS
5230	15.39	15.33		18.39	0.069			
5270	15.10	14.98		18.06	0.064			
5310	15.63	15.39		18.51	0.071			
5510	14.39	13.97		17.24	0.053			
5630	15.23	14.93		18.13	0.065			
5710	15.83	15.53		18.69	0.074			
5755	15.97	15.79		18.92	0.078	30	1	
5795	15.78	15.54		18.69	0.074			

Note: Directional gain = 2.7dBi + 10log(2) = 5.71dBi < 6dBi, so the power limit shall be 24dBm for 5.18-5.24 GHz band and 30dBm for 5.745-5.825 GHz band.

**802.11ac (VHT80) Mode**

Frequency (MHz)	Average Power					Limit		Verdict
	Measured		Duty Factor	Total Power with Duty Factor				
	ANT0	ANT1						
	dBm	dBm		dBm	W	dBm	W	
5210	14.95	14.51	0.00	17.78	0.060	24	0.25	PASS
5290	15.02	14.49		17.78	0.060			
5530	13.22	13.07		16.13	0.041			
5610	13.46	13.24		16.33	0.043			
5690	14.39	14.55		17.48	0.056			
5775	15.71	15.23		18.51	0.071	30	1	

Note: Directional gain = 2.7dBi + 10log(2) = 5.71dBi < 6dBi, so the power limit shall be 24dBm for 5.18-5.24 GHz band and 30dBm for 5.745-5.825 GHz band.

802.11ax (HEW20) Mode

Frequency (MHz)	Average Power					Limit		Verdict
	Measured		Duty Factor	Total Power with Duty Factor				
	ANT0	ANT1						
	dBm	dBm		dBm	W			
5180	15.29	15.09	0.02	18.20	0.066	24	0.25	PASS
5220	15.37	15.17		18.33	0.068			
5240	15.19	14.76		17.99	0.063			
5260	15.23	14.74		17.99	0.063			
5300	15.27	15.04		18.20	0.066			
5320	15.22	15.17		18.20	0.066			
5500	13.74	13.71		16.72	0.047			
5600	14.24	13.78		17.08	0.051			
5720	15.22	14.83		18.06	0.064			
5745	15.33	15.18		18.26	0.067	30	1	
5785	15.20	15.00		18.13	0.065			
5825	15.05	14.71		17.92	0.062			

Note: Directional gain = 2.7dBi + 10log(2) = 5.71dBi < 6dBi, so the power limit shall be 24dBm for 5.18-5.24 GHz band and 30dBm for 5.745-5.825 GHz band.

**802.11ax (HEW20) RU26 Mode**

Frequency (MHz)	Average Power				Limit		Verdict	
	Measured		Duty Factor	Total Power with Duty Factor				
	ANT0	ANT1				dBm		W
5180	7.02	7.78	0.00	10.41	0.011	24	0.25	PASS
5220	7.45	8.26		10.79	0.012			
5240	8.29	8.64		11.46	0.014			
5260	8.06	7.68		10.79	0.012	23.97	0.25	
5300	8.52	8.35		11.46	0.014	24.00	0.25	
5320	7.47	7.32		10.41	0.011	23.97	0.25	
5500	5.70	7.08		9.54	0.009	23.98	0.25	
5600	5.43	7.06		9.54	0.009	24.00	0.25	
5720	8.22	7.77		11.14	0.013	24.00	0.25	
5745	8.93	7.64		11.46	0.014	30	1	
5785	8.25	7.39		10.79	0.012			
5825	7.81	7.11		10.41	0.011			
Note: Directional gain =2.7dBi +10log(2) = 5.71dBi<6dBi, so the power limit shall be 24dBm for 5.18-5.24 GHz band and 30dBm for 5.745-5.825 GHz band.								

**802.11ax (HEW20) RU52 Mode**

Frequency (MHz)	Average Power				Limit		Verdict	
	Measured		Duty Factor	Total Power with Duty Factor				
	ANT0 dBm	ANT1 dBm				dBm		W
5180	10.62	9.81	0.00	13.22	0.021	24	0.25	PASS
5220	10.77	9.31		13.01	0.020			
5240	10.73	9.44		13.22	0.021			
5260	10.64	9.52		13.22	0.021			
5300	10.90	9.64		13.42	0.022			
5320	10.83	9.77		13.42	0.022			
5500	9.56	8.96		12.30	0.017			
5600	9.66	8.99		12.30	0.017			
5720	10.39	9.58		13.01	0.020			
5745	11.27	9.89		13.62	0.023	30	1	
5785	11.28	10.17		13.80	0.024			
5825	11.39	10.22		13.80	0.024			
Note: Directional gain =2.7dBi +10log(2) = 5.71dBi<6dBi, so the power limit shall be 24dBm for 5.18-5.24 GHz band and 30dBm for 5.745-5.825 GHz band.								


802.11ax (HEW20) RU106 Mode

Frequency (MHz)	Average Power				Limit		Verdict	
	Measured		Duty Factor	Total Power with Duty Factor				
	ANT0	ANT1				dBm		W
5180	12.23	11.51	0.00	14.91	0.031	24	0.25	PASS
5220	12.42	12.41		15.44	0.035			
5240	12.44	12.30		15.44	0.035			
5260	12.31	12.28		15.31	0.034			
5300	12.04	11.10		14.62	0.029			
5320	12.49	11.72		15.19	0.033			
5500	10.21	10.91		13.62	0.023			
5600	10.59	9.78		13.22	0.021			
5720	10.65	10.21		13.42	0.022			
5745	11.21	11.06		14.15	0.026	30	1	
5785	12.18	11.82		15.05	0.032			
5825	12.36	11.39		14.91	0.031			
Note: Directional gain =2.7dBi +10log(2) = 5.71dBi<6dBi, so the power limit shall be 24dBm for 5.18-5.24 GHz band and 30dBm for 5.745-5.825 GHz band.								

**802.11ax (HEW40) Mode**

Frequency (MHz)	Average Power					Limit		Verdict
	Measured		Duty Factor	Total Power with Duty Factor				
	ANT0	ANT1		dBm	W	dBm	W	
5190	15.61	15.13	0.02	18.39	0.069	24	0.25	PASS
5230	15.70	15.52		18.63	0.073			
5270	15.58	15.48		18.57	0.072			
5310	15.67	15.36		18.57	0.072			
5510	14.18	13.78		16.99	0.050			
5630	15.10	15.02		18.06	0.064			
5710	15.75	15.43		18.63	0.073			
5755	15.95	15.84		18.92	0.078	30	1	
5795	15.57	15.26	18.45	0.070				
Note: Directional gain =2.7dBi +10log(2) = 5.71dBi<6dBi, so the power limit shall be 24dBm for 5.18-5.24 GHz band and 30dBm for 5.745-5.825 GHz band.								

802.11ax (HEW80) Mode

Frequency (MHz)	Average Power					Limit		Verdict
	Measured		Duty Factor	Total Power with Duty Factor				
	ANT0	ANT1		dBm	W	dBm	W	
5210	15.62	15.50	0.00	18.57	0.072	24	0.25	PASS
5290	15.55	15.10		18.33	0.068			
5530	14.31	14.10		17.24	0.053			
5610	14.80	14.75		17.78	0.060			
5690	15.47	15.44		18.45	0.070			
5775	15.78	15.72		18.75	0.075	30	1	
Note: Directional gain =2.7dBi +10log(2) = 5.71dBi<6dBi, so the power limit shall be 24dBm for 5.18-5.24 GHz band and 30dBm for 5.745-5.825 GHz band.								


2.4. Emission Bandwidth

2.4.1. Requirement

For purposes of this subpart the emission bandwidth shall be determined by measuring the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, that are 26 dB down relative to the maximum level of the modulated carrier. Determination of the emissions bandwidth is based on the use of measurement instrumentation employing a peak detector function with an instrument resolution bandwidth approximately equal to 1.0 percent of the emission bandwidth of the device under measurement. Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

2.4.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50 Ohm; the path loss as the factor is calibrated to correct the reading.

2.4.3. Test Procedure

1. KDB 789033 Section C) 1) Emission Bandwidth was used in order to prove compliance
 - a) Set RBW = approximately 1% of the emission bandwidth.
 - b) Set VBW > RBW.
 - c) Detector = Peak.
 - d) Trace mode = max hold.
 - e) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.
 2. KDB 789033 Section C) 2) minimum emission bandwidth for the band 5.725-5.85GHz was used in order to prove compliance.
- Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:



- a) Set RBW = 100 kHz.
- b) Set video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

2.4.4. Test Result

802.11a Mode

A.Test Verdict:

Channel	Frequency (MHz)	26 dB Bandwidth (MHz)
36	5180	19.72
44	5220	18.49
48	5240	18.54
52	5260	18.55
60	5300	18.55
64	5320	18.80
100	5500	18.48
120	5600	18.86
144	5720	18.61
Channel	Frequency (MHz)	6 dB Bandwidth (MHz)
144	5720	16.02
149	5745	16.30
157	5785	16.32
165	5825	16.30



B.Test Plot:



(Channel 36, 5180MHz, 802.11a)



(Channel 44, 5220 MHz, 802.11a)



(Channel 48, 5240MHz, 802.11a)



(Channel 52, 5260MHz, 802.11a)



(Channel 60, 5300 MHz, 802.11a)



(Channel 64, 5320MHz, 802.11a)



(Channel 100,5500MHz, 802.11a)





(Channel 120, 5600 MHz, 802.11a)




(Channel 144, 5720MHz, 802.11a)



(Channel 144, 5720MHz, 802.11a)





(Channel 165, 5825MHz, 802.11a)

**802.11n (HT20) Mode****A.Test Verdict:**

Channel	Frequency (MHz)	26 dB Bandwidth (MHz)
36	5180	19.70
44	5220	19.73
48	5240	19.67
52	5260	19.55
60	5300	19.82
64	5320	19.85
100	5500	19.77
120	5600	20.21
144	5720	19.86
Channel	Frequency (MHz)	6 dB Bandwidth (MHz)
144	5720	17.56
149	5745	16.30
157	5785	17.54
165	5825	17.65

B.Test Plot:

(Channel 36, 5180MHz, 802.11n (HT20))



(Channel 44, 5220MHz, 802.11n (HT20))




(Channel 48, 5240MHz, 802.11n (HT20))



(Channel 52, 5260MHz, 802.11n (HT20))



(Channel 60, 5300MHz, 802.11n (HT20))



(Channel 64, 5320MHz, 802.11n (HT20))



(Channel 100, 5500MHz, 802.11n (HT20))



(Channel 120, 5600MHz, 802.11n (HT20))



(Channel 144, 5720MHz, 802.11n (HT20))



(Channel 144, 5720MHz, 802.11 n (HT20))



(Channel 149, 5745MHz, 802.11 n (HT20))



(Channel 157, 5785MHz, 802.11 n (HT20))



(Channel 165, 5825MHz, 802.11 n (HT20))

**802.11n (HT40) Test mode****A.Test Verdict:**

Channel	Frequency (MHz)	26 dB Bandwidth (MHz)
38	5190	39.17
46	5230	38.88
54	5270	39.17
62	5310	39.41
102	5510	38.92
126	5630	39.37
142	5710	39.48
Channel	Frequency (MHz)	6 dB Bandwidth (MHz)
142	5710	35.27
151	5755	36.39
159	5795	36.29

B.Test Plot:

(Channel 38, 5190MHz, 802.11n (HT40))



(Channel 46, 5230MHz, 802.11n (HT40))



(Channel 54, 5270MHz, 802.11n (HT40))



(Channel 62, 5310MHz, 802.11n (HT40))



(Channel 102, 5510MHz, 802.11n (HT40))



(Channel 126, 5630MHz, 802.11n (HT40))



(Channel 142, 5710MHz, 802.11n (HT40))



(Channel 142, 5710MHz, 802.11n (HT40))



(Channel 151, 5755MHz, 802.11n (HT40))



(Channel 159, 5795MHz, 802.11n (HT40))

**802.11ac (VHT20) Mode****A.Test Verdict:**

Channel	Frequency (MHz)	26 dB Bandwidth (MHz)
36	5180	20.05
44	5220	19.81
48	5240	19.74
52	5260	19.98
60	5300	19.97
64	5320	20.06
100	5500	19.70
120	5600	20.05
144	5720	19.92
Channel	Frequency (MHz)	6 dB Bandwidth (MHz)
144	5720	17.03
149	5745	17.57
157	5785	17.55
165	5825	17.59

B.Test Plot:

(Channel 36, 5180MHz, 802.11ac (VHT20))



(Channel 44, 5220MHz, 802.11ac (VHT20))



(Channel 48, 5240MHz, 802.11ac (VHT20))



(Channel 52, 5260MHz, 802.11ac (VHT20))



(Channel 60, 5300MHz, 802.11ac (VHT20))



(Channel 64, 5320MHz, 802.11ac (VHT20))



(Channel 100, 5500MHz, 802.11ac (VHT20))



(Channel 120, 5600MHz, 802.11ac (VHT20))



(Channel 144, 5720MHz, 802.11ac (VHT20))



(Channel 144, 5720MHz, 802.11ac (VHT20))



(Channel 149, 5745MHz, 802.11 ac (VHT20))



(Channel 157, 5785MHz, 802.11 ac (VHT20))



(Channel 165, 5825MHz, 802.11 ac (VHT20))



802.11ac (VHT40) Mode

A. Test Verdict:

Channel	Frequency (MHz)	26 dB Bandwidth (MHz)
38	5190	39.49
46	5230	39.28
54	5270	38.99
62	5310	38.99
102	5510	39.52
126	5630	38.89
142	5710	39.37
Channel	Frequency (MHz)	6 dB Bandwidth (MHz)
142	5710	35.35
151	5755	34.76
159	5795	36.36

B. Test Plot:



(Channel 38, 5190MHz, 802.11ac (VHT40))



(Channel 46, 5230MHz, 802.11ac (VHT40))



(Channel 54, 5270MHz, 802.11ac (VHT40))



(Channel 62, 5310MHz, 802.11ac (VHT40))



(Channel 102, 5510MHz, 802.11ac (VHT40))