

FCC Part 27 Compliance Test Report

Test Report no.:	FCC_Cellular_RM-1073_46_Ant2.docx	Date of Report:	11-Feb-2015
Number of pages:	12	Customer's Contact person:	Juha Paukku
Testing laboratory:	TCC Microsoft Salo Laboratory P.O.Box(86) Joensuunkatu 7E FIN-24101 SALO, FINLAND Tel. +358 (0) 7180 08000 Fax. +358 71 80 44122	Customer:	Microsoft P.O. Box 403 Visiokatu 4 FIN-33720 TAMPERE, FINLAND Tel. +358 (0) 7180 46800 Fax. +358 (0) 7180 46880
FCC listing no.:	533467		
IC recognition no.:	661V-1		
Tested devices/ accessories:	Phone RM-1073 / Dummy battery SD-131 / Headset WH-108		
FCC ID:	PYARM-1073	IC:	661X-RM1073
Supplement reports:	-		
Testing has been carried out in accordance with:	CFR 47, FCC rules Parts 27, TIA-603-C-2004 and IC standards, RSS-GEN (Issue 4, November 2014), RSS-139 (Issue 2, February 2009), RSS-199 (Issue 2, October 2014), RSS-130 (Issue 1, October 2013). Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Microsoft.		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document		
Date and signature for the contents:			

Kalle Hannila, System Manager, EMC

1. Summary for FCC Part 27 Compliance Test Report

Date of receipt	2-Feb-2015
Testing completed	3-Feb-2015
The customer's contact person	Juha Paukku
Test Plan referred to	T:\Projects\RM-1073\TestPlan\RS_TestPlan_RM-1073.xlsm
Notes	-
Document name	T:\Projects\RM-1073\EMC\FCC_Cellular_RM-1073_46_Ant2.docx

1.1. EUT and Accessory Information

The EUT is a mobile phone with following features:

GSM/WCDMA/WLAN/Bluetooth

The EUT is tested with maximum rated TX power.

Devices under tests

Product	Type	SN	HW	MV	SW	DUT
Phone	RM-1073	004402740501139	1540	-	02149.00000.14441.39000	18901
Dummy battery	SD-131		v.1	-	-	18902
Headset	WH-108	2265171	-	-	-	18677

1.2. Summary of Test Results

LTE7:

Section in CFR 47	Section in RSS-GEN or RSS-199	Name of the test	Result
§2.1046(a)	4.4	Conducted RF output power	-
§27.50(h)(2)	4.4	Radiated RF output power	-
N/A	N/A	Peak to average power ratio	-
§2.1049(h)	6.6	99 % occupied bandwidth	-
§27.53(l)	4.5(b)	Band edge compliance	-
§2.1051	4.5(b)	Spurious emissions at antenna terminals	-
§27.53(l), §2.1053	4.5(b)	Spurious radiated emissions	-
§27.54	4.3	Frequency stability, temperature variation	PASSED
§27.54	4.3	Frequency stability, voltage variation	PASSED

PASSED

FAILED

NP

The EUT complies with the essential requirements in the standard.

The EUT does not comply with the essential requirements in the standard.

The test was not performed by the TCC Microsoft Laboratory.


CONTENTS

1. Summary for FCC Part 27 Compliance Test Report	2
1.1. EUT and Accessory Information.....	2
1.2. Summary of Test Results.....	2
2. Frequency stability, temperature variation, (Band edge method) (RSS-139 6.3, RSS-199 4.3, RSS-130 4.3, RSS-130 4.3 (a)).....	4
2.1. Test Setup.....	4
2.2. Test method and limit.....	4
2.3. LTE7 Test results.....	6
3. Frequency stability, voltage variation, (Band edge method) §2.1055(d), §27.54,(RSS-139 6.3, RSS-199 4.3, RSS-130 4.3, RSS-130 4.3 (a)).....	8
3.1. Test Setup.....	8
3.2. Test method and limit.....	8
3.3. LTE7 Test results.....	9
4. Test Equipment.....	11
4.1. Conducted measurements	11
4.2. Radiated measurements	12

2. Frequency stability, temperature variation, (Band edge method) (RSS-139 6.3, RSS-199 4.3, RSS-130 4.3, RSS-130 4.3 (a))

EUT with DUT number	RM-1073, DUT 18901
Accessories with DUT numbers	SD-131, DUT 18902 ; WH-108, DUT 18677
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	Measured from Antenna 2.
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	22 / 35 / 100
Date of measurements	02-Feb-2015
Measured by	Tomi Lipponen

2.1. Test Setup



2.2. Test method and limit

The measurement is made according to applicable FCC rule parts and IC standards as follows:

The climate chamber temperature is set to the maximum value and the temperature is allowed to stabilize.

The EUT is placed in the chamber.

The EUT is set in idle mode for 15 minutes.

The EUT is set to transmit.

The transmit frequency error was measured immediately.

The steps c - e were repeated for each temperature.


The results were then calculated as per section 4.3 of RSS-130.

Limits for frequency stability, temperature variation measurements

Limit
The results must be within the operating band.

2.3. LTE7 Test results


Channel 21100 / 2535.0 MHz



RMS (RBW: 500 kHz, VBW: 2 MHz)

Temperature [°C]	Deviation [Hz]	Low marker [MHz]	Marker - Dev [MHz]	High marker [MHz]	Marker + Dev [MHz]	Result
50	-9.77039	2500.704000	2500.703990	2569.292000	2569.292009	PASSED


Channel 21100 / 2535.0 MHz



RMS (RBW: 500 kHz, VBW: 2 MHz)

Temperature [°C]	Deviation [Hz]	Low marker [MHz]	Marker - Dev [MHz]	High marker [MHz]	Marker + Dev [MHz]	Result
20	1.95980	2500.692000	2500.691998	2569.292000	2569.292001	PASSED

Channel 21100 / 2535.0 MHz




RMS (RBW: 500 kHz, VBW: 2 MHz)

Temperature [°C]	Deviation [Hz]	Low marker [MHz]	Marker – Dev [MHz]	High marker [MHz]	Marker + Dev [MHz]	Result
-30	0.75817	2500.696000	2500.695999	2569.288000	2569.288000	PASSED

3. Frequency stability, voltage variation, (Band edge method) §2.1055(d), §27.54, (RSS-139 6.3, RSS-199 4.3, RSS-130 4.3, RSS-130 4.3 (a))

EUT with DUT number	RM-1073, DUT 18901
Accessories with DUT numbers	SD-131, DUT 18902 ; WH-108, DUT 18677
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	Measured from Antenna 1.
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	22 / 35 / 100
Date of measurements	02-Feb-2015
Measured by	Tomi Lipponen

3.1. Test Setup



3.2. Test method and limit

The measurement is made according to applicable FCC rule parts and IC standards as follows:

The EUT battery was replaced with an adjustable power supply. The frequency stability was measured at nominal voltage and at the battery cut-off point.


The results were then calculated as per section 4.3 of RSS-130.

Limits for frequency stability, voltage variation measurements

Limit
The results must be within the operating band.

3.3. LTE7 Test results


Channel 21100 / 2535.0 MHz



RMS (RBW: 500 kHz, VBW: 2 MHz)

Voltage level [V]	Deviation [Hz]	Low marker [MHz]	Marker - Dev [MHz]	High marker [MHz]	Marker + Dev [MHz]	Result
Max / 4.4	-4.10557	2500.700000	2500.699995	2569.292000	2569.292004	PASSED


Channel 21100 / 2535.0 MHz



RMS (RBW: 500 kHz, VBW: 2 MHz)

Voltage level [V]	Deviation [Hz]	Low marker [MHz]	Marker - Dev [MHz]	High marker [MHz]	Marker + Dev [MHz]	Result
Battery cut-off point / 3.4	-2.53201	2500.692000	2500.691997	2569.292000	2569.292002	PASSED

Channel 21100 / 2535.0 MHz



RMS (RBW: 500 kHz, VBW: 2 MHz)

Voltage level [V]	Deviation [Hz]	Low marker [MHz]	Marker – Dev [MHz]	High marker [MHz]	Marker + Dev [MHz]	Result
Nominal / 3.8	0.24319	2500.692000	2500.691999	2569.292000	2569.292000	PASSED

4. Test Equipment

4.1. Conducted measurements

Eq. No	Equipment	Type	Manufacturer	Used in
6039	USB Interface	5541765	Testo	22/24/27, 15C, 15B
6044	V-network	ESH3-Z6	R&S	-
2059	V-network	ESH3-Z6	R&S	-
1759	LISN 50 µH	ESH3-Z5	R&S	22/24/27, 15C, 15B
2097	Pulse Limiter	ESH3-Z2	R&S	22/24/27, 15C, 15B
1999	Receiver	ESIB26	R&S	22/24/27, 15C, 15B
2180	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
2390	Directional Coupler	DC2600	AR	-
-	RF immunity / Emission Software	EMC32	R&S	22/24/27, 15C, 15B
2060	LISN 50 µH	ESH3-Z5	R&S	15C, 15B
1759	LISN 50 µH	ESH3-Z5	R&S	15C, 15B
2039	Power Supply	PL330QMD	Thurlby	15C, 15B
6036	Data Logger	175-H2	Testo	22/24/27, 15C, 15B
2359	Temperature Test Chamber	VT4002	Vötsch	22/24/27
2352	Spectrum Analyzer	FSP-30	R&S	22/24/27, 15C
6109	Communication Tester	CMU200	R&S	22/24/27, 15C
6246	Power Supply	66332A	HP	22/24/27, 15C
1992	Signal Generator	83630B	Agilent	15C, 15B
6098	Signal Generator	8648C	Agilent	-
6046	Attenuator 10dB	8493C	Agilent	22/24/27, 15C
6047	Attenuator 20dB	8493C	Agilent	22/24/27, 15C
6045	Power splitter	11667B	Agilent	22/24/27, 15C
6247	Communication Tester	CBT	R&S	22/24/27, 15C 15B
6052	Communication Tester	CMU200	R&S	22/24/27, 15C 15B
6248	Power Supply	6632B	-	22/24/27, 15C 15B
6106	Spectrum Analyzer	FSP-30	R&S	22/24/27, 15C 15B
6113	Signal Generator	SMF100A	R&S	22/24/27, 15C 15B
6202	Temperature Test Chamber	VT4002	Vötsch	22/24/27, 15C 15B
6122	Power Splitter	11667B	Agilent	22/24/27, 15C 15B
6134	Attenuator 10dB	BW-S10-2W263+	Mini-Circuits	22/24/27, 15C
6136	Attenuator 20dB	BW-S20-2W263+	Mini-Circuits	22/24/27, 15C
6103	Bluetooth tester	CBT	R&S	22/24/27, 15C 15B
6250	Power Supply	6651A	Agilent	22/24/27, 15C 15B
6108	Communication Tester	CMU200	R&S	22/24/27, 15C 15B
6105	Spectrum Analyzer	FSV-30	R&S	22/24/27, 15C 15B
6251	Temperature Test Chamber	VT4002	Vötsch	22/24/27, 15C 15B
6243	Power Splitter	1167B	Agilent	22/24/27, 15C 15B
6245	Attenuator 10dB	BW-S10-2W263+	Mini-Circuits	22/24/27, 15C 15B
6244	Attenuator 20dB	BW-S20-2W263+	Mini-Circuits	22/24/27, 15C 15B

4.2. Radiated measurements

Eq. No	Equipment	Type	Manufacturer	Used in
2388	Bluetooth Tester	CBT	R&S	15B
10479	Communication Tester	CMW500	R&S	22/24/27, 15C, 15B
2347	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
2009	Signal Generator	SMP 22	R&S	22/24/27, 15C, 15B
2348	Controller	G-1000DXC	Yaesu	22/24/27, 15C, 15B
2349	Computer Controller	g-1000DXC	Yaesu	22/24/27, 15C, 15B
2116	Controller	EMCO 2090	ETS	22/24/27, 15C, 15B
2109	Power Supply	PL330QMD	Thurlby	22/24/27, 15C, 15B
2353	Receiver	ESIB26	R&S	22/24/27, 15C, 15B
6115	Open switch and control unit	OSP 130	R&S	22/24/27, 15C 15B
6116	Open switch and control unit	OSP 150	R&S	22/24/27, 15C 15B
6117	Open switch and control unit	OSP 150	R&S	22/24/27, 15C 15B
6131	Notch Filter	WRCT902.4-0.4/40-8SS	Wainwright	22/24/27, 15C 15B
6130	Notch Filter	WRCD1880-1.1.25/50-10SS	Wainwright	22/24/27
6159	Band Reject Filter	WRCD1747.8-0.4/40-5SS	Wainwright	22/24/27, 15C, 15B
6158	Band Reject Filter	WRCT836.6-0.4/40-8SS	Wainwright	22/24/27, 15C, 15B
6197	Band Reject Filter	WRCJV2531/2539-2523/2547-60/12SS	Wainwright	22/24/27, 15C, 15B
2231	Band Reject Filter	WRCG1947/1953-1940/1960-40/6SS	Wainwright	22/24/27, 15C, 15B
2391	Band Reject Filter	WRCG1729.4/1735.4-1722.4/1742.4-40/6SS	Wainwright	27
2386	Band Reject Filter	WRCG1764.4/1770.4-1760.4/1774.4-40/6SS	Wainwright	22/24/27, 15C, 15B
2385	Band Reject Filter	WRCG1744.4/1750.4-1740.4/1754.4-40/6SS	Wainwright	22/24/27, 15C, 15B
2357	Band Reject Filter	WRCG2400/2483-2390/2493-35/10SS	Wainwright	15C
2188	Preamplifier	AFS4-00100300-20-23P-6	Miteq	22/24/27, 15C, 15B
6195	High Pass Filter	-	Wainwright	22/24/27, 15C, 15B
2364	Band Reject Filter	WRCG1877/1883 - 1870/1890-40/6SS	Wainwright	24
2361	Anechoic Chamber	3 m Semi / Full Anechoic Chamber	Euroshield	22/24/27, 15C, 15B
6212	Antenna Array system	-	TCC	22/24/27, 15C, 15B
-	RF immunity / Emission Software	EMC32	R&S	22/24/27, 15C, 15B
6089	Antenna	HFH2-Z2	R&S	15C, 15B
2027	CDN	M2 (modified) DC1	MEB	22/24/27, 15C, 15B
2028	CDN	M3 (modified) DC2	MEB	22/24/27, 15C, 15B
2176	CDN	CDN 801-M3	Lüthi	22/24/27, 15C, 15B
2135	CDN	CDN 801-M3	Lüthi	22/24/27, 15C, 15B
2029	Power Supply	PL330	Thurlby	22/24/27, 15C
6038	Data Logger	Testo 580	Testo	22/24/27, 15C, 15B
6037	Data Logger	175-H2	Testo	22/24/27, 15C, 15B
6039	USB Interface	5541765	Testo	22/24/27, 15C, 15B