



REPORT No. : SZ14090074W04

FCC RF TEST REPORT

APPLICANT : Motic China Group Co., Ltd
PRODUCT NAME : Moticam S2 Smart Camera
MODEL NAME : Moticam S2
TRADE NAME : Motic
BRAND NAME : Motic
FCC ID : PVEMOTICAMS2
STANDARD(S) : 47 CFR Part 15 Subpart C
ISSUE DATE : 2014-10-23



SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB GROUP

FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen , Guangdong Province, P. R. China

Tel: 86-755-36698555
[Http://www.morlab.com](http://www.morlab.com)

Fax: 86-755-36698525
E-mail: service@morlab.cn



DIRECTORY

TEST REPORT DECLARATION	5
1. TECHNICAL INFORMATION.....	6
1.1. APPLICANT INFORMATION.....	6
1.2. EQUIPMENT UNDER TEST (EUT) DESCRIPTION.....	6
1.2.1. IDENTIFICATION OF ALL USED EUTS	7
1.3. TEST STANDARDS AND RESULTS.....	7
1.3.1. TEST ENVIRONMENT CONDITIONS.....	8
2. 47 CFR PART 15C REQUIREMENTS	9
2.1. ANTENNA REQUIREMENT	9
2.1.1. APPLICABLE STANDARD	9
2.1.2. RESULT: COMPLIANT.....	9
2.2. PEAK OUTPUT POWER	9
2.2.1. REQUIREMENT	9
2.2.2. TEST DESCRIPTION	9
2.2.3. TEST RESULT	11
2.2.3.1. 802.11B TEST MODE	11
2.2.3.2. 802.11G TEST MODE	11
2.2.3.3. 802.11N-20MHZ TEST MODE	11
2.2.3.4. 802.11N-40MHZ TEST MODE	12
2.3. BANDWIDTH.....	13
2.3.1. REQUIREMENT	13
2.3.2. TEST DESCRIPTION	13
2.3.3. TEST RESULT	13
2.3.3.1. 802.11B TEST MODE.....	14
2.3.3.2. 802.11G TEST MODE	16
2.3.3.3. 802.11N-20 TEST MODE.....	18
2.3.3.4. 802.11N-40 TEST MODE.....	20
2.4. CONDUCTED SPURIOUS EMISSIONS AND BAND EDGE	22
2.4.1. REQUIREMENT	22
2.4.2. TEST DESCRIPTION	22
2.4.3. TEST RESULT	22



2.4.3.1. 802.11B TEST MODE.....	23
2.4.3.2. 802.11G TEST MODE	26
2.4.3.3. 802.11N -20MHZ TEST MODE.....	29
2.4.3.4. 802.11N -40MHZ TEST MODE.....	32
2.5. POWER SPECTRAL DENSITY (PSD).....	35
2.5.1. REQUIREMENT	35
2.5.2. TEST DESCRIPTION	35
2.5.3. TEST RESULT	36
2.5.3.1. 802.11B TEST MODE.....	36
2.5.3.2. 802.11G TEST MODE	38
2.5.3.3. 802.11N-20MHZ TEST MODE	40
2.5.3.4. 802.11N-40MHZ TEST MODE	42
2.6. RESTRICTED FREQUENCY BANDS	44
2.6.1. REQUIREMENT	44
2.6.2. TEST DESCRIPTION	44
2.6.3. TEST RESULT	45
2.6.3.1. 802.11B TEST MODE.....	45
2.6.3.2. 802.11G TEST MODE	48
2.6.3.3. 802.11N-20MHZ TEST MODE	50
2.6.3.4. 802.11N-40MHZ TEST MODE	53
2.7. CONDUCTED EMISSION.....	55
2.7.1. REQUIREMENT	55
2.7.2. TEST DESCRIPTION	56
2.7.3. TEST RESULT	56
2.8. RADIATED EMISSION.....	59
2.8.1. REQUIREMENT	59
2.8.2. TEST DESCRIPTION	59
2.8.3. TEST RESULT	62
2.8.3.1. 802.11B TEST MODE.....	62
2.8.3.2. 802.11G TEST MODE	69
2.8.3.3. 802.11N-20MHZ TEST MODE	75
2.8.3.4. 802.11N-40MHZ TEST MODE	81
<u>ANNEX A GENERAL INFORMATION</u>	<u>87</u>
1.1 IDENTIFICATION OF THE RESPONSIBLE TESTING LABORATORY	87
1.2 IDENTIFICATION OF THE RESPONSIBLE TESTING LOCATION.....	87
1.3 FACILITIES AND ACCREDITATIONS.....	87



1.4	TEST EQUIPMENTS UTILIZED	88
1.4.1	CONDUCTED TEST EQUIPMENTS	88
1.4.2	CONDUCTED EMISSION TEST EQUIPMENTS	88
1.4.3	RADIATED TEST EQUIPMENTS	88
1.4.4	CLIMATE CHAMBER	89
1.4.5	VIBRATION TABLE	89
1.4.6	ANECHOIC CHAMBER	89

Change History

Issue	Date	Reason for change
1.0	2014-10-23	First edition



REPORT No. : SZ14090074W04

Test Report Declaration

Applicant	Motic China Group Co., Ltd
Applicant Address	MOTIC BLDG, TORCH HI-TECH INDUSTRIAL DEV ZONE XIAMEN FUJIAN; 361006;CN
Manufacturer	Motic China Group Co., Ltd
Manufacturer Address	MOTIC BLDG, TORCH HI-TECH INDUSTRIAL DEV ZONE XIAMEN FUJIAN; 361006;CN
Product Name	Moticam S2 Smart Camera
Model Name	Moticam S2
Brand Name	Motic
HW Version	1.0.0.0
SW Version	4.2.2.0
Test Standards	47 CFR Part 15 Subpart C
Test Date	2014-09-17 to 2014-09-29
Test Result	PASS

Tested by : Nie Quan
Nie Quan

Reviewed by : Qiu Xiaojun
Qiu Xiaojun

Approved by : Zeng Dexin
Zeng Dexin



1. Technical Information

Note: Provide by applicant.

1.1. Applicant Information

Company:	Motic China Group Co., Ltd
Address:	MOTIC BLDG, TORCH HI-TECH INDUSTRIAL DEV ZONE XIAMEN FUJIAN; 361006;CN

1.2. Equipment under Test (EUT) Description

Brand Name:	Moticam S2 Smart Camera
Trade Name:	Motic
Model Name:	Motic
Frequency Range:	802.11b/g/n-20MHz: 2.412GHz - 2.462GHz 802.11n-40MHz: 2.422GHz - 2.452GHz
Channel Number:	802.11b/g/n-20MHz: 11 802.11n-40MHz: 7
Modulation Type:	DSSS, OFDM
Antenna Type:	PIFA Antenna
Antenna Gain:	1.21dBi

NOTE:

The EUT is a Moticam S2 Smart Camera, it contains WIFI Module operating at 2.4GHz ISM; it supports 802.11b, 802.11g, 802.11n and they are all tested in this report.

For 802.11b/g/n-20MHz (2.4GHz band), the frequencies allocated is $F \text{ (MHz)} = 2412 + 5 \cdot (n-1)$ ($1 \leq n \leq 11$). The lowest, middle, highest channel numbers of the EUT used and tested in this report are separately 1 (2412MHz), 6 (2437MHz) and 11 (2462MHz).

For 802.11n-40MHz, the frequencies allocated is $F \text{ (MHz)} = 2412 + 5 \cdot (n-1)$ ($3 \leq n \leq 9$). The lowest, middle, highest channel numbers of the EUT used and tested in this report are separately 3 (2422MHz), 6 (2437MHz) and 9 (2452MHz).

For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

The antenna connector of EUT is designed with permanent attachment and no consideration of replacement.



1.2.1. Identification of all used EUTs

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version
A01	V1.0	V1

1.3. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C (Bluetooth, 2.4GHz ISM band radiators) for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15 (10-1-13 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Result
1	15.203	Antenna Requirement	<u>PASS</u>
2	15.247(b)	Peak Output Power	<u>PASS</u>
3	15.247(a)	Bandwidth	<u>PASS</u>
4	15.247(d)	Conducted Spurious Emission and Band Edge	<u>PASS</u>
5	15.247(d)	Restricted Frequency Bands	<u>PASS</u>
6	15.207	Conducted Emission	<u>PASS</u>
7	15.209 ,15.247(d)	Radiated Emission	<u>PASS</u>
8	15.247(e)	Power spectral density (PSD)	<u>PASS</u>
9	15.247(i),1.1307& 2.1093	RF exposure evaluation	<u>PASS</u>

The tests of Conducted Emission and Radiated Emission were performed according to the method of measurements prescribed in ANSI C63.4 2009.

These RF tests were performed according to the method of measurements prescribed in KDB558074 D01 v03r01 (04/09/2013).



REPORT No. : SZ14090074W04

1.3.1. Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 -60
Atmospheric Pressure (kPa):	86-106



2. 47 CFR PART 15C REQUIREMENTS

2.1. Antenna requirement

2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

2.1.2. Result: Compliant

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

2.2. Peak Output Power

2.2.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

2.2.2. Test Description


KDB 558074 Section 9.1.3 was used in order to prove compliance.

The measured output power was calculated by the reading of the Power Meter and calibration.

A. Test Setup:



REPORT No. : SZ14090074W04



The EUT (Equipment under the test) which is powered by the Battery is coupled to the Power Meter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading, all test result in power meter.

**B. Equipments List:**

Please reference ANNEX A(1.4).

2.2.3. Test Result

The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

2.2.3.1. 802.11b Test Mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	13.36	0.021677	30	1	PASS
6	2437	13.01	0.019999			PASS
11	2462	12.62	0.01828			PASS

2.2.3.2. 802.11g Test mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	15.76	0.03767	30	1	PASS
6	2437	15.49	0.0354			PASS
11	2462	15.00	0.03162			PASS

2.2.3.3. 802.11n-20MHz Test mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	15.90	0.038905	30	1	PASS
6	2437	15.95	0.039355			PASS
11	2462	14.94	0.031189			PASS



REPORT No. : SZ14090074W04

2.2.3.4. 802.11n-40MHz Test mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
3	2422	16.20	0.041687	30	1	PASS
6	2437	15.92	0.039084			PASS
9	2452	15.67	0.03690			PASS


2.3. Bandwidth

2.3.1. Requirement

According to FCC section 15.247(a) (2), Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

2.3.2. Test Description

A. Test Set:



The EUT which is powered by the Battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

KDB 558074 Section 8.1 Option 1 was used in order to prove compliance.

B. Equipments List:

Please reference ANNEX A(1.4).

2.3.3. Test Result

The lowest, middle and highest channels are selected to perform testing to record the 6 dB bandwidth of the Module.




2.3.3.1. 802.11b Test mode

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits(kHz)	Result
1	2412	14.9041	≥500	PASS
6	2437	14.8928	≥500	PASS
11	2462	14.9012	≥500	PASS


B. Test Plots




(Channel 1: 2412MHz @ 802.11b)



REPORT No. : SZ14090074W04



(Channel 6: 2437 MHz @ 802.11b)



(Channel 11: 2462MHz @ 802.11b)




2.3.3.2. 802.11g Test mode

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
1	2412	16.4232	≥ 500	PASS
6	2437	16.4189	≥ 500	PASS
11	2462	16.4083	≥ 500	PASS


B. Test Plots:




(Channel 1: 2412MHz @ 802.11g)



REPORT No. : SZ14090074W04



(Channel 6: 2437MHz @ 802.11g)



(Channel 11: 2462MHz @ 802.11g)




REPORT No. : SZ14090074W04

2.3.3.3. 802.11n-20 Test mode

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
1	2412	17.6289	≥500	PASS
6	2437	17.6377	≥500	PASS
11	2462	17.6195	≥500	PASS


B. Test Plots:




(Channel 1: 2412MHz @ 802.11n-20)



REPORT No. : SZ14090074W04



(Channel 6: 2437MHz @ 802.11n-20)



(Channel 11: 2462MHz @ 802.11n-20)




2.3.3.4. 802.11n-40 Test mode

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
3	2422	35.9281	≥500	PASS
6	2437	35.9467	≥500	PASS
9	2452	35.9319	≥500	PASS


B. Test Plots:




(Channel 3: 2422MHz @ 802.11n-40)



REPORT No. : SZ14090074W04



(Channel 6: 2437MHz @ 802.11n-40)



(Channel 9: 2452MHz @ 802.11n-40)


2.4. Conducted Spurious Emissions and Band Edge

2.4.1. Requirement

According to FCC section 15.247(c), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

2.4.2. Test Description

A. Test Set:



The EUT which is powered by the Battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

KDB 558074 Section 11.0 was used in order to prove compliance.

B. Equipments List:

Please reference ANNEX A(1.4).

2.4.3. Test Result

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions.




2.4.3.1. 802.11b Test mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-38.76	1.059	-18.941	PASS
6	2437	-39.79	0.645	-19.355	PASS
11	2462	-41.04	0.367	-19.633	PASS

B. Test Plots:


Note: the power of the Module transmitting frequency should be ignored.




(Channel = 1, 30MHz to 25GHz)



REPORT No. : SZ14090074W04




(Band Edge @ Channel = 1)




(Channel = 6, 30MHz to 25GHz)



REPORT No. : SZ14090074W04



(Channel = 11, 30MHz to 25GHz)



(Band Edge @ Channel = 11)




2.4.3.2. 802.11g Test mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-47.86	-3.152	-23.152	PASS
6	2437	-48.08	-3.881	-23.881	PASS
11	2462	-48.91	-3.975	-23.975	PASS

B. Test Plots:


Note: the power of the Module transmitting frequency should be ignored.




(Channel = 1, 30MHz to 25GHz)



REPORT No. : SZ14090074W04




(Band Edge @ Channel = 1)




(Channel = 6, 30MHz to 25GHz)



REPORT No. : SZ14090074W04



(Channel = 11, 30MHz to 25GHz)



(Band Edge @ Channel = 11)




2.4.3.3. 802.11n -20MHz Test mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-48.46	-3.465	-23.465	PASS
6	2437	-47.81	-4.339	-24.339	PASS
11	2462	-49.65	-4.957	-24.957	PASS

B. Test Plots:


Note: the power of the Module transmitting frequency should be ignored.




(Channel = 1, 30MHz to 25GHz)



REPORT No. : SZ14090074W04




(Band Edge @ Channel = 1)




(Channel = 6, 30MHz to 25GHz)



REPORT No. : SZ14090074W04



(Channel = 11, 30MHz to 25GHz)



(Band Edge @ Channel = 11)




2.4.3.4. 802.11n -40MHz Test mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
3	2422	-49.42	-5.812	-25.812	PASS
6	2437	-48.79	-6.685	-26.685	PASS
9	2452	-50.84	-6.794	-26.794	PASS

B. Test Plots:


Note: the power of the Module transmitting frequency should be ignored.




(Channel = 3, 30MHz to 25GHz)



REPORT No. : SZ14090074W04




(Band Edge @ Channel = 3)




(Channel = 6, 30MHz to 25GHz)



REPORT No. : SZ14090074W04



(Channel = 9, 30MHz to 25GHz)



(Band Edge @ Channel = 9)


2.5. Power spectral density (PSD)

2.5.1. Requirement

According to FCC section 15.247(e), the same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

2.5.2. Test Description

A. Test Set:



The EUT which is powered by the Battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

KDB 558074 Section 10.2 was used in order to prove compliance.

B. Equipments List:

Please reference ANNEX A(1.4).




2.5.3. Test Result

2.5.3.1. 802.11b Test mode

A. Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	2412	-17.92	8	PASS
6	2437	-17.88	8	PASS
11	2462	-18.33	8	PASS
Measurement uncertainty: ± 1.3 dB				


B. Test Plots:




(Channel = 1 @ 802.11b)



REPORT No. : SZ14090074W04



(Channel = 6 @ 802.11b)



(Channel = 11 @ 802.11b)



REPORT No. : SZ14090074W04


2.5.3.2. 802.11g Test mode

A. Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	2412	-17.13	8	PASS
6	2437	-17.53	8	PASS
11	2462	-17.78	8	PASS

Measurement uncertainty: ± 1.3 dB


B. Test Plots:




(Channel = 1 @ 802.11g)



REPORT No. : SZ14090074W04



(Channel = 6 @ 802.11g)



(Channel = 11 @ 802.11g)




2.5.3.3. 802.11n-20MHz Test mode

A. Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	2412	-16.81	8	PASS
6	2437	-16.59	8	PASS
11	2462	-17.29	8	PASS
Measurement uncertainty: ± 1.3 dB				


B. Test Plots:




(Channel = 1 @ 802.11n-20MHz)



REPORT No. : SZ14090074W04



(Channel = 6 @ 802.11n-20MHz)



(Channel = 11 @ 802.11n-20MHz)




2.5.3.4. 802.11n-40MHz Test mode

A. Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
3	2422	-18.42	8	PASS
6	2437	-18.36	8	PASS
9	2452	-17.98	8	PASS
Measurement uncertainty: ± 1.3 dB				


B. Test Plots:




(Channel = 3 @ 802.11n-40MHz)



REPORT No. : SZ14090074W04



(Channel = 6 @ 802.11n-40MHz)



(Channel = 9 @ 802.11n-40MHz)


2.6. Restricted Frequency Bands

2.6.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

2.6.2. Test Description

A. Test Setup



The Module is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the



ground to determine the maximum value of the field strength.

KDB 558074 Section 12.1 was used in order to prove compliance.

B. Equipments List:

Please reference ANNEX A(1.4).

2.6.3. Test Result

The lowest and highest channels are tested to verify Restricted Frequency Bands.

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

Note: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (vertical) was recorded in this test report.

2.6.3.1. 802.11b Test mode


The lowest and highest channels are tested to verify the band edge emissions.

A. Test Verdict:


Channel	Frequency (MHz)	Detector	Receiver Reading UR (dBuV)	AT (dB)	AFactor (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
1	2339.76	PK	47.62	-33.63	32.56	46.55	74	Pass
1	2357.68	AV	35.86	-33.63	32.56	34.79	54	Pass
11	2484.14	PK	47.32	-33.18	32.5	46.64	74	Pass
11	2493.64	AV	37.28	-33.18	32.5	36.6	54	Pass



B. Test Plots:




(Plot A1: Channel = 1 PEAK @ 802.11b)




(Plot A2: Channel = 1 AVG @ 802.11b)



REPORT No. : SZ14090074W04



(Plot B1: Channel = 11 PEAK @ 802.11b)



(Plot B2: Channel = 11 AVG @ 802.11b)



REPORT No. : SZ14090074W04


2.6.3.2. 802.11g Test mode

The lowest and highest channels are tested to verify the band edge emissions.

A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading UR (dBuV)	AT (dB)	AFactor (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
1	2370.00	PK	44.78	-33.63	32.56	43.71	74	Pass
1	2387.64	AV	35.31	-33.63	32.56	34.24	54	Pass
11	2496.39	PK	49.29	-33.18	32.5	48.61	74	Pass
11	2484.04	AV	38.57	-33.18	32.5	37.89	54	Pass


B. Test Plots:




(Plot C1: Channel = 1 PEAK @ 802.11g)



REPORT No. : SZ14090074W04




(Plot C2: Channel = 1 AVG @ 802.11g)



(Plot D1: Channel = 11 PEAK @ 802.11g)



REPORT No. : SZ14090074W04



(Plot D2: Channel = 11 AVG @ 802.11g)


2.6.3.3. 802.11n-20MHz Test mode

The lowest and highest channels are tested to verify the band edge emissions.


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading UR (dBuV)	AT (dB)	AFactor (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
1	2365.52	PK	46.57	-33.63	32.56	45.5	74	Pass
1	2389.99	AV	36.93	-33.63	32.56	35.86	54	Pass
11	2485.75	PK	49.11	-33.18	32.5	48.43	74	Pass
11	2486.42	AV	38.26	-33.18	32.5	37.58	54	Pass

B. Test Plots:




(Plot E1: Channel = 1 PEAK @ 802.11n-20)




(Plot E2: Channel = 1 AVG @ 802.11n-20)



REPORT No. : SZ14090074W04



(Plot F1: Channel = 11 PEAK @ 802.11n-20)



(Plot F2: Channel = 11 AVG @ 802.11n-20)




2.6.3.4. 802.11n-40MHz Test mode

The lowest and highest channels are tested to verify the band edge emissions.

A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading UR (dBuV)	AT (dB)	AFactor (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
3	2387.92	PK	48.6	-33.63	32.56	47.53	74	Pass
3	2385.68	AV	37.66	-33.63	32.56	36.59	54	Pass
9	2484.04	PK	59.01	-33.18	32.5	58.33	74	Pass
9	2486.23	AV	39.13	-33.18	32.5	38.45	54	Pass


B. Test Plots:




(Plot E1: Channel = 3 PEAK @ 802.11n-40)




REPORT No. : SZ14090074W04



(Plot E2: Channel = 3 AVG @ 802.11n-40)



(Plot F1: Channel = 9 PEAK @ 802.11n-40)



(Plot F2: Channel = 9 AVG @ 802.11n-40)

2.7. Conducted Emission

2.7.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50μH/50Ω line impedance stabilization network (LISN).


Frequency (MHz)	range	Conducted Limit (dBμV)	
		Quai-peak	Average
0.15 - 0.50		66 to 56	56 to 46
0.50 - 5		56	46
5 - 30		60	50

NOTE:

- The lower limit shall apply at the band edges.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

2.7.2. Test Description

A. Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.4:2009

The EUT is powered by the Battery charged with the AC Adapter which is powered by 120V, 60Hz AC mains supply.

B. Equipments List:

Please reference ANNEX A(1.4).

2.7.3. Test Result

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Note: All test modes are performed, only the worst case is recorded in this report.




REPORT No. : SZ14090074W04

A. Test setup:


The EUT configuration of the emission tests is EUT + Link.



B. Test Plots:



(Plot A: L Phase)



(Plot B: N Phase)



2.8. Radiated Emission

2.8.1. Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:


1. For Above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
2. For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK)

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table)


2.8.2. Test Description

A. Test Setup:


- 1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz



The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.4 (2009). The EUT was set-up on insulator 80cm above the Ground Plane. The set-up and test methods were according to ANSI C63.4.

The EUT of the EUT is powered by the Battery charged with the AC Adapter which is powered by 120V, 60Hz AC mains supply. The Module is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading. During the measurement, the EUT is activated and controlled by the Wireless Router via a Common Antenna, and is set to operate under hopping-on test mode.

For the Test Antenna:

- In the frequency range of 9kHz to 30MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 2GHz) and Horn Test Antenna (above 2GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

**B. Equipments List:**

Please reference ANNEX A(1.4).

2.8.3. Test Result

According to ANSI C63.4 selection 4.2.2, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak limit, it is unnecessary to perform an quasi-peak measurement.

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.


Note: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

The low frequency, which started from 9KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

2.8.3.1. 802.11b Test mode**A. Test Plots for the Whole Measurement Frequency Range:**




Plots for Channel = 1



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
192.070	35.59	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
317.855	39.69	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
380.748	41.95	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
603.292	47.93	45.34	N.A	N.A	46.0	N.A	Horizontal	PASS
2412.000	59.67	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
13917.706	46.21	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
34.838	30.88	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
63.865	28.26	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
170.299	19.43	N.A	N.A	N.A	43.5	N.A	Vertical	PASS
412.195	38.91	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2412.000	57.48	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
13917.706	45.68	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)




REPORT No. : SZ14090074W04

Plot for Channel = 6



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
37.257	25.38	N.A	N.A	N.A	40.0	N.A	Horizontal	PASS
163.042	24.37	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
380.748	36.28	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
700.050	38.20	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2437.000	59.82	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
13917.706	46.89	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
34.838	27.21	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
63.865	22.41	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
317.855	27.72	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
540.399	30.91	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2437.000	60.37	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
13917.706	47.26	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)




Plot for Channel = 11



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
37.257	23.97	N.A	N.A	N.A	40.0	N.A	Horizontal	PASS
163.042	24.47	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
380.748	37.38	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
697.631	37.39	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2462.000	62.67	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
18197.007	46.38	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
34.838	30.82	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
63.865	22.44	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
155.786	20.06	N.A	N.A	N.A	43.5	N.A	Vertical	PASS
591.197	31.01	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2462.000	60.78	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
16825.436	45.59	N.A	N.A	74.0	N.A	54.0	Vertical	PASS


(Antenna Vertical, 30MHz to 25GHz)



2.8.3.2. 802.11g Test mode


A. Test Plots for the Whole Measurement Frequency Range:

Plots for Channel = 1



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
192.070	33.65	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
317.855	42.85	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
571.845	42.68	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
666.185	44.84	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2412.000	59.51	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
13917.706	46.50	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
39.676	23.36	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
63.865	22.91	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
167.880	19.56	N.A	N.A	N.A	43.5	N.A	Vertical	PASS
446.060	28.06	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2412.000	58.89	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
13917.706	48.79	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)




Plot for Channel = 6




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
34.838	26.45	N.A	N.A	N.A	40.0	N.A	Horizontal	PASS
163.042	24.73	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
380.748	37.09	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
700.050	38.05	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2437.000	61.28	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
13917.706	47.87	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
34.838	29.75	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
170.299	20.70	N.A	N.A	N.A	43.5	N.A	Vertical	PASS
380.748	29.22	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
1254.364	40.45	N.A	N.A	54.0	N.A	54.0	Vertical	PASS
2437.000	61.56	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
13917.706	46.12	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 11

Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
34.838	22.40	N.A	N.A	N.A	40.0	N.A	Horizontal	PASS
61.446	20.07	N.A	N.A	N.A	40.0	N.A	Horizontal	PASS
380.748	36.17	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
700.050	37.97	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2462.000	61.80	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
18197.007	46.42	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
63.865	21.88	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
160.623	20.89	N.A	N.A	N.A	43.5	N.A	Vertical	PASS
317.855	29.28	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
1259.352	38.33	N.A	N.A	54.0	N.A	54.0	Vertical	PASS
2462.000	59.29	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
13588.529	45.00	N.A	N.A	74.0	N.A	54.0	Vertical	PASS


(Antenna Vertical, 30MHz to 25GHz)



2.8.3.3. 802.11n-20MHz Test mode


A. Test Plots for the Whole Measurement Frequency Range:

Plots for Channel = 1



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
39.676	30.58	N.A	N.A	N.A	40.0	N.A	Horizontal	PASS
192.070	34.11	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
317.855	43.06	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
446.060	38.26	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
571.845	42.69	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2412.000	58.91	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A


(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
39.676	28.62	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
63.865	22.79	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
167.880	19.90	N.A	N.A	N.A	43.5	N.A	Vertical	PASS
446.060	30.05	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2412.000	57.35	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
13917.706	47.12	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 6




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
37.257	25.45	N.A	N.A	N.A	40.0	N.A	Horizontal	PASS
158.204	24.10	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
317.855	36.11	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
700.050	38.09	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2437.000	60.79	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
13917.706	46.05	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




REPORT No. : SZ14090074W04




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
34.838	26.85	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
150.948	20.68	N.A	N.A	N.A	43.5	N.A	Vertical	PASS
380.748	29.68	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
508.953	31.99	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2437.000	60.72	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
16825.436	47.24	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 11

Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
83.217	22.22	N.A	N.A	N.A	40.0	N.A	Horizontal	PASS
163.042	24.76	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
380.748	35.62	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
700.050	38.68	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2462.000	61.28	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
13039.900	45.06	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
34.838	28.27	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
63.865	22.59	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
317.855	29.37	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
1109.726	37.66	N.A	N.A	54.0	N.A	54.0	Vertical	PASS
2462.000	60.93	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
16825.436	45.40	N.A	N.A	74.0	N.A	54.0	Vertical	PASS


(Antenna Vertical, 30MHz to 25GHz)



2.8.3.4. 802.11n-40MHz Test mode


A. Test Plots for the Whole Measurement Frequency Range:

Plots for Channel = 3



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
88.055	19.76	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
160.623	25.31	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
317.855	36.82	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
700.050	38.76	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2422.000	60.69	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
13917.706	47.77	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS


(Plot A.2: Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
39.676	27.68	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
63.865	22.16	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
317.855	28.89	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
600.873	31.29	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2422.000	59.98	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
13917.706	46.66	N.A	N.A	74.0	N.A	54.0	Vertical	PASS


(Plot A.3: Antenna Vertical, 30MHz to 25GHz)

Plots for Channel = 6



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
34.838	26.23	N.A	N.A	N.A	40.0	N.A	Horizontal	PASS
88.055	20.98	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
380.748	36.10	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
700.050	37.10	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2437.000	60.41	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
13917.706	47.20	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS


(Plot B.2: Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
34.838	29.96	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
63.865	22.34	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
158.204	20.88	N.A	N.A	N.A	43.5	N.A	Vertical	PASS
317.855	27.28	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2437.000	62.94	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
13917.706	46.19	N.A	N.A	74.0	N.A	54.0	Vertical	PASS


(Plot B.3: Antenna Vertical, 30MHz to 25GHz)

Plots for Channel = 9



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
37.257	25.27	N.A	N.A	N.A	40.0	N.A	Horizontal	PASS
83.217	21.86	N.A	N.A	N.A	40.0	N.A	Horizontal	PASS
317.855	35.56	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
700.050	37.92	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2452.000	63.40	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
18197.007	46.77	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Plot C.2: Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
63.865	23.20	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
148.529	20.77	N.A	N.A	N.A	43.5	N.A	Vertical	PASS
317.855	29.04	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
1229.426	38.58	N.A	N.A	54.0	N.A	54.0	Vertical	PASS
2452.000	61.10	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
13039.900	46.01	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot C.3: Antenna Vertical, 30MHz to 25GHz)



Annex A General Information

1.1 Identification of the Responsible Testing Laboratory

Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Department:	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Responsible Test Lab Manager:	Mr. Su Feng
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

1.2 Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

1.3 Facilities and Accreditations

Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L3572.

All measurement facilities used to collect the measurement data are located at FL.1, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10 2009, ANSI C63.4 2009 and CISPR Publication 22; the FCC registration number is 695796.

The IC registration number is 7183A-2.



REPORT No. : SZ14090074W04

1.4 Test Equipments Utilized

1.4.1 Conducted Test Equipments

Conducted Test Equipment						
No	Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
1	Spectrum Analyzer	US44210471	E7405A	Agilent	2014.02.26	2015.02.25
2	Power Splitter	NW521	1506A	Weinschel	2014.02.26	2015.02.25
3	Attenuator 1	(n.a.)	10dB	Resnet	2014.02.26	2015.02.25
4	Attenuator 2	(n.a.)	3dB	Resnet	2014.02.26	2015.02.25
5	USB Wideband Power Sensor	MY52280010	U2021XA	Agilent	2014.02.26	2015.02.25
6	EXA Signal Analyzer	MY51440152	N9010A	Agilent	2014.02.26	2015.02.25

1.4.2 Conducted Emission Test Equipments

Conducted Emission Test Equipments						
No	Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
1	Receiver	US44210471	E7405A	Agilent	2014.02.26	2015.02.25
2	LISN	812744	NSLK 8127	Schwarzbeck	2014.02.26	2015.02.25
3	Service Supplier	100448	CMU200	R&S	2014.02.26	2015.02.25
4	Pulse Limiter (20dB)	9391	VTSD 9561-D	Schwarzbeck	2014.02.26	2015.02.25

1.4.3 Radiated Test Equipments

Radiated Test Equipments						
No	Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal.Due Date
1	System Simulator	100448	CMU200	R&S	2014.02.26	2015.02.25
2	Receiver	US44210471	E7405A	Agilent	2014.02.26	2015.02.25
3	Test Antenna -	9163-274	9m*6m*6m	Albatross	2014.02.26	2015.02.25



REPORT No. : SZ14090074W04

	Bi-Log					
4	Test Antenna - Horn	9120D-963	VULB 9163	Schwarzbeck	2014.02.26	2015.02.25
5	Test Antenna - Horn	71688	BBHA 9120D	Schwarzbeck	2014.02.26	2015.02.25
6	Test Antenna - Loop	1519-022	HL050S7	R&S	2014.02.26	2015.02.25

1.4.4 Climate Chamber

Climate Chamber

No.	Equipment Name	Serial No.	Type	Manufacturer	Cal.Date	Cal.Due Date
1	Climate Chamber	2004012	HL4003T	Yinhe	2014.02.26	2015.02.25

1.4.5 Vibration Table

Vibration Table

No.	Equipment Name	Serial No.	Type	Manufacturer	Cal.Date	Cal.Due Date
1	Vibration Table	N/A	ACT2000-S015L	CMI-COM	2014.02.26	2015.02.25

1.4.6 Anechoic Chamber

Anechoic Chamber

No.	Equipment Name	Serial No.	Type	Manufacturer	Cal.Date	Cal.Due Date
1	Anechoic Chamber	N/A	9m*6m*6m	Albatross	2014.02.26	2015.02.25

***** END OF REPORT *****