

## RF Exposure Evaluation Report

**Client:** Garmin International Inc.

**Address:** 1200 E. 151st Street  
Olathe, Kansas 66062 USA

**EUT:** A04868

**Test Report No.:** RFE230919-20-M1 Rev: 0

**Approved By:**   
Fox Lane,  
EMC Test Engineer

**Date:** December 12, 2023

**Total Pages:** 7

*The Nebraska Center for Excellence in Electronics (NCEE) authorizes the above-named company to reproduce this report provided it is reproduced in its entirety for use by the company's employees only. Any use that a third party makes of this report, or any reliance on or decisions made based on it, are the responsibility of such third parties. NCEE accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. This report applies only to the items tested.*

## Revision Page

Rev. No.	Date	Description
0	12 December 2023	Issued by FLane Prepared by FLane

# 1 Regulatory Requirements:

FCC Part 1.1310, 2.1091, 2.1093  
KDB 447498 D01  
RSS-102, Issue 5

## **Summary:**

The purpose of this report is to evaluate the EUT's transmitter for exemption from routine SAR testing.

## **EUT:**

Model:	<b>A04868</b>
FCC ID:	<b>IPH-04868</b>
IC:	<b>1792A-04868</b>

MPE Lab	Nebraska Center for Excellence in Electronics
MPE Labs FCC Cab Designation:	US1060
MPE Labs ISED Cab Designation:	US0177

## 2 FCC Limits, Part 1.1310

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

Occupational/Controlled	<input type="checkbox"/>
General Population/uncontrolled	<input checked="" type="checkbox"/>

FCC Power Density Calculations								
Frequency	Conducted Power	Antenna Gain	Peak Power EIRP	Peak Power EIRP +25% for Tolerance	Power Density	Limit at specified distance	% of limit	Result
MHz	mW	numerical	mW	mW	mW/cm <sup>2</sup>	mW/cm <sup>2</sup>	%	
2412.00	21.33	2.72	57.94	72.43	0.014	1.00	1.441	PASS
2437.00	93.11	2.72	252.93	316.16	0.063	1.00	6.290	PASS
2462.00	22.12	2.72	60.09	75.11	0.015	1.00	1.494	PASS

Distance (d)	20	cm
--------------	----	----

**Result:**  
**Complies**

**Note:**

The user's manual will stipulate that a 20cm distance from the user is to be maintained.  
EIRP values in mW were multiplied by 1.1 to account for a 10% tolerance.

### 3 ISED Limits, RSS 102

#### April 2021 TCB Workshop Training

## Canada's new localized limits > 6 GHz

- February 2021, Health Canada introduced new localized (basic restrictions and reference levels) PD limits
  - < 30 GHz → harmonized w/ ICNIRP-2020 (averaged over 4-cm<sup>2</sup>)
  - > 30 GHz → spatial peak instead 1 cm<sup>2</sup> average
- New limits are now in effect

#### RSS 102, Issue 5, Section 2.5.2

##### 2.5.2 Exemption Limits for Routine Evaluation – RF Exposure Evaluation

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz<sup>6</sup> and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $4.49/f^{0.5}$  W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834}$  W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

ISED Power Density Calculations						
Frequency	Conducted Power	Antenna Gain	Peak EIRP Power	EIRP +25% Tolerance	Exemption Limit	Result
MHz	mW	Num.	mW	mW	mW	
2412.00	21.33	2.72	57.94	72.43	5000.00	PASS
2437.00	93.11	2.72	252.93	316.16	5000.00	PASS
2462.00	22.12	2.72	60.09	75.11	5000.00	PASS

#### Result:

The EUT was found to be exempt from routine SAR testing and **COMPLIANT** with FCC and ISED RF exposure requirements.

**REPORT END**