



The University of Michigan
Radiation Laboratory
3228 EECS Building
Ann Arbor, MI 48109-2122
Tel: (734) 764-0500

Measured Radio Frequency Emissions
From

Omron 315 MHz RKE Transmitter
Model(s): 6U5T-19136

Report No. 415031-262
October 20, 2005

Copyright © 2005

For:
Omron Automotive Electronics Corporation
3709 Ohio Street
St. Charles, IL 60174

Contact:
Nick Karnezos
Tel: 630 443-6800 Ext. 347
Fax: 630 587-0578
PO: Verbal

Measurements made by:

Valdis V. Liepa
Joseph D. Brunett

Tests supervised by:
Report approved by:

Valdis V. Liepa
Valdis V. Liepa
Research Scientist

Summary

Tests for compliance with FCC Regulations Part 15, Subpart C, and Industry Canada RSS-210/Gen, were performed on Omron model(s) 6U5T-19136. This device is subject to the Rules and Regulations as a Transmitter.

In testing completed on October 10, 2005, the device tested in the worst case met the allowed FCC specifications for radiated emissions by 1.3 dB (see p. 6). Besides harmonics, there were no other significant spurious emissions found; emissions from digital circuitry were negligible. The conducted emission tests do not apply, since the device is powered from a 3 VDC battery.

1. Introduction

Omron model 6U5T-19136 was tested for compliance with FCC Regulations, Part 15, adopted under Docket 87-389, April 18, 1989, and with Industry Canada RSS-210/Gen, Issue 6, September 2005. The tests were performed at the University of Michigan Radiation Laboratory Willow Run Test Range following the procedures described in ANSI C63.4-2003 "Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz". The Site description and attenuation characteristics of the Open Site facility are on file with FCC Laboratory, Columbia, Maryland (FCC Reg. No: 91050) and with Industry Canada, Ottawa, ON (File Ref. No: IC 2057).

2. Test Procedure and Equipment Used

The pertinent test equipment commonly used in our facility for measurements is listed in Table 2.1 below. The middle column identifies the specific equipment used in these tests.

Table 2.1 Test Equipment.

Test Instrument	Eqpt. Used	Manufacturer/Model
Spectrum Analyzer (0.1-1500 MHz)		Hewlett-Packard, 182T/8558B
Spectrum Analyzer (9kHz-22GHz)	X	Hewlett-Packard 8593A SN: 3107A01358
Spectrum Analyzer (9kHz-26GHz)	X	Hewlett-Packard 8593E, SN: 3412A01131
Spectrum Analyzer (9kHz-26GHz)		Hewlett-Packard 8563E, SN: 3310A01174
Spectrum Analyzer (9kHz-40GHz)		Hewlett-Packard 8564E, SN: 3745A01031
Power Meter		Hewlett-Packard, 432A
Power Meter		Anritsu, ML4803A/MP
Harmonic Mixer (26-40 GHz)		Hewlett-Packard 11970A, SN: 3003A08327
Harmonic Mixer (40-60 GHz)		Hewlett-Packard 11970U, SN: 2332A00500
Harmonic Mixer (75-110 GHz)		Hewlett-Packard 11970W, SN: 2521A00179
Harmonic Mixer (140-220 GHz)		Pacific Millimeter Prod., GMA, SN: 26
S-Band Std. Gain Horn		S/A, Model SGH-2.6
C-Band Std. Gain Horn		University of Michigan, NRL design
XN-Band Std. Gain Horn		University of Michigan, NRL design
X-Band Std. Gain Horn		S/A, Model 12-8.2
X-band horn (8.2- 12.4 GHz)		Narda 640
X-band horn (8.2- 12.4 GHz)		Scientific Atlanta , 12-8.2, SN: 730
K-band horn (18-26.5 GHz)		FXR, Inc., K638KF
Ka-band horn (26.5-40 GHz)		FXR, Inc., U638A
U-band horn (40-60 GHz)		Custom Microwave, HO19
W-band horn(75-110 GHz)		Custom Microwave, HO10
G-band horn (140-220 GHz)		Custom Microwave, HO5R
Bicone Antenna (30-250 MHz)	X	University of Michigan, RLBC-1
Bicone Antenna (200-1000 MHz)	X	University of Michigan, RLBC-2
Dipole Antenna Set (30-1000 MHz)	X	University of Michigan, RLDP-1,-2,-3
Dipole Antenna Set (30-1000 MHz)		EMCO 2131C, SN: 992
Active Rod Antenna (30 Hz-50 MHz)		EMCO 3301B, SN: 3223
Active Loop Antenna (30 Hz-50 MHz)		EMCO 6502, SN:2855
Ridge-horn Antenna (300-5000 MHz)	X	University of Michigan
Amplifier (5-1000 MHz)	X	Avantak, A11-1, A25-1S
Amplifier (5-4500 MHz)	X	Avantak
Amplifier (4.5-13 GHz)		Avantek, AFT-12665
Amplifier (6-16 GHz)		Trek
Amplifier (16-26 GHz)		Avantek
LISN Box		University of Michigan
Signal Generator		Hewlett-Packard 8657B

3. Configuration and Identification of Device Under Test

The DUT is a 315 MHz, 3 or 4 button transmitter approximately 1 x 0.75 x 3.5 inches in size. The device is actuated via mechanical keys, and contains 134 kHz Immobilizer passive circuitry on the PCB. The emission is Manchester encoded, ASK modulated. On a single actuation, the DUT will transmit 4 words over a period of approximately 350 ms. Note that the DUT is manually activated and ceases to transmit within 5 seconds of deactivation (see Figure 6.5).

The DUT was designed and manufactured by Omron Automotive Electronics Corporation, 3709 Ohio Street, St. Charles, IL 60174. It is identified as:

Omron Automotive Electronics Corporation Transmitter
Model: 6U5T-19136
S/N or P/N: Transmitter
FCC ID: OUCD6000022
IC: 850K- D6000022

For testing and evaluation, plastics for 3 and 4 button versions were provided, along with CW and momentary pulse PCBs. The three button version was fully tested, while the 4 button version was tested only at the worst case emission of the 3 button version.

3.1 Modifications Made

There were no modifications made to the DUT by this laboratory.

4. Emission Limits

The DUT tested falls under the category of an Intentional Radiators and the Digital Devices. For FCC, it is subject to Part 15, Subpart C, (Section 15.231), Subpart B, (Section 15.109), and Subpart A, (Section 15.33). For Industry Canada it is subject to RSS-210, (Section 2.6 and 2.7). The applicable testing frequencies with corresponding emission limits are given in Tables 4.1 and 4.2 below. As a digital device, the DUT is considered as a Class B device.

4.1 Radiated Emission Limits

Table 4.1. Radiated Emission Limits (FCC: 15.33, 15.35, 15.109; IC: RSS-210, 2.7 Table 2).
(Digital Class B)

Freq. (MHz)	E _{lim} (3m) μ V/m	E _{lim} dB(μ V/m)
30-88	100	40.0
88-216	150	43.5
216-960	200	46.0
960-2000	500	54.0

Note: Average readings apply above 1000 MHz (1 MHz BW)
Quasi-Peak readings apply to 1000 MHz (120 kHz BW)

Table 4.2. Radiated Emission Limits (FCC: 15.231(b), 15.205(a); IC: RSS-210; 2.7 Table 1).
(Transmitter)

Frequency (MHz)	Fundamental Ave. E _{lim} (3m)		Spurious** Ave. E _{lim} (3m)	
	(μV/m)	dB (μV/m)	(μV/m)	dB (μV/m)
260.0-470.0	3750-12500*		375-1250	
322-335.4 399.9-410 608-614	Restricted Bands		200	46.0
960-1240/1427(IC) 1300-1427 1435-1626.5 1645.5-1646.5 (IC) 1660-1710 1718.9-1722.2 2200-2300	Restricted Bands		500	54.0

* Linear interpolation, formula: $E = -7083 + 41.67 \cdot f$ (MHz)

** Measure up to tenth harmonic; 120 kHz BW up to 1 GHz, 1 MHz BW above 1 GHz

4.3 Conducted Emissions Limits

The conducted emission limits and tests do not apply here, since the DUT is powered by a 3 VDC battery.

4.4 Supply Voltage Variation (FCC 15.31(e))

For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.

5. Radiated Emission Tests and Results

5.1 Semi-Anechoic Chamber Measurements

To familiarize with the radiated emission behavior of the DUT, the DUT was first studied and measured in a shielded semi-anechoic chamber. In the chamber there is a set-up similar to that of an outdoor 3-meter site, with a turntable, an antenna mast, and a ground plane. Instrumentation includes spectrum analyzers and other equipment as needed.

In testing for radiated emissions, the transmitter was activated using the lock/unlock button with a special wooden clamp for repeated pulse emissions. It was placed on the test table flat, on its side, or on its end.

In the chamber we studied and recorded all the emissions using a Bicone antenna up to 300 MHz and a ridged horn antenna above 200 MHz. The measurements made in the chamber below 1 GHz are used for pre-test evaluation only. The measurements made above 1 GHz are used in pre-test evaluation and in the final compliance assessment. We note that for the horn antenna, the antenna pattern is more directive and hence the measurement is essentially that of free space (no ground reflection). Consequently it is not essential to measure the DUT for both antenna polarizations, as long as the DUT is measured on all three of its major axis. In the chamber we also recorded the spectrum and modulation

characteristics of the carrier. These data are presented in subsequent sections. We also note that in scanning from 30 MHz to 4.5 GHz using Bicone and the ridge horn antennas, there were no other significant spurious emissions observed.

5.2 Open Site Radiated Emission Tests

After the chamber measurements, the emissions were re-measured on the outdoor 3-meter site at fundamental and harmonics up to 1 GHz using tuned dipoles and/or the high frequency Bicone. Photographs included show the DUT on the Open Area Test Site (OATS).

5.3 Computations and Results for Radiated Emissions

To convert the dBm's measured on the spectrum analyzer to dB(μ V/m), we use expression

$$E_3(\text{dB}\mu\text{V/m}) = 107 + P_R + K_A - K_G$$

where P_R = power recorded on spectrum analyzer, dB, measured at 3m
 K_A = antenna factor, dB/m
 K_G = pre-amplifier gain, including cable loss, dB

When presenting the data, at each frequency the highest measured emission under all of the possible orientations is given. Computations and results are given in Table 5.1. There we see that the DUT meets the limit by 1.3 dB.

5.4 Conducted Emission Tests

These tests do not apply, since the DUT is powered from a 3 VDC battery.

6. Other Measurements

6.1 Correction For Pulse Operation

When the transmitter is activated by push action, it transmits 4 encoded words, each with 100 ms period. Each word consists of 90 Manchester pulses, each of which has an on time of 258.75 μ s. See Figure 6.1. Thus, the duty factor is

$$K_E = 90 \times 0.25875 \text{ ms} / 100 \text{ ms} = 0.233 \text{ or } -12.7 \text{ dB.}$$

Note: In the original filing, 92 pulses were counted. There are actually only 90 pulses as confirmed with the manufacturer. The original filing is in error.

6.2 Emission Spectrum

Using the ridge-horn antenna and DUT placed in its aperture, emission spectrum was recorded and is shown in Figure 6.2.

6.3 Bandwidth of the Emission Spectrum

The measured spectrum of the signal is shown in Figure 6.3. The allowed (-20 dB) bandwidth is 0.25% of 315 MHz, or 787.25 kHz. From the plot we see that the -20 dB bandwidth is 18.5 kHz, and the center frequency is 315 MHz.

6.4 Effect of Supply Voltage Variation

The DUT has been designed to be powered by 3 VDC battery. For this test, the battery was replaced by a laboratory variable power supply. Relative power radiated was measured at the fundamental as the voltage was varied from 1.8 to 4.0 volts. The emission variation is shown in Figure 6.4.

6.5 Input Voltage at Battery Terminals

Batteries:	before testing	$V_{oc} =$	3.29 V
	after testing	$V_{oc} =$	2.91 V
Ave. current from batteries		$I =$	5.5 mA (pulsed)

Table 5.1 Highest Emissions Measured

Radiated Emission - RF											Omron TX, FCC/IC
#	Freq. MHz	Ant. Used	Ant. Pol.	Pr dBm	Det. Used	Ka dB/m	Kg dB	E3* dBμV/m	E3lim dBμV/m	Pass dB	Comments
1	3 Button Version										
2	315.0	Dip	H	-16.3	Pk	18.6	22.3	74.3	75.6	1.3	flat
3	315.0	Dip	V	-19.2	Pk	18.6	22.3	71.4	75.6	4.2	side
4	630.0	Dip	H	-55.3	Pk	24.4	19.2	44.2	55.6	11.5	flat
5	630.0	Dip	V	-59.3	Pk	24.4	19.2	40.2	55.6	15.5	end
6	945.0	Dip	H	-55.1	Pk	28.8	17.3	50.7	55.6	4.9	flat
7	945.0	Dip	V	-56.8	Pk	28.8	17.3	49.0	55.6	6.6	end
8	1260.0	Horn	H	-51.5	Pk	20.6	28.0	35.4	54.0	18.6	flat
9	1575.0	Horn	H	-51.6	Pk	21.5	28.0	36.2	54.0	17.8	flat
10	1890.0	Horn	H	-39.9	Pk	22.2	28.0	48.6	55.6	7.0	side
11	2205.0	Horn	H	-42.7	Pk	23.0	28.1	46.5	54.0	7.5	side
12	2520.0	Horn	H	-45.2	Pk	23.9	28.3	44.7	55.6	11.0	flat
13	2835.0	Horn	H	-48.6	Pk	24.8	28.2	42.3	54.0	11.7	side
14	3150.0	Horn	H	-44.6	Pk	25.8	27.9	47.6	55.6	8.0	side
15											
16	4 Button Version										
17	315.0	Dip	H	-17.1	Pk	18.6	22.3	73.5	75.6	2.1	flat
18											
19											
20	* Includes 12.7 dB duty factor										
21											
22	Digital emissions more than 20 dB below FCC/IC Class B Limit.										
23											
24											
25											
26											
27											

Conducted Emissions							
#	Freq. MHz	Line Side	Det. Used	Vtest dBμV	Vlim dBμV	Pass dB	Comments
	Not applicable						

Meas. 10/10/2005; U of Mich.

University of Michigan Radiation Laboratory
FCC Part 15, IC RSS-210/Gen - Test Report No. 415031-262




Figure 6.1. Transmissions modulation characteristics: (top) complete transmission, (center) expanded bit, (bottom) expanded period.




Figure 6.2. Emission spectrum of the DUT (pulsed emission).
The amplitudes are only indicative (not calibrated).




Figure 6.3. Measured bandwidth of the DUT (pulsed emission).




Figure 6.4. Transmitter 5 sec. transmission limit verification




Figure 6.5. Relative emission at 315.0 MHz vs. supply voltage
(cw emission).



DUT on OATS



DUT on OATS (close-up)