



FCC ID.: Y4O-NH09
Report No.: T210303N01-MF

Page: 1 / 7
Rev.: 01

KDB 447498 D03
47 C.F.R. Part 1, Subpart I, Section 1.1310
47 C.F.R. Part 2, Subpart J, Section 2.1091

RF EXPOSURE REPORT

For

Stand-Alone Media Player

Model: MIXSTREAM

Trade Name: Numark

Issued to

inMusic Brands, Inc.
200 Scenic View Drive, Suite 201, Cumberland, RI 02864, U.S.A.

Issued By

Compliance Certification Services Inc.
No.11, Wugong 6th Rd., Wugu Dist.,
New Taipei City 24891, Taiwan. (R.O.C.)

Issued Date: June 11, 2021

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: T210303N01-MF

Page: 2 / 7
Rev.: 01

REVISION HISTORY

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	May 20, 2021	Initial Issue	ALL	Angel Cheng
01	June 11, 2021	See the following note rev.01	ALL	Angel Cheng

Note:

※ Rev.00 Issue Date: May 20, 2021

Original Report

※ Rev.01 Issue Date: June 11, 2021

Update EUT Specification & Maximum Permissible Exposure from Bluetooth 4.0 to Bluetooth 5.0



Report No.: T210303N01-MF

Page: 3 / 7
Rev.: 01

TABLE OF CONTENTS

1. LIMIT..... 4

2. EUT SPECIFICATION 5

3. TEST RESULTS..... 6

4. MAXIMUM PERMISSIBLE EXPOSURE..... 7



Report No.: T210303N01-MF

Page: 4 / 7
Rev.: 01

1. TEST RESULT CERTIFICATION

We hereby certify that:

The equipment has been tested by Compliance Certification Services Inc., and found compliance with the requirement of the applicable standards. The test record, data evaluation and Equipment under Test (EUT) configurations represented herein are true and accurate accounts of the measurement of the sample's RF characteristics under the conditions specified in this report.

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
KDB 447498 D03 47 C.F.R. Part 1, Subpart I, Section 1.1310 47 C.F.R. Part 2, Subpart J, Section 2.1091	No non-compliance noted
Statements of Conformity	
Determining compliance shall be based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.	


Approved by:

Kevin Tsai
Deputy Manager
Compliance Certification Services Inc.

2. LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

3. EUT SPECIFICATION

EUT	Stand-Alone Media Player		
Model	MIXSTREAM		
Brand			
RF Module	Broadcom	Model:	AP6256
Frequency band (Operating)	<input checked="" type="checkbox"/> IEEE 802.11b/g, 802.11n HT20: 2412MHz~2462MHz <input checked="" type="checkbox"/> Bluetooth 5.0: 2402MHz~2480MHz		
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others		
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²)		
Antenna Specification	WLAN EMBEDDEN ANTENNA / Gain: 4.6 dBi (Numeric gain: 2.88)		
Maximum Average output power	IEEE 802.11b Mode :	13.00 dBm	(19.953 mW)
	IEEE 802.11g Mode :	9.31 dBm	(8.531 mW)
	IEEE 802.11n HT20 Mode :	8.33 dBm	(6.808 mW)
	Bluetooth 5.0 Mode :	-5.11 dBm	(0.308 mW)
Maximum Tune up Power	IEEE 802.11b Mode :	13.50 dBm	(22.387 mW)
	IEEE 802.11g Mode :	10.00 dBm	(10.000 mW)
	IEEE 802.11n HT20 Mode :	9.00 dBm	(7.943 mW)
	Bluetooth 5.0 Mode :	-5.00 dBm	(0.316 mW)
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation* <input type="checkbox"/> SAR Evaluation <input type="checkbox"/> N/A		
Received Date	February 01, 2021		
Reported Date	May 20, 2021		

Remark:

- RF power data reference report (T210303N01-RP1)
- Disclaimer: Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.

4. TEST RESULTS

No non-compliance noted.

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

5. MAXIMUM PERMISSIBLE EXPOSURE

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where $P = \text{Power in mW}$

$G = \text{Numeric antenna gain}$

$S = \text{Power density in mW / cm}^2$

IEEE 802.11b Mode :

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)	Result
High	2462	22.387	2.88	20	0.0128	1	Pass

IEEE 802.11g Mode :

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)	Result
High	2462	10.000	2.88	20	0.0057	1	Pass

IEEE 802.11n HT 20 Mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)	Result
Mid	2437	7.943	2.88	20	0.0046	1	Pass

Bluetooth 5.0 Mode :

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)	Result
Low	2402	0.316	2.88	20	0.0002	1	Pass