




Antenna 0 / 30 MHz ~ Low Edge - 100 MHz / B66 LTE 20 MHz 1 Carrier + 5G NR n66 5 MHz 1 Carrier [2 Carrier] /
Contiguous / 256QAM / Low




Antenna 1 / Low Edge - 100 MHz ~ Low Edge / B66 LTE 20 MHz 1 Carrier + 5G NR n66 5 MHz 1 Carrier [2 Carrier] /
Contiguous / QPSK / High




Antenna 1 / High Edge ~ High Edge + 100 MHz / B66 LTE 20 MHz 1 Carrier + 5G NR n66 5 MHz 1 Carrier [2 Carrier] /
Contiguous / 16QAM / Low




Antenna 1 / High Edge + 100 MHz ~ 10 GHz / B66 LTE 20 MHz 1 Carrier + 5G NR n66 5 MHz 1 Carrier [2 Carrier] /
Contiguous / QPSK / Low



Antenna 1 / 10 GHz ~ 26.5 GHz / B66 LTE 20 MHz 1 Carrier + 5G NR n66 5 MHz 1 Carrier [2 Carrier] / Contiguous / 256QAM / Low




Antenna 1 / 9 kHz ~ 150 kHz / B66 LTE 20 MHz 1 Carrier + 5G NR n66 10 MHz 1 Carrier [2 Carrier] / Contiguous / QPSK / Low




Antenna 1 / 150 kHz ~ 30 MHz / B66 LTE 20 MHz 1 Carrier + 5G NR n66 10 MHz 1 Carrier [2 Carrier] / Contiguous / 16QAM / Middle


Antenna 1 / 30 MHz ~ Low Edge - 100 MHz / B66 LTE 20 MHz 1 Carrier + 5G NR n66 10 MHz 1 Carrier [2 Carrier] /
Contiguous / 64QAM / Middle




Antenna 1 / Low Edge - 100 MHz ~ Low Edge / B66 LTE 20 MHz 1 Carrier + 5G NR n66 10 MHz 1 Carrier [2 Carrier] /
Contiguous / 64QAM / High




Antenna 1 / High Edge ~ High Edge + 100 MHz / B66 LTE 20 MHz 1 Carrier + 5G NR n66 10 MHz 1 Carrier [2 Carrier] /
Contiguous / 256QAM / High




Antenna 1 / High Edge + 100 MHz ~ 10 GHz / B66 LTE 20 MHz 1 Carrier + 5G NR n66 10 MHz 1 Carrier [2 Carrier] /
Contiguous / QPSK / Middle




Antenna 1 / 10 GHz ~ 26.5 GHz / B66 LTE 20 MHz 1 Carrier + 5G NR n66 10 MHz 1 Carrier [2 Carrier] / Contiguous / 16QAM / Middle




Antenna 1 / 9 kHz ~ 150 kHz / B66 LTE 5 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / QPSK




Antenna 0 / 150 kHz ~ 30 MHz / B66 LTE 5 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 16QAM




Antenna 1 / 30 MHz ~ Low Edge - 100 MHz / B66 LTE 5 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / QPSK




Antenna 1 / Low Edge - 100 MHz ~ Low Edge / B66 LTE 5 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / QPSK




Antenna 0 / High Edge ~ High Edge + 100 MHz / B66 LTE 5 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 64QAM



Antenna 1 / High Edge + 100 MHz ~ 10 GHz / B66 LTE 5 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 64QAM




Antenna 1 / 10 GHz ~ 26.5 GHz / B66 LTE 5 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / QPSK




Antenna 1 / 9 kHz ~ 150 kHz / B66 LTE 20 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 16QAM




Antenna 0 / 150 kHz ~ 30 MHz / B66 LTE 20 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 16QAM




Antenna 0 / 30 MHz ~ Low Edge - 100 MHz / B66 LTE 20 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 256QAM




Antenna 0 / Low Edge - 100 MHz ~ Low Edge / B66 LTE 20 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / QPSK



Antenna 0 / High Edge ~ High Edge + 100 MHz / B66 LTE 20 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 16QAM



Antenna 0 / High Edge + 100 MHz ~ 10 GHz / B66 LTE 20 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 256QAM




Antenna 1 / 10 GHz ~ 26.5 GHz / B66 LTE 20 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 16QAM




Antenna 1 / 9 kHz ~ 150 kHz / B66 LTE 20 MHz 1 Carrier + B66 LTE 10 MHz 1 Carrier [2 Carrier] / Non-Contiguous / QPSK




Antenna 1 / 150 kHz ~ 30 MHz / B66 LTE 20 MHz 1 Carrier + B66 LTE 10 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 16QAM




Antenna 1 / 30 MHz ~ Low Edge - 100 MHz / B66 LTE 20 MHz 1 Carrier + B66 LTE 10 MHz 1 Carrier [2 Carrier] / Non-Contiguous / QPSK




Antenna 1 / Low Edge - 100 MHz ~ Low Edge / B66 LTE 20 MHz 1 Carrier + B66 LTE 10 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 64QAM




Antenna 1 / High Edge ~ High Edge + 100 MHz / B66 LTE 20 MHz 1 Carrier + B66 LTE 10 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 256QAM



Antenna 1 / High Edge + 100 MHz ~ 10 GHz / B66 LTE 20 MHz 1 Carrier + B66 LTE 10 MHz 1 Carrier [2 Carrier] / Non-Contiguous / QPSK




Antenna 1 / 10 GHz ~ 26.5 GHz / B66 LTE 20 MHz 1 Carrier + B66 LTE 10 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 16QAM




Antenna 1 / 9 kHz ~ 150 kHz / 5G NR n66 5 MHz 1 Carrier + 5G NR n66 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 16QAM




Antenna 1 / 150 kHz ~ 30 MHz / 5G NR n66 5 MHz 1 Carrier + 5G NR n66 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 256QAM




Antenna 1 / 30 MHz ~ Low Edge - 100 MHz / 5G NR n66 5 MHz 1 Carrier + 5G NR n66 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / QPSK




Antenna 1 / Low Edge - 100 MHz ~ Low Edge / 5G NR n66 5 MHz 1 Carrier + 5G NR n66 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / QPSK




Antenna 1 / High Edge ~ High Edge + 100 MHz / 5G NR n66 5 MHz 1 Carrier + 5G NR n66 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 64QAM



Antenna 0 / High Edge + 100 MHz ~ 10 GHz / 5G NR n66 5 MHz 1 Carrier + 5G NR n66 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 64QAM




Antenna 1 / 10 GHz ~ 26.5 GHz / 5G NR n66 5 MHz 1 Carrier + 5G NR n66 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 64QAM




Antenna 0/ 9 kHz ~ 150 kHz / 5G NR n66 20 MHz 1 Carrier + 5G NR n66 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 16QAM




Antenna 1 / 150 kHz ~ 30 MHz / 5G NR n66 20 MHz 1 Carrier + 5G NR n66 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 256QAM




Antenna 1 / 30 MHz ~ Low Edge - 100 MHz / 5G NR n66 20 MHz 1 Carrier + 5G NR n66 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 64QAM




Antenna 1 / Low Edge - 100 MHz ~ Low Edge / 5G NR n66 20 MHz 1 Carrier + 5G NR n66 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 16QAM




Antenna 1 / High Edge ~ High Edge + 100 MHz / 5G NR n66 20 MHz 1 Carrier + 5G NR n66 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 256QAM




Antenna 0 / High Edge + 100 MHz ~ 10 GHz / 5G NR n66 20 MHz 1 Carrier + 5G NR n66 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 16QAM




Antenna 1 / 10 GHz ~ 26.5 GHz / 5G NR n66 20 MHz 1 Carrier + 5G NR n66 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 64QAM




Antenna 1 / 9 kHz ~ 150 kHz / 5G NR n66 20 MHz 1 Carrier + 5G NR n66 10 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 256QAM




Antenna 0 / 150 kHz ~ 30 MHz / 5G NR n66 20 MHz 1 Carrier + 5G NR n66 10 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 256QAM




Antenna 1 / 30 MHz ~ Low Edge - 100 MHz / 5G NR n66 20 MHz 1 Carrier + 5G NR n66 10 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 256QAM




Antenna 1 / Low Edge - 100 MHz ~ Low Edge / 5G NR n66 20 MHz 1 Carrier + 5G NR n66 10 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 64QAM




Antenna 0 / High Edge ~ High Edge + 100 MHz / 5G NR n66 20 MHz 1 Carrier + 5G NR n66 10 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 256QAM




Antenna 0 / High Edge + 100 MHz ~ 10 GHz / 5G NR n66 20 MHz 1 Carrier + 5G NR n66 10 MHz 1 Carrier [2 Carrier] / Non-Contiguous / QPSK




Antenna 1 / 10 GHz ~ 26.5 GHz / 5G NR n66 20 MHz 1 Carrier + 5G NR n66 10 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 256QAM




Antenna 1 / 9 kHz ~ 150 kHz / 5G NR n66 5 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 16QAM




Antenna 0 / 150 kHz ~ 30 MHz / 5G NR n66 5 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / QPSK




Antenna 1 / 30 MHz ~ Low Edge - 100 MHz / 5G NR n66 5 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 64QAM




Antenna 1 / Low Edge - 100 MHz ~ Low Edge / 5G NR n66 5 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 16QAM




Antenna 1 / High Edge ~ High Edge + 100 MHz / 5G NR n66 5 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / QPSK



Antenna 0 / High Edge + 100 MHz ~ 10 GHz / 5G NR n66 5 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / QPSK




Antenna 1 / 10 GHz ~ 26.5 GHz / 5G NR n66 5 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 64QAM




Antenna 0 / 9 kHz ~ 150 kHz / 5G NR n66 20 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 64QAM




Antenna 1 / 150 kHz ~ 30 MHz / 5G NR n66 20 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / QPSK




Antenna 0 / 30 MHz ~ Low Edge - 100 MHz / 5G NR n66 20 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / QPSK




Antenna 1 / Low Edge - 100 MHz ~ Low Edge / 5G NR n66 20 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 256QAM




Antenna 0 / High Edge ~ High Edge + 100 MHz / 5G NR n66 20 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / QPSK




Antenna 1 / High Edge + 100 MHz ~ 10 GHz / 5G NR n66 20 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 16QAM




Antenna 1 / 10 GHz ~ 26.5 GHz / 5G NR n66 20 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 256QAM




Antenna 0 / 9 kHz ~ 150 kHz / 5G NR n66 20 MHz 1 Carrier + B66 LTE 10 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 16QAM




Antenna 1 / 150 kHz ~ 30 MHz / 5G NR n66 20 MHz 1 Carrier + B66 LTE 10 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 256QAM




Antenna 1 / 30 MHz ~ Low Edge - 100 MHz / 5G NR n66 20 MHz 1 Carrier + B66 LTE 10 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 256QAM




Antenna 1 / Low Edge - 100 MHz ~ Low Edge / 5G NR n66 20 MHz 1 Carrier + B66 LTE 10 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 256QAM




Antenna 1 / High Edge ~ High Edge + 100 MHz / 5G NR n66 20 MHz 1 Carrier + B66 LTE 10 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 256QAM




Antenna 1 / High Edge + 100 MHz ~ 10 GHz / 5G NR n66 20 MHz 1 Carrier + B66 LTE 10 MHz 1 Carrier [2 Carrier] / Non-Contiguous / QPSK




Antenna 1 / 10 GHz ~ 26.5 GHz / 5G NR n66 20 MHz 1 Carrier + B66 LTE 10 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 256QAM




Antenna 1 / 9 kHz ~ 150 kHz / B66 LTE 20 MHz 1 Carrier + 5G NR n66 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 256QAM




Antenna 1 / 150 kHz ~ 30 MHz / B66 LTE 20 MHz 1 Carrier + 5G NR n66 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 256QAM




Antenna 1 / 30 MHz ~ Low Edge - 100 MHz / B66 LTE 20 MHz 1 Carrier + 5G NR n66 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 16QAM




Antenna 1 / Low Edge - 100 MHz ~ Low Edge / B66 LTE 20 MHz 1 Carrier + 5G NR n66 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / QPSK




Antenna 1 / High Edge ~ High Edge + 100 MHz / B66 LTE 20 MHz 1 Carrier + 5G NR n66 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / QPSK




Antenna 0 / High Edge + 100 MHz ~ 10 GHz / B66 LTE 20 MHz 1 Carrier + 5G NR n66 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / QPSK




Antenna 1 / 10 GHz ~ 26.5 GHz / B66 LTE 20 MHz 1 Carrier + 5G NR n66 5 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 16QAM




Antenna 0 / 9 kHz ~ 150 kHz / B66 LTE 20 MHz 1 Carrier + 5G NR n66 10 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 16QAM




Antenna 0 / 150 kHz ~ 30 MHz / B66 LTE 20 MHz 1 Carrier + 5G NR n66 10 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 16QAM




Antenna 0 / 30 MHz ~ Low Edge - 100 MHz / B66 LTE 20 MHz 1 Carrier + 5G NR n66 10 MHz 1 Carrier [2 Carrier] / Non-Contiguous / QPSK




Antenna 0 / Low Edge - 100 MHz ~ Low Edge / B66 LTE 20 MHz 1 Carrier + 5G NR n66 10 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 64QAM




Antenna 0 / High Edge ~ High Edge + 100 MHz / B66 LTE 20 MHz 1 Carrier + 5G NR n66 10 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 16QAM



Antenna 0 / High Edge + 100 MHz ~ 10 GHz / B66 LTE 20 MHz 1 Carrier + 5G NR n66 10 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 256QAM



Antenna 1 / 10 GHz ~ 26.5 GHz / B66 LTE 20 MHz 1 Carrier + 5G NR n66 10 MHz 1 Carrier [2 Carrier] / Non-Contiguous / 16QAM



5.6. RADIATED EMISSIONS

Test Requirements:

§ 2.1053 Measurements required: Field strength of spurious radiation.

- (a) Measurements shall be made to detect spurious emissions that may be radiated directly from the cabinet, control circuits, power leads, or intermediate circuit elements under normal conditions of installation and operation. Curves or equivalent data shall be supplied showing the magnitude of each harmonic and other spurious emission. For this test, single sideband, independent sideband, and controlled carrier transmitters shall be modulated under the conditions specified in paragraph (c) of § 2.1049, as appropriate. For equipment operating on frequencies below 890 MHz, an open field test is normally required, with the measuring instrument antenna located in the far-field at all test frequencies. In the event it is either impractical or impossible to make open field measurements (e.g. a broadcast transmitter installed in a building) measurements will be accepted of the equipment as installed. Such measurements must be accompanied by a description of the site where the measurements were made showing the location of any possible source of reflections which might distort the field strength measurements. Information submitted shall include the relative radiated power of each spurious emission with reference to the rated power output of the transmitter, assuming all emissions are radiated from halfwave dipole antennas.
- (b) The measurements specified in paragraph (a) of this section shall be made for the following equipment:
- (1) Those in which the spurious emissions are required to be 60 dB or more below the mean power of the transmitter.
 - (2) All equipment operating on frequencies higher than 25 MHz.
 - (3) All equipment where the antenna is an integral part of, and attached directly to the transmitter.
 - (4) Other types of equipment as required, when deemed necessary by the Commission.

§ 27.53 Emission limits.

- (c) For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:
- (1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;
 - (2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;
 - (3) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $76 + 10 \log (P)$ dB in a 6.25 kHz band segment, for base and fixed stations;
 - (4) Omitted
 - (5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed;
 - (6) Compliance with the provisions of paragraphs (c)(3) and (c)(4) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

- (f) For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.
- (h) AWS emission limits
- (1) General protection levels. Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.
 - (3) Measurement procedure.
 - (i) Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 1 megahertz or greater. However, in the 1 megahertz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.
 - (ii) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.
 - (iii) The measurements of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

Test Procedures:

The measurement is performed in accordance with Section 5.5.3.2 of ANSI C63.26.

- a) Place the EUT in the center of the turntable. The EUT shall be configured to transmit into the standard non-radiating load (for measuring radiated spurious emissions), connected with cables of minimal length unless specified otherwise. If the EUT uses an adjustable antenna, the antenna shall be positioned to the length that produces the worst case emission at the fundamental operating frequency.
- b) Each emission under consideration shall be evaluated:
 - 1) Raise and lower the measurement antenna in accordance 5.5.2, as necessary to enable detection of the maximum emission amplitude relative to measurement antenna height.
 - 2) Rotate the EUT through 360° to determine the maximum emission level relative to the axial position.
 - 3) Return the turntable to the azimuth where the highest emission amplitude level was observed.
 - 4) Vary the measurement antenna height again through 1 m to 4 m again to find the height associated with the maximum emission amplitude.
 - 5) Record the measured emission amplitude level and frequency using the appropriate RBW.
- c) Repeat step b) for each emission frequency with the measurement antenna oriented in both the horizontal and vertical polarizations to determine the orientation that gives the maximum emissions amplitude.
- d) ~ j) Omitted

k) Provide the complete measurement results as a part of the test report.

Note:

1. The results of the Radiated Emissions test shown above are measured at maximum power, and data values are attached only in the worst case.
2. The amplitude of the spurious domain emission attenuated by more than 20 dB over the permissible value was not recorded according to ANSI C63.26, clause 5.1.1., c).
3. Measure distance = 3 m

Test Results:
B13 LTE 5 MHz 1 Carrier

Freq.(MHz)	Measured Level	Ant. Factor	A.G.+C.L.+H.P.F.	Pol.	Measured Power	Result
	[dBuV]	[dB/m]	[dB]		[dBm]	[dBm/m]

No Critical Peaks found

* C.L.: Cable Loss / A.G.: Amp Gain / H.P.F.: High Pass Filter

B66 LTE 5 MHz 1 Carrier


Freq.(MHz)	Measured Level	Ant. Factor	A.G.+C.L.+H.P.F.	Pol.	Measured Power	Result
	[dBuV]	[dB/m]	[dB]		[dBm]	[dBm/m]

No Critical Peaks found


* C.L.: Cable Loss / A.G.: Amp Gain / H.P.F.: High Pass Filter

Plot data of Radiated Emissions

B13 LTE 5 MHz 1 Carrier




Date: 1.JAN.2003 02:07:00




Date: 1.JAN.2003 02:08:35

Note: Only the worst case plots for Radiated Spurious Emissions.


B66 LTE 5 MHz 1 Carrier




Date: 1.JAN.2003 00:25:06



Date: 1.JAN.2003 00:27:08



Date: 1.JAN.2003 00:28:55



Date: 1.JAN.2003 00:30:36

Note: Only the worst case plots for Radiated Spurious Emissions.

5.7. FREQUENCY STABILITY

Test Requirements:

§ 2.1055 Measurements required: Frequency stability.

(a) The frequency stability shall be measured with variation of ambient temperature as follows:

- (1) From -30° to $+50^{\circ}$ centigrade for all equipment except that specified in paragraphs (a) (2) and (3) of this section.

§ 27.54 Frequency stability.

The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

Test Procedures:

The measurement is performed in accordance with Section 5.6.3, 5.6.4 and 5.6.5 of ANSI C63.26.

5.6.3 Procedure for frequency stability testing

Frequency stability is a measure of the frequency drift due to temperature and supply voltage variations, with reference to the frequency measured at $+20^{\circ}\text{C}$ and rated supply voltage.

The operating carrier frequency shall be set up in accordance with the manufacturer's published operation and instruction manual prior to the commencement of these tests. No adjustment of any frequency determining circuit element shall be made subsequent to this initial set-up. Frequency stability is tested:

- a) At 10°C intervals of temperatures between -30°C and $+50^{\circ}\text{C}$ at the manufacturer's rated supply voltage, and
- b) At $+20^{\circ}\text{C}$ temperature and $\pm 15\%$ supply voltage variations. If a product is specified to operate over a range of input voltage then the -15% variation is applied to the lowermost voltage and the $+15\%$ is applied to the uppermost voltage.

During the test all necessary settings, adjustments and control of the EUT have to be performed without disturbing the test environment, i.e., without opening the environmental chamber. The frequency stabilities can be maintained to a lesser temperature range provided that the transmitter is automatically inhibited from operating outside the lesser temperature range. For handheld equipment that is only capable of operating from internal batteries and the supply voltage cannot be varied, the frequency stability tests shall be performed at the nominal battery voltage and the battery end point voltage specified by the manufacturer. An external supply voltage can be used and set at the internal battery nominal voltage, and again at the battery operating end point voltage which shall be specified by the equipment manufacturer.

If an unmodulated carrier is not available, the mean frequency of a modulated carrier can be obtained by using a frequency counter with gating time set to an appropriately large multiple of bit periods (gating time depending on the required accuracy).

Full details on the choice of values shall be included in the test report.

5.6.4 Frequency stability over variations in temperature

- a) Supply the EUT with a nominal 60 Hz ac voltage, dc voltage, or install a new or fully charged battery in the EUT.
- b) If possible a dummy load should be connected to the EUT because an antenna near the metallic walls of an environmental test chamber could affect the output frequency of the EUT. If the EUT is equipped with a permanently attached, adjustable-length antenna, the EUT should be placed in the center of the chamber with the antenna adjusted to the shortest length possible.
- c) Turn on the EUT, and tune it to the center frequency of the operating band.
- d) Couple the transmitter output to the measuring instrument through a suitable attenuator and coaxial cable. If connection to the EUT output is not possible, make the measurement by connecting an antenna to the measuring instrument with a suitable length of coaxial cable and placing the measuring antenna near the EUT (e.g., 15 cm away).

NOTE—An instrument that has an adequate level of accuracy as specified by the procuring or regulatory authority is the recommended measuring instrument.

- e) Adjust the location of the measurement antenna and the controls on the measurement instrument to obtain a suitable signal level (i.e., a level that will not overload the measurement instrument, but is strong enough to allow measurement of the operating or fundamental frequency of the EUT). Adjust the detector bandwidth and span settings to achieve a resolution capable of accurate frequency measurements over the applicable frequency stability limits.
- f) Turn the EUT off, and place it inside the environmental temperature chamber. For devices that have oscillator heaters, energize only the heater circuit.
- g) Set the temperature control on the chamber to the Highest temperature specified in the regulatory requirements for the type of device, and allow the oscillator heater and the chamber temperature to stabilize. Unless otherwise instructed by the regulatory authority, this temperature should be 50 °C.
- h) While maintaining a constant temperature inside the environmental chamber, turn on the EUT and allow sufficient time for the EUT temperature to stabilize.
- i) Measure the frequency.
- j) Switch off the EUT, but do not switch off the oscillator heater.
- k) Lower the chamber temperature to the next level that is required by the standard and allow the temperature inside the chamber to stabilize. Unless otherwise instructed by the regulators, this temperature step should be 10 °C.
- l) Repeat step h) through step k) down to the lowest specified temperature. Unless otherwise instructed by the regulators, this temperature should be –30 °C. When the frequency stability limit is stated as being sufficient such that the fundamental emissions stay within the authorized bands of operation, a reference point shall be established at the applicable unwanted emissions limit using a RBW equal to the RBW required by the unwanted emissions specification of the applicable regulatory standard. These reference points measured using the lowest and Highest channel of operation shall be identified as f_L and f_H respectively. The worst-case frequency offset determined in the above methods shall be added or subtracted from the values of f_L and f_H and the resulting frequencies must remain within the band.
- m) Omitted

5.6.5 Frequency stability when varying supply voltage

- a) Couple the transmitter output to the measuring instrument through a suitable attenuator and coaxial cable. If connection to the EUT output is not possible make the measurement by connecting an antenna to the measuring instrument with a suitable length of coaxial cable and placing the measuring antenna near the EUT (e.g., 15 cm away)
- b) Supply the EUT with nominal ac or dc voltage. The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided. Effects on frequency of transmitter keying (except for broadcast transmitters) and any heating element cycling at the nominal supply voltage and at each extreme also shall be shown.
- c) Turn on the EUT, and couple its output to a frequency counter or other frequency-measuring instrument.
- d) Tune the EUT to the center frequency of the operating band. Adjust the location of the measurement antenna and the controls on the measurement instrument to obtain a suitable signal level (i.e., a level that will not overload the measurement instrument, but is strong enough to allow measurement of the operating or fundamental frequency of the EUT). Adjust the detector bandwidth and span settings to achieve a resolution capable of accurate frequency measurements over the applicable frequency stability limits.

NOTE—An instrument that has an adequate level of accuracy as specified by the procuring or regulatory authority is the recommended measuring instrument.

- e) Measure the frequency.
- f) Unless otherwise specified, vary primary supply voltage from 85% to 115% of the nominal value for other than hand carried battery equipment.
- g) For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
- h) Repeat the frequency measurement.

NOTE—For band-edge compliance, it can be required to make these measurements at the low and High channel of the operating band.

Note:

1. The results of the frequency stability test shown above the frequency deviation measured values are very small and similar trend for each port, so we are attached only the worst case data.
2. This test was performed From -20° to $+50^{\circ}$ centigrade according to the operational description.

Test Results:

AWS

Reference: - 48 Vdc at 20°C Freq. = 2,145,000,000 Hz

Voltage	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(°C)	(Hz)	Error (Hz)	(Hz)	
100%	+20(Ref)	2145 000 001	1.156	0.000	0.00000
	-20	2145 000 004	3.715	2.560	0.00119
	-10	2145 000 002	1.955	0.799	0.00037
	0	2145 000 010	9.830	8.674	0.00404
	+10	2145 000 003	3.052	1.896	0.00088
	+30	2145 000 008	8.477	7.321	0.00341
	+40	2145 000 008	7.940	6.784	0.00316
	+50	2145 000 003	3.259	2.104	0.00098
115%	+20	2145 000 006	6.143	4.988	0.00233
85%	+20	2145 000 003	3.052	1.897	0.00088

Note: The results of the frequency stability test shown above the frequency deviation measured values are very small and similar trend for each port, so attached datas were only the port 0.

Upper 700 MHz

Reference: - 48 Vdc at 20°C Freq. = 751,000,000 Hz

Voltage	Temp.	Frequency	Frequency	Deviation	ppm
(%)	(°C)	(Hz)	Error (Hz)	(Hz)	
100%	+20(Ref)	751 000 009	9.427	0.000	0.00000
	-20	751 000 006	5.764	-3.663	-0.00488
	-10	751 000 001	1.205	-8.223	-0.01095
	0	751 000 003	3.000	-6.427	-0.00856
	+10	751 000 000	0.440	-8.987	-0.01197
	+30	751 000 004	4.268	-5.160	-0.00687
	+40	751 000 009	8.969	-0.458	-0.00061
	+50	751 000 008	7.925	-1.503	-0.00200
115%	+20	751 000 009	8.763	-0.664	-0.00088
85%	+20	751 000 008	8.077	-1.350	-0.00180

Note: The results of the frequency stability test shown above the frequency deviation measured values are very small and similar trend for each port, so attached datas were only the port 0.

6. Annex B_EUT AND TEST SETUP PHOTO

Please refer to test setup photo file no. as follows;

No.	Description
1	HCT-RF-2111-FC093-P