

Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V05

Report Template Revision Date: 2021-11-03

TEST REPORT

Report No.: CQASZ20240801591E-01

Applicant: Shenzhen Kean Digital Co., Ltd.

Address of Applicant: Room 1001, Rujun Building, No. 105, Zhongxing Road, Ma'antang Community, Bantian Street, Longgang District, Shenzhen

Equipment Under Test (EUT):

Product: Network Video Recorder

Model No.: N48WHR, N48WHE, N44WEK, N44WEV, N44WEW, N48WHV, N48WHW, N48WHY, N48WHZ, N98WHD, N98WHE, N98WHF, N98WHG, N98WHR, N58WHD, N58WHE, N58WHF, N58WHG, N54WHD, N54WHE, N94WHD, N94WHE

Test Model No.: N48WHE

Brand Name: N/A

FCC ID: 2AKL2N98WHE

Standards: 47 CFR Part 15, Subpart C

Date of Receipt: 2024-08-02

Date of Test: 2024-08-02 to 2024-09-03

Date of Issue: 2024-09-26

Test Result : PASS*

*In the configuration tested, the EUT complied with the standards specified above

Tested By: Lewis Zhou
(Lewis Zhou)

Reviewed By: Timo Lei
(Timo Lei)

Approved By: Alex
(Alex Wang)



The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20240801591E-01	Rev.01	Initial report	2024-09-26

2 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15.203	N/A	PASS
AC Power Line Conducted Emission	47 CFR Part 15.207	ANSI C63.10-2013	PASS
Conducted Peak & Average Output Power	47 CFR Part 15.247	ANSI C63.10-2013	PASS
6dB Occupied Bandwidth	47 CFR Part 15.247	ANSI C63.10-2013	PASS
Power Spectral Density	47 CFR Part 15.247	ANSI C63.10-2013	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15.247	ANSI C63.10-2013	PASS
RF Conducted Spurious Emissions	47 CFR Part 15.247	ANSI C63.10-2013	PASS
Radiated Spurious Emissions	47 CFR Part 15.209	ANSI C63.10-2013	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15.205/15.209	ANSI C63.10-2013	PASS

Remark:

The tested sample(s) and the sample information are provided by the client.

Tx: In this whole report Tx (or tx) means Transmitter.

Rx: In this whole report Rx (or rx) means Receiver.

RF: In this whole report RF means Radiated Frequency.

CH: In this whole report CH means channel.

Volt: In this whole report Volt means Voltage.

Temp: In this whole report Temp means Temperature.

Humid: In this whole report Humid means humidity.

Press: In this whole report Press means Pressure.

N/A: In this whole report not application

3 Contents

	Page
1 VERSION	2
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	5
4.1 CLIENT INFORMATION	5
4.2 GENERAL DESCRIPTION OF EUT	5
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	5
4.4 TEST ENVIRONMENT AND MODE	7
4.5 DESCRIPTION OF SUPPORT UNITS	8
4.6 TEST LOCATION	8
4.7 TEST FACILITY.....	8
4.8 STATEMENT OF THE MEASUREMENT UNCERTAINTY	9
4.9 DEVIATION FROM STANDARDS.....	9
4.10 ABNORMALITIES FROM STANDARD CONDITIONS.....	9
4.11 OTHER INFORMATION REQUESTED BY THE CUSTOMER	9
4.12 EQUIPMENT LIST	10
5 TEST RESULTS AND MEASUREMENT DATA	11
5.1 ANTENNA REQUIREMENT.....	11
5.2 CONDUCTED EMISSIONS.....	13
5.3 CONDUCTED PEAK & AVERAGE OUTPUT POWER.....	17
Test Result.....	18
Note: When Duty cycle >98%, D.C.F is not required.	19
Test Graphs	20
5.4 6dB OCCUPIED BANDWIDTH	35
Test Result.....	36
Test Graphs	38
5.5 POWER SPECTRAL DENSITY.....	53
Test Result.....	53
Test Graphs	55
5.6 BAND-EDGE FOR RF CONDUCTED EMISSIONS	70
Test Result.....	71
Test Graphs	72
5.7 RF CONDUCTED SPURIOUS EMISSIONS	82
5.8 RADIATED SPURIOUS EMISSIONS.....	126
5.8.1 Radiated emission below 1GHz	129
5.8.2 Transmitter emission above 1GHz.....	131
5.9 RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY.....	155
6 PHOTOGRAPHS - EUT TEST SETUP.....	169
6.1 RADIATED SPURIOUS EMISSION	169
6.2 CONDUCTED EMISSION.....	170
7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS.....	171

4 General Information

4.1 Client Information

Applicant:	Shenzhen Kean Digital Co., Ltd.
Address of Applicant:	Room 1001, Rujun Building, No. 105, Zhongxing Road, Ma'antang Community, Bantian Street, Longgang District, Shenzhen
Manufacturer:	Shenzhen Kean Digital Co., Ltd.
Address of Manufacturer:	Room 1001, Rujun Building, No. 105, Zhongxing Road, Ma'antang Community, Bantian Street, Longgang District, Shenzhen
Factory:	Shenzhen Chengan Electronics Co., Ltd.
Address of Factory:	Room 502, Building 46, No. 25, Honghua Road, Gongming Community, Gongming Street, Guangming District, Shenzhen

4.2 General Description of EUT

Product Name:	Network Video Recorder
Model No.:	N48WHR, N48WHE, N44WEK, N44WEV, N44WEW, N48WHV, N48WHW, N48WHY, N48WHZ, N98WHD, N98WHE, N98WHF, N98WHG, N98WHR, N58WHD, N58WHE, N58WHF, N58WHG, N54WHD, N54WHE, N94WHD, N94WHE
Test Model No.:	N48WHE
Trade Mark:	N/A
Software Version:	V1.0
Hardware Version:	V1.0
Power Supply:	Power supply DC12V form adapter
EUT Supports Radios application:	2.4GHz: Wi-Fi: 802.11b/g/n(HT20): 2412MHz~2462MHz; 802.11n(HT40): 2422MHz~2452MHz
Simultaneous Transmission	☐ Simultaneous TX is supported and evaluated in this report. ☐ Simultaneous TX is not supported.

4.3 Product Specification subjective to this standard

Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE for 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40): OFDM (64QAM, 16QAM, QPSK, BPSK)
Transfer Rate:	IEEE for 802.11b: 1Mbps/2Mbps/5.5Mbps/11Mbps IEEE for 802.11g: 6Mbps/9Mbps/12Mbps/18Mbps/24Mbps/36Mbps/48Mbps/54Mbps IEEE for 802.11n(HT20): 6.5Mbps/13Mbps/19.5Mbps/26Mbps/39Mbps/52Mbps/58.5Mbps/65Mbps

	IEEE for 802.11n(HT40): 13.5Mbps/27Mbps/40.5Mbps/54Mbps/81Mbps/108Mbps/121.5Mbps/135Mbps
Product Type:	☒ Mobile ☐ Portable
Test Software of EUT:	CMD.exe
Antenna Type:	FPC antenna, Knife-edge antenna
Antenna Gain:	FPC antenna: 3.42 dBi, Knife-edge antenna: 5 dBi

Operation Frequency each of channel (802.11b/g/n HT20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		
Operation Frequency each of channel(802.11n HT40)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
3	2422MHz	6	2437MHz	9	2452MHz		
4	2427MHz	7	2442MHz				
5	2432MHz	8	2447MHz				

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

For 802.11b/g/n (HT20):

Channel	Frequency
The Lowest channel	2412MHz
The Middle channel	2437MHz
The Highest channel	2462MHz


For 802.11n (HT40):

Channel	Frequency
The Lowest channel	2422MHz
The Middle channel	2437MHz
The Highest channel	2452MHz

Note:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.4 Test Environment and Mode

Operating Environment:	
Radiated Emissions:	
Temperature:	25.3 °C
Humidity:	55 % RH
Atmospheric Pressure:	1009 mbar
Conducted Emissions:	
Temperature:	25.6 °C
Humidity:	60 % RH
Atmospheric Pressure:	1009 mbar
Radio conducted item test (RF Conducted test room):	
Temperature:	25.5 °C
Humidity:	52 % RH
Atmospheric Pressure:	1009 mbar
Test mode:	
Transmitting mode:	EUT is set in RF test mode in all supported modulation types, bandwidth and data rate, etc.
Run Software:	
	

4.5 Description of Support Units

The EUT has been tested with associated equipment below.

1) Support equipment

Description	Manufacturer	Model No.	Certification	Supplied by

2) Cable

Cable No.	Description	Manufacturer	Cable Type/Length	Supplied by
/	/	/	/	/

4.6 Test Location

All tests were performed at:

Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua New District, Shenzhen, Guangdong, China

4.7 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 4742.01)**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

- **FCC Registration No.: 522263**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

4.8 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **Shenzhen Huaxia Testing Technology Co., Ltd.** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

No.	Item	Uncertainty	Notes
1	Radiated Emission (Below 1GHz)	5.12dB	(1)
2	Radiated Emission (Above 1GHz)	4.60dB	(1)
3	Conducted Disturbance (0.15~30MHz)	3.34dB	(1)
4	Radio Frequency	3×10^{-8}	(1)
5	Duty cycle	0.6 %.	(1)
6	Occupied Bandwidth	1.1%	(1)
7	RF conducted power	0.86dB	(1)
8	RF power density	0.74	(1)
9	Conducted Spurious emissions	0.86dB	(1)
10	Temperature test	0.8℃	(1)
11	Humidity test	2.0%	(1)
12	Supply voltages	0.5 %.	(1)
13	Frequency Error	5.5 Hz	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

4.9 Deviation from Standards

None.

4.10 Abnormalities from Standard Conditions

None.

4.11 Other Information Requested by the Customer

None.

4.12 Equipment List


Test Equipment	Manufacturer	Model No.	Instrument No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESR7	CQA-005	2023/09/08	2024/09/07
Spectrum analyzer	R&S	FSU26	CQA-038	2023/09/08	2024/09/07
Spectrum analyzer	R&S	FSU40	CQA-075	2023/09/08	2024/09/07
Preamplifier	MITEQ	AFS4-00010300-18-10P-4	CQA-035	2023/09/08	2024/09/07
Preamplifier	MITEQ	AMF-6D-02001800-29-20P	CQA-036	2023/09/08	2024/09/07
Preamplifier	EMCI	EMC184055SE	CQA-089	2023/09/08	2024/09/07
Loop antenna	Schwarzbeck	FMZB1516	CQA-060	2021/09/16	2024/09/15
Bilog Antenna	R&S	HL562	CQA-011	2021/09/16	2024/09/15
Horn Antenna	R&S	HF906	CQA-012	2021/09/16	2024/09/15
Horn Antenna	Schwarzbeck	BBHA 9170	CQA-088	2021/09/16	2024/09/15
Coaxial Cable (Above 1GHz)	CQA	N/A	C007	2023/09/08	2024/09/07
Coaxial Cable (Below 1GHz)	CQA	N/A	C013	2023/09/08	2024/09/07
RF cable(9KHz~40GHz)	CQA	RF-01	CQA-079	2023/09/08	2024/09/07
Antenna Connector	CQA	RFC-01	CQA-080	2023/09/08	2024/09/07
Power Sensor	KEYSIGHT	U2021XA	CQA-30	2023/09/08	2024/09/07
N1918A Power Analysis Manager Power Panel	Agilent	N1918A	CQA-074	2023/09/08	2024/09/07
Power meter	R&S	NRVD	CQA-029	2023/09/08	2024/09/07
Power divider	MIDWEST	PWD-2533-02-SMA-79	CQA-067	2023/09/08	2024/09/07
EMI Test Receiver	R&S	ESR7	CQA-005	2023/09/08	2024/09/07
LISN	R&S	ENV216	CQA-003	2023/09/08	2024/09/07
Coaxial cable	CQA	N/A	CQA-C009	2023/09/08	2024/09/07
DC power	KEYSIGHT	E3631A	CQA-028	2023/09/08	2024/09/07

Test software:

	Manufacturer	Software brand
Radiated Emissions test software	Tonscend	JS1120-3
Conducted Emissions test software	Audix	e3
RF Conducted test software	Audix	e3


5 Test results and Measurement Data

5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
EUT Antenna:	
The antenna is FPC antenna. The connection/connection type between the antenna to the EUT's antenna port is: unique coupling. This is either permanently attachment or a unique coupling that satisfies the requirement.	
EUT Antenna:	
The antenna is Knife-edge antenna. The connection/connection type between the antenna to the EUT's antenna port is: unique coupling. This is either permanently attachment or a unique coupling that satisfies the requirement.	

EUT Antenna:	
The antenna is Knife-edge antenna. The connection/connection type between the antenna to the EUT's antenna port is: unique coupling. This is either permanently attachment or a unique coupling that satisfies the requirement.	


5.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2013		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	1) The mains terminal disturbance voltage test was conducted in a shielded room.		
	2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.		
	3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,		
	4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.		
	5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.		
Test Setup:			

Exploratory Test Mode:	Transmitting with all kind of modulations, data rates at lowest, middle and highest channel.
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate of 802.11b at middle channel is the worst case. Only the worst case is recorded in the report.
Test Voltage:	AC120V/60Hz
Test Results:	Pass

Measurement Data

Live Line:




	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.160	24.19	9.68	33.87	55.46	-21.59	Average	Line
2	0.160	36.73	9.68	46.41	65.46	-19.05	QP	Line
3	0.180	23.37	9.64	33.01	54.49	-21.48	Average	Line
4	0.180	34.55	9.64	44.19	64.49	-20.30	QP	Line
5	0.205	22.45	9.61	32.06	53.41	-21.35	Average	Line
6	0.205	31.24	9.61	40.85	63.41	-22.56	QP	Line
7	0.270	20.66	9.52	30.18	51.12	-20.94	Average	Line
8	0.270	26.21	9.52	35.73	61.12	-25.39	QP	Line
9	0.365	21.57	9.57	31.14	48.61	-17.47	Average	Line
10	0.365	27.35	9.57	36.92	58.61	-21.69	QP	Line
11	1.240	20.32	10.30	30.62	46.00	-15.38	Average	Line
12	1.240	25.68	10.30	35.98	56.00	-20.02	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral Line:





	Freq	Read	Factor	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.160	24.29	9.68	33.97	55.46	-21.49	Average	Neutral
2	0.160	36.76	9.68	46.44	65.46	-19.02	QP	Neutral
3	0.180	23.94	9.64	33.58	54.49	-20.91	Average	Neutral
4	0.180	34.17	9.64	43.81	64.49	-20.68	QP	Neutral
5	0.205	23.02	9.60	32.62	53.41	-20.79	Average	Neutral
6	0.205	31.23	9.60	40.83	63.41	-22.58	QP	Neutral
7 PP	0.350	26.99	9.55	36.54	48.96	-12.42	Average	Neutral
8 QP	0.350	32.96	9.55	42.51	58.96	-16.45	QP	Neutral
9	0.525	19.41	9.72	29.13	46.00	-16.87	Average	Neutral
10	0.525	24.33	9.72	34.05	56.00	-21.95	QP	Neutral
11	0.650	18.72	9.85	28.57	46.00	-17.43	Average	Neutral
12	0.650	23.69	9.85	33.54	56.00	-22.46	QP	Neutral

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

5.3 Conducted Peak & Average Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	ANSI C63.10: 2013
Test Setup:	<i>Setup for Power meter measurement method</i>  <i>Setup for Spectrum analyser measurement method</i> 
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Only the worst case is recorded in the report.
Limit:	30dBm
Test Results:	Pass

Test Result

Module 1 (AIC8800D40L) (

Test Mode	Antenna	Frequency [MHz]	Output Power[dBm]	Limit[dBm]	Verdict
11B	Ant1	2412	10.78	≤30	PASS
		2437	9.58	≤30	PASS
		2462	9.82	≤30	PASS
11G	Ant1	2412	5.58	≤30	PASS
		2437	4.85	≤30	PASS
		2462	5.57	≤30	PASS
11N20SISO	Ant1	2412	9.68	≤30	PASS
		2437	10.37	≤30	PASS
		2462	7.42	≤30	PASS
11N40SISO	Ant1	2422	7.10	≤30	PASS
		2437	7.00	≤30	PASS
		2452	7.45	≤30	PASS

Module 2 (RTL8192FS)

Test Mode	Antenna	Frequency [MHz]	Output Power[dBm]	Limit[dBm]	Verdict
11B	Ant2	2412	9.50	≤30	PASS
		2437	9.44	≤30	PASS
		2462	9.41	≤30	PASS
11G	Ant2	2412	10.22	≤30	PASS
		2437	9.22	≤30	PASS
		2462	9.06	≤30	PASS
11N20SISO	Ant2	2412	9.23	≤30	PASS
		2437	9.20	≤30	PASS
		2462	9.14	≤30	PASS
11N40SISO	Ant2	2422	8.59	≤30	PASS
		2437	9.03	≤30	PASS
		2452	9.05	≤30	PASS


Module 2 (RTL8192FS)


Test Mode	Antenna	Frequency [MHz]	Output Power[dBm]	Limit[dBm]	Verdict
11B	Ant3	2412	9.51	≤30	PASS
		2437	9.33	≤30	PASS
		2462	9.51	≤30	PASS
11G	Ant3	2412	9.21	≤30	PASS
		2437	9.22	≤30	PASS
		2462	9.26	≤30	PASS
11N20SISO	Ant3	2412	9.25	≤30	PASS
		2437	9.46	≤30	PASS
		2462	9.49	≤30	PASS
11N40SISO	Ant3	2422	9.12	≤30	PASS
		2437	9.07	≤30	PASS
		2452	9.52	≤30	PASS

Note: When Duty cycle >98%, D.C.F is not required.

Test Graphs


Module 1 (AIC8800D40L)






Date: 22 AUG. 2024 14:04:25

11G_Ant1_2412




Date: 22 AUG. 2024 14:10:14

11G_Ant1_2437




Date: 22 AUG. 2024 14:11:53

11G_Ant1_2462




Date: 22 AUG 2024 14:13:41

11N20SISO_Ant1_2412




Date: 26 AUG 2024 17:09:04

11N20SISO_Ant1_2437




Date: 26 AUG. 2024 17:11:24

11N20SISO_Ant1_2462




Date: 26 AUG. 2024 17:13:52


11N40SISO_Ant1_2422




Date: 26 AUG. 2024 17:15:48




Module 2 (RTL8192FS)







11B_Ant2_2437



11B_Ant2_2462




11G_Ant2_2412




Date: 26 AUG 2024 17:32:08

11G_Ant2_2437




Date: 26 AUG 2024 17:34:36


11G_Ant2_2462




11N20SISO_Ant2_2412



11N20SISO_Ant2_2437




11N20SISO_Ant2_2462




Date: 26 AUG 2024 17:45:19

11N40SISO_Ant2_2422




Date: 26 AUG 2024 17:47:12

11N40SISO_Ant2_2437




11N40SISO_Ant2_2452




Module 2 (RTL8192FS)


11B_Ant3_2412




11B_Ant3_2437



11B_Ant3_2462




11G_Ant3_2412




Date: 26 AUG 2024 18:11:06

11G_Ant3_2437




Date: 26 AUG 2024 18:13:02

11G_Ant3_2462




Date: 26 AUG.2024 18:14:41

11N20SISO_Ant3_2412




Date: 26 AUG.2024 18:16:31

11N20SISO_Ant3_2437




Date: 26 AUG.2024 18:18:40

11N20SISO_Ant3_2462




Date: 26 AUG 2024 18:20:36

11N40SISO_Ant3_2422




Date: 26 AUG 2024 18:23:34


11N40SISO_Ant3_2437



11N40SISO_Ant3_2452



5.4 6dB Occupied Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	ANSI C63.10: 2013
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Only the worst case is recorded in the report.
Limit:	≥ 500 kHz
Test Results:	Pass

Test Result

Module 1 (AIC8800D40L)

TestMode	Antenna	Channel	DTS BW [MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	9.56	0.5	PASS
		2437	9.56	0.5	PASS
		2462	9.56	0.5	PASS
11G	Ant1	2412	11.32	0.5	PASS
		2437	12.56	0.5	PASS
		2462	13.80	0.5	PASS
11N20SISO	Ant1	2412	16.44	0.5	PASS
		2437	16.32	0.5	PASS
		2462	12.76	0.5	PASS
11N40SISO	Ant1	2422	35.04	0.5	PASS
		2437	36.08	0.5	PASS
		2452	31.36	0.5	PASS

Module 2 (RTL8192FS)


TestMode	Antenna	Channel	DTS BW [MHz]	Limit[MHz]	Verdict
11B	Ant2	2412	8.56	0.5	PASS
		2437	8.04	0.5	PASS
		2462	7.56	0.5	PASS
11G	Ant2	2412	15.92	0.5	PASS
		2437	15.68	0.5	PASS
		2462	12.56	0.5	PASS
11N20SISO	Ant2	2412	16.40	0.5	PASS
		2437	16.32	0.5	PASS
		2462	12.64	0.5	PASS
11N40SISO	Ant2	2422	35.36	0.5	PASS
		2437	35.84	0.5	PASS
		2452	31.36	0.5	PASS

Module 2 (RTL8192FS)

TestMode	Antenna	Channel	DTS BW [MHz]	Limit[MHz]	Verdict
11B	Ant3	2412	8.56	0.5	PASS
		2437	7.56	0.5	PASS
		2462	7.04	0.5	PASS
11G	Ant1	2412	15.72	0.5	PASS
		2437	15.36	0.5	PASS
		2462	12.56	0.5	PASS
11N20SISO	Ant1	2412	16.36	0.5	PASS
		2437	16.40	0.5	PASS
		2462	13.24	0.5	PASS
11N40SISO	Ant1	2422	35.04	0.5	PASS
		2437	35.84	0.5	PASS
		2452	31.36	0.5	PASS


Test Graphs

Module 1 (AIC8800D40L)







11G Ant1 2412



11G Ant1 2437




11G_Ant1_2462




Date: 22 AUG 2024 14:13:28

11N20SISO_Ant1_2412




Date: 26 AUG 2024 17:08:51


11N20SISO_Ant1_2437




11N20SISO_Ant1_2462



11N40SISO_Ant1_2422




11N40SISO_Ant1_2437



Date: 26 AUG 2024 17:20:24


11N40SISO_Ant1_2452




Date: 26 AUG 2024 17:21:59

Module 2 (RTL8192FS)


11B_Ant2_2412




11B_Ant2_2437



11B_Ant2_2462




11G_Ant2_2412




Date: 26 AUG 2024 17:31:55

11G_Ant2_2437




Date: 26 AUG 2024 17:34:23

11G_Ant2_2462




Date: 26 AUG.2024 17:35:55

11N20SISO_Ant2_2412




Date: 26 AUG.2024 17:39:14

11N20SISO_Ant2_2437




Date: 26 AUG.2024 17:43:35

11N20SISO_Ant2_2462




Date: 26 AUG 2024 17:45:06

11N40SISO_Ant2_2422




Date: 26 AUG 2024 17:46:59

11N40SISO_Ant2_2437



11N40SISO_Ant2_2452




Module 2 (RTL8192FS)


11B_Ant3_2412




11B_Ant3_2437



11B_Ant3_2462




11G_Ant3_2412




Date: 26 AUG 2024 18:10:53

11G_Ant3_2437




Date: 26 AUG 2024 18:12:49

11G_Ant3_2462




Date: 26 AUG.2024 18:14:28

11N20SISO_Ant3_2412



Date: 26 AUG.2024 18:16:18

11N20SISO_Ant3_2437



Date: 26 AUG.2024 18:18:26