

## **MODULAR APPROVAL LETTER**

2019-12-19

Applicant : EVERINT Co.,Ltd.

## FCC ID: 2AKMF-BT-MSOIII

We would like to answer for Single Modular Approval in accordance with the requirement of rule part 15.212 as described below

No.	Requirements	Comment	Comply (Y/N)
1	The radio element of the modular transmitter has its own shielding	Refer to the external photo	Υ
2	The modular transmitter must have buffered modulation	All input to the modules are	r inputs.
	data/inputs (if such inputs are provided)	buffered through microprocessor inputs.	
3	The modular transmitter must have its own power supply	Internal power regulators	Υ
	regulation.	Refer to the Block-diagram	
4	The modular transmitter must comply with the antenna	Refer to the internal photo	Υ
	requirements of Section 15.203 and 15.204(c).		
5	The modular transmitter must be tested in a stand-alone	The EUT was tested in a standalone	
	configuration, i.e., the module must not be inside another device	configuration via a SD extension cable	Υ
	during testing.	Refer to the test setup photo	
6	The modular transmitter must be labeled with its own FCC ID.	Refer to the user manual	Υ
	If the FCC ID is not visible when the module is installed inside		
	another device, then the outside of the device into which the		
	module is installed must also display a label referring to the		
	enclosed module		
7	The modular transmitter must comply with any specific rules or	Refer to the user manual	Y
	operating requirements that ordinarily apply to a complete		
	transmitter and the manufacturer must provide adequate		
	instructions along with the module to explain any such		
	requirements		
8	The modular transmitter must comply with any applicable RF	Refer to the RF exposure	Y
	exposure requirements	statement for more details.	

Sincerely,

JiSung Shin / Manager EVERINT Co.,Ltd.