

RF EXPOSURE REPORT

REPORT NO.: SA140415C27

MODEL NO.: PCE4552AH

FCC ID: QXO-57G45

RECEIVED: Mar. 07, 2014

TESTED: Apr. 09 ~ May 30, 2014

ISSUED: Jun. 05, 2014

APPLICANT: Extreme Networks, Inc.

ADDRESS: 9 Northeastern Blvd. Salem, New Hampshire,
United States, 03079

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist.,
New Taipei City, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by any government agencies.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1. CERTIFICATION	4
2. RF EXPOSURE.....	5
2.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	5
2.2 MPE CALCULATION FORMULA	5
2.3 CLASSIFICATION	5
2.4 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	6



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA140415C27	Original release.	Jun. 05, 2014

1. CERTIFICATION

PRODUCT: DBDC 3X3 AP

MODEL: PCE4552AH

BRAND: Extreme

APPLICANT: Extreme Networks, Inc.

TESTED: Apr. 09 ~ May 30, 2014

TEST SAMPLE: ENGINEERING SAMPLE

STANDARDS: FCC Part 2 (Section 2.1091)

FCC OET Bulletin 65, Supplement C (01-01)

IEEE C95.1

The above equipment (Model: PCE4552AH) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY :  , **DATE :** Jun. 05, 2014
Pettie Chen / Senior Specialist

APPROVED BY :  , **DATE :** Jun. 05, 2014
Ken Liu / Senior Manager

2. RF EXPOSURE

2.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

2.2 MPE CALCULATION FORMULA

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away or farther depends on the antenna type used as evaluated in following section. So, this device is classified as Mobile Device.

2.4 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

Ant.	FREQUENCY BAND (MHz)	MAX POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
1	5745-5825	29.96	9.77	28	0.954	1
2	5745-5825	19.20	26.01	52	0.977	1
3	5745-5825	24.36	16.27	31	0.957	1
4	5745-5825	27.99	12.77	31	0.986	1
5	5745-5825	27.43	6.77	20	0.523	1
6	5745-5825	28.99	11.77	32	0.926	1
6	5180-5240	15.61	11.77	32	0.043	1
7	5745-5825	28.03	11.97	29	0.945	1

NOTE:

Ant. 1: Directional gain = 5dBi + 10log(3) = 9.77dBi

Ant. 2: Directional gain = 23dBi + 10log(2) = 26.01dBi

Ant. 3: Directional gain = 11.5dBi + 10log(3) = 16.27dBi

Ant. 4: Directional gain = 8dBi + 10log(3) = 12.77dBi

Ant. 5: Directional gain = 2dBi + 10log(3) = 6.77dBi

Ant. 6: Directional gain = 7dBi + 10log(3) = 11.77dBi

Ant. 7: Directional gain = 7.2dBi + 10log(3) = 11.97dBi

CONCLUSION:

For antenna 6:

Only antenna 6 can support both 5180~5240MHz and 5745~5825MHz co-transmit, the formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

$$1. \text{ WLAN 5GHz (5180~5240MHz) Antenna 6 + WLAN 5.0GHz (5745~5825MHz) Antenna 6} \\ = 0.926 + 0.043 = 0.969$$

Therefore, the maximum calculation of this situation is 0.969, which is less than the "1" limit.