




RADIO TEST REPORT

FCC ID : NKR-ATT CGW450
Equipment : 5G Residential Gateway
Brand Name : WNC
Model Name : CGW450-400
Applicant : Wistron NeWeb Corp.
20 Park Avenue II, Hsinchu Science Park, Hsinchu 308,
Taiwan, R.O.C
Manufacturer : NEWEB VIET NAM CO., LTD.
Land Lot CN01, Dong Van III Industrial zone, Dong Van
Ward, Duy Tien Town, Ha Nam Province, VietNam
Standard : 47 CFR FCC Part 15.247

The product was received on Aug. 01, 2022, and testing was started from Aug. 03, 2022 and completed on Aug. 15, 2022. We, Sporton International Inc. Hsinchu Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2013 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. Hsinchu Laboratory, the test report shall not be reproduced except in full.



Approved by: Sam Chen

Sporton International Inc. Hsinchu Laboratory
No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)



Table of Contents

History of this test report	3
Summary of Test Result	4
1 General Description	5
1.1 Information	5
1.2 Applicable Standards	9
1.3 Testing Location Information	9
1.4 Measurement Uncertainty	10
2 Test Configuration of EUT	11
2.1 Test Channel Mode	11
2.2 The Worst Case Measurement Configuration	12
2.3 EUT Operation during Test	13
2.4 Accessories	13
2.5 Support Equipment	13
2.6 Test Setup Diagram	14
3 Transmitter Test Result	16
3.1 AC Power-line Conducted Emissions	16
3.2 DTS Bandwidth	18
3.3 Maximum Conducted Output Power	19
3.4 Power Spectral Density	22
3.5 Emissions in Non-restricted Frequency Bands	24
3.6 Emissions in Restricted Frequency Bands	25
4 Test Equipment and Calibration Data	29
Appendix A. Test Results of AC Power-line Conducted Emissions	
Appendix B. Test Results of DTS Bandwidth	
Appendix C. Test Results of Maximum Conducted Output Power	
Appendix D. Test Results of Power Spectral Density	
Appendix E. Test Results of Emissions in Non-restricted Frequency Bands	
Appendix F. Test Results of Emissions in Restricted Frequency Bands	
Appendix G. Test Results of Radiated Emission Co-location	
Appendix H. Test Photos	
Photographs of EUT v02	



TEL : 886-3-656-9065
FAX : 886-3-656-9085
Report Template No.: CB-A10_10 Ver1.3



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
1.1.2	15.203	Antenna Requirement	PASS	-
3.1	15.207	AC Power-line Conducted Emissions	PASS	-
3.2	15.247(a)	DTS Bandwidth	PASS	-
3.3	15.247(b)	Maximum Conducted Output Power	PASS	-
3.4	15.247(e)	Power Spectral Density	PASS	-
3.5	15.247(d)	Emissions in Non-restricted Frequency Bands	PASS	-
3.6	15.247(d)	Emissions in Restricted Frequency Bands	PASS	-

Declaration of Conformity:

1. The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers. It's means measurement values may risk exceeding the limit of regulation standards, if measurement uncertainty is include in test results.
2. The measurement uncertainty please refer to report "Measurement Uncertainty".

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Sam Chen**Report Producer: Sandy Chuang**



1 General Description

1.1 Information

1.1.1 RF General Information

Frequency Range (MHz)	IEEE Std. 802.11	Ch. Frequency (MHz)	Channel Number
2400-2483.5	b, g, n (HT20), VHT20, ax (HEW20)	2412-2462	1-11 [11]
2400-2483.5	n (HT40), VHT40, ax (HEW40)	2422-2452	3-9 [7]

Band	Mode	BWch (MHz)	Nant
2.4-2.4835GHz	802.11b	20	4TX
2.4-2.4835GHz	802.11g	20	4TX
2.4-2.4835GHz	802.11n HT20	20	4TX
2.4-2.4835GHz	VHT20	20	4TX
2.4-2.4835GHz	802.11ax HEW20	20	4TX
2.4-2.4835GHz	802.11n HT40	40	4TX
2.4-2.4835GHz	VHT40	40	4TX
2.4-2.4835GHz	802.11ax HEW40	40	4TX

Note:

- ♦ 11b mode uses a combination of DSSS-DBPSK, DQPSK, CCK modulation.
- ♦ 11g, HT20 and HT40 use a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.
- ♦ VHT20, VHT40 use a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM, 256QAM modulation.
- ♦ HEW20, HEW40 use a combination of OFDMA-BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM modulation.
- ♦ BWch is the nominal channel bandwidth.

1.1.2 Antenna Information

Ant.	Port		Brand	Model Name	Antenna Type	Connector	Modes of Operation
	WLAN 2.4GHz	WLAN 5GHz					
1	1	1	WNC	48XKAC42	Dipole	I-PEX	WLAN 2.4GHz, 5GHz UNII 1, 3
2	2	2	WNC	48XKAC3F	Dipole	I-PEX	
3	3	3	WNC	48XKAC45	Dipole	I-PEX	
4	4	4	WNC	48XKAC46	Dipole	I-PEX	
5	-	-	WNC	48XKAC3G	Dipole	I-PEX	WLAN 6GHz
6	-	-	WNC	48XKAC3G	Dipole	I-PEX	
7	-	-	WNC	48XKAC3G	Dipole	I-PEX	
8	-	-	WNC	48XKAC3N	Dipole	I-PEX	
9	5	-	WNC	48XKAC3H	Dipole	I-PEX	WLAN 5GHz UNII 2C
10	-	-	WNC	48XKAC3L	Dipole	I-PEX	WWAN full band
11	-	-	WNC	48XKAC3P	Dipole	I-PEX	
12	-	-	WNC	48XKAC3R	Dipole	I-PEX	WWAN dual band
13	-	-	WNC	48XKAC3X	Dipole	I-PEX	
14	-	-	WNC	48XKAC3J	Dipole	I-PEX	
15	-	-	WNC	48XKAC3K	Dipole	I-PEX	WWAN single band
16	-	-	WNC	48XKAC3Y	Dipole	I-PEX	
17	-	-	WNC	48XKAC3Z	Dipole	I-PEX	

Ant.	Antenna Gain (dBi)									
	WLAN 2.4GHz			WLAN 5GHz UNII 1			WLAN 5GHz UNII 3			
1	6.15			4.38			5.49			
2	5.22			3.21			5.48			
3	4.46			4.16			4.07			
4	4.87			4.01			5.91			
Freq.	700 MHz	780 MHz	850 MHz	1800 MHz	2100 MHz	2300 MHz	3300 MHz	4200 MHz		
10	1.7	2.1	3.8	2.8	2.6	5.6	5.0	2.2		
11	2.2	2.8	0.9	3.9	2.4	3.9	4.5	3.4		
Freq.	1800 MHz		2100 MHz		2300 MHz		3300 MHz		4200 MHz	
12	4.1		3.2		3.3		2.8		3.1	
13	3.3		4.1		4.2		3.6		3.5	
14	2.8		3.6		2.7		5.2		4.5	
Freq.	3300 MHz					4200 MHz				
15	4.2					3.6				
16	4.2					3.7				
17	3.0					3.0				

Note1: The above information was declared by manufacturer.

Note2: The antenna 5~9 don't function in this application.

Note3: **For WLAN 2.4GHz function:**

For IEEE 802.11 b/g/n/VHT/ax (4TX/4RX):

Port 1, Port 2, Port 3 and Port 4 can be used as transmitting/receiving antenna.

Port 1, Port 2, Port 3 and Port 4 could transmit/receive simultaneously.

For WLAN 5GHz function:

For IEEE 802.11a/n/ac/ax (4TX/5RX that it includes 1RX for UNII 2A):

Port 1, Port 2, Port 3 and Port 4 can be used as transmitting/receiving antenna.

Port 1, Port 2, Port 3, Port 4 and Port 5 could transmit/receive simultaneously.

Note4: The EUT doesn't enable the DFS band at this time.

**1.1.3 Mode Test Duty Cycle**

Mode	DC	DCF(dB)	T(s)	VBW(Hz) $\geq 1/T$
802.11b	0.994	0.03	n/a (DC $\geq$ 0.98)	n/a (DC $\geq$ 0.98)
802.11g	0.992	0.03	n/a (DC $\geq$ 0.98)	n/a (DC $\geq$ 0.98)
802.11ax HEW20	0.992	0.03	n/a (DC $\geq$ 0.98)	n/a (DC $\geq$ 0.98)
802.11ax HEW40	0.992	0.03	n/a (DC $\geq$ 0.98)	n/a (DC $\geq$ 0.98)

Note:

- ♦ DC is Duty Cycle.
- ♦ DCF is Duty Cycle Factor.

1.1.4 EUT Operational Condition

EUT Power Type	From power adapter			
Beamforming Function	☐	With beamforming	☒	Without beamforming
Function	☒	Point-to-multipoint	☐	Point-to-point
Test Software Version	Mtool_3.2.1.4			

Note: The above information was declared by manufacturer.

1.1.5 Table for Certified WWAN Module Information

Brand Name	Model Name	FCC ID	Bands
WNC	IMQC	NKRIMQC	4G Band (LTE): B2/B5/B12/B14/B30/B66 5G Band (NR): n2/n5/n12/n30/n66/n77(3450~3550MHz)/n77(3700~3980MHz)

Note: The above information was declared by manufacturer.



1.2 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 15.247
- ♦ ANSI C63.10-2013

The following reference test guidance is not within the scope of accreditation of TAF.

- ♦ FCC KDB 558074 D01 v05r02
- ♦ FCC KDB 662911 D01 v02r01
- ♦ FCC KDB 414788 D01 v01r01

1.3 Testing Location Information

Testing Location Information	
Test Lab. : Sporton International Inc. Hsinchu Laboratory	
Hsinchu	ADD: No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)
(TAF: 3787)	TEL: 886-3-656-9065 FAX: 886-3-656-9085
	Test site Designation No. TW3787 with FCC.
	Conformity Assessment Body Identifier (CABID) TW3787 with ISED.

Test Condition	Test Site No.	Test Engineer	Test Environment (°C / %)	Test Date
RF Conducted	TH02-CB	Jay Lo	23.5-23.8 / 52-58	Aug. 04, 2022
Radiated <Below 1GHz>	03CH06-CB	Gordon Huang	23.8~25.2 / 63~69	Aug. 15, 2022
Radiated <Above 1GHz>	03CH02-CB	Gordon Huang	23.8~25 / 65~67	Aug. 03, 2022~ Aug. 05, 2022
Radiated <Co-location>	03CH03-CB	Gordon Huang	24.7~26.1 / 65~65	Aug. 03, 2022~ Aug. 05, 2022
AC Conduction	CO02-CB	Ryan Huang	22~24 / 55~56	Aug. 15, 2022

1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	3.4 dB	Confidence levels of 95%
Radiated Emission (9kHz ~ 30MHz)	3.4 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	5.6 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	5.2 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	4.7 dB	Confidence levels of 95%
Conducted Emission	3.2 dB	Confidence levels of 95%
Output Power Measurement	0.8 dB	Confidence levels of 95%
Power Density Measurement	3.2 dB	Confidence levels of 95%
Bandwidth Measurement	2.0 %	Confidence levels of 95%



2 Test Configuration of EUT

2.1 Test Channel Mode

Mode	Power Setting
802.11b_Nss1,(1Mbps)_4TX	-
2412MHz	98
2437MHz	97
2462MHz	94
802.11g_Nss1,(6Mbps)_4TX	-
2412MHz	97
2437MHz	92
2457MHz	92
2462MHz	79
802.11ax HEW20_Nss1,(MCS0)_4TX	-
2412MHz	96
2437MHz	86
2457MHz	86
2462MHz	74
802.11ax HEW40_Nss1,(MCS0)_4TX	-
2422MHz	82
2437MHz	72
2452MHz	69

Note : Evaluated HEW20/HEW40 mode only, due to similar modulation. The power setting of HT20/HT40/VHT20/VHT40 mode are the same or lower than HEW20/HEW40.



2.2 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Condition	AC power-line conducted measurement for line and neutral Test Voltage: 120Vac / 60Hz
Operating Mode	CTX
1	EUT_WLAN 2.4GHz
2	EUT_WLAN 5GHz
For operating mode 2 is the worst case and it was record in this test report.	

The Worst Case Mode for Following Conformance Tests	
Tests Item	DTS Bandwidth Maximum Conducted Output Power Power Spectral Density Emissions in Non-restricted Frequency Bands
Test Condition	Conducted measurement at transmit chains

The Worst Case Mode for Following Conformance Tests	
Tests Item	Emissions in Restricted Frequency Bands
Test Condition	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.
Operating Mode < 1GHz	CTX
The EUT was performed at X axis, Y axis and Z axis position for Radiated measurement<Above 1GHz>, and the worst case was found at X axis position for 2.4GHz and Y axis position for 5GHz.	
1	EUT in X axis_WLAN 2.4GHz
2	EUT in Y axis_WLAN 5GHz
For operating mode 2 is the worst case and it was record in this test report.	
Operating Mode > 1GHz	CTX
The EUT was performed at X axis, Y axis and Z axis position, and the worst case was found at X axis. So the measurement will follow this same test configuration.	
1	EUT in X axis



The Worst Case Mode for Following Conformance Tests	
Tests Item	Simultaneous Transmission Analysis - Radiated Emission Co-location
Test Condition	Radiated measurement
Operating Mode	Normal Link
The EUT was performed at X axis, Y axis and Z axis position. EUT Y axis has been evaluated to be the worst case at Radiated measurement <Above 1GHz>; thus, the measurement will follow this same test configuration	
1	EUT in Y axis: WLAN 2.4GHz + WLAN 5GHz
Refer to Appendix G for Radiated Emission Co-location.	

The Worst Case Mode for Following Conformance Tests	
Tests Item	Simultaneous Transmission Analysis - Co-location RF Exposure Evaluation
Operating Mode	
1	WLAN 2.4GHz + WLAN 5GHz + WWAN
Refer to Sporton Test Report No.: FA280117 for Co-location RF Exposure Evaluation.	

2.3 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

2.4 Accessories

Accessories			
Equipment Name	Brand Name	Model Name	Rating
AC Adapter	AT&T	EPS72R0-16	INPUT: 120V~1.8A, 60Hz OUTPUT: 12V, 6A, 72W

2.5 Support Equipment


For AC Conduction:


Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
A	LAN NB	DELL	E6430	N/A
B	Flash disk3.0	Transcend	JetFlash-700	N/A

For Radiated and RF Conducted:

Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
A	Notebook	DELL	E4300	N/A

2.6 Test Setup Diagram



Test Setup Diagram - Radiated Test


Item	Connection	Shielded	Length
1	Power cable	No	3m
2	RJ-45 cable	No	10m

3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedures

Test Method
☒ Refer as ANSI C63.10-2013, clause 6.2 for AC power-line conducted emissions.

3.1.4 Test Setup



3.1.5 Measurement Results Calculation

The measured Level is calculated using:

- Corrected Reading: LISN Factor (LISN) + Attenuator (AT/AUX) + Cable Loss (CL) + Read Level (Raw) = Level
- Margin = -Limit + Level

3.1.6 Test Result of AC Power-line Conducted Emissions

Refer as Appendix A

3.2 DTS Bandwidth

3.2.1 6dB Bandwidth Limit

6dB Bandwidth Limit
Systems using digital modulation techniques:
6 dB bandwidth $\geq$ 500 kHz.


3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures

Test Method
For the emission bandwidth shall be measured using one of the options below:
☒ Refer as FCC KDB 558074, clause 8.2 & C63.10 clause 11.8.1 Option 1 for 6 dB bandwidth measurement.
☐ Refer as FCC KDB 558074, clause 8.2 & C63.10 clause 11.8.2 Option 2 for 6 dB bandwidth measurement.
☐ Refer as ANSI C63.10, clause 6.9.1 for occupied bandwidth testing.

3.2.4 Test Setup



3.2.5 Test Result of Emission Bandwidth

Refer as Appendix B

3.3 Maximum Conducted Output Power

3.3.1 Maximum Conducted Output Power Limit

Maximum Conducted Output Power Limit	
	▪ If $G_{TX} \leq 6$ dBi, then $P_{Out} \leq 30$ dBm (1 W)
	▪ Point-to-multipoint systems (P2M): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$ dBm
	▪ Point-to-point systems (P2P): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	▪ Smart antenna system (SAS):
	- Single beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	- Overlap beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	- Aggregate power on all beams: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3 + 8$ dB dBm
P_{Out} = maximum peak conducted output power or maximum conducted output power in dBm, G_{TX} = the maximum transmitting antenna directional gain in dBi.	

3.3.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.



3.3.3 Test Procedures

Test Method	
Maximum Peak Conducted Output Power	
☐	Refer as FCC KDB 558074, clause 8.3.1.1 & C63.10 clause 11.9.1.1 (RBW ≥ EBW method).
☐	Refer as FCC KDB 558074, clause 8.3.1.3 & C63.10 clause 11.9.1.3 (peak power meter).
Maximum Conducted Output Power	
[duty cycle ≥ 98% or external video / power trigger]	
☐	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.2 Method AVGSA-1.
☐	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.3 Method AVGSA-1A. (alternative)
duty cycle < 98% and average over on/off periods with duty factor	
☐	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.4 Method AVGSA-2.
☐	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.5 Method AVGSA-2A (alternative)
☐	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.6 Method AVGSA-3
☐	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.7 Method AVGSA-3A (alternative)
Measurement using a power meter (PM)	
☐	Refer as FCC KDB 558074, clause 8.3.2.3 & C63.10 clause 11.9.2.3.1 Method AVGPM (using an RF average power meter).
☒	Refer as FCC KDB 558074, clause 8.3.2.3 & C63.10 clause 11.9.2.3.2 Method AVGPM-G (using an gate RF average power meter).
For conducted measurement.	
If the EUT supports multiple transmit chains using options given below: Refer as FCC KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them.	
If multiple transmit chains, EIRP calculation could be following as methods: $P_{total} = P_1 + P_2 + \dots + P_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = P_{total} + DG$	

3.3.4 Test Setup



3.3.5 Test Result of Maximum Conducted Output Power

Refer as Appendix C



3.4 Power Spectral Density

3.4.1 Power Spectral Density Limit

Power Spectral Density Limit
▪ Power Spectral Density (PSD) ≤ 8 dBm/3kHz


3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.4.3 Test Procedures

Test Method	
▪ Peak power spectral density procedures that the same method as used to determine the conducted output power. If maximum peak conducted output power was measured to demonstrate compliance to the output power limit, then the peak PSD procedure below (Method PKPSD) shall be used. If maximum conducted output power was measured to demonstrate compliance to the output power limit, then one of the average PSD procedures shall be used, as applicable based on the following criteria (the peak PSD procedure is also an acceptable option).	
☒	Refer as FCC KDB 558074, clause 8.4 & C63.10 clause 11.10 Method Max. PSD.
▪ For conducted measurement.	
▪ If The EUT supports multiple transmit chains using options given below:	
☒	Option 1: Measure and sum the spectra across the outputs. Refer as FCC KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the NTX output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace.
☐	Option 2: Measure and sum spectral maxima across the outputs. With this technique, spectra are measured at each output of the device at the required resolution bandwidth. The maximum value (peak) of each spectrum is determined. These maximum values are then summed mathematically in linear power units across the outputs. These operations shall be performed separately over frequency spans that have different out-of-band or spurious emission limits,
☐	Option 3: Measure and add 10 log(N) dB, where N is the number of transmit chains. Refer as FCC KDB 662911, In-band power spectral density (PSD). Performed at each transmit chains and each transmit chains shall be compared with the limit have been reduced with 10 log(N). Or each transmit chains shall be add 10 log(N) to compared with the limit.

3.4.4 Test Setup



3.4.5 Test Result of Power Spectral Density

Refer as Appendix D

3.5 Emissions in Non-restricted Frequency Bands

3.5.1 Emissions in Non-restricted Frequency Bands Limit

Un-restricted Band Emissions Limit	
RF output power procedure	Limit (dBc)
Peak output power procedure	20
Average output power procedure	30
Note 1: If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level. Note 2: If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.	


3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.5.3 Test Procedures

Test Method
Refer as FCC KDB 558074, clause 8.5 for unwanted emissions into non-restricted bands.

3.5.4 Test Setup



3.5.5 Test Result of Emissions in Non-restricted Frequency Bands

Refer as Appendix E

3.6 Emissions in Restricted Frequency Bands

3.6.1 Emissions in Restricted Frequency Bands Limit

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Note 3: Using the distance of 1m during the test for above 18 GHz, and the test value to correct for the distance factor at 3m.

3.6.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.




3.6.3 Test Procedures

Test Method	
▪ The average emission levels shall be measured in [duty cycle ≥ 98 or duty factor].	
▪ Refer as ANSI C63.10, clause 6.10.3 band-edge testing shall be performed at the lowest frequency channel and highest frequency channel within the allowed operating band.	
▪ For the transmitter unwanted emissions shall be measured using following options below:	
	▪ Refer as FCC KDB 558074, clause 8.6 for unwanted emissions into restricted bands.
	☐ Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.5.1(trace averaging for duty cycle $\geq 98\%$).
	☐ Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.5.2(trace averaging + duty factor).
	☒ Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.5.3(Reduced VBW $\geq 1/T$).
	☐ Refer as ANSI C63.10, clause 11.12.2.5.3 (Reduced VBW). VBW $\geq 1/T$, where T is pulse time.
	☐ Refer as ANSI C63.10, clause 7.5 average value of pulsed emissions.
	☒ Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.4 measurement procedure peak limit.
▪ For the transmitter band-edge emissions shall be measured using following options below:	
	▪ Refer as FCC KDB 558074 clause 8.7 & C63.10 clause 11.13.1, When the performing peak or average radiated measurements, emissions within 2 MHz of the authorized band edge may be measured using the marker-delta method described below.
	▪ Refer as FCC KDB 558074, clause 8.7 (ANSI C63.10, clause 6.10.6) for marker-delta method for band-edge measurements.
	▪ Refer as FCC KDB 558074, clause 8.7 for narrower resolution bandwidth (100kHz) using the band power and summing the spectral levels (i.e., 1 MHz).
	▪ For conducted unwanted emissions into restricted bands (absolute emission limits). Devices with multiple transmit chains using options given below: (1) Measure and sum the spectra across the outputs or (2) Measure and add 10 log(N) dB
	▪ For FCC KDB 662911 The methodology described here may overestimate array gain, thereby resulting in apparent failures to satisfy the out-of-band limits even if the device is actually compliant. In such cases, compliance may be demonstrated by performing radiated tests around the frequencies at which the apparent failures occurred.

3.6.4 Test Setup





3.6.5 Measurement Results Calculation

The measured Level is calculated using:

Corrected Reading: Antenna factor (AF) + Cable loss (CL) + Read level (Raw) - Preamp factor (PA)(if applicable) = Level.

3.6.6 Emissions in Restricted Frequency Bands (Below 30MHz)

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to KDB414788 Radiated Test Site, and the result came out very similar.

All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

The radiated emissions were investigated from 9 kHz or the lowest frequency generated within the device, up to the 10th harmonic or 40 GHz, whichever is appropriate.

3.6.7 Test Result of Emissions in Restricted Frequency Bands

Refer as Appendix F



4 Test Equipment and Calibration Data

Instrument	Brand	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
LISN	Schwarzbeck	NSLK 8127	8127650	9kHz ~ 30MHz	Jan. 07, 2022	Jan. 06, 2023	Conduction (CO02-CB)
LISN	Schwarzbeck	NSLK 8127	8127478	9kHz ~ 30MHz	Dec. 22, 2021	Dec. 21, 2022	Conduction (CO02-CB)
EMI Receiver	Agilent	N9038A	MY52260140	9kHz ~ 8.4GHz	May 06, 2022	May 05, 2023	Conduction (CO02-CB)
Pulse Limiter	Schwarzbeck	VTSD 9561F-N	00378	9kHz ~ 30MHz	Mar. 18, 2022	Mar. 17, 2023	Conduction (CO02-CB)
COND Cable	Woken	Cable	2	0.15MHz ~ 30MHz	Oct. 19, 2021	Oct. 18, 2022	Conduction (CO02-CB)
Software	SPORTON	SENSE	V5.10	-	N.C.R.	N.C.R.	Conduction (CO02-CB)
Loop Antenna	Teseq	HLA 6120	24155	9kHz - 30 MHz	May 14, 2022	May 13, 2023	Radiation (03CH06-CB)
3m Semi Anechoic Chamber NSA	TDK	SAC-3M	03CH01-CB	30 MHz ~ 1 GHz	Jan. 25, 2022	Jan. 24, 2023	Radiation (03CH06-CB)
BILOG ANTENNA with 6dB Attenuator	TESEQ & EMCI	CBL6112D N-6-06	37880 & AT-N0609	20MHz ~ 2GHz	Feb. 21, 2022	Feb. 20, 2023	Radiation (03CH06-CB)
Amplifier	EMCI	EMC330N	980332	20MHz ~ 3GHz	Jul. 01, 2022	Jun. 30, 2023	Radiation (03CH06-CB)
Spectrum Analyzer	R&S	FSP40	100056	9kHz ~ 40GHz	May 06, 2022	May 05, 2023	Radiation (03CH06-CB)
EMI Test Receiver	R&S	ESCS	826547/017	9kHz ~ 2.75GHz	Jun. 17, 2022	Jun. 16, 2023	Radiation (03CH06-CB)
RF Cable-low	Woken	RG402	Low Cable-16+17	30 MHz ~ 1 GHz	Oct. 04, 2021	Oct. 03, 2022	Radiation (03CH06-CB)
Test Software	SPORTON	SENSE	V5.10	-	N.C.R.	N.C.R.	Radiation (03CH06-CB)
3m Semi Anechoic Chamber VSWR	RIKEN	SAC-3M	03CH02-CB	1GHz ~18GHz	Mar. 26, 2022	Mar. 25, 2023	Radiation (03CH02-CB)
Horn Antenna	EMCO	3115	9610-4976	1GHz ~ 18GHz	Apr. 19, 2022	Apr. 18, 2023	Radiation (03CH02-CB)
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170507	15GHz ~ 40GHz	Jul. 05, 2022	Jul. 04, 2023	Radiation (03CH02-CB)
Pre-Amplifier	Agilent	83017A	MY39501305	1GHz ~ 26.5GHz	Jul. 01, 2022	Jun. 30, 2023	Radiation (03CH02-CB)
Spectrum analyzer	R&S	FSU	100015	9kHz~26GHz	Oct. 25, 2021	Oct. 24, 2022	Radiation (03CH02-CB)
RF Cable-high	Woken	RG402	High Cable-18	1GHz ~ 18GHz	Oct. 04, 2021	Oct. 03, 2022	Radiation (03CH02-CB)
RF Cable-high	Woken	RG402	High Cable-18+19	1GHz ~ 18GHz	Oct. 04, 2021	Oct. 03, 2022	Radiation (03CH02-CB)
High Cable	Woken	WCA0929M	40G#5+7	1GHz ~ 40 GHz	Dec. 14, 2021	Dec. 13, 2022	Radiation (03CH02-CB)



Instrument	Brand	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
High Cable	Woken	WCA0929M	40G#5	1GHz ~ 40 GHz	Dec. 08, 2021	Dec. 07, 2022	Radiation (03CH02-CB)
High Cable	Woken	WCA0929M	40G#7	1GHz ~ 40 GHz	Dec. 14, 2021	Dec. 13, 2022	Radiation (03CH02-CB)
Test Software	SPORTON	SENSE	V5.10	-	N.C.R.	N.C.R.	Radiation (03CH02-CB)
3m Semi Anechoic Chamber VSWR	TDK	SAC-3M	03CH03-CB	1GHz ~18GHz 3m	May 05, 2022	May 04, 2023	Radiation (03CH03-CB)
Horn Antenna	ETS • Lindgren	3115	6821	750MHz~18GHz	Jan. 21, 2022	Jan. 20, 2023	Radiation (03CH03-CB)
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170507	15GHz ~ 40GHz	Jul. 05, 2022	Jul. 04, 2023	Radiation (03CH03-CB)
Pre-Amplifier	Agilent	8449B	3008A02097	1GHz ~ 26.5GHz	Jul. 01, 2022	Jun. 30, 2023	Radiation (03CH03-CB)
Spectrum Analyzer	R&S	FSP40	100019	9kHz ~ 40GHz	Jun. 10, 2022	Jun. 09, 2023	Radiation (03CH03-CB)
RF Cable-high	Woken	RG402	High Cable-20+29	1GHz ~ 18GHz	Oct. 04, 2021	Oct. 03, 2022	Radiation (03CH03-CB)
RF Cable-high	Woken	RG402	High Cable-29	1GHz ~ 18GHz	Oct. 04, 2021	Oct. 03, 2022	Radiation (03CH03-CB)
High Cable	Woken	WCA0929M	40G#5+7	1GHz ~ 40 GHz	Dec. 14, 2021	Dec. 13, 2022	Radiation (03CH03-CB)
High Cable	Woken	WCA0929M	40G#5	1GHz ~ 40 GHz	Dec. 08, 2021	Dec. 07, 2022	Radiation (03CH03-CB)
High Cable	Woken	WCA0929M	40G#7	1GHz ~ 40 GHz	Dec. 14, 2021	Dec. 13, 2022	Radiation (03CH03-CB)
Test Software	SPORTON	SENSE	V5.10	-	N.C.R.	N.C.R.	Radiation (03CH03-CB)
Signal Analyzer	R&S	FSV40	101904	9kHz ~ 40GHz	Apr. 26, 2022	Apr. 25, 2023	Conducted (TH02-CB)
Power Sensor	Anritsu	MA2411B	1126203	300MHz~40GHz	Oct. 25, 2021	Oct. 24, 2022	Conducted (TH02-CB)
Power Meter	Anritsu	ML2495A	1210004	300MHz~40GHz	Oct. 25, 2021	Oct. 24, 2022	Conducted (TH02-CB)
RF Cable-high	Woken	RG402	High Cable-01	1 GHz – 18 GHz	Oct. 04, 2021	Oct. 03, 2022	Conducted (TH02-CB)
RF Cable-high	Woken	RG402	High Cable-02	1 GHz – 18 GHz	Oct. 04, 2021	Oct. 03, 2022	Conducted (TH02-CB)
RF Cable-high	Woken	RG402	High Cable-03	1 GHz – 18 GHz	Oct. 04, 2021	Oct. 03, 2022	Conducted (TH02-CB)
RF Cable-high	Woken	RG402	High Cable-04	1 GHz – 18 GHz	Oct. 04, 2021	Oct. 03, 2022	Conducted (TH02-CB)
RF Cable-high	Woken	RG402	High Cable-05	1 GHz – 18 GHz	Oct. 04, 2021	Oct. 03, 2022	Conducted (TH02-CB)
Switch	SPTCB	SP-SWI	SWI-03	1 GHz –26.5 GHz	Dec. 13, 2021	Dec. 12, 2022	Conducted (TH02-CB)
RF Cable-high	Woken	RG402	SWI-03-P1	1 GHz –26.5 GHz	Dec. 13, 2021	Dec. 12, 2022	Conducted (TH02-CB)



Instrument	Brand	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
RF Cable-high	Woken	RG402	SWI-03-P2	1 GHz –26.5 GHz	Dec. 13, 2021	Dec. 12, 2022	Conducted (TH02-CB)
RF Cable-high	Woken	RG402	SWI-03-P3	1 GHz –26.5 GHz	Dec. 13, 2021	Dec. 12, 2022	Conducted (TH02-CB)
RF Cable-high	Woken	RG402	SWI-03-P4	1 GHz –26.5 GHz	Dec. 13, 2021	Dec. 12, 2022	Conducted (TH02-CB)
RF Cable-high	Woken	RG402	SWI-03-P5	1 GHz –26.5 GHz	Dec. 13, 2021	Dec. 12, 2022	Conducted (TH02-CB)
Test Software	SPORTON	SENSE	V5.10	-	N.C.R.	N.C.R.	Conducted (TH02-CB)

Note: Calibration Interval of instruments listed above is one year.

NCR means Non-Calibration required.



Conducted Emissions at Powerline


Appendix A

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Condition
Mode 2	Pass	AV	388.5k	42.40	48.10	-5.70	Line

Mode 2


15/08/2022



Type	Freq (Hz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Factor (dB)	Condition	Comment	Raw (dBuV)	LISN (dB)	CL (dB)	AT (dB)			
QP	388.5k	46.47	58.10	-11.63	10.25	Line	-	36.22	0.12	0.02	10.11			
AV	388.5k	42.40	48.10	-5.70	10.25	Line	"Worst"	32.15	0.12	0.02	10.11			
QP	429k	44.20	57.28	-13.08	10.25	Line	-	33.95	0.12	0.02	10.11			
AV	429k	34.76	47.28	-12.52	10.25	Line	-	24.51	0.12	0.02	10.11			
QP	861k	30.45	56.00	-25.55	10.30	Line	-	20.15	0.14	0.02	10.14			
AV	861k	23.28	46.00	-22.72	10.30	Line	-	12.98	0.14	0.02	10.14			
QP	2.22M	29.79	56.00	-26.21	10.39	Line	-	19.40	0.18	0.05	10.16			
AV	2.22M	23.22	46.00	-22.78	10.39	Line	-	12.83	0.18	0.05	10.16			
QP	2.693M	29.12	56.00	-26.88	10.43	Line	-	18.69	0.20	0.06	10.17			
AV	2.693M	22.61	46.00	-23.39	10.43	Line	-	12.18	0.20	0.06	10.17			
QP	10.883M	31.71	60.00	-28.29	10.62	Line	-	21.09	0.34	0.08	10.20			
AV	10.883M	25.64	50.00	-24.36	10.62	Line	-	15.02	0.34	0.08	10.20			
QP	16.463M	35.00	60.00	-25.00	10.70	Line	-	24.30	0.37	0.11	10.22			
AV	16.463M	33.22	50.00	-16.78	10.70	Line	-	22.52	0.37	0.11	10.22			

Mode 2

15/08/2022



Type	Freq (Hz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Factor (dB)	Condition	Comment	Raw (dBuV)	LISN (dB)	CL (dB)	AT (dB)			
QP	388.5k	46.49	58.10	-11.61	10.29	Neutral	-	36.20	0.16	0.02	10.11			
AV	388.5k	42.34	48.10	-5.76	10.29	Neutral	"Worst"	32.05	0.16	0.02	10.11			
QP	636k	29.88	56.00	-26.12	10.32	Neutral	-	19.56	0.17	0.02	10.13			
AV	636k	22.00	46.00	-24.00	10.32	Neutral	-	11.68	0.17	0.02	10.13			
QP	1.397M	29.08	56.00	-26.92	10.35	Neutral	-	18.73	0.18	0.03	10.14			
AV	1.397M	22.84	46.00	-23.16	10.35	Neutral	-	12.49	0.18	0.03	10.14			
QP	1.887M	29.30	56.00	-26.70	10.39	Neutral	-	18.91	0.19	0.05	10.15			
AV	1.887M	22.90	46.00	-23.10	10.39	Neutral	-	12.51	0.19	0.05	10.15			
QP	4.952M	30.52	56.00	-25.48	10.50	Neutral	-	20.02	0.24	0.07	10.19			
AV	4.952M	24.19	46.00	-21.81	10.50	Neutral	-	13.69	0.24	0.07	10.19			
QP	10.518M	30.87	60.00	-29.13	10.55	Neutral	-	20.32	0.29	0.07	10.19			
AV	10.518M	24.91	50.00	-25.09	10.55	Neutral	-	14.36	0.29	0.07	10.19			

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
802.11b_Nss1,(1Mbps)_4TX	7.55M	10.37M	10M4G1D	6.55M	10.195M
802.11g_Nss1,(6Mbps)_4TX	16.375M	17.341M	17M3D1D	16.3M	16.792M
802.11ax HEW20_Nss1,(MCS0)_4TX	19M	19.09M	19M1D1D	18.7M	19.015M
802.11ax HEW40_Nss1,(MCS0)_4TX	37.85M	38.031M	38M0D1D	36.85M	37.781M

Max-N dB = Maximum 6dB down bandwidth; Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth; Min-OBW = Minimum 99% occupied bandwidth


Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)	Port 2-N dB (Hz)	Port 2-OBW (Hz)	Port 3-N dB (Hz)	Port 3-OBW (Hz)	Port 4-N dB (Hz)	Port 4-OBW (Hz)
802.11b_Nss1,(1Mbps)_4TX	-	-	-	-	-	-	-	-	-	-
2412MHz	Pass	500k	7.025M	10.32M	7.05M	10.245M	7.025M	10.27M	7.55M	10.195M
2437MHz	Pass	500k	7.025M	10.32M	7.025M	10.32M	7.05M	10.295M	7.075M	10.295M
2462MHz	Pass	500k	7.05M	10.22M	7.05M	10.345M	6.55M	10.37M	7.025M	10.27M
802.11g_Nss1,(6Mbps)_4TX	-	-	-	-	-	-	-	-	-	-
2412MHz	Pass	500k	16.3M	16.992M	16.325M	16.892M	16.325M	16.942M	16.3M	16.917M
2437MHz	Pass	500k	16.325M	17.341M	16.325M	16.867M	16.325M	16.792M	16.375M	16.917M
2462MHz	Pass	500k	16.35M	16.942M	16.325M	16.917M	16.325M	17.041M	16.3M	16.917M
802.11ax HEW20_Nss1,(MCS0)_4TX	-	-	-	-	-	-	-	-	-	-
2412MHz	Pass	500k	18.725M	19.09M	18.775M	19.04M	18.85M	19.04M	18.7M	19.065M
2437MHz	Pass	500k	19M	19.065M	18.925M	19.04M	18.975M	19.015M	18.975M	19.04M
2462MHz	Pass	500k	18.75M	19.065M	18.825M	19.04M	18.9M	19.09M	18.725M	19.065M
802.11ax HEW40_Nss1,(MCS0)_4TX	-	-	-	-	-	-	-	-	-	-
2422MHz	Pass	500k	37.6M	37.881M	37.55M	37.981M	37.65M	37.881M	37.65M	37.931M
2437MHz	Pass	500k	37.8M	37.781M	37.75M	37.831M	37.35M	37.881M	37.75M	37.881M
2452MHz	Pass	500k	37.85M	38.031M	36.85M	37.981M	37.65M	37.981M	37.6M	37.981M


Port X-N dB = Port X 6dB down bandwidth;
Port X-OBW = Port X 99% occupied bandwidth

802.11b_Nss1,(1Mbps)_4TX
EBW
2412MHz

04/08/2022


802.11b_Nss1,(1Mbps)_4TX
EBW
2437MHz


04/08/2022



802.11b_Nss1,(1Mbps)_4TX

EBW
2462MHz


04/08/2022



802.11g_Nss1,(6Mbps)_4TX

EBW
2412MHz


04/08/2022



802.11g_Nss1,(6Mbps)_4TX

2437MHz


04/08/2022



802.11g_Nss1,(6Mbps)_4TX


2462MHz

04/08/2022




802.11ax HEW20_Nss1,(MCS0)_4TX
EBW
2412MHz

04/08/2022



802.11ax HEW20_Nss1,(MCS0)_4TX
EBW
2437MHz

04/08/2022




802.11ax HEW20_Nss1,(MCS0)_4TX
EBW
2462MHz

04/08/2022



802.11ax HEW40_Nss1,(MCS0)_4TX
EBW
2422MHz

04/08/2022




802.11ax HEW40_Nss1,(MCS0)_4TX
EBW
2437MHz

04/08/2022


802.11ax HEW40_Nss1,(MCS0)_4TX
EBW
2452MHz

04/08/2022





Average Power

Appendix C

Summary

Mode	Total Power (dBm)	Total Power (W)
2.4-2.4835GHz	-	-
802.11b_Nss1,(1Mbps)_4TX	29.77	0.94842
802.11g_Nss1,(6Mbps)_4TX	28.35	0.68391
802.11ax HEW20_Nss1,(MCS0)_4TX	28.05	0.63826
802.11ax HEW40_Nss1,(MCS0)_4TX	25.34	0.34198

Result

Mode	Result	DG (dBi)	Port 1 (dBm)	Port 2 (dBm)	Port 3 (dBm)	Port 4 (dBm)	Total Power (dBm)	Power Limit (dBm)
802.11b_Nss1,(1Mbps)_4TX	-	-	-	-	-	-	-	-
2412MHz	Pass	6.15	24.74	23.22	22.99	23.85	29.77	29.85
2437MHz	Pass	6.15	24.48	23.76	23.30	23.25	29.75	29.85
2462MHz	Pass	6.15	24.13	22.82	22.62	22.78	29.15	29.85
802.11g_Nss1,(6Mbps)_4TX	-	-	-	-	-	-	-	-
2412MHz	Pass	6.15	23.41	22.02	21.55	22.11	28.35	29.85
2437MHz	Pass	6.15	22.65	22.40	21.86	21.51	28.15	29.85
2457MHz	Pass	6.15	23.11	21.64	21.27	21.96	28.07	29.85
2462MHz	Pass	6.15	18.93	18.06	17.57	17.72	24.12	29.85
802.11ax HEW20_Nss1,(MCS0)_4TX	-	-	-	-	-	-	-	-
2412MHz	Pass	6.15	23.03	21.52	21.62	21.78	28.05	29.85
2437MHz	Pass	6.15	21.35	21.12	20.68	20.33	26.91	29.85
2457MHz	Pass	6.15	20.82	19.81	19.01	19.86	25.94	29.85
2462MHz	Pass	6.15	17.74	16.52	16.33	16.33	22.79	29.85
802.11ax HEW40_Nss1,(MCS0)_4TX	-	-	-	-	-	-	-	-
2422MHz	Pass	6.15	19.77	19.55	19.04	18.87	25.34	29.85
2437MHz	Pass	6.15	17.71	17.89	17.28	16.83	23.47	29.85
2452MHz	Pass	6.15	16.82	16.53	16.09	15.60	22.30	29.85

DG = Directional Gain; Port X = Port X output power

Summary

Mode	PD (dBm/RBW)
2.4-2.4835GHz	-
802.11b_Nss1,(1Mbps)_4TX	-0.96
802.11g_Nss1,(6Mbps)_4TX	0.84
802.11ax HEW20_Nss1,(MCS0)_4TX	-0.42
802.11ax HEW40_Nss1,(MCS0)_4TX	-6.29

RBW = 3kHz;

Result

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	Port 2 (dBm/RBW)	Port 3 (dBm/RBW)	Port 4 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)
802.11b_Nss1,(1Mbps)_4TX	-	-	-	-	-	-	-	-
2412MHz	Pass	11.22	-5.40	-6.82	-7.53	-6.25	-0.96	2.78
2437MHz	Pass	11.22	-6.02	-6.71	-6.91	-6.41	-1.03	2.78
2462MHz	Pass	11.22	-5.96	-7.49	-7.98	-7.82	-1.70	2.78
802.11g_Nss1,(6Mbps)_4TX	-	-	-	-	-	-	-	-
2412MHz	Pass	11.22	-1.14	-3.72	-4.18	-3.66	0.84	2.78
2437MHz	Pass	11.22	-1.69	-3.16	-3.97	-3.99	0.77	2.78
2462MHz	Pass	11.22	-6.72	-7.68	-7.65	-7.89	-3.46	2.78
802.11ax HEW20_Nss1,(MCS0)_4TX	-	-	-	-	-	-	-	-
2412MHz	Pass	11.22	-3.00	-4.64	-5.44	-4.39	-0.42	2.78
2437MHz	Pass	11.22	-5.82	-4.31	-5.20	-5.33	-1.80	2.78
2462MHz	Pass	11.22	-9.59	-9.66	-10.45	-10.29	-6.55	2.78
802.11ax HEW40_Nss1,(MCS0)_4TX	-	-	-	-	-	-	-	-
2422MHz	Pass	11.22	-9.17	-9.73	-10.02	-9.99	-6.29	2.78
2437MHz	Pass	11.22	-11.02	-11.04	-12.38	-12.81	-7.80	2.78
2452MHz	Pass	11.22	-10.97	-12.35	-12.32	-13.30	-8.58	2.78


DG = Directional Gain; RBW = 3kHz;
 PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;

802.11b_Nss1,(1Mbps)_4TX

PSD

2412MHz

04/08/2022




Sum	PD	Port 1	Port 2	Port 3	Port 4
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-0.96	-0.96	-5.40	-6.82	-7.53	-6.25

802.11b_Nss1,(1Mbps)_4TX

PSD

2437MHz

04/08/2022




Sum	PD	Port 1	Port 2	Port 3	Port 4
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-1.03	-1.03	-6.02	-6.71	-6.91	-6.41

802.11b_Nss1,(1Mbps)_4TX

2462MHz

PSD

04/08/2022




802.11g_Nss1,(6Mbps)_4TX

2412MHz

PSD

04/08/2022




802.11g_Nss1,(6Mbps)_4TX

PSD

2437MHz

04/08/2022




802.11g_Nss1,(6Mbps)_4TX

PSD

2462MHz

04/08/2022



802.11ax HEW20_Nss1,(MCS0)_4TX

2412MHz

PSD

04/08/2022




802.11ax HEW20_Nss1,(MCS0)_4TX

2437MHz

PSD

04/08/2022




802.11ax HEW20_Nss1,(MCS0)_4TX

PSD

2462MHz

04/08/2022




802.11ax HEW40_Nss1,(MCS0)_4TX

PSD

2422MHz

04/08/2022




802.11ax HEW40_Nss1,(MCS0)_4TX

PSD

2437MHz

04/08/2022




802.11ax HEW40_Nss1,(MCS0)_4TX

PSD

2452MHz

04/08/2022



**Summary**

Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
802.11b_Nss1(1Mbps)_4TX	Pass	2.41148G	17.03	-12.97	825.7M	-51.66	2.39998G	-32.78	2.4G	-33.16	2.48352G	-50.08	5.79945G	-47.55	4
802.11g_Nss1(6Mbps)_4TX	Pass	2.41449G	12.99	-17.01	897.63M	-52.65	2.39982G	-30.72	2.4G	-31.23	2.48392G	-49.34	24.87638G	-47.46	1
802.11ax HEW20_Nss1(MCS0)_4TX	Pass	2.41323G	12.31	-17.69	2.06584G	-51.57	2.4G	-31.15	2.4G	-31.10	2.48386G	-49.06	6.65356G	-46.98	1
802.11ax HEW40_Nss1(MCS0)_4TX	Pass	2.42697G	5.83	-24.17	642.58M	-52.87	2.4G	-32.05	2.4G	-32.30	2.48418G	-48.39	5.87569G	-47.55	1


Result

Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
802.11b_Nss1(1Mbps)_4TX	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
2412MHz	Pass	2.41148G	17.03	-12.97	934.62M	-52.61	2.3985G	-37.62	2.4G	-39.37	2.48462G	-49.46	14.56809G	-46.69	1
2412MHz	Pass	2.41148G	17.03	-12.97	802.1M	-51.94	2.39832G	-39.72	2.4G	-43.08	2.48372G	-50.97	17.66423G	-47.67	2
2412MHz	Pass	2.41148G	17.03	-12.97	2.13283G	-51.85	2.39802G	-40.09	2.4G	-41.83	2.48458G	-49.72	5.89498G	-47.43	3
2412MHz	Pass	2.41148G	17.03	-12.97	825.7M	-51.66	2.39998G	-32.78	2.4G	-33.16	2.48352G	-50.08	5.79945G	-47.55	4
2437MHz	Pass	2.41148G	17.03	-12.97	1.64323G	-52.75	2.398G	-46.26	2.4G	-47.05	2.48402G	-47.23	16.46174G	-46.25	1
2437MHz	Pass	2.41148G	17.03	-12.97	907.54M	-52.84	2.3989G	-45.61	2.4G	-49.40	2.48492G	-49.26	16.30159G	-47.06	2
2437MHz	Pass	2.41148G	17.03	-12.97	892.1M	-52.89	2.39686G	-47.37	2.4G	-47.89	2.48414G	-48.01	16.49826G	-47.85	3
2437MHz	Pass	2.41148G	17.03	-12.97	884.82M	-52.97	2.398G	-46.24	2.4G	-47.34	2.48508G	-48.78	5.9315G	-47.18	4
2462MHz	Pass	2.41148G	17.03	-12.97	2.09671G	-52.28	2.39906G	-48.97	2.4835G	-41.20	2.48454G	-43.44	16.32969G	-48.10	1
2462MHz	Pass	2.41148G	17.03	-12.97	2.30612G	-52.21	2.3983G	-48.49	2.4835G	-49.29	2.484G	-48.16	5.91464G	-48.10	2
2462MHz	Pass	2.41148G	17.03	-12.97	839.09M	-52.60	2.39896G	-48.61	2.4G	-49.00	2.48462G	-46.85	5.72921G	-46.35	3
2462MHz	Pass	2.41148G	17.03	-12.97	2.19166G	-53.28	2.39996G	-48.20	2.4835G	-47.99	2.48384G	-47.09	17.68109G	-46.52	4
802.11g_Nss1(6Mbps)_4TX	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
2412MHz	Pass	2.41449G	12.99	-17.01	897.63M	-52.65	2.39982G	-30.72	2.4G	-31.23	2.48392G	-49.34	24.87638G	-47.46	1
2412MHz	Pass	2.41449G	12.99	-17.01	945.4M	-52.25	2.39826G	-31.84	2.4G	-36.54	2.48372G	-50.12	15.22553G	-47.28	2
2412MHz	Pass	2.41449G	12.99	-17.01	2.17447G	-53.02	2.39798G	-32.12	2.4G	-36.11	2.48494G	-48.77	16.36902G	-46.74	3
2412MHz	Pass	2.41449G	12.99	-17.01	1.95079G	-52.63	2.39854G	-34.03	2.4G	-35.74	2.48432G	-49.11	17.65299G	-47.68	4
2437MHz	Pass	2.41449G	12.99	-17.01	2.30408G	-52.83	2.3998G	-33.53	2.4G	-37.12	2.48376G	-35.80	6.97666G	-48.13	1
2437MHz	Pass	2.41449G	12.99	-17.01	2.15147G	-52.95	2.39922G	-37.92	2.4G	-38.89	2.4839G	-42.02	5.93712G	-47.30	2
2437MHz	Pass	2.41449G	12.99	-17.01	2.30292G	-52.10	2.39638G	-39.32	2.4G	-43.08	2.4839G	-41.37	16.50107G	-47.71	3
2437MHz	Pass	2.41449G	12.99	-17.01	2.01137G	-53.20	2.3976G	-35.67	2.4G	-38.84	2.4835G	-40.70	24.74714G	-47.58	4
2462MHz	Pass	2.41449G	12.99	-17.01	823.66M	-53.44	2.39864G	-50.11	2.4835G	-49.42	2.48492G	-48.58	17.65299G	-46.53	1
2462MHz	Pass	2.41449G	12.99	-17.01	1.84361G	-51.94	2.39968G	-48.98	2.4G	-50.33	2.4841G	-47.53	6.98228G	-46.62	2
2462MHz	Pass	2.41449G	12.99	-17.01	1.98516G	-52.29	2.3966G	-50.16	2.4835G	-47.29	2.4835G	-44.45	6.21527G	-46.71	3
2462MHz	Pass	2.41449G	12.99	-17.01	823.66M	-52.13	2.3973G	-49.27	2.4G	-50.79	2.48728G	-49.27	17.66985G	-47.06	4
802.11ax HEW20_Nss1(MCS0)_4TX	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
2412MHz	Pass	2.41323G	12.31	-17.69	2.06584G	-51.57	2.4G	-31.15	2.4G	-31.10	2.48386G	-49.06	6.65356G	-46.98	1
2412MHz	Pass	2.41323G	12.31	-17.69	914.24M	-52.49	2.39998G	-33.72	2.4G	-34.46	2.48514G	-50.19	16.60784G	-47.17	2
2412MHz	Pass	2.41323G	12.31	-17.69	912.49M	-53.03	2.39702G	-35.27	2.4G	-33.58	2.48474G	-49.49	17.66704G	-47.69	3
2412MHz	Pass	2.41323G	12.31	-17.69	1.79585G	-52.92	2.39992G	-35.16	2.4G	-33.74	2.4865G	-48.23	21.70157G	-47.71	4
2437MHz	Pass	2.41323G	12.31	-17.69	667.55M	-52.82	2.3996G	-35.70	2.4G	-36.63	2.4844G	-34.74	6.98789G	-47.25	1
2437MHz	Pass	2.41323G	12.31	-17.69	2.17185G	-52.92	2.39976G	-41.26	2.4G	-43.34	2.48358G	-44.93	17.65861G	-46.78	2
2437MHz	Pass	2.41323G	12.31	-17.69	2.02361G	-52.43	2.39966G	-39.49	2.4G	-44.81	2.4838G	-46.43	5.94274G	-47.67	3
2437MHz	Pass	2.41323G	12.31	-17.69	1.72245G	-52.82	2.39998G	-38.72	2.4G	-38.06	2.4836G	-43.12	16.40555G	-46.63	4
2462MHz	Pass	2.41323G	12.31	-17.69	636.09M	-52.18	2.3953G	-50.84	2.4835G	-50.12	2.48404G	-48.81	5.86407G	-47.46	1
2462MHz	Pass	2.41323G	12.31	-17.69	2.12729G	-52.81	2.3998G	-50.57	2.4835G	-50.02	2.4848G	-48.27	22.00501G	-47.51	2
2462MHz	Pass	2.41323G	12.31	-17.69	674.83M	-52.50	2.39858G	-50.21	2.4835G	-47.22	2.48352G	-46.50	17.67266G	-47.32	3
2462MHz	Pass	2.41323G	12.31	-17.69	2.18205G	-52.81	2.39986G	-50.71	2.4835G	-52.09	2.48408G	-49.47	6.76875G	-47.23	4
802.11ax HEW40_Nss1(MCS0)_4TX	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
2422MHz	Pass	2.42697G	5.83	-24.17	642.58M	-52.87	2.4G	-32.05	2.4G	-32.30	2.48418G	-48.39	5.87569G	-47.55	1
2422MHz	Pass	2.42697G	5.83	-24.17	910.22M	-52.54	2.4G	-32.70	2.4G	-33.93	2.48454G	-49.21	17.67729G	-47.24	2
2422MHz	Pass	2.42697G	5.83	-24.17	777.11M	-52.59	2.39996G	-32.08	2.4G	-32.26	2.48378G	-47.18	5.84764G	-47.21	3
2422MHz	Pass	2.42697G	5.83	-24.17	917.09M	-53.11	2.39996G	-33.70	2.4G	-32.79	2.4845G	-48.66	17.66046G	-46.54	4
2437MHz	Pass	2.42697G	5.83	-24.17	937.99M	-52.64	2.3996G	-38.45	2.4G	-43.11	2.48366G	-45.88	17.68851G	-46.34	1
2437MHz	Pass	2.42697G	5.83	-24.17	918.81M	-52.51	2.3974G	-47.73	2.4G	-49.94	2.48422G	-50.48	6.41416G	-47.28	2
2437MHz	Pass	2.42697G	5.83	-24.17	2.0973G	-52.66	2.39748G	-47.75	2.4G	-49.81	2.4837G	-48.75	5.89252G	-47.20	3
2437MHz	Pass	2.42697G	5.83	-24.17	2.30311G	-52.55	2.39948G	-37.24	2.4G	-44.68	2.48514G	-45.79	15.32987G	-47.42	4
2452MHz	Pass	2.42697G	5.83	-24.17	2.06238G	-52.79	2.39956G	-39.05	2.4G	-42.32	2.48446G	-43.81	5.78033G	-46.66	1
2452MHz	Pass	2.42697G	5.83	-24.17	2.09157G	-52.37	2.39944G	-38.92	2.4G	-40.97	2.48446G	-41.31	17.66046G	-46.80	2
2452MHz	Pass	2.42697G	5.83	-24.17	2.10073G	-52.91	2.39952G	-38.84	2.4G	-39.94	2.4857G	-40.02	16.52742G	-47.11	3
2452MHz	Pass	2.42697G	5.83	-24.17	953.16M	-52.59	2.39952G	-38.77	2.4G	-41.53	2.48362G	-47.92	6.76193G	-46.24	4

802.11b_Nss1,(1Mbps)_4TX

CSEndB


2412MHz



802.11b_Nss1,(1Mbps)_4TX

CSEndB

2437MHz




802.11b_Nss1,(1Mbps)_4TX


2462MHz

CSENdB

04/08/2022



Port 1
Port 2
Port 3
Port 4



RBW (Hz)
100k
VBW (Hz)
300k
Detector
Peak


Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.41148G	17.03	-12.97	2.09671G	-52.28	2.39906G	-48.97	2.4835G	-41.20	2.48454G	-43.44	16.32969G	-48.10	1
2.41148G	17.03	-12.97	2.30612G	-52.21	2.3983G	-48.49	2.4835G	-49.29	2.484G	-48.16	5.91464G	-48.10	2
2.41148G	17.03	-12.97	839.09M	-52.60	2.39896G	-48.61	2.4G	-49.00	2.48462G	-46.85	5.72921G	-46.35	3
2.41148G	17.03	-12.97	2.19166G	-53.28	2.39996G	-48.20	2.4835G	-47.99	2.48384G	-47.09	17.68109G	-46.52	4

802.11g_Nss1,(6Mbps)_4TX


2412MHz

CSENdB

04/08/2022



Port 1
Port 2
Port 3
Port 4



RBW (Hz)
100k
VBW (Hz)
300k
Detector
Peak


Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.41449G	12.99	-17.01	897.63M	-52.65	2.39982G	-30.72	2.4G	-31.23	2.48392G	-49.34	24.87638G	-47.46	1
2.41449G	12.99	-17.01	945.4M	-52.25	2.39826G	-31.84	2.4G	-36.54	2.48372G	-50.12	15.22593G	-47.28	2
2.41449G	12.99	-17.01	2.17447G	-53.02	2.39798G	-32.12	2.4G	-36.11	2.48494G	-48.77	16.36902G	-46.74	3
2.41449G	12.99	-17.01	1.95079G	-52.63	2.39854G	-34.03	2.4G	-35.74	2.48432G	-49.11	17.65299G	-47.68	4

802.11g_Nss1,(6Mbps)_4TX


2437MHz

CSENdB

04/08/2022



Port 1
Port 2
Port 3
Port 4



RBW (Hz)
100k
VBW (Hz)
300k
Detector
Peak


Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.41449G	12.99	-17.01	2.30408G	-52.83	2.3998G	-33.53	2.4G	-37.12	2.48376G	-35.80	6.97666G	-48.13	1
2.41449G	12.99	-17.01	2.15147G	-52.95	2.39922G	-37.92	2.4G	-38.89	2.4839G	-42.02	5.93712G	-47.30	2
2.41449G	12.99	-17.01	2.30292G	-52.10	2.39638G	-39.32	2.4G	-43.08	2.4839G	-41.37	16.50107G	-47.71	3
2.41449G	12.99	-17.01	2.01137G	-53.20	2.3976G	-35.67	2.4G	-38.84	2.4835G	-40.70	24.74714G	-47.58	4

802.11g_Nss1,(6Mbps)_4TX


2462MHz

CSENdB

04/08/2022



Port 1
Port 2
Port 3
Port 4




RBW (Hz)
100k
VBW (Hz)
300k
Detector
Peak

Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.41449G	12.99	-17.01	823.66M	-53.44	2.39864G	-50.11	2.4835G	-40.42	2.48492G	-48.58	17.65399G	-46.53	1
2.41449G	12.99	-17.01	1.84361G	-51.94	2.39868G	-48.98	2.4G	-50.33	2.4841G	-47.53	6.98228G	-46.62	2
2.41449G	12.99	-17.01	1.98516G	-52.29	2.3966G	-50.16	2.4835G	-47.29	2.4835G	-44.45	6.21527G	-46.71	3
2.41449G	12.99	-17.01	823.66M	-52.13	2.3973G	-49.27	2.4G	-50.79	2.48728G	-49.27	17.66985G	-47.06	4

802.11ax HEW20_Nss1,(MCS0)_4TX

CSENdB

2412MHz



802.11ax HEW20_Nss1,(MCS0)_4TX

CSENdB

2437MHz




802.11ax HEW20_Nss1,(MCS0)_4TX


CSENdB

2462MHz

04/08/2022



Port 1
Port 2
Port 3
Port 4



RBW (Hz)
100k
VBW (Hz)
300k
Detector
Peak


Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.41323G	12.31	-17.69	636.09M	-52.18	2.3953G	-50.84	2.4835G	-50.12	2.48404G	-48.81	5.86407G	-47.46	1
2.41323G	12.31	-17.69	2.12729G	-52.81	2.3998G	-50.57	2.4835G	-50.02	2.4848G	-48.27	22.00501G	-47.51	2
2.41323G	12.31	-17.69	674.83M	-52.50	2.39858G	-50.21	2.4835G	-47.22	2.48352G	-46.50	17.67266G	-47.32	3
2.41323G	12.31	-17.69	2.18205G	-52.81	2.39986G	-50.71	2.4835G	-52.09	2.48408G	-49.47	6.76879G	-47.23	4

802.11ax HEW40_Nss1,(MCS0)_4TX


CSENdB

2422MHz

04/08/2022



Port 1
Port 2
Port 3
Port 4



RBW (Hz)
100k
VBW (Hz)
300k
Detector
Peak


Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.42697G	5.83	-24.17	642.58M	-52.87	2.4G	-32.05	2.4G	-32.30	2.48418G	-48.39	5.87569G	-47.55	1
2.42697G	5.83	-24.17	910.22M	-52.54	2.4G	-32.70	2.4G	-33.93	2.48454G	-49.21	17.67729G	-47.24	2
2.42697G	5.83	-24.17	777.11M	-52.59	2.39996G	-32.08	2.4G	-32.26	2.48378G	-47.18	5.84764G	-47.21	3
2.42697G	5.83	-24.17	917.09M	-53.11	2.39996G	-33.70	2.4G	-32.79	2.4845G	-48.66	17.66046G	-46.54	4

802.11ax HEW40_Nss1,(MCS0)_4TX


CSENdB

2437MHz

04/08/2022



Port 1
Port 2
Port 3
Port 4



RBW (Hz)
100k
VBW (Hz)
300k
Detector
Peak


Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.42697G	5.83	-24.17	937.99M	-52.64	2.39956G	-38.45	2.4G	-43.11	2.48366G	-45.88	17.68851G	-46.34	1
2.42697G	5.83	-24.17	918.81M	-52.51	2.39746G	-47.73	2.4G	-49.94	2.48422G	-50.48	6.41416G	-47.28	2
2.42697G	5.83	-24.17	2.0973G	-52.66	2.39748G	-47.75	2.4G	-49.81	2.4837G	-48.75	5.89252G	-47.20	3
2.42697G	5.83	-24.17	2.30311G	-52.55	2.39948G	-37.24	2.4G	-44.68	2.48514G	-45.79	15.32987G	-47.42	4

802.11ax HEW40_Nss1,(MCS0)_4TX


CSENdB

2452MHz

04/08/2022



Port 1
Port 2
Port 3
Port 4



RBW (Hz)
100k
VBW (Hz)
300k
Detector
Peak

Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.42697G	5.83	-24.17	2.06238G	-52.79	2.39956G	-39.05	2.4G	-42.32	2.48446G	-43.81	5.78033G	-46.66	1
2.42697G	5.83	-24.17	2.09157G	-52.37	2.39944G	-38.92	2.4G	-40.97	2.48446G	-41.31	17.66046G	-46.80	2
2.42697G	5.83	-24.17	2.10073G	-52.91	2.39953G	-38.84	2.4G	-39.94	2.4857G	-40.02	16.52742G	-47.11	3
2.42697G	5.83	-24.17	953.16M	-52.59	2.39952G	-38.77	2.4G	-41.53	2.48362G	-47.92	6.76193G	-46.24	4




Radiated Emissions below 1GHz

Appendix F.1

Summary


Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Condition
Mode 2	Pass	PK	295.78M	42.40	46.00	-3.60	Horizontal

Mode 2



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB/m)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	Raw (dBuV/m)	AF (dB/m)	CL (dB)	PA (dB)
QP	30.97M	35.47	40.00	-4.53	-7.41	3	Vertical	87	1.00	"Worst"	42.88	24.02	1.00	32.43
QP	42.61M	32.07	40.00	-7.93	-13.58	3	Vertical	339	1.00	-	45.65	17.74	1.15	32.47
QP	57.16M	33.74	40.00	-6.26	-18.48	3	Vertical	272	1.00	-	52.22	12.65	1.34	32.47
PK	67.83M	30.16	40.00	-9.84	-18.62	3	Vertical	125	2.00	-	48.78	12.35	1.46	32.43
PK	99.84M	30.77	43.50	-12.73	-13.92	3	Vertical	222	1.00	-	44.69	16.62	1.80	32.34
PK	293.84M	33.61	46.00	-12.39	-10.24	3	Vertical	154	1.25	-	43.85	18.96	3.16	32.36

Mode 2



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB/m)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	Raw (dBuV/m)	AF (dB/m)	CL (dB)	PA (dB)
PK	77.53M	30.26	40.00	-9.74	-18.09	3	Horizontal	61	2.00	-	48.35	12.76	1.55	32.40
PK	105.66M	33.45	43.50	-10.05	-13.20	3	Horizontal	275	3.00	-	46.65	17.30	1.86	32.36
PK	180.35M	31.51	43.50	-11.99	-14.57	3	Horizontal	20	1.25	-	46.08	15.18	2.50	32.25
PK	295.78M	42.40	46.00	-3.60	-10.20	3	Horizontal	211	1.00	"Worst"	52.60	18.99	3.17	32.36
PK	321M	37.96	46.00	-8.04	-9.49	3	Horizontal	359	1.00	-	47.45	19.46	3.33	32.28
PK	844.8M	34.48	46.00	-11.52	0.17	3	Horizontal	319	1.25	-	34.31	26.12	5.68	31.63




Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-
802.11b_Nss1(1Mbps)_4TX	Pass	AV	2.3898G	53.94	54.00	-0.06	3	Vertical	355	1.72	-

802.11b_Nss1,(1Mbps)_4TX

2412MHz_TX




EUT_X_4TX
Setting 103
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	2.3898G	69.09	74.00	-4.91	37.92	3	Vertical	355	1.72	-	28.38	2.79	-	
AV	2.3898G	53.94	54.00	-0.06	22.77	3	Vertical	355	1.72	-	28.38	2.79	-	
PK	2.413G	126.79	Inf	-Inf	95.58	3	Vertical	355	1.72	-	28.40	2.81	-	
AV	2.4112G	122.73	Inf	-Inf	91.52	3	Vertical	355	1.72	-	28.40	2.81	-	

802.11b_Nss1,(1Mbps)_4TX

2412MHz_TX




EUT_X_4TX
Setting 103
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	2.39G	67.51	74.00	-6.49	36.34	3	Horizontal	36	2.60	-	28.38	2.79	-	
AV	2.39G	51.05	54.00	-2.95	19.88	3	Horizontal	36	2.60	-	28.38	2.79	-	
PK	2.411G	123.91	Inf	-Inf	92.70	3	Horizontal	36	2.60	-	28.40	2.81	-	
AV	2.4112G	119.91	Inf	-Inf	88.70	3	Horizontal	36	2.60	-	28.40	2.81	-	

802.11b_Nss1,(1Mbps)_4TX

2412MHz_TX




EUT X_4TX
Setting 103
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	4.82394G	53.74	74.00	-20.26	46.50	3	Vertical	350	1.91	-	32.94	5.10	30.80	
AV	4.82398G	49.73	54.00	-4.27	42.49	3	Vertical	350	1.91	-	32.94	5.10	30.80	

802.11b_Nss1,(1Mbps)_4TX

2412MHz_TX




EUT X_4TX
Setting 103
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	4.82406G	56.33	74.00	-17.67	49.09	3	Horizontal	18	2.72	-	32.94	5.10	30.80
AV	4.82396G	53.53	54.00	-0.47	46.29	3	Horizontal	18	2.72	-	32.94	5.10	30.80

802.11b_Nss1,(1Mbps)_4TX

2437MHz_TX




EUT_X_4TX
Setting 101
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	2.3898G	60.99	74.00	-13.01	29.82	3	Vertical	-0	1.31	-	28.38	2.79	-	
AV	2.3898G	46.77	54.00	-7.23	15.60	3	Vertical	-0	1.31	-	28.38	2.79	-	
PK	2.4362G	125.91	Inf	-Inf	94.67	3	Vertical	-0	1.31	-	28.40	2.84	-	
AV	2.4362G	121.85	Inf	-Inf	90.61	3	Vertical	-0	1.31	-	28.40	2.84	-	
PK	2.4835G	65.55	74.00	-8.45	34.14	3	Vertical	-0	1.31	-	28.53	2.88	-	
AV	2.4835G	53.52	54.00	-0.48	22.11	3	Vertical	-0	1.31	-	28.53	2.88	-	

802.11b_Nss1,(1Mbps)_4TX

2437MHz_TX




EUT_X_4TX
Setting 101
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.3898G	58.26	74.00	-15.74	27.09	3	Horizontal	30	2.32	-	28.38	2.79	-
AV	2.3898G	47.35	54.00	-6.65	16.18	3	Horizontal	30	2.32	-	28.38	2.79	-
PK	2.4378G	123.36	Inf	-Inf	92.12	3	Horizontal	30	2.32	-	28.40	2.84	-
AV	2.4362G	119.35	Inf	-Inf	88.11	3	Horizontal	30	2.32	-	28.40	2.84	-
PK	2.4835G	61.90	74.00	-12.10	30.49	3	Horizontal	30	2.32	-	28.53	2.88	-
AV	2.4835G	51.22	54.00	-2.78	19.81	3	Horizontal	30	2.32	-	28.53	2.88	-

802.11b_Nss1,(1Mbps)_4TX

2437MHz_TX




EUT X_4TX
Setting 101
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	4.87406G	49.28	74.00	-24.72	41.81	3	Vertical	351	1.99	-	33.15	5.10	30.78	
AV	4.87394G	41.62	54.00	-12.38	34.15	3	Vertical	351	1.99	-	33.15	5.10	30.78	

802.11b_Nss1,(1Mbps)_4TX

2437MHz_TX




EUT X_4TX
Setting 101
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	4.87426G	49.90	74.00	-24.10	42.43	3	Horizontal	19	2.68	-	33.15	5.10	30.78
AV	4.87398G	43.77	54.00	-10.23	36.30	3	Horizontal	19	2.68	-	33.15	5.10	30.78

802.11b_Nss1,(1Mbps)_4TX

2462MHz_TX




EUT_X_4TX
Setting 94
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	2.461G	120.88	Inf	-Inf	89.58	3	Vertical	342	3.00	-	28.44	2.86	-	
AV	2.4612G	116.90	Inf	-Inf	85.60	3	Vertical	342	3.00	-	28.44	2.86	-	
PK	2.4842G	68.71	74.00	-5.29	37.29	3	Vertical	342	3.00	-	28.54	2.88	-	
AV	2.4835G	51.46	54.00	-2.54	20.05	3	Vertical	342	3.00	-	28.53	2.88	-	

802.11b_Nss1,(1Mbps)_4TX

2462MHz_TX




EUT_X_4TX
Setting 94
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.463G	122.60	Inf	-Inf	91.29	3	Horizontal	17	2.05	-	28.45	2.86	-
AV	2.4632G	118.11	Inf	-Inf	86.80	3	Horizontal	17	2.05	-	28.45	2.86	-
PK	2.4835G	71.58	74.00	-2.42	40.17	3	Horizontal	17	2.05	-	28.53	2.88	-
AV	2.4835G	53.28	54.00	-0.72	21.87	3	Horizontal	17	2.05	-	28.53	2.88	-

802.11b_Nss1,(1Mbps)_4TX

2462MHz_TX




EUT X_4TX
Setting 94
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	4.92392G	51.08	74.00	-22.92	43.49	3	Vertical	38	1.83	-	33.25	5.10	30.76	
AV	4.92396G	45.58	54.00	-8.42	37.99	3	Vertical	38	1.83	-	33.25	5.10	30.76	

802.11b_Nss1,(1Mbps)_4TX

2462MHz_TX




EUT X_4TX
Setting 94
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	4.92403G	51.37	74.00	-22.63	43.78	3	Horizontal	26	3.00	-	33.25	5.10	30.76	
AV	4.924G	46.79	54.00	-7.21	39.20	3	Horizontal	26	3.00	-	33.25	5.10	30.76	

802.11g_Nss1,(6Mbps)_4TX

2412MHz_TX




EUT_X_4TX
Setting 97
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.3898G	67.14	74.00	-6.86	35.97	3	Vertical	-0	1.72	-	28.38	2.79	-
AV	2.39G	53.43	54.00	-0.57	22.26	3	Vertical	-0	1.72	-	28.38	2.79	-
PK	2.4132G	124.84	Inf	-Inf	93.63	3	Vertical	-0	1.72	-	28.40	2.81	-
AV	2.4132G	113.76	Inf	-Inf	82.55	3	Vertical	-0	1.72	-	28.40	2.81	-

802.11g_Nss1,(6Mbps)_4TX

2412MHz_TX




EUT_X_4TX
Setting 97
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	2.39G	63.04	74.00	-10.96	31.87	3	Horizontal	7	1.94	-	28.38	2.79	-	
AV	2.39G	49.85	54.00	-4.15	18.68	3	Horizontal	7	1.94	-	28.38	2.79	-	
PK	2.4162G	123.98	Inf	-Inf	92.76	3	Horizontal	7	1.94	-	28.40	2.82	-	
AV	2.4168G	113.50	Inf	-Inf	82.28	3	Horizontal	7	1.94	-	28.40	2.82	-	

802.11g_Nss1,(6Mbps)_4TX

2412MHz_TX




EUT X_4TX
Setting 97
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	4.8201G	51.16	74.00	-22.84	43.95	3	Vertical	83	1.76	-	32.92	5.10	30.81	
AV	4.8196G	37.90	54.00	-16.10	30.69	3	Vertical	83	1.76	-	32.92	5.10	30.81	

802.11g_Nss1,(6Mbps)_4TX

2412MHz_TX




EUT X_4TX
Setting 97
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	4.8156G	49.74	74.00	-24.26	42.56	3	Horizontal	5	1.73	-	32.89	5.10	30.81	
AV	4.8155G	36.41	54.00	-17.59	29.23	3	Horizontal	5	1.73	-	32.89	5.10	30.81	

802.11g_Nss1,(6Mbps)_4TX

2437MHz_TX




EUT_X_4TX
Setting 92
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.3894G	59.05	74.00	-14.95	27.88	3	Vertical	360	1.33	-	28.38	2.79	-
AV	2.3898G	46.19	54.00	-7.81	15.02	3	Vertical	360	1.33	-	28.38	2.79	-
PK	2.4386G	123.29	Inf	-Inf	92.05	3	Vertical	360	1.33	-	28.40	2.84	-
AV	2.4382G	112.93	Inf	-Inf	81.69	3	Vertical	360	1.33	-	28.40	2.84	-
PK	2.4838G	73.89	74.00	-0.11	42.47	3	Vertical	360	1.33	-	28.54	2.88	-
AV	2.4835G	52.73	54.00	-1.27	21.32	3	Vertical	360	1.33	-	28.53	2.88	-

802.11g_Nss1,(6Mbps)_4TX

2437MHz_TX




EUT_X_4TX
Setting 92
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.3898G	64.83	74.00	-9.17	33.66	3	Horizontal	31	2.31	-	28.38	2.79	-
AV	2.3898G	48.66	54.00	-5.34	17.49	3	Horizontal	31	2.31	-	28.38	2.79	-
PK	2.435G	123.98	Inf	-Inf	92.75	3	Horizontal	31	2.31	-	28.40	2.83	-
AV	2.4346G	113.42	Inf	-Inf	82.19	3	Horizontal	31	2.31	-	28.40	2.83	-
PK	2.4838G	73.50	74.00	-0.50	42.08	3	Horizontal	31	2.31	-	28.54	2.88	-
AV	2.4835G	53.02	54.00	-0.98	21.61	3	Horizontal	31	2.31	-	28.53	2.88	-

802.11g_Nss1,(6Mbps)_4TX

2437MHz_TX




EUT X_4TX
Setting 92
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	4.8662G	46.77	74.00	-27.23	39.33	3	Vertical	271	1.80	-	33.13	5.10	30.79	
AV	4.8725G	33.19	54.00	-20.81	25.72	3	Vertical	271	1.80	-	33.15	5.10	30.78	

802.11g_Nss1,(6Mbps)_4TX

2437MHz_TX




EUT X_4TX
Setting 92
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	4.8822G	47.26	74.00	-26.74	39.78	3	Horizontal	61	2.28	-	33.16	5.10	30.78
AV	4.8728G	33.72	54.00	-20.28	26.25	3	Horizontal	61	2.28	-	33.15	5.10	30.78

802.11g_Nss1,(6Mbps)_4TX

2457MHz_TX




EUT_X_4TX
Setting 92
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.3666G	55.61	74.00	-18.39	24.50	3	Vertical	342	3.00	-	28.33	2.78	-
AV	2.3898G	43.63	54.00	-10.37	12.46	3	Vertical	342	3.00	-	28.38	2.79	-
PK	2.459G	121.90	Inf	-Inf	90.60	3	Vertical	342	3.00	-	28.44	2.86	-
AV	2.459G	111.41	Inf	-Inf	80.11	3	Vertical	342	3.00	-	28.44	2.86	-
PK	2.4846G	63.79	74.00	-10.21	32.37	3	Vertical	342	3.00	-	28.54	2.88	-
AV	2.4838G	50.65	54.00	-3.35	19.23	3	Vertical	342	3.00	-	28.54	2.88	-

802.11g_Nss1,(6Mbps)_4TX

2457MHz_TX




EUT_X_4TX
Setting 92
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.3898G	57.16	74.00	-16.84	25.99	3	Horizontal	19	2.30	-	28.38	2.79	-
AV	2.3898G	45.17	54.00	-8.83	14.00	3	Horizontal	19	2.30	-	28.38	2.79	-
PK	2.4498G	123.58	Inf	-Inf	92.33	3	Horizontal	19	2.30	-	28.40	2.85	-
AV	2.4494G	113.60	Inf	-Inf	82.35	3	Horizontal	19	2.30	-	28.40	2.85	-
PK	2.4835G	66.91	74.00	-7.09	35.50	3	Horizontal	19	2.30	-	28.53	2.88	-
AV	2.4835G	53.24	54.00	-0.76	21.83	3	Horizontal	19	2.30	-	28.53	2.88	-

802.11g_Nss1,(6Mbps)_4TX

2462MHz_TX




EUT_X_4TX
Setting 79
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.4552G	118.65	Inf	-Inf	87.37	3	Vertical	356	1.59	-	28.42	2.86	-
AV	2.4552G	107.91	Inf	-Inf	76.63	3	Vertical	356	1.59	-	28.42	2.86	-
PK	2.4835G	64.55	74.00	-9.45	33.14	3	Vertical	356	1.59	-	28.53	2.88	-
AV	2.4835G	50.91	54.00	-3.09	19.50	3	Vertical	356	1.59	-	28.53	2.88	-

802.11g_Nss1,(6Mbps)_4TX

2462MHz_TX




EUT X_4TX
Setting 79
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.4546G	119.00	Inf	-Inf	87.73	3	Horizontal	10	2.56	-	28.42	2.85	-
AV	2.4544G	108.76	Inf	-Inf	77.49	3	Horizontal	10	2.56	-	28.42	2.85	-
PK	2.4835G	67.98	74.00	-6.02	36.57	3	Horizontal	10	2.56	-	28.53	2.88	-
AV	2.4835G	53.46	54.00	-0.54	22.05	3	Horizontal	10	2.56	-	28.53	2.88	-

802.11g_Nss1,(6Mbps)_4TX

2462MHz_TX




EUT X_4TX
Setting 79
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	4.92382G	46.34	74.00	-27.66	38.75	3	Vertical	149	2.35	-	33.25	5.10	30.76
AV	4.9257G	32.60	54.00	-21.40	25.01	3	Vertical	149	2.35	-	33.25	5.10	30.76

802.11g_Nss1,(6Mbps)_4TX

2462MHz_TX




EUT X_4TX
Setting 79
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	4.92427G	45.79	74.00	-28.21	38.20	3	Horizontal	306	1.74	-	33.25	5.10	30.76
AV	4.92436G	32.60	54.00	-21.40	25.01	3	Horizontal	306	1.74	-	33.25	5.10	30.76

802.11ax HEW20_Nss1,(MCS0)_4TX

2412MHz_TX




EUT_X_4TX
Setting 96
02-F-K-3

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	2.3898G	66.15	74.00	-7.85	34.98	3	Vertical	3	1.11	-	28.38	2.79	-	
AV	2.39G	53.40	54.00	-0.60	22.23	3	Vertical	3	1.11	-	28.38	2.79	-	
PK	2.4074G	125.54	Inf	-Inf	94.33	3	Vertical	3	1.11	-	28.40	2.81	-	
AV	2.4172G	112.86	Inf	-Inf	81.64	3	Vertical	3	1.11	-	28.40	2.82	-	

802.11ax HEW20_Nss1,(MCS0)_4TX

2412MHz_TX




EUT_X_4TX
Setting 96
02-F-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA	
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)	
PK	2.39G	66.52	74.00	-7.48	35.35	3	Horizontal	21	2.11	-	28.38	2.79	-	
AV	2.39G	53.86	54.00	-0.14	22.69	3	Horizontal	21	2.11	-	28.38	2.79	-	
PK	2.4146G	127.21	Inf	-Inf	96.00	3	Horizontal	21	2.11	-	28.40	2.81	-	
AV	2.4098G	113.41	Inf	-Inf	82.20	3	Horizontal	21	2.11	-	28.40	2.81	-	

802.11ax HEW20_Nss1,(MCS0)_4TX

2412MHz_TX




EUT X_4TX
Setting 96
02-F-K-3

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	4.8162G	50.34	74.00	-23.66	43.15	3	Vertical	89	1.80	-	32.90	5.10	30.81
AV	4.8163G	36.45	54.00	-17.55	29.26	3	Vertical	89	1.80	-	32.90	5.10	30.81

802.11ax HEW20_Nss1,(MCS0)_4TX

2412MHz_TX




EUT X_4TX
Setting 96
02-F-K-3

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	4.8171G	50.80	74.00	-23.20	43.61	3	Horizontal	9	2.29	-	32.90	5.10	30.81	
AV	4.8224G	37.70	54.00	-16.30	30.47	3	Horizontal	9	2.29	-	32.93	5.10	30.80	

802.11ax HEW20_Nss1,(MCS0)_4TX

2437MHz_TX




EUT X_4TX
Setting 86
02-F-K-3

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.3874G	59.74	74.00	-14.26	28.58	3	Vertical	0	1.32	-	28.37	2.79	-
AV	2.3898G	45.44	54.00	-8.56	14.27	3	Vertical	0	1.32	-	28.38	2.79	-
PK	2.4422G	124.15	Inf	-Inf	92.91	3	Vertical	0	1.32	-	28.40	2.84	-
AV	2.4322G	111.31	Inf	-Inf	80.08	3	Vertical	0	1.32	-	28.40	2.83	-
PK	2.4842G	69.71	74.00	-4.29	38.29	3	Vertical	0	1.32	-	28.54	2.88	-
AV	2.4835G	49.85	54.00	-4.15	18.44	3	Vertical	0	1.32	-	28.53	2.88	-

802.11ax HEW20_Nss1,(MCS0)_4TX

2437MHz_TX




EUT X_4TX
Setting 86
02-F-K-3

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.3898G	64.46	74.00	-9.54	33.29	3	Horizontal	17	2.09	-	28.38	2.79	-
AV	2.3898G	46.70	54.00	-7.30	15.53	3	Horizontal	17	2.09	-	28.38	2.79	-
PK	2.4302G	124.73	Inf	-Inf	93.50	3	Horizontal	17	2.09	-	28.40	2.83	-
AV	2.4398G	111.11	Inf	-Inf	79.87	3	Horizontal	17	2.09	-	28.40	2.84	-
PK	2.485G	73.56	74.00	-0.44	42.13	3	Horizontal	17	2.09	-	28.54	2.89	-
AV	2.4835G	51.92	54.00	-2.08	20.51	3	Horizontal	17	2.09	-	28.53	2.88	-

802.11ax HEW20_Nss1,(MCS0)_4TX

2437MHz_TX




EUT X_4TX
Setting 86
02-F-K-3

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	4.8758G	46.76	74.00	-27.24	39.29	3	Vertical	90	2.62	-	33.15	5.10	30.78	
AV	4.87336G	33.13	54.00	-20.87	25.66	3	Vertical	90	2.62	-	33.15	5.10	30.78	

802.11ax HEW20_Nss1,(MCS0)_4TX

2437MHz_TX




EUT X_4TX
Setting 86
02-F-K-3

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	4.8722G	46.80	74.00	-27.20	39.34	3	Horizontal	248	1.45	-	33.14	5.10	30.78	
AV	4.87344G	33.09	54.00	-20.91	25.62	3	Horizontal	248	1.45	-	33.15	5.10	30.78	

802.11ax HEW20_Nss1,(MCS0)_4TX

2457MHz_TX




EUT_X_4TX
Setting 86
02-F-K-3

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.4642G	122.44	Inf	-Inf	91.12	3	Vertical	-0	1.47	-	28.46	2.86	-
AV	2.4588G	109.31	Inf	-Inf	78.01	3	Vertical	-0	1.47	-	28.44	2.86	-
PK	2.4835G	69.37	74.00	-4.63	37.96	3	Vertical	-0	1.47	-	28.53	2.88	-
AV	2.4835G	53.80	54.00	-0.20	22.39	3	Vertical	-0	1.47	-	28.53	2.88	-

802.11ax HEW20_Nss1,(MCS0)_4TX

2457MHz_TX




EUT X_4TX
Setting 86
02-F-K-3

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.4532G	123.93	Inf	-Inf	92.67	3	Horizontal	21	2.30	-	28.41	2.85	-
AV	2.458G	111.48	Inf	-Inf	80.19	3	Horizontal	21	2.30	-	28.43	2.86	-
PK	2.4846G	67.56	74.00	-6.44	36.14	3	Horizontal	21	2.30	-	28.54	2.88	-
AV	2.4835G	53.33	54.00	-0.67	21.92	3	Horizontal	21	2.30	-	28.53	2.88	-

802.11ax HEW20_Nss1,(MCS0)_4TX

2462MHz_TX




EUT_X_4TX
Setting 74
02-F-K-3

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.4636G	119.22	Inf	-Inf	87.91	3	Vertical	356	1.45	-	28.45	2.86	-
AV	2.4638G	106.36	Inf	-Inf	75.04	3	Vertical	356	1.45	-	28.46	2.86	-
PK	2.4835G	69.02	74.00	-4.98	37.61	3	Vertical	356	1.45	-	28.53	2.88	-
AV	2.4835G	53.79	54.00	-0.21	22.38	3	Vertical	356	1.45	-	28.53	2.88	-

802.11ax HEW20_Nss1,(MCS0)_4TX

2462MHz_TX




EUT_X_4TX
Setting 74
02-F-K-3

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	2.463G	120.84	Inf	-Inf	89.53	3	Horizontal	18	2.26	-	28.45	2.86	-	
AV	2.4632G	107.84	Inf	-Inf	76.53	3	Horizontal	18	2.26	-	28.45	2.86	-	
PK	2.4842G	68.18	74.00	-5.82	36.76	3	Horizontal	18	2.26	-	28.54	2.88	-	
AV	2.4835G	52.76	54.00	-1.24	21.35	3	Horizontal	18	2.26	-	28.53	2.88	-	

802.11ax HEW20_Nss1,(MCS0)_4TX

2462MHz_TX




EUT X_4TX
Setting 74
02-F-K-3

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	4.92244G	46.41	74.00	-27.59	38.83	3	Vertical	290	1.90	-	33.24	5.10	30.76	
AV	4.92545G	32.74	54.00	-21.26	25.15	3	Vertical	290	1.90	-	33.25	5.10	30.76	

802.11ax HEW20_Nss1,(MCS0)_4TX

2462MHz_TX




EUT X_4TX
Setting 74
02-F-K-3

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	4.92467G	47.03	74.00	-26.97	39.44	3	Horizontal	292	2.13	-	33.25	5.10	30.76	
AV	4.92611G	32.76	54.00	-21.24	25.17	3	Horizontal	292	2.13	-	33.25	5.10	30.76	

802.11ax HEW40_Nss1,(MCS0)_4TX

2422MHz_TX




EUT X_4TX
Setting 82
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.39G	63.99	74.00	-10.01	32.82	3	Vertical	1	1.45	-	28.38	2.79	-
AV	2.39G	51.57	54.00	-2.43	20.40	3	Vertical	1	1.45	-	28.38	2.79	-
PK	2.4276G	120.61	Inf	-Inf	89.38	3	Vertical	1	1.45	-	28.40	2.83	-
AV	2.4272G	107.59	Inf	-Inf	76.36	3	Vertical	1	1.45	-	28.40	2.83	-
PK	2.4835G	61.13	74.00	-12.87	29.72	3	Vertical	1	1.45	-	28.53	2.88	-
AV	2.4835G	49.28	54.00	-4.72	17.87	3	Vertical	1	1.45	-	28.53	2.88	-

802.11ax HEW40_Nss1,(MCS0)_4TX

2422MHz_TX




EUT X_4TX
Setting 82
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.3896G	65.35	74.00	-8.65	34.18	3	Horizontal	20	2.34	-	28.38	2.79	-
AV	2.39G	53.61	54.00	-0.39	22.44	3	Horizontal	20	2.34	-	28.38	2.79	-
PK	2.42G	121.13	Inf	-Inf	89.91	3	Horizontal	20	2.34	-	28.40	2.82	-
AV	2.4248G	107.80	Inf	-Inf	76.58	3	Horizontal	20	2.34	-	28.40	2.82	-
PK	2.4835G	62.56	74.00	-11.44	31.15	3	Horizontal	20	2.34	-	28.53	2.88	-
AV	2.4835G	50.50	54.00	-3.50	19.09	3	Horizontal	20	2.34	-	28.53	2.88	-

802.11ax HEW40_Nss1,(MCS0)_4TX

2422MHz_TX




EUT X_4TX
Setting 82
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	4.84223G	46.69	74.00	-27.31	39.34	3	Vertical	171	1.04	-	33.05	5.10	30.80	
AV	4.84255G	32.83	54.00	-21.17	25.47	3	Vertical	171	1.04	-	33.06	5.10	30.80	

802.11ax HEW40_Nss1,(MCS0)_4TX

2422MHz_TX




EUT X_4TX
Setting 82
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	4.84154G	46.69	74.00	-27.31	39.34	3	Horizontal	232	2.80	-	33.05	5.10	30.80
AV	4.84357G	32.80	54.00	-21.20	25.44	3	Horizontal	232	2.80	-	33.06	5.10	30.80

802.11ax HEW40_Nss1,(MCS0)_4TX

2437MHz_TX




EUT X_4TX
Setting 72
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.3898G	58.03	74.00	-15.97	26.86	3	Vertical	-0	1.34	-	28.38	2.79	-
AV	2.3898G	46.82	54.00	-7.18	15.65	3	Vertical	-0	1.34	-	28.38	2.79	-
PK	2.4326G	117.21	Inf	-Inf	85.98	3	Vertical	-0	1.34	-	28.40	2.83	-
AV	2.4322G	104.85	Inf	-Inf	73.62	3	Vertical	-0	1.34	-	28.40	2.83	-
PK	2.4838G	65.91	74.00	-8.09	34.49	3	Vertical	-0	1.34	-	28.54	2.88	-
AV	2.4835G	50.33	54.00	-3.67	18.92	3	Vertical	-0	1.34	-	28.53	2.88	-

802.11ax HEW40_Nss1,(MCS0)_4TX

2437MHz_TX




EUT X_4TX
Setting 72
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.3898G	63.02	74.00	-10.98	31.85	3	Horizontal	14	2.34	-	28.38	2.79	-
AV	2.3898G	48.86	54.00	-5.14	17.69	3	Horizontal	14	2.34	-	28.38	2.79	-
PK	2.425G	117.70	Inf	-Inf	86.48	3	Horizontal	14	2.34	-	28.40	2.82	-
AV	2.4302G	105.04	Inf	-Inf	73.81	3	Horizontal	14	2.34	-	28.40	2.83	-
PK	2.485G	69.18	74.00	-4.82	37.75	3	Horizontal	14	2.34	-	28.54	2.89	-
AV	2.4846G	53.79	54.00	-0.21	22.37	3	Horizontal	14	2.34	-	28.54	2.88	-

802.11ax HEW40_Nss1,(MCS0)_4TX

2437MHz_TX




EUT X_4TX
Setting 72
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	4.87397G	46.87	74.00	-27.13	39.40	3	Vertical	303	2.33	-	33.15	5.10	30.78
AV	4.87465G	33.09	54.00	-20.91	25.62	3	Vertical	303	2.33	-	33.15	5.10	30.78

802.11ax HEW40_Nss1,(MCS0)_4TX

2437MHz_TX




EUT X_4TX
Setting 72
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)	
PK	4.87494G	46.96	74.00	-27.04	39.49	3	Horizontal	128	1.44	-	33.15	5.10	30.78	
AV	4.87483G	33.11	54.00	-20.89	25.64	3	Horizontal	128	1.44	-	33.15	5.10	30.78	

802.11ax HEW40_Nss1,(MCS0)_4TX

2452MHz_TX




EUT X_4TX
Setting 69
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.3896G	55.48	74.00	-18.52	24.31	3	Vertical	341	1.90	-	28.38	2.79	-
AV	2.39G	44.29	54.00	-9.71	13.12	3	Vertical	341	1.90	-	28.38	2.79	-
PK	2.4376G	114.50	Inf	-Inf	83.26	3	Vertical	341	1.90	-	28.40	2.84	-
AV	2.4472G	102.17	Inf	-Inf	70.92	3	Vertical	341	1.90	-	28.40	2.85	-
PK	2.484G	65.35	74.00	-8.65	33.93	3	Vertical	341	1.90	-	28.54	2.88	-
AV	2.4835G	53.59	54.00	-0.41	22.18	3	Vertical	341	1.90	-	28.53	2.88	-

802.11ax HEW40_Nss1,(MCS0)_4TX

2452MHz_TX




EUT_X_4TX
Setting 69
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.3896G	56.80	74.00	-17.20	25.63	3	Horizontal	22	2.32	-	28.38	2.79	-
AV	2.39G	45.48	54.00	-8.52	14.31	3	Horizontal	22	2.32	-	28.38	2.79	-
PK	2.4448G	115.96	Inf	-Inf	84.72	3	Horizontal	22	2.32	-	28.40	2.84	-
AV	2.4548G	104.12	Inf	-Inf	72.85	3	Horizontal	22	2.32	-	28.42	2.85	-
PK	2.4848G	66.26	74.00	-7.74	34.84	3	Horizontal	22	2.32	-	28.54	2.88	-
AV	2.4848G	53.03	54.00	-0.97	21.61	3	Horizontal	22	2.32	-	28.54	2.88	-

802.11ax HEW40_Nss1,(MCS0)_4TX

2452MHz_TX




EUT X_4TX
Setting 69
02-F-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	4.90255G	46.42	74.00	-27.58	38.88	3	Vertical	170	1.58	-	33.21	5.10	30.77
AV	4.90578G	32.72	54.00	-21.28	25.18	3	Vertical	170	1.58	-	33.21	5.10	30.77

802.11ax HEW40_Nss1,(MCS0)_4TX

2452MHz_TX



EUT X_4TX
Setting 69
02-F-G-4


Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	4.90198G	47.20	74.00	-26.80	39.67	3	Horizontal	182	1.18	-	33.20	5.10	30.77
AV	4.90471G	32.71	54.00	-21.29	25.17	3	Horizontal	182	1.18	-	33.21	5.10	30.77



Summary


Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Condition
Mode 1	Pass	AV	1.74456G	25.13	54.00	-28.87	Vertical

Mode 1



Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comment	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB/m)	(m)		(°)	(m)		(dBuV/m)	(dB/m)	(dB)	(dB)
PK	1.74276G	37.17	74.00	-36.83	-4.45	3	Vertical	111	1.50	-	41.62	26.46	4.40	35.31
AV	1.74456G	25.13	54.00	-28.87	-4.44	3	Vertical	111	1.50	"Worst"	29.57	26.47	4.40	35.31

Mode 1



Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comment	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB/m)	(m)		(°)	(m)		(dBuV/m)	(dB/m)	(dB)	(dB)
PK	1.73022G	38.52	74.00	-35.48	-4.53	3	Horizontal	221	1.50	-	43.05	26.38	4.40	35.31
AV	1.74418G	25.00	54.00	-29.00	-4.44	3	Horizontal	221	1.50	"Worst"	29.44	26.47	4.40	35.31