



FCC RADIO TEST REPORT

Applicant : Newline Interactive Inc.
Address : 101 East Park Blvd. Suite 807 Plano, TX 75074, USA
Equipment : Newline Chromebox A10
Model No. : TCB-AC2
Trade Name : **newline**
FCC ID. : 2APNX00TCBAC2

I HEREBY CERTIFY THAT :

The sample was received on Apr. 15, 2019 and the testing was carried out on Jun. 08, 2019 at CerpPASS Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of CerpPASS Technology Corp., the test report shall not be reproduced except in full.

Approved by:

Mark Liao / Supervisor

Laboratory Accreditation:

CerpPASS Technology Corporation Test Laboratory





Contents

1. Summary of Test Procedure and Test Results.....	4
1.1 Applicable Standards	4
2. Test Configuration of Equipment under Test.....	5
2.1 Feature of Equipment under Test.....	5
2.2 Test Mode and Test Software	6
2.3 Description of Test System.....	6
2.4 General Information of Test	7
2.5 Measurement Uncertainty	8
3. Test Equipment and Ancillaries Used for Tests	9
4. Test of AC Power Line Conducted Emission	10
4.1 Test Result and Data	10
4.2 Test Photographs	14
5. Test of Spurious Emission (Radiated)	15
5.1 Test Limit	15
5.2 Test Procedures	15
5.3 Typical Test Setup	16
5.4 Test Result and Data (9kHz ~ 30MHz).....	17
5.5 Test Result and Data (30MHz ~ 1GHz).....	17
5.6 Test Result and Data (1GHz ~ 40GHz).....	21
5.7 Restricted Bands of Operation	25
5.8 Test Photographs (30MHz ~ 1GHz)	26
5.9 Test Photographs (1GHz ~ 40GHz)	27



History of this test report

Report No.	Issue Date	Description
TEFU2002144	Mar. 20, 2020	Original

Report Type		Description
☐	Original report	NA
☒	Derivative Report	This sample provided has been confirmed to be identical to the original report sample. The only difference are as listed below. As it doesn't affect the test result, the original report number: TEFU1903256 and content will be used. 1.Applicant information change. 2.Model No. change. 3.Trade Name change.



1. Summary of Test Procedure and Test Results

1.1 Applicable Standards

ANSI C63.4:2014

ANSI C63.10:2013

FCC Rule	Description of Test	Result
15.203	CO-LOCATION	PASS

*The principle of judgment is made according to the laboratory's reporting control and measurement uncertainty standard procedures.

*This EUT has been also tested and compiled with the requirement of FCC Part 15, Subpart B, recorded in a separate test report(TEFD1901352).



2. Test Configuration of Equipment under Test

2.1 Feature of Equipment under Test

WLAN Module	Intel / Dual Band Wireless-AC 7265(Stone Peak)
Frequency Range	BT / BLE: 2400-2483.5MHz 802.11b/g/n: 2400-2483.5MHz 802.11a/n/ac: 5150-5250MHz, 5250-5350MHz, 5470-5725MHz, 5725-5850MHz
Modulation Type	BT: GFSK, $\pi/4$ -DQPSK, 8DPSK BLE: GFSK 802.11b: CCK, DQPSK, DBPSK 802.11g/n/a: BPSK, QPSK, 16QAM, 64QAM 802.11ac: BPSK, QPSK, 16QAM, 64QAM, 256QAM
Data Rate	BT: GFSK: 1Mbps, $\pi/4$ -DQPSK: 2Mbps, 8DPSK: 3Mbps BLE: GFSK: 1Mbps WLAN: 802.11b: 1, 2, 5.5, 11Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54Mbps 802.11n: MCS0 – MCS15, HT20/40 802.11a: 6, 9, 12, 18, 24, 36, 48, 54Mbps 802.11ac: MCS0 – MCS9, VHT20/40/80
Antenna Type	Dipole Antenna
Antenna Gain	2400-2483.5MHz: 3.53dBi 5150-5250MHz: 2.52dBi 5250-5350MHz: 2.52dBi 5470-5725MHz: 2.02dBi 5725-5850MHz: 1.59dBi
Data Rate	BT: GFSK: 1Mbps, $\pi/4$ -DQPSK: 2Mbps, 8DPSK: 3Mbps BLE: GFSK: 1Mbps WLAN: 802.11b: 1, 2, 5.5, 11Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54Mbps 802.11n: MCS0 – MCS15, HT20/40 802.11a: 6, 9, 12, 18, 24, 36, 48, 54Mbps 802.11ac: MCS0 – MCS9, VHT20/40/80
Adapter	Chicony \ A11-065N1A INPUT: 100-240V~1.7A 50-60Hz OUTPUT: 19V / 3.42A 65W Chicony \ A16-090P1A INPUT: 100-240V~1.5A 50-60Hz OUTPUT: 19V / 4.74A 90W

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
2. EUT support TPC function.



2.2 Test Mode and Test Software

- During testing, the interface cables and equipment positions were varied according to ANSI C63.4.
- The complete test system included Notebook and EUT for RF test.
- An executive program, "DRTU v.11.1833.0-08103" under win7 was executed to transmit and receive data via Bluetooth.
- The following test modes were performed for the test:

Conducted Emissions from the AC mains power ports	
Test Mode	Operating Description
1	BT GFSK CH78+11n HT20 CH6
2	BT GFSK CH78+11ac VHT40 CH151
caused "Test Mode 1.2" generated the worst case, it was reported as the final data.	
Radiation Emissions (30MHz ~ 1GHz)	
Test Mode	Operating Description
1	BT GFSK CH78+WIFI 2.4G 11n HT20 CH6
2	BT GFSK CH78+WIFI 5G 11ac VHT40 CH151
caused "Test Mode 1.2" generated the worst case, they were reported as the final data.	
Radiation Emissions (1GHz ~ 40GHz)	
Test Mode	Operating Description
1	BT GFSK CH78+WIFI 2.4G 11n HT20 CH6
2	BT GFSK CH78+WIFI 5G 11ac VHT40 CH151
caused "Test Mode 1.2" generated the worst case, they were reported as the final data.	

2.3 Description of Test System

Radiated Emissions				
Equipment	Brand	Model	Length/Type	Power cord/Length/Type
Notebook	ASUS	P2430U	N/A	Adapter / 1.8m / NS
AC Power Line Conducted Emission				
Equipment	Brand	Model	Length/Type	Power cord/Length/Type
Notebook	DELL	Latitude E5470	N/A	Adapter / 1.8m / NS



2.4 General Information of Test

Test Site	Cerpass Technology Corporation Test Laboratory Address: No.10, Ln. 2, Lianfu St., Luzhu Dist., Taoyuan City 33848, Taiwan (R.O.C.) Tel:+886-3-3226-888 Fax:+886-3-3226-881 Address: No.68-1, Shihbachongsi, Shihding Township, New Taipei City 223, Taiwan, R.O.C. Tel: +886-2-2663-8582	
	FCC	TW1079, TW1061, TW1439
	IC	4934E-1, 4934E-2
	VCCI	T-2205 for Telecommunication test C-4663 for Conducted emission test R-4399, R-4218 for Radiated emission test G-10812, G-10813 for radiated disturbance above 1GHz
Frequency Range Investigated:	Conducted: from 150kHz to 30 MHz Radiation: from 30 MHz to 40,000MHz	
Test Distance:	The test distance of radiated emission from antenna to EUT is 3 M.	

Test Item	Test Site	Tested Date	Environmental Conditions	Tested By
Radiated Emissions	3M02-NK	2019/06/06	23°C / 54%	Spree Yeh
RF Conduction	CON01-NK	2019/06/08	24°C / 45%	Leon Huang



2.5 Measurement Uncertainty

Measurement Item	Uncertainty
Radiated Spurious Emission(9KHz~30MHz)	$\pm 3.405\text{dB}$
Radiated Spurious Emission(30MHz~1GHz)	$\pm 5.326\text{dB}$
Radiated Spurious Emission(1GHz~40GHz)	$\pm 5.011\text{dB}$
6dB Bandwidth	$\pm 4.407\%$
26dB Bandwidth	$\pm 4.459\%$
Occupied Bandwidth	$\pm 4.403\%$
Peak Output Power(Conducted Power Meter)	$\pm 1.31\text{dB}$
Power Spectral Density	$\pm 2.106\text{dB}$
Duty Cycle	$\pm 0.17\%$
Frequency Stability	$\pm 156.543\text{Hz}$
Temperature	$\pm 1.2^{\circ}\text{C}$
Humidity	$\pm 2.7\%$



3. Test Equipment and Ancillaries Used for Tests

Test Item	Radiated Emissions				
Test Site	Semi Anechoic Room(3M02-NK)				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
Bilog Antenna	Schwarzbeck	VULB9168	275	2018/09/17	2019/09/16
Active Loop Antenna	EMCO	6507	40855	2019/05/24	2020/05/23
Horn Antenna	EMCO	3115	31589	2019/04/01	2020/03/31
Horn Antenna	EMCO	3116	31974	2018/09/07	2019/09/06
EMI Receiver	ROHDE & SCHWARZ	ESCI	101423	2018/06/11	2019/06/10
Spectrum Analyzer	ROHDE & SCHWARZ	FSP 40	100219	2018/07/03	2019/07/02
Preamplifier	EM Electronics corp.	EM330	60660	2019/03/11	2020/03/10
Preamplifier	EMC INSTRUMENTS	EMC051845SE	980333	2018/09/18	2019/09/17
Bluetooth Tester	ROHDE & SCHWARZ	CBT	101133	2019/04/07	2020/04/06
Cable-3in1(30M-1G)	HARBOUR INDUSTRIES	LL142	CCE1316	2018/09/12	2019/09/11
Cable-0.5m(1G-40G)	Rapidtek	40GHZ 50CM	38MS-38MS50314	2019/04/09	2020/04/08
Cable-3m(1G-40G)	Rapidtek	40GHZ 300CM	38MS-38MS300314	2019/04/09	2020/04/08
Cable-8m(1G-40G)	Rapidtek	40GHZ 800CM	38MS-38MS800314	2019/04/10	2020/04/09
E3	AUDIX	v8.2014-8-6	RK-000529	NA	NA

Test Item	RF Conducted				
Test Site	RFCON01-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
Spectrum Analyzer	ROHDE & SCHWARZ	FSP 40	100219	2018/07/03	2019/07/02
Bluetooth Tester	ROHDE & SCHWARZ	CBT	101133	2019/04/07	2020/04/06
Attenuator	KEYSIGHT	8491B	MY39250705	2018/09/04	2019/09/03
TEMP & HUMIDITY CHAMBER	T-MACHINE	TMJ-9712	T-12-040111	2018/08/30	2019/08/29
Power Sensor	Anritsu	MA2411B	1207295	2019/04/11	2020/04/10


Test Item	AC Power Line Conducted Emission				
Test Site	CON01-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
EMI Receiver	ROHDE & SCHWARZ	ESCI	100821	2018/9/12	2019/09/11
Line Impedance Stabilization Network	Schwarzbeck	NSLK 8127	8127-740	2018/6/13	2019/06/12
Pulse Limiter	ROHDE & SCHWARZ	ESH3-Z2	101933	2018/9/4	2019/09/03
E3	AUDIX	v8.2014-8-6	RK-000531	NA	NA



4. Test of AC Power Line Conducted Emission

4.1 Test Result and Data

Power	: AC 120V / 60Hz	Pol/Phase	: LINE
Test Mode	: Mode 1		



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.15	9.92	20.41	30.33	56.00	-25.67	Average	P
2	0.15	9.92	35.74	45.66	66.00	-20.34	QP	P
3	0.15	9.92	21.65	31.57	55.84	-24.27	Average	P
4	0.15	9.92	35.66	45.58	65.84	-20.26	QP	P
5	0.16	9.92	20.42	30.34	55.46	-25.12	Average	P
6	0.16	9.92	34.41	44.33	65.46	-21.13	QP	P
7	0.17	9.92	16.86	26.78	55.02	-28.24	Average	P
8	0.17	9.92	31.95	41.87	65.02	-23.15	QP	P
9	0.19	9.92	15.99	25.91	54.16	-28.25	Average	P
10	0.19	9.92	30.47	40.39	64.16	-23.77	QP	P
11	26.42	10.86	20.46	31.32	50.00	-18.68	Average	P
12	26.42	10.86	26.02	36.88	60.00	-23.12	QP	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=(LISN or ISN or Current Probe)Factor + Cable Loss



Power	: AC 120V / 60Hz	Pol/Phase	: NEUTRAL
Test Mode	: Mode 1		



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.15	9.95	19.46	29.41	55.96	-26.55	Average	P
2	0.15	9.95	35.40	45.35	65.96	-20.61	QP	P
3	0.15	9.95	20.24	30.19	55.81	-25.62	Average	P
4	0.15	9.95	34.75	44.70	65.81	-21.11	QP	P
5	0.17	9.95	16.04	25.99	55.18	-29.19	Average	P
6	0.17	9.95	32.28	42.23	65.18	-22.95	QP	P
7	0.18	9.95	15.28	25.23	54.43	-29.20	Average	P
8	0.18	9.95	30.70	40.65	64.43	-23.78	QP	P
9	0.19	9.95	13.19	23.14	53.87	-30.73	Average	P
10	0.19	9.95	28.96	38.91	63.87	-24.96	QP	P
11	26.34	10.88	21.20	32.08	50.00	-17.92	Average	P
12	26.34	10.88	26.72	37.60	60.00	-22.40	QP	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=(LISN or ISN or Current Probe)Factor + Cable Loss



Power	:	AC 120V / 60Hz	Pol/Phase	:	LINE
Test Mode	:	Mode 2		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.16	9.92	21.36	31.28	55.54	-24.26	Average	P
2	0.16	9.92	35.89	45.81	65.54	-19.73	QP	P
3	0.16	9.92	18.99	28.91	55.28	-26.37	Average	P
4	0.16	9.92	34.81	44.73	65.28	-20.55	QP	P
5	0.17	9.92	16.79	26.71	54.94	-28.23	Average	P
6	0.17	9.92	32.83	42.75	64.94	-22.19	QP	P
7	0.18	9.92	16.57	26.49	54.36	-27.87	Average	P
8	0.18	9.92	31.98	41.90	64.36	-22.46	QP	P
9	0.21	9.92	11.87	21.79	53.30	-31.51	Average	P
10	0.21	9.92	28.62	38.54	63.30	-24.76	QP	P
11	26.61	10.87	20.33	31.20	50.00	-18.80	Average	P
12	26.61	10.87	26.04	36.91	60.00	-23.09	QP	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=(LISN or ISN or Current Probe)Factor + Cable Loss



Power	: AC 120V / 60Hz	Pol/Phase	: NEUTRAL
Test Mode	: Mode 2		:



Note: Level=Reading+Factor

Margin=Level-Limit

Factor=(LISN or ISN or Current Probe)Factor + Cable Loss



5. Test of Spurious Emission (Radiated)

5.1 Test Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3


5.2 Test Procedures

- The EUT was placed on a rotatable table top 0.8 meter above ground.
- The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- The table was rotated 360 degrees to determine the position of the highest radiation.
- The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- "Cone of radiation" has been considered to be 3dB bandwidth of the measurement antenna.




5.3 Typical Test Setup


Below 30MHz test setup



30MHz- 1GHz Test Setup



Above 1GHz Test Setup






5.4 Test Result and Data (9kHz ~ 30MHz)

The 9kHz - 30MHz spurious emission is under limit 20dB more.

5.5 Test Result and Data (30MHz ~ 1GHz)

Power	:	AC 120V / 60Hz	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	31.94	-10.57	46.20	35.63	40.00	-4.37	QP	100	52	P
2	40.67	-9.60	45.37	35.77	40.00	-4.23	Peak	400	0	P
3	68.80	-11.42	43.28	31.86	40.00	-8.14	Peak	400	0	P
4	188.11	-11.79	47.79	36.00	43.50	-7.50	Peak	400	0	P
5	250.19	-10.37	47.89	37.52	46.00	-8.48	Peak	400	0	P
6	375.32	-6.51	38.58	32.07	46.00	-13.93	Peak	400	0	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 1		:



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	73.65	-12.33	39.00	26.67	40.00	-13.33	Peak	100	0	P
2	147.37	-9.66	46.61	36.95	43.50	-6.55	Peak	100	0	P
3	196.84	-12.16	47.36	35.20	43.50	-8.30	Peak	100	0	P
4	250.19	-10.37	48.57	38.20	46.00	-7.80	Peak	100	0	P
5	304.51	-8.57	39.36	30.79	46.00	-15.21	Peak	100	0	P
6	375.32	-6.51	44.73	38.22	46.00	-7.78	Peak	100	0	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 2		:



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	31.94	-10.57	46.58	36.01	40.00	-3.99	QP	100	59	P
2	40.67	-9.60	42.66	33.06	40.00	-6.94	QP	100	179	P
3	85.29	-14.85	47.43	32.58	40.00	-7.42	Peak	400	0	P
4	185.20	-11.51	46.51	35.00	43.50	-8.50	Peak	400	0	P
5	250.19	-10.37	47.89	37.52	46.00	-8.48	Peak	400	0	P
6	375.32	-6.51	36.67	30.16	46.00	-15.84	Peak	400	0	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 2		:



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	71.71	-11.92	38.49	26.57	40.00	-13.43	Peak	100	0	P
2	148.34	-9.59	46.89	37.30	43.50	-6.20	Peak	100	0	P
3	195.87	-12.24	46.21	33.97	43.50	-9.53	Peak	100	0	P
4	219.15	-11.68	42.91	31.23	46.00	-14.77	Peak	100	0	P
5	250.19	-10.37	48.31	37.94	46.00	-8.06	Peak	100	0	P
6	375.32	-6.51	44.47	37.96	46.00	-8.04	Peak	100	0	P

Note: Level=Reading+Factor


Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



5.6 Test Result and Data (1GHz ~ 40GHz)

Power	:	AC 120V / 60Hz	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2520.00	-14.09	54.79	40.70	54.00	-13.30	Average	100	98	P
2	2520.00	-14.09	65.49	51.40	74.00	-22.60	Peak	100	98	P
3	4874.00	-6.63	45.77	39.14	54.00	-14.86	Average	100	157	P
4	4874.00	-6.63	60.20	53.57	74.00	-20.43	Peak	100	157	P
5	7311.00	-1.28	50.50	49.22	54.00	-4.78	Average	311	100	P
6	7311.00	-1.28	62.40	61.12	74.00	-12.88	Peak	311	100	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	AC 120V / 60Hz	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2520.00	-14.09	58.65	44.56	54.00	-9.44	Average	342	311	P
2	2520.00	-14.09	70.49	56.40	74.00	-17.60	Peak	342	311	P
3	4874.00	-6.63	45.60	38.97	54.00	-15.03	Average	100	158	P
4	4874.00	-6.63	58.60	51.97	74.00	-22.03	Peak	100	158	P
5	7311.00	-1.28	46.81	45.53	54.00	-8.47	Average	100	322	P
6	7311.00	-1.28	60.25	58.97	74.00	-15.03	Peak	100	322	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 2		:



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	4960.00	-6.39	58.49	52.10	54.00	-1.90	Average	100	160	P
2	4960.00	-6.39	63.69	57.30	74.00	-16.70	Peak	100	160	P
3	7440.00	-1.14	46.70	45.56	54.00	-8.44	Average	324	152	P
4	7440.00	-1.14	48.60	47.46	74.00	-26.54	Peak	324	152	P
5	11510.00	3.98	44.85	48.83	54.00	-5.17	Average	100	66	P
6	11510.00	3.98	58.60	62.58	74.00	-11.42	Peak	100	66	P

Note: Level=Reading+Factor


Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor

+



Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 2		:



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	4960.00	-6.39	48.84	42.45	54.00	-11.55	Average	300	255	P
2	4960.00	-6.39	62.69	56.30	74.00	-17.70	Peak	300	255	P
3	7440.00	-1.14	46.77	45.63	54.00	-8.37	Average	114	308	P
4	7440.00	-1.14	60.47	59.33	74.00	-14.67	Peak	114	308	P
5	11510.00	3.98	44.14	48.12	54.00	-5.88	Average	100	329	P
6	11510.00	3.98	57.85	61.83	74.00	-12.17	Peak	100	329	P

Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



5.7 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.09000 – 0.11000	16.42000 – 16.42300	399.9 – 410.0	4.500 – 5.250
0.49500 – 0.505**	16.69475 – 16.69525	608.0 – 614.0	5.350 – 5.460
2.17350 – 2.19050	16.80425 – 16.80475	960.0 – 1240.0	7.250 – 7.750
4.12500 – 4.12800	25.50000 – 25.67000	1300.0 – 1427.0	8.025 – 8.500
4.17725 – 4.17775	37.50000 – 38.25000	1435.0 – 1626.5	9.000 – 9.200
4.20725 – 4.20775	73.00000 – 74.60000	1645.5 – 1646.5	9.300 – 9.500
6.21500 – 6.21800	74.80000 – 75.20000	1660.0 – 1710.0	10.600 – 12.700
6.26775 – 6.26825	108.00000 – 121.94000	1718.8 – 1722.2	13.250 – 13.400
6.31175 – 6.31225	123.00000 – 138.00000	2200.0 – 2300.0	14.470 – 14.500
8.29100 – 8.29400	149.90000 – 150.05000	2310.0 – 2390.0	15.350 – 16.200
8.36200 – 8.36600	156.52475 – 156.52525	2483.5 – 2500.0	17.700 – 21.400
8.37625 – 8.38675	156.70000 – 156.90000	2655.0 – 2900.0	22.010 – 23.120
8.41425 – 8.41475	162.01250 – 167.17000	3260.0 – 3267.0	23.600 – 24.000
12.29000 – 12.29300	167.72000 – 173.20000	3332.0 – 3339.0	31.200 – 31.800
12.51975 – 12.52025	240.00000 – 285.00000	3345.8 – 3358.0	36.430 – 36.500
12.57675 – 12.57725	322.00000 – 335.40000	3600.0 – 4400.0	Above 38.6
13.36000 – 13.41000			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz