



Willow Run Test Labs, LLC
 8501 Beck Road, Building 2227
 Belleville, MI 48111
 Phone: (734) 252-9785, Fax (734) 926-9785
 e-mail: info@wrtest.com

RF EXPOSURE CALCULATIONS

Requirement:

According to USA CFR 15 §1.1307 (b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. For Canada, RSS-102 sets out the requirements and measurement techniques used to evaluate radio frequency (RF) exposure compliance of radiocommunication apparatus designed to be used within the vicinity of the human body.

Maximum Permissible Exposure Calculations:

USA REF: 1.1310, 2.1091/1093, 447498 D01 General RF Exposure Guidance v06
 IC REF: RSS-102 Issue 5, Safety Code 6
 Min. Sep. Distance: 20 cm (Mobile)

Test Date: 25-Oct-16
 Test Engineer: Joseph Brunett
 EUT: Allegion LE
 EUT Mode: Worst Case
 Meas. Distance: 3 meters

Mode	Freq. MHz	Worst Case E3(Avg)* dBuV/m	E20cm(Avg) dBuV/m	H20cm(Avg) dBuA/m	Canada ISSED RSS-102 MPE			USA FCC 1.1310 MPE		
					SC6 Limit (E20cm) dBuV/m	SC6 Limit (H20cm) dBuA/m	Worst Case MPE Ratio	E20cm Limit*** dBuV/m	H20cm Limit*** dBuA/m	Worst Case MPE Ratio
LF Entry	0.12500	56.90000	103.94365	52.64365		135.32826	0.00007	175.76337	124.24375	0.00026
LF Entry	13.56000	54.80000	101.84365	50.54365	148.77401	97.24263	0.00462	155.67335	104.16369	0.00208
Mode	Freq. MHz	Worst Case EIRP(Avg)** dBm	E20cm(Avg) dBuV/m	S20cm(Avg)**** mW/cm2	SC6 Limit (S20cm) mW/cm2			S Limit mW/cm2		
BLE (module)	2400-2483.5	11.15000	129.87183	0.00259	5.47422			1.00000		
WiLAN (module)	2400-2483.5	16.54000	135.26183	0.00897	5.47422			1.00000		
					MPE Total (<1):			MPE Total (<1):		
					Complies?			Complies?		
					Yes			Yes		

*As Measured / Computed from highest fundamental emission, see fundamental emission section of this report.

**EIRP, as computed from Modular Device RF Exposure Exhibits.

*** For FCC MPE, use of 300 kHz limit at 125 kHz as previously allowed by FCC.

**** EIRP (mW) = S (mW/cm²) x 4 x PI x 20cm²

Summary:

The EUT with all transmitters is compliant with both the FCC power density limit and the ISSED Exposure Evaluation limits.