

## **Askey Computer Corporation**

10F, No. 119, Jiankang Rd., Zhonghe Dist., New Taipei City, Taiwan

## Request for Modular/Limited Modular Approval

Dat	e: December 27, 2023					
Subject: Manufacturer's Declaration for		<ul><li>☑ - Modular Approval</li><li>☐ - Limited Modular Approval</li></ul>	☐ - Split Modular Approval ☐ - Limited Split Modular Approval			
Con	fidentiality Request for: H8N-WAH00	<u>70</u>				
		Basic Requirements – FCC Part 15.212(a				
For Items Marked "NO(*)", the Limited Module Description Must be Filled Out on the Following Pa  Modular Approval Requirement Re				1	ges quirement Met	
1.	The modular transmitter must have its own RF shielding. This is intended to ensure that the module does not have to rely upon the shielding provided by the device into which it is installed in order for all modular transmitter emissions to comply with FCC limits. It is also intended to prevent coupling between the RF circuitry of the module and any wires or circuits in the device into which the module is installed. Such coupling may result in non-compliant operation. The physical crystal and tuning capacitors may be located external to the shielded radio elements. 15.212(a)(1)(i)		talled in order for prevent coupling which the module	⊠ - YES	□ - NO(*)	
	The module contains a metal shield which of to antenna connector.	covers all RF components and circuitry.	The shield is located o	on the top of t	he board next	
2.	The modular transmitter must have buffered ensure that the module will comply with FO or over-modulation. 15.212(a)(1)(ii)			⊠ - YES	□ - NO(*)	
	Data to the modulation circuit is buffered a	s described in the operational description	on provided with the o	application.		
3.	The modular transmitter must have its own to ensure that the module will comply with supplying circuitry in the device into which	FCC requirements regardless of the de	sign of the power	⊠ - YES	□ - NO(*)	
	The module contains its own power supply	regulation. Please refer to schematic fil	led with this application	on.		
4.	The modular transmitter must comply with §§ 15.203, 15.204(b), 15.204(c), 15.212(a), attached or employ a "unique" antenna co antenna, including the cable). The "profess to modules but can apply to limited modula	and 2.929(b). The antenna must either upler (at all connections between the nional installation" provision of § 15.203	be permanently nodule and the B is not applicable	⊠ - YES	□ - NO(*)	
	The module connects to its antenna using a tested and approved with this device may be			or. A list of aı	ntennas	
5.	The modular transmitter must be tested in inside another device during testing. This is complying with Part 15 emission limits regardless the transmitter module will be batter requirements found in Section 15.207. ACC the module must not contain ferrites, unless 15.27(a)). The length of these lines shall be at least 10 centimeters to insure that there supporting equipment. Any accessories, peduring testing shall be unmodified or commodified or commodified.	intended to demonstrate that the moderdless of the device into which it is every powered, it must comply with the Apr DC power lines and data input/outpuss they will be marketed with the modulength typical of actual use or, if that less no coupling between the case of the ripherals, or support equipment connections.	dule is capable of ntually installed. C line conducted t lines connected to le (see Section ength is unknown, module and cted to the module	⊠ - YES	□ - NO(*)	
	The module was tested stand-alone as show	wn in test setup photographs filed with	this application.			

**Modular Approval Requirement** 

Requirement Met



## **Askey Computer Corporation**

10F, No. 119, Jiankang Rd., Zhonghe Dist., New Taipei City, Taiwan

6.	The modular transmitter must be labeled with its own FCC ID number, or use an electron display (see KDB Publication 784748).		
	If using a permanently affixed label with its own FCC ID number, if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: XYZMODEL1" or "Contains FCC ID: XYZMODEL1." Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization.	⊠ - YES	□ - NO(*)
	If the modular transmitter uses an electronic display of the FCC identification number, the information must be readily accessible and visible on the modular transmitter or on the device in which it is installed. If the module is installed inside another device, then the outside of the device into which the module is installed must display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains FCC certified transmitter module(s)." Any similar wording that expresses the same meaning may be used. The user manual must include instructions on how to access the electronic display. A copy of these instructions must be included in the application for equipment authorization. 15.212(a)(1)(vi)		
	There is a label on the module as shown in the labeling exhibit filed with this application. Host specific loshown in the installation manual filed with this application.	abeling instruc	tions are
7.	The modular transmitter must comply with all specific rule or operating requirements applicable to the transmitter, including all the conditions provided in the integration instructions by the grantee. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(e), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured. 15.212(a)(1)(vii)	⊠ - YES	□ - NO(*)
	The module complies with FCC Part 15C requirements. Instructions to the OEM installer are provided in filed with this application.	the installatio	n manual
8.	The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 2.1091, 2.1093 and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance in accordance with Section 15.247(b)(4). Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance. 15.212(a)(1)(viii)	⊠ - YES	□ - NO(*)
		-	

Sincerely,

Name: Jack Po

Title: Manager

Date: 2023-12-27