



**ANSI/IEEE Std. C95.1-1992**

in accordance with the requirements of

FCC Report and Order: ET Docket 93-62, and OET Bulletin 65 Supplement C

## **FCC SAR TEST REPORT**

**For**

**High Tech Computer Corp.**

**POCKET PC**

**Model: PL400MD**

**Trade Name: FUJITSU SIEMENS COMPUTER**

*Prepared for*

**High Tech Computer Corp.  
23 Hsin Hua Rd., Taoyuan 330, Taiwan, R.O.C.**

*Prepared by*

**Compliance Certification Services Inc.  
No. 81-1, Lane 210, Bade Rd. 2, Luchu Hsiang,  
Taoyuan Hsien, (338) Taiwan, R.O.C.  
TEL: 886-3-324-0332  
FAX: 886-3-324-5235**



---

***Note:** This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.*



## CERTIFICATE OF COMPLIANCE (SAR EVALUATION)

**Dates of Test:** March 05-April 27, 2004

<b>Applicant:</b>	High Tech Computer Corp. 23 Hsin Hua Rd., Taoyuan 330, Taiwan, R.O.C.
<b>Model Number:</b>	PL400MD
<b>Device Category:</b>	PORTABLE DEVICES
<b>Exposure Category:</b>	GENERAL POPULATION/UNCONTROLLED EXPOSURE

**Test Sample is a:** Production unit  
**Modulation type:** 802.11b  
Direct Sequence Spread Spectrum  
**Tx Frequency:** 2412 ~ 2462 MHz  
**Max. O/P Power:** 17.39dBm  
(Conducted/Peak)  
**Max. SAR (1g):** 0.709W/kg  
**Application Type:** Certification  
**FCC Rule Part(s):** 15C



**Note:** This Report is only applicable for 802.11b.

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE Std. C95.1-1992 and had been tested in accordance with the measurement procedures specified in FCC OET 65 Supplement C (released on 6/29/2001 see Test Report).

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

**Approved by:**

**Reviewed by:**

Harris Lai / Executive Vice President  
Compliance Certification Services Inc.

James Lee / Senior engineer  
Compliance Certification Services Inc.



## **TABLE OF CONTENTS**

<b>1.</b>	<b>EUT DESCRIPTION .....</b>	<b>4</b>
<b>2.</b>	<b>REQUIREMENTS FOR COMPLIANCE TESTING DEFINED BY THE FCC ....</b>	<b>5</b>
<b>3.</b>	<b>DOSIMETRIC ASSESSMENT SYSTEM .....</b>	<b>5</b>
3.1	MEASUREMENT SYSTEM DIAGRAM .....	6
3.2	SYSTEM COMPONENTS.....	7
	DASY4 Measurement Server.....	7
	Data Acquisition Electronics (DAE).....	7
	ET3DV6 Isotropic E-Field Probe for Dosimetric Measurements .....	7
	ES3DV2 Isotropic E-Field Probe for Dosimetric Measurements .....	8
	SAM Phantom (V4.0) .....	8
	Device Holder for SAM Twin Phantom .....	8
	System Validation Kits .....	9
<b>4.</b>	<b>EVALUATION PROCEDURES.....</b>	<b>10</b>
<b>5.</b>	<b>MEASUREMENT UNCERTAINTY .....</b>	<b>13</b>
<b>6.</b>	<b>EXPOSURE LIMIT .....</b>	<b>14</b>
<b>7.</b>	<b>MEASUREMENT RESULTS .....</b>	<b>15</b>
7.1	SYSTEM PERFORMANCE CHECK.....	15
7.2	TEST LIQUID CONFIRMATION .....	17
7.3	EUT TUNE-UP PROCEDURES.....	19
7.4	SAR MEASUREMENTS RESULTS.....	20
<b>8.</b>	<b>EUT PHOTOS .....</b>	<b>22</b>
<b>9.</b>	<b>EQUIPMENT LIST &amp; CALIBRATION STATUS.....</b>	<b>23</b>
<b>10.</b>	<b>FACILITIES .....</b>	<b>24</b>
<b>11.</b>	<b>REFERENCES .....</b>	<b>24</b>
<b>12.</b>	<b>ATTACHMENTS .....</b>	<b>25</b>

## 1. EUT DESCRIPTION

<b>Applicant:</b>	High Tech Computer Corp. 23 Hsin Hua Rd., Taoyuan 330, Taiwan, R.O.C.
<b>Model Number:</b>	PL400MD
<b>Device Category:</b>	PORTABLE DEVICES
<b>Exposure Category:</b>	GENERAL POPULATION/UNCONTROLLED EXPOSURE

<b>Test Sample is a:</b>	Production unit
<b>Modulation type:</b>	802.11b Direct Sequence Spread Spectrum
<b>Tx Frequency:</b>	2412 ~ 2462 MHz
<b>Max. O/P Power:</b> (Conducted/Peak)	17.39dBm
<b>Max. SAR (1g):</b>	0.709W/kg
<b>Application Type:</b>	Certification
<b>FCC Rule Part(s):</b>	15C
<b>Antennas:</b>	PIFA Ant.






## **2. REQUIREMENTS FOR COMPLIANCE TESTING DEFINED BY THE FCC**

The US Federal Communications Commission has released the report and order "Guidelines for Evaluating the Environmental Effects of RF Radiation", ET Docket No. 93-62 in August 1996 [1]. The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g for an uncontrolled environment and 8.0 mW/g for an occupational/controlled environment as recommended by the ANSI/IEEE standard C95.1-1992 [6]. According to the Supplement C of OET Bulletin 65 "Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

## **3. DOSIMETRIC ASSESSMENT SYSTEM**

These measurements were performed with the automated near-field scanning system DASY4 from Schmid & Partner Engineering AG (SPEAG). The system is based on a high precision robot (working range greater than 0.9 m) which positions the probes with a positional repeatability of better than  $\pm 0.02$  mm. Special E- and H-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines to the data acquisition unit. The SAR measurements were conducted with the dosimetric probe ET3DV6-SN: 1762 and ES3DV2-SN: 3023 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe has been calibrated according to the procedure with accuracy of better than  $\pm 10\%$ . The spherical isotropy was evaluated with the procedure and found to be better than  $\pm 0.25$  dB. The phantom used was the SAM Twin Phantom as described in FCC supplement C, IEEE P1528 and EN50361.

### 3.1 MEASUREMENT SYSTEM DIAGRAM



**The DASY4 system for performing compliance tests consists of the following items:**

- A standard high precision 6-axis robot (Stäubli RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to the DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows 2000 or Windows XP.
- DASY4 software.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand and right-hand usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing validating the proper functioning of the system.

## 3.2 SYSTEM COMPONENTS

### DASY4 Measurement Server



The DASY4 measurement server is based on a PC/104 CPU board with a 166MHz low-power Pentium, 32MB chip disk and 64MB RAM. The necessary circuits for communication with either the DAE3 electronic box as well as the 16-bit AD-converter system for optical detection and digital I/O interface are contained on the DASY4 I/O-board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation.

The PC-operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with two expansion slots which are reserved for future applications. Please note that the expansion slots do not have a standardized pinout and therefore only the expansion cards provided by SPEAG can be inserted. Expansion cards from any other supplier could seriously damage the measurement server. Calibration: No calibration required.

### Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE3) consists of a highly sensitive electrometer grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock. The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection. The input impedance of the DAE3 box is 200M $\Omega$ ; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



### ET3DV6 Isotropic E-Field Probe for Dosimetric Measurements

- Construction:** Symmetrical design with triangular core  
Built-in optical fiber for surface detection system (ET3DV6 only)  
Built-in shielding against static charges  
PEEK enclosure material (resistant to organic solvents, e.g., glycolether)
- Calibration:** Basic Broad Band Calibration in air: 10-2500 MHz.  
Conversion Factors (CF) for HSL 900 and HSL 1800  
CF-Calibration for other liquids and frequencies upon request.
- Frequency:** 10 MHz to 3 GHz; Linearity:  $\pm 0.2$  dB (30 MHz to 3 GHz)
- Directivity:**  $\pm 0.2$  dB in HSL (rotation around probe axis)  
 $\pm 0.4$  dB in HSL (rotation normal to probe axis)
- Dynamic Range:** 2  $\mu$ W/g to > 100 mW/g; Linearity:  $\pm 0.2$  dB
- Optical Surface**
- Detection:**  $\pm 0.2$  mm repeatability in air and clear liquids over diffuse reflecting surfaces (ET3DV6 only)
- Dimensions:** Overall length: 330 mm (Tip: 16 mm)  
Tip diameter: 6.8 mm (Body: 12 mm)  
Distance from probe tip to dipole centers: 2.7 mm
- Application:** General dosimetric measurements up to 3 GHz  
Compliance tests of mobile phones  
Fast automatic scanning in arbitrary phantoms (ET3DV6)



Interior of probe



E-Field probe



### ES3DV2 Isotropic E-Field Probe for Dosimetric Measurements

<b>Construction:</b>	Symmetrical design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., glycoether)
<b>Calibration:</b>	Basic Broad Band Calibration in air: 10-2500 MHz. Conversion Factors (CF) for HSL 900 and HSL 1800 CF- Calibration for other liquids and frequencies upon request.
<b>Frequency:</b>	10 MHz to > 6 GHz; Linearity: $\pm 0.2$ dB
<b>Directivity:</b>	$\pm 0.2$ dB in HSL (rotation around probe axis); $\pm 0.3$ dB in tissue material (rotation normal to probe axis)
<b>Dynamic Range:</b>	5 $\mu$ W/g to > 100 mW/g; Linearity: $\pm 0.2$ dB
<b>Dimensions:</b>	Overall length: 330 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.7 mm
<b>Application:</b>	General dosimetry up to 6 GHz Dosimetry in strong gradient fields Compliance tests of mobile phones



### SAM Phantom (V4.0)

**Construction:** The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528-200X, CENELEC 50361 and IEC 62209. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot.

**Shell Thickness:**  $2 \pm 0.2$  mm

**Filling Volume:** Approx. 25 liters

**Dimensions:** Height: 810mm; Length: 1000mm; Width: 500mm



### Device Holder for SAM Twin Phantom

**Construction:** In combination with the Twin SAM Phantom V4.0 or Twin SAM, the Mounting Device (made from POM) enables the rotation of the mounted transmitter in spherical coordinates, whereby the rotation point is the ear opening. The devices can be easily and accurately positioned according to IEC, IEEE, CENELEC, FCC or other specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).







## System Validation Kits

- Construction:** Symmetrical dipole with 1/4 balun Enables measurement of feedpoint impedance with NWA Matched for use near flat phantoms filled with brain simulating solutions Includes distance holder and tripod adaptor.
- Frequency:** 450, 900, 1800, 2450, 5800 MHz
- Return loss:** > 20 dB at specified validation position
- Power capability:** > 100 W ( $f < 1\text{GHz}$ ); > 40 W ( $f > 1\text{GHz}$ )
- Dimensions:** 450V2: dipole length: 270 mm; overall height: 330 mm  
D900V2: dipole length: 149 mm; overall height: 330 mm  
D1800V2: dipole length: 72 mm; overall height: 300 mm  
D2450V2: dipole length: 51.5 mm; overall height: 300 mm D5GHzV2: dipole length: 25.5 mm; overall height: 290 mm



## 4. EVALUATION PROCEDURES

### DATA EVALUATION

The DASY4 post processing software (SEMCAD) automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	$Norm_i, a_{i0}, a_{i1}, a_{i2}$
	- Conversion factor	$ConvF_i$
	- Diode compression point	$dcp_i$
Device parameters:	- Frequency	$f$
	- Crest factor	$cf$
Media parameters:	- Conductivity	$\sigma$
	- Density	$\rho$

These parameters must be set correctly in the software. They can be found in the component documents or be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multi-meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

with	$V_i$	= Compensated signal of channel i	(i = x, y, z)
	$U_i$	= Input signal of channel i	(i = x, y, z)
	$cf$	= Crest factor of exciting field	(DASY parameter)
	$dcp_i$	= Diode compression point	(DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

$$\text{E-field probes: } E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$

$$\text{H-field probes: } H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f}$$

with	$V_i$	= Compensated signal of channel i	(i = x, y, z)
	$Norm_i$	= Sensor sensitivity of channel i	(i = x, y, z)
		$\mu V/(V/m)^2$ for E0field Probes	
	$ConvF$	= Sensitivity enhancement in solution	
	$a_{ij}$	= Sensor sensitivity factors for H-field probes	
	$f$	= Carrier frequency (GHz)	
	$E_i$	= Electric field strength of channel i in V/m	
	$H_i$	= Magnetic field strength of channel i in A/m	

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

- with  $SAR$  = local specific absorption rate in mW/g  
 $E_{tot}$  = total field strength in V/m  
 $\sigma$  = conductivity in [mho/m] or [Siemens/m]  
 $\rho$  = equivalent tissue density in g/cm<sup>3</sup>

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.

The power flow density is calculated assuming the excitation field as a free space field.

$$P_{pwe} = \frac{E_{tot}^2}{3770} \quad \text{or} \quad P_{pwe} = H_{tot}^2 \cdot 37.7$$

- with  $P_{pwe}$  = Equivalent power density of a plane wave in mW/cm<sup>2</sup>  
 $E_{tot}$  = total electric field strength in V/m  
 $H_{tot}$  = total magnetic field strength in A/m



## **SAR MEASUREMENT PROCEDURES**

The procedure for assessing the peak spatial-average SAR value consists of the following steps:

- **Power Reference Measurement**

The reference and drift jobs are useful jobs for monitoring the power drift of the device under test in the batch process. Both jobs measure the field at a specified reference position, at a selectable distance from the phantom surface. The reference position can be either the selected section's grid reference point or a user point in this section. The reference job projects the selected point onto the phantom surface, orients the probe perpendicularly to the surface, and approaches the surface using the selected detection method.

- **Area Scan**

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a finer measurement around the hot spot. The sophisticated interpolation routines implemented in DASY4 software can find the maximum locations even in relatively coarse grids. The scan area is defined by an editable grid. This grid is anchored at the grid reference point of the selected section in the phantom. When the area scan's property sheet is brought-up, grid was at to **15 mm by 15 mm** and can be edited by a user.

- **Zoom Scan**

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The default zoom scan measures **5x5x7** points within a cube whose base faces are centered around the maximum found in a preceding area scan job within the same procedure. If the preceding Area Scan job indicates more than one maximum, the number of Zoom Scans has to be enlarged accordingly (The default number inserted is 1).

- **Power Drift measurement**

The drift job measures the field at the same location as the most recent reference job within the same procedure, and with the same settings. The drift measurement gives the field difference in dB from the reading conducted within the last reference measurement. Several drift measurements are possible for one reference measurement. This allows a user to monitor the power drift of the device under test within a batch process. In the properties of the Drift job, the user can specify a limit for the drift and have DASY4 software stop the measurements if this limit is exceeded.

- **Z-Scan**

The Z Scan job measures points along a vertical straight line. The line runs along the Z-axis of a one-dimensional grid. A user can anchor the grid to the current probe location. As with any other grids, the local Z-axis of the anchor location establishes the Z-axis of the grid.

## 5. MEASUREMENT UNCERTAINTY

UNCERTAINTY BUDGE ACCORDING TO IEEE P1528						
Error Description	Uncertainty Value $\pm\%$	Probability distribution	Divisor	C <sub>1</sub> 1g	Standard unc.(1g) $\pm\%$	V <sub>1</sub> or V <sub>eff</sub>
Measurement System						
Probe calibration	$\pm 4.8$	normal	1	1	$\pm 4.8$	
Axial isotropy of probe	$\pm 4.6$	rectangular	3	$(1-C_p)^{1/2}$	$\pm 1.9$	
Sph. Isotropy of probe	$\pm 9.7$	rectangular	3	$(C_p)^{1/2}$	$\pm 3.9$	
Probe linearity	$\pm 4.5$	rectangular	3	1	$\pm 2.7$	
Detection Limit	$\pm 0.9$	rectangular	3	1	$\pm 0.6$	
Boundary effects	$\pm 8.5$	rectangular	3	1	$\pm 4.8$	
Readoutelectronics	$\pm 1.0$	normal	1	1	$\pm 1.0$	
Response time	$\pm 0.9$	rectangular	3	1	$\pm 0.5$	
Integration time	$\pm 1.2$	rectangular	3	1	$\pm 0.8$	
Mech Constrains of robot	$\pm 0.5$	rectangular	3	1	$\pm 0.2$	
Probe positioning	$\pm 2.7$	rectangular	3	1	$\pm 1.7$	
Extrap. And integration	$\pm 4.0$	rectangular	3	1	$\pm 2.3$	
RF ambient conditiona	$\pm 0.54$	rectangular	3	1	$\pm 0.43$	
Test Sample Related						
Device positioning	$\pm 2.2$	normal	1	1	$\pm 2.23$	11
Device holder uncertainty	$\pm 5$	normal	1	1	$\pm 5.0$	7
Power drift	$\pm 5$	rectangular	3	1	$\pm 2.9$	
Phantom and Set up						
Phantom uncertainty	$\pm 4$	rectangular	3	1	$\pm 2.3$	
Liquid conductivity	$\pm 5$	rectangular	3	0.6	$\pm 1.7$	
Liquid conductivity	$\pm 5$	rectangular	3	0.6	$\pm 3.5/1.7$	
Liquid permittivity	$\pm 5$	rectangular	3	0.6	$\pm 1.7$	
Liquid permittivity	$\pm 5$	rectangular	3	0.6	$\pm 1.7$	
Combined Standard Uncertainty					$\pm 12.14/11.76$	
Coverage Factor for 95%		kp=2				
Expanded Standard Uncertainty					$\pm 24.29/23.51$	

Table: Worst-case uncertainty for DASY4 assessed according to IEEE P1528.

The budge is valid for the frequency range 300 MHz to 6G Hz and represents a worst-case analysis.



## 6. EXPOSURE LIMIT

(A).Limits for Occupational/Controlled Exposure (W/kg)

<u>Whole-Body</u>	<u>Partial-Body</u>	<u>Hands, Wrists, Feet and Ankles</u>
0.4	8.0	2.0

(B).Limits for General Population/Uncontrolled Exposure (W/kg)

<u>Whole-Body</u>	<u>Partial-Body</u>	<u>Hands, Wrists, Feet and Ankles</u>
0.08	1.6	4.0

NOTE: **Whole-Body SAR** is averaged over the entire body, **partial-body SAR** is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. **SAR for hands, wrists, feet and ankles** is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

### **Population/Uncontrolled Environments:**

are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

### **Occupational/Controlled Environments:**

are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

**NOTE**  
**GENERAL POPULATION/UNCONTROLLED EXPOSURE**  
**PARTIAL BODY LIMIT**  
**1.6 W/kg**

## 7. MEASUREMENT RESULTS

### 7.1 SYSTEM PERFORMANCE CHECK

The system performance check is performed prior to any usage of the system in order to guarantee reproducible results. The system performance check verifies that the system operates within its specifications. The system performance check results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

#### SYSTEM PERFORMANCE CHECK MEASUREMENT CONDITIONS

- The measurements were performed in the flat section of the SAM twin phantom filled with Head and Body simulating liquid of the following parameters.
- The DASY4 system with an E-filed probe ET3DV6 SN: 1762 was used for the measurements.
- The DASY4 system with an E-filed probe ES3DV2 SN: 3023 was used for the measurements.
- The dipole was mounted on the small tripod so that the dipole feed point was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 10 mm (above 1 GHz) from dipole center to the simulating liquid surface.
- The coarse grid with a grid spacing of 10mm was aligned with the dipole.
- Special 5x5x7 fine cube was chosen for cube integration ( $dx=dy=7.5$  mm,  $dz=3$  mm).
- Distance between probe sensors and phantom surface was set to 3.0 mm.
- The dipole input power (forward power) was  $250\text{ mW}\pm 3\%$ .
- The results are normalized to 1 W input power.

#### Reference SAR values

The reference SAR values were using measurement results indicated in the dipole calibration document (see table below)

Frequency (MHz)	1g SAR	10g SAR	Local SAR at Surface (Above Feed Point)	Local SAR at Surface (y = 2cm offset from feed point)
900	10.3	6.57	16.4	5.4
1800	38.2	20.3	69.5	6.8
2450	54.8	24.2	104.2	7.7
2450(Body)	53.2	24.3	104.2	7.7



## **SYSTEM PERFORMANCE CHECK RESULTS**

**Dipole:** D2450V2 SN: 728

**Date:** March 05, 2004

**Ambient condition:** Temperature 24.4°C; Relative humidity: 50%

Head Simulating Liquid			Parameters	Target	Measured	Deviation[% ]	Limited[% ]
f(MHz)	Temp. [°C]	Depth [cm]					
2450.00	23.00	15.00	Permittivity:	39.20	39.04	-0.41	± 5
			Conductivity:	1.80	1.84	2.22	± 5
			1g SAR:	54.80	56.00	2.19	± 5

**Dipole:** D2450V2 SN: 731

**Date:** April 27, 2004

**Ambient condition:** Temperature 24.6°C; Relative humidity: 53%

Head Simulating Liquid			Parameters	Target	Measured	Deviation[% ]	Limited[% ]
f(MHz)	Temp. [°C]	Depth [cm]					
2450.00	23.10	15.00	Permittivity:	52.70	51.00	-3.23	± 5
			Conductivity:	1.95	1.96	0.51	± 5
			1g SAR:	53.20	53.20	0.00	± 5

## 7.2 TEST LIQUID CONFIRMATION

### SIMULATING LIQUIDS PARAMETER CHECK

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values

The relative permittivity and conductivity of the tissue material should be within  $\pm 5\%$  of the values given in the table below. 5% may not be easily achieved at certain frequencies. Under such circumstances, 10% tolerance may be used until more precise tissue recipes are available

### IEEE SCC-34/SC-2 P1528 RECOMMENDED TISSUE DIELECTRIC PARAMETERS

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations and extrapolated according to the head parameters specified in P1528

Target Frequency	Head		Body	
(MHz)	$\epsilon_r$	$\sigma$ (S/m)	$\epsilon_r$	$\sigma$ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800-2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5800	45.3	5.27	48.2	6.00



### **SIMULATING LIQUIDS PARAMETER CHECK RESULTS**

**Ambient condition:** Temperature: 24.0°C; Relative humidity: 50%

**Date:** March 05, 2004

Body Simulating Liquid			Parameters	Target	Measured	Deviation[%]	Limited[%]
f (MHz)	Temp. [°C]	Depth (cm)					
2450.00	23.00	15.00	Permittivity:	52.70	51.05	-3.13	± 5
			Conductivity:	1.95	1.95	0.00	± 5

**Ambient condition:** Temperature: 24.6°C; Relative humidity: 53%

**Date:** April 27, 2004

Body Simulating Liquid			Parameters	Target	Measured	Deviation[%]	Limited[%]
f (MHz)	Temp. [°C]	Depth (cm)					
2450.00	23.10	15.00	Permittivity:	52.70	51.00	-3.23	± 5
			Conductivity:	1.95	1.96	0.51	± 5



### 7.3 EUT TUNE-UP PROCEDURES

The following procedure had been used to prepare the EUT for the SAR test.

- The client supplied a special driver to program the EUT, allowing it to continually transmit the specified maximum power and change the channel frequency.
- The conducted power was measured at the high, middle and low channel frequency before and after the SAR measurement.
- The output power (dBm) we measured before SAR test in different transition rate and channel.

#### IEEE802.11b:

<b>Rate CH</b>	<b>1M</b>	<b>2M</b>	<b>5.5M</b>	<b>11M</b>
1	16.07	16.17	16.22	16.35
6	16.60	16.70	16.76	16.89
11	17.10	17.20	17.26	<b>17.39</b>

## 7.4 SAR MEASUREMENTS RESULTS

### EUT Setup Configuration 1



802.11b (DSSS): Duty Cycle =100 %, Crest Factor: 1.

Depth of liquid: 15.0 cm

Sep. [mm]	Antenna	Channel	Frequency [MHz]	*Conducted Power_dBm		Liquid Temp [°C]	SAR (W/kg)	Limit (W/kg)
				Before	After			
0	1	1	2412	16.35	16.33	23.0	0.659	1.6
0	1	6	2437	16.89	16.87	23.0	<b>0.709</b>	1.6
0	1	11	2462	<b>17.39</b>	17.37	23.0	0.661	1.6

802.11b (DSSS)with Bluetooth: Duty Cycle =100 %, Crest Factor: 1.


Depth of liquid: 15.0 cm

Sep. [mm]	Antenna	Channel	Frequency [MHz]	*Conducted Power_dBm		Liquid Temp [°C]	SAR (W/kg)	Limit (W/kg)
				Before	After			
0	1	6	2437	16.89	16.87	23.1	0.708	1.6

#### Notes:

1. \*: Peak power.
2. Bottom face in parallel with flat phantom.
3. See attachment for the result presentation in plot format.

## EUT Setup Configuration 2



802.11b (DSSS): Duty Cycle = 100 %, Crest Factor: 1.


Depth of liquid: 15.0 cm

Sep. [mm]	Antenna	Channel	Frequency [MHz]	*Conducted Power_dBm		Liquid Temp [°C]	SAR (W/kg)	Limit (W/kg)
				Before	After			
15	1	1	2412	16.32	16.30	23.0	0.126	1.6
15	1	6	2437	16.87	16.85	23.0	0.135	1.6
15	1	11	2462	<b>17.37</b>	17.35	23.0	0.124	1.6

### Notes:

1. \*: Peak power.
2. Host device perpendicular to flat phantom.
3. See attachment for the result presentation in plot format.

## 8. EUT PHOTOS





**9. EQUIPMENT LIST & CALIBRATION STATUS**

Name of Equipment	Manufacturer	Type/Model	Serial Number	Calibration Due
S-Parameter Network Analyzer	Agilent	E8358A	US40280243	05/24/04
Electronic Probe kit	Hewlett Packard	85070D	N/A	N/A
Power Meter	Boonton	4531	13061	07/13/04
Power Sensor	Boonton	56218	2240	07/13/04
Power Meter	Agilent	E4416A	GB41291611	03/15/04
Power Sensor	Agilent	E9327A	US40441097	03/15/04
Thermometer	Amarell	4046	24775	10/10/13
Thermometer	Amarell	4046	23641	12/12/12
Universal Radio Communication Tester	Rohde & Schwarz	CMU 200	1100.0008.02	N/A
Signal Generator	Agilent	E8257C	US542340383	04/22/04
Amplifier	Mini-Circuit	ZHL-1724HLN	N/A	N/A
DC Power generator	ABM	8301HD		N/A
Data Acquisition Electronics (DAE)	SPEAG	DAE3	558	03/07/04
Data Acquisition Electronics (DAE)	SPEAG	DAE3	427	03/15/05
Dosimetric E-Field Probe	SPEAG	ET3DV6	1762	03/31/04
Dosimetric E-Field Probe	SPEAG	ES3DV2	3023	09/23/04
900 MHz System Validation Dipole	SPEAG	D900V2	179	01/12/05
1800 MHz System Validation Dipole	SPEAG	D1800V2	2d026	02/09/05
2450 MHz System Validation Dipole	SPEAG	D2450V2	728	03/21/04
2450 MHz System Validation Dipole	SPEAG	D2450V2	731	03/21/05
Probe Alignment Unit	SPEAG	LB (V2)	348	N/A
Robot	Staubli	RX90B L	F02/5T69A1/A/01	N/A
SAM Twin Phantom V4.0	SPEAG	N/A	N/A	N/A
Devices Holder	SPEAG	N/A	N/A	N/A
Head 835 MHz	CCS	H835A	N/A	N/A
Muscle 835 MHz	CCS	M835A	N/A	N/A
Head 900 MHz	CCS	H900A	N/A	N/A
Muscle 900 MHz	CCS	M900A	N/A	N/A
Head 1800 MHz	CCS	H1800A	N/A	N/A
Muscle 1800 MHz	CCS	M1800A	N/A	N/A
Head 1900 MHz	CCS	H1900A	N/A	N/A
Muscle 1900 MHz	CCS	M1900A	N/A	N/A
Head 2450 MHz	CCS	H2450A	N/A	N/A
Muscle 2450 MHz	CCS	M2450A	N/A	N/A
Note: SPEAG will arrange the calibration date for equipment DAE3. The equipment accuracy, please refer to "The System performance check " of this test report on P.16-17.				

## 10. FACILITIES

All measurement facilities used to collect the measurement data are located at

- ☐ No. 81-1, Lane 210, Bade Rd. 2, Luchu Hsiang, Taoyuan Hsien, Taiwan, R.O.C.
- ☒ No. 11, Wu-Kung 6 Rd, Wu-Ku Hsiang, Wu-Ku Industrial District, Taipei Hsien, (248) Taiwan.
- ☐ No. 199, Chungshen Road, Hsintien City, Taipei Hsien, Taiwan, R.O.C.

## 11. REFERENCES

- [1] Federal Communications Commission, \Report and order: Guidelines for evaluating the environ-mental effects of radiofrequency radiation", Tech. Rep. FCC 96-326, FCC, Washington, D.C. 20554, 1996.
- [2] David L. Means Kwok Chan, Robert F. Cleveland, \Evaluating compliance with FCC guidelines for human exposure to radiofrequency electromagnetic fields", Tech. Rep., Federal Communication Commision, O\_ice of Engineering & Technology, Washington, DC, 1997.
- [3] Thomas Schmid, Oliver Egger, and Niels Kuster, \Automated E-\_eld scanning system for dosimetric assessments", IEEE Transactions on Microwave Theory and Techniques, vol. 44, pp. 105{113, Jan. 1996.
- [4] Niels Kuster, Ralph K.astle, and Thomas Schmid, \Dosimetric evaluation of mobile communications equipment with known precision", IEICE Transactions on Communications, vol. E80-B, no. 5, pp. 645{652, May 1997.
- [5] CENELEC, \Considerations for evaluating of human exposure to electromagnetic fields (EMFs) from mobile telecommunication equipment (MTE) in the frequency range 30MHz - 6GHz", Tech. Rep., CENELEC, European Committee for Electrotechnical Standardization, Brussels, 1997.
- [6] ANSI, ANSI/IEEE C95.1-1992: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz, The Institute of Electrical and Electronics Engineers, Inc., New York, NY 10017, 1992.
- [7] Katja Pokovic, Thomas Schmid, and Niels Kuster, \Robust setup for precise calibration of E-\_eld probes in tissue simulating liquids at mobile communications frequencies", in ICECOM \_97, Dubrovnik, October 15{17, 1997, pp. 120{124.
- [8] Katja Pokovic, Thomas Schmid, and Niels Kuster, \E-\_eld probe with improved isotropy in brain simulating liquids", in Proceedings of the ELMAR, Zadar, Croatia, 23{25 June, 1996, pp. 172{175.
- [9] Volker Hombach, Klaus Meier, Michael Burkhardt, Eberhard K. uhn, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 900 MHz", IEEE Transactions onMicrowave Theory and Techniques, vol. 44, no. 10, pp. 1865{1873, Oct. 1996.
- [10] Klaus Meier, Ralf Kastle, Volker Hombach, Roger Tay, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 1800 MHz", IEEE Transactions on Microwave Theory and Techniques, Oct. 1997, in press.
- [11] W. Gander, Computermathematik, Birkhaeuser, Basel, 1992.
- [12] W. H. Press, S. A. Teukolsky, W. T. Vetterling, and B. P. Flannery, Numerical Recepies in C, The Art of Scientific Computing, Second Edition, Cambridge University Press, 1992..Dosimetric Evaluation of Sample device, month 1998 9
- [13] NIS81 NAMAS, \The treatment of uncertainty in EMC measurement", Tech. Rep., NAMAS Executive, National Physical Laboratory, Teddington, Middlesex, England, 1994.
- [14] Barry N. Taylor and Christ E. Kuyatt, \Guidelines for evaluating and expressing the uncertainty of NIST measurement results", Tech. Rep., National Institute of Standards and Technology, 1994. Dosimetric Evaluation of Sample device, month 1998 10



## 12. ATTACHMENTS

Exhibit	Content
1	System Performance Check Plots
2	SAR Test Plots

**END OF REPORT**

Test Laboratory: Compliance Certification Services Inc.

## **D2450V2 SN 728**

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 728**

Communication System: CW2450; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: HSL2450 ( $\sigma = 1.84$  mho/m,  $\epsilon_r = 39.04$ ,  $\rho = 1000$  kg/m<sup>3</sup>)

Air Temperature 24.4 deg C ; Liquid Temperature 23.0 deg C

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1762; ConvF(5.1, 5.1, 5.1); Calibrated: 3/31/2003
- Sensor-Surface: 4mm (Mechanical Surface Detection)  
Sensor-Surface: 0mm (Fix Surface)  
Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn558; Calibrated: 3/7/2003
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.8 Build 62

**Pin=250mW,d=10mm/Area Scan (6x6x1):** Measurement grid: dx=15mm, dy=15mm

Reference Value = 98.3 V/m

Power Drift = -0.0 dB

Maximum value of SAR = 10.4 mW/g

**Pin=250mW,d=10mm/Z Scan (1x1x21):** Measurement grid: dx=20mm, dy=20mm, dz=5mm

Reference Value = 98.3 V/m

Power Drift = -0.0 dB

Maximum value of SAR = 23.6 mW/g

**Pin=250mW,d=10mm/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm



Peak SAR (extrapolated) = 30.9 W/kg

SAR(1 g) = 14 mW/g; SAR(10 g) = 6.34 mW/g

Reference Value = 98.3 V/m

Power Drift = -0.0 dB

Maximum value of SAR = 15.6 mW/g



Test Laboratory: Compliance Certification Services Inc.

## **D2450V2 SN 728**

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 731**

Communication System: CW2450; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Air Temperature: 24.6 deg C; Liquid Temperature: 23.1 deg C

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV2 - SN3023; ConvF(4.1, 4.1, 4.1); Calibrated: 9/23/2003
- Sensor-Surface: 3mm (Mechanical Surface Detection)  
Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn427; Calibrated: 3/15/2004
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1271
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

**Pin=250mW,d=10mm/Area Scan (6x6x1):** Measurement grid: dx=15mm, dy=15mm

Reference Value = 97.9 V/m; Power Drift = -0.0 dB

Maximum value of SAR (measured) = 10.3 mW/g

**Pin=250mW,d=10mm/Z Scan (1x1x21):** Measurement grid: dx=20mm, dy=20mm, dz=5mm

Reference Value = 97.9 V/m; Power Drift = -0.0 dB

Maximum value of SAR (measured) = 18.9 mW/g



**Pin=250mW,d=10mm/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 97.9 V/m; Power Drift = -0.0 dB

Maximum value of SAR (measured) = 17.5 mW/g

Peak SAR (extrapolated) = 26.4 W/kg


**SAR(1 g) = 13.3 mW/g; SAR(10 g) = 6.19 mW/g**





Test Laboratory: Compliance Certification Services Inc.

# Test Configuration-1



Test Laboratory: Compliance Certification Services Inc.

## Touch mode

**DUT: PDA; Type: PL400MD; Serial: N/A**

Communication System: 802.11b; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium: BSL2450 ( $\sigma = 1.95$  mho/m,  $\epsilon_r = 51.05$ ,  $\rho = 1000$  kg/m<sup>3</sup>)

Air Temperature 24.4 deg C ; Liquid Temperature 23.0 deg C

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1762; ConvF(4.6, 4.6, 4.6); Calibrated: 3/31/2003
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)  
Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn558; Calibrated: 3/7/2003
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.8 Build 62

**Low Rate=11M bit/Area Scan (8x7x1):** Measurement grid: dx=15mm, dy=15mm

Reference Value = 14.5 V/m

Power Drift = 0.0 dB

Maximum value of SAR = 0.644 mW/g

**Low Rate=11M bit/Z Scan (1x1x21):** Measurement grid: dx=20mm, dy=20mm, dz=5mm

Reference Value = 14.5 V/m

Power Drift = 0.0 dB

Maximum value of SAR = 0.625 mW/g

**Low Rate=11M bit/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm



Peak SAR (extrapolated) = 1.58 W/kg

SAR(1 g) = 0.659 mW/g; SAR(10 g) = 0.310 mW/g

Reference Value = 14.5 V/m

Power Drift = 0.0 dB

Maximum value of SAR = 0.725 mW/g



Test Laboratory: Compliance Certification Services Inc.

## Touch mode

**DUT: PDA; Type: PL400MD; Serial: N/A**

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: BSL2450 ( $\sigma = 1.95$  mho/m,  $\epsilon_r = 51.05$ ,  $\rho = 1000$  kg/m<sup>3</sup>)

Air Temperature 24.4 deg C ; Liquid Temperature 23.0 deg C

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1762; ConvF(4.6, 4.6, 4.6); Calibrated: 3/31/2003
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)  
Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn558; Calibrated: 3/7/2003
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.8 Build 62

**mid Rate=11M bit/Area Scan (6x6x1):** Measurement grid: dx=15mm, dy=15mm

Reference Value = 14.9 V/m

Power Drift = 0.1 dB

Maximum value of SAR = 0.745 mW/g

**mid Rate=11M bit/Z Scan (1x1x21):** Measurement grid: dx=20mm, dy=20mm, dz=5mm

Reference Value = 14.9 V/m

Power Drift = 0.1 dB

Maximum value of SAR = 0.671 mW/g

**mid Rate=11M bit/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm



Peak SAR (extrapolated) = 1.77 W/kg

SAR(1 g) = 0.709 mW/g; SAR(10 g) = 0.332 mW/g

Reference Value = 14.9 V/m

Power Drift = 0.1 dB

Maximum value of SAR = 0.775 mW/g



Test Laboratory: Compliance Certification Services Inc.

## Touch mode

**DUT: PDA; Type: PL400MD; Serial: N/A**

Communication System: 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: BSL2450 ( $\sigma = 1.95$  mho/m,  $\epsilon_r = 51.05$ ,  $\rho = 1000$  kg/m<sup>3</sup>)

Air Temperature 24.4 deg C ; Liquid Temperature 23.0 deg C

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1762; ConvF(4.6, 4.6, 4.6); Calibrated: 3/31/2003
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)  
Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn558; Calibrated: 3/7/2003
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.8 Build 62

**High Rate=11M bit/Area Scan (6x6x1):** Measurement grid: dx=15mm, dy=15mm

Reference Value = 14.4 V/m

Power Drift = 0.1 dB

Maximum value of SAR = 0.720 mW/g

**High Rate=11M bit/Z Scan (1x1x21):** Measurement grid: dx=20mm, dy=20mm, dz=5mm

Reference Value = 14.4 V/m

Power Drift = 0.1 dB

Maximum value of SAR = 0.613 mW/g

**High Rate=11M bit/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm



Peak SAR (extrapolated) = 1.65 W/kg

SAR(1 g) = 0.661 mW/g; SAR(10 g) = 0.309 mW/g

Reference Value = 14.4 V/m

Power Drift = 0.1 dB

Maximum value of SAR = 0.715 mW/g





Test Laboratory: Compliance Certification Services Inc.

## Co-location

**DUT: PDA; Type: PL400MD; Serial: N/A**

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2437 \text{ MHz}$ ;  $\sigma = 1.96 \text{ mho/m}$ ;  $\epsilon_r = 51$ ;  $\rho = 1000 \text{ kg/m}^3$

Air Temperature: 25.8 deg C; Liquid Temperature: 24.8 deg C

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV2 - SN3023; ConvF(4.1, 4.1, 4.1); Calibrated: 9/23/2003
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)  
Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn427; Calibrated: 3/15/2004
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1271
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

**mid Rate=11M bit/Area Scan (6x6x1):** Measurement grid: dx=15mm, dy=15mm

Reference Value = 14.8 V/m; Power Drift = 0.1 dB

Maximum value of SAR (measured) = 0.745 mW/g

**mid Rate=11M bit/Z Scan (1x1x21):** Measurement grid: dx=20mm, dy=20mm, dz=5mm

Reference Value = 14.8 V/m; Power Drift = 0.1 dB

Maximum value of SAR (measured) = 0.670 mW/g



**mid Rate=11M bit/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 14.8 V/m; Power Drift = 0.1 dB

Maximum value of SAR (measured) = 0.774 mW/g


Peak SAR (extrapolated) = 1.75 W/kg

SAR(1 g) = **0.708 mW/g**; SAR(10 g) = **0.331 mW/g**



Test Laboratory: Compliance Certification Services Inc.

# Test Configuration-2



Test Laboratory: Compliance Certification Services Inc.

## 15mm mode

**DUT: PDA; Type: PL400MD; Serial: N/A**

Communication System: 802.11b; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium: BSL2450 ( $\sigma = 1.95$  mho/m,  $\epsilon_r = 51.05$ ,  $\rho = 1000$  kg/m<sup>3</sup>)

Air Temperature 24.4 deg C ; Liquid Temperature 23.0 deg C

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1762; ConvF(4.6, 4.6, 4.6); Calibrated: 3/31/2003
- Sensor-Surface: 4mm (Mechanical Surface Detection)  
Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn558; Calibrated: 3/7/2003
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.8 Build 62

**Low Rate=11M bit/Area Scan (7x7x1):** Measurement grid: dx=15mm, dy=15mm

Reference Value = 7.94 V/m

Power Drift = -0.1 dB

Maximum value of SAR = 0.128 mW/g

**Low Rate=11M bit/Z Scan (1x1x21):** Measurement grid: dx=20mm, dy=20mm, dz=5mm

Reference Value = 7.94 V/m

Power Drift = -0.1 dB

Maximum value of SAR = 0.120 mW/g

**Low Rate=11M bit/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm



Peak SAR (extrapolated) = 0.266 W/kg

SAR(1 g) = 0.126 mW/g; SAR(10 g) = 0.063 mW/g

Reference Value = 7.94 V/m

Power Drift = -0.1 dB

Maximum value of SAR = 0.138 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 15mm mode

**DUT: PDA; Type: PL400MD; Serial: N/A**

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: BSL2450 ( $\sigma = 1.95$  mho/m,  $\epsilon_r = 51.05$ ,  $\rho = 1000$  kg/m<sup>3</sup>)

Air Temperature 24.4 deg C ; Liquid Temperature 23.0 deg C

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1762; ConvF(4.6, 4.6, 4.6); Calibrated: 3/31/2003
- Sensor-Surface: 4mm (Mechanical Surface Detection)  
Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn558; Calibrated: 3/7/2003
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.8 Build 62

**mid Rate=11M bit/Area Scan (6x6x1):** Measurement grid: dx=15mm, dy=15mm

Reference Value = 8.08 V/m

Power Drift = -0.1 dB

Maximum value of SAR = 0.117 mW/g

**mid Rate=11M bit/Z Scan (1x1x21):** Measurement grid: dx=20mm, dy=20mm, dz=5mm

Reference Value = 8.08 V/m

Power Drift = -0.0 dB

Maximum value of SAR = 0.131 mW/g

**mid Rate=11M bit/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm



Peak SAR (extrapolated) = 0.283 W/kg

SAR(1 g) = 0.135 mW/g; SAR(10 g) = 0.068 mW/g

Reference Value = 8.08 V/m

Power Drift = -0.1 dB

Maximum value of SAR = 0.151 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 15mm mode

**DUT: PDA; Type: PL400MD; Serial: N/A**

Communication System: 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: BSL2450 ( $\sigma = 1.95$  mho/m,  $\epsilon_r = 51.05$ ,  $\rho = 1000$  kg/m<sup>3</sup>)

Air Temperature 24.4 deg C ; Liquid Temperature 23.0 deg C

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1762; ConvF(4.6, 4.6, 4.6); Calibrated: 3/31/2003
- Sensor-Surface: 4mm (Mechanical Surface Detection)  
Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn558; Calibrated: 3/7/2003
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.8 Build 62

**High Rate=11M bit/Area Scan (6x6x1):** Measurement grid: dx=15mm, dy=15mm

Reference Value = 7.74 V/m

Power Drift = -0.0 dB

Maximum value of SAR = 0.109 mW/g

**High Rate=11M bit/Z Scan (1x1x21):** Measurement grid: dx=20mm, dy=20mm, dz=5mm

Reference Value = 7.74 V/m

Power Drift = -0.0 dB

Maximum value of SAR = 0.121 mW/g

**High Rate=11M bit/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Peak SAR (extrapolated) = 0.263 W/kg

SAR(1 g) = 0.124 mW/g; SAR(10 g) = 0.062 mW/g

Reference Value = 7.74 V/m

Power Drift = -0.0 dB

Maximum value of SAR = 0.138 mW/g



