

## RF EXPOSURE EVALUATION

### EUT Specification

|                            |                               |
|----------------------------|-------------------------------|
| <b>EUT</b>                 | WIRELESS FULL DUPLEX INTERCOM |
| <b>Model Number</b>        | HY812                         |
| <b>FCC ID</b>              | 2AXOF-HY812                   |
| <b>Antenna gain (Max)</b>  | -2.12dBi                      |
| <b>Operation Frequency</b> | 915MHz                        |
| <b>Modulation</b>          | GFSK                          |
| <b>Input Rating</b>        | 120Vac, 60Hz                  |
| <b>Max. output power</b>   | 89.85 dBμV/m(-5.45dBm)        |

### Test Requirement:

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF)

Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

| Frequency Range(MHz)   | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density(mW/cm <sup>2</sup> ) | Average Time |
|--|------------------------------|------------------------------|------------------------------------|--------------|
| <b>(A) Limits for Occupational/Control Exposures</b>         |                              |                              |                                    |              |
| <b>300-1500</b>  | --                           | --                           | <b>F/300</b>                       | <b>6</b>     |
| <b>1500-100000</b>   | --                           | --                           | <b>5</b>                           | <b>6</b>     |
| <b>(B) Limits for General Population/Uncontrol Exposures</b> |                              |                              |                                    |              |
| <b>300-1500</b>  | --                           | --                           | <b>F/1500</b>                      | <b>6</b>     |
| <b>1500-100000</b>   | --                           | --                           | <b>1</b>                           | <b>30</b>    |

### 11.1 Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

$P_d$ = Power density in mW/cm<sup>2</sup>

$P_{out}$ =output power to antenna in mW

$G$ = Numeric gain of the antenna relative to isotropic antenna

$\pi$ =3.1416

$R$ = distance between observation point and center of the radiator in cm=20cm

Pd the limit of MPE,  $1\text{mW}/\text{cm}^2$ . If we know the maximum gain of the nd total  
 power input to the antenna, through the calculation, we will know the distance  
 where the MPE limit is reached.

## 11.2 Measurement Result

Antenna gain: -2.12dBi

| Mode | Channel Freq. (MHz) | Measured power (dBm) | Tune-up power (dBm) | Max tune-up power (dBm) | Antenna Gain (Numeric) | Evaluation result (mW/cm <sup>2</sup> ) | Power density Limits (mW/cm <sup>2</sup> ) |
|------|---------------------|----------------------|---------------------|-------------------------|------------------------|---|--|
| GFSK | 915                 | -5.45                | $-5 \pm 1$          | -4                      | 0.614                  | 0.000049                                | 0.61                                       |

Signature:

*Shawn Wen*

Shawn Wen

Date: 2023-12-15

