

Appendix B

Highest Test Plots

Table of Contents

1. BT Head-worn 0mm SAR 3

1. BT Head-worn 0mm SAR

Date: 13.05.2024

Test Laboratory: Guangdong Dongdian Testing Service Co., Ltd.

Q24032615-1E

DUT: WIRELESS HEADPHONES; Model Number: HA-S95N; Serial: S24032615-018

Communication System: UID 0, Bluetooth (0); Communication System Band: Bluetooth; Frequency: 2480 MHz; Communication System PAR: 0 dB; PMF: 1.12202e-005

Medium parameters used: $f = 2480 \text{ MHz}$; $\sigma = 1.862 \text{ S/m}$; $\epsilon_r = 38.105$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3906; ComF(7.95, 7.95, 7.95); Calibrated: 29.04.2024;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1366; Calibrated: 29.04.2024
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP-1197
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Bottom side 3DH5 2480/Area Scan (11x13x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Maximum value of SAR (measured) = 0.238 W/kg

Configuration/Bottom side 3DH5 2480/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 6.274 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.302 W/kg

SAR(1 g) = 0.163 W/kg; SAR(10 g) = 0.089 W/kg

Maximum value of SAR (measured) = 0.248 W/kg

