



SGS-CSTC Standards
Technical Services Ltd.

1/F., Building No. 1 Building, Agriculture Machinery Materials Co. Wushan
Road, Shipai, Tianhe District, Guangzhou, China
Telephone: +86 (0) 20 3848 1001 Fax: +86 (0) 20 3848 1006
kent_hsu@sgs.com



FEDERAL COMMUNICATIONS COMMISSION
Registration number: 282399

Report No.: 03.03.0241E-2

Page: 1 of 9

FCC ID: HAP91252R49

FCC TEST REPORT

Application No. : 03.03.0162E-2

Applicant : Echo Toys Ltd

FCC ID : HAP91252R49

Equipment under Test (EUT):

Name : Silver Echo

Model : 91252

Standards : FCC PART 15, SUBPART B : 2002

Date of Receipt : 13 March 2003

Date of Test : 14 March 2003

Date of Issue : 17 March 2003

Test Result :	PASS *
----------------------	---------------

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Kent Hsu
Laboratory Manager
SGS-CSTC Co., Ltd.

This report refers to the General Conditions for Inspection and Testing Services, printed overleaf

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the SGS PRODUCT CERTIFICATION MARK.. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.



2 **Contents**

	Page
1 COVER PAGE.....	1
2 CONTENTS	2
3 GENERAL INFORMATION.....	3
3.1 CLIENT INFORMATION	3
3.2 DETAILS OF E.U.T.	3
3.3 DESCRIPTION OF SUPPORT UNITS	3
3.4 TEST LOCATION.....	3
3.5 OTHER INFORMATION REQUESTED BY THE CUSTOMER	3
3.6 TEST FACILITY.....	4
4 TEST RESULTS.....	5
4.1 TEST INSTRUMENTS	5
4.2 E.U.T. OPERATION	5
4.3 TEST PROCEDURE & MEASUREMENT DATA	6
4.3.1 <i>Radiated Emissions</i>	6
4.4 PHOTOGRAPHS - RADIATED EMISSION TEST SETUP IN CHAMBER	7
5 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS.....	8-9

3 General Information

3.1 Client Information

Applicant: Echo Toys Ltd

Address of Applicant: Room 1108, Peninsula Centre 67 Mody Road, Tism Sha Tusi East, Kowloon, Hong Kong.

3.2 Details of E.U.T.

Product Name: Silver Echo

Model: 91252 (Receiver Part)

Power Supply: 6V DC Recycled Battery (1 x 'Ni-MH' Battery)

Power Cord: N/A-

3.3 Description of Support Units

The EUT was tested as an independent unit: a receiver for a radio transmitter.

3.4 Test Location

All tests were performed at:-

SGS-CSTC Standards Technical Services Ltd., Guangzhou Safety & EMC Laboratory, 1/F, Building No. 1, Agriculture Machinery Materials Company Warehouse Ltd., Wushan Road Shipai, Tianhe District, Guangzhou, China. P.C. 510630.

Tel: +86 20 3848 1001

Fax: +86 20 3848 1006

3.5 Other Information Requested by the Customer

None.

3.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

1. **NVLAP – Lab Code: 200611-0**
SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is recognized under the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 2000611-0. Effective through February 2, 2003.
2. **ACA**
SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our NVLAP accreditation.
3. **SGS UK -- Certificate No.: 32, SGS-TUV SAARLAND and SGS-FINKO**
Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.
4. **CNAL – LAB Code: L0141**
SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAL/AC01:2002 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:1999 General Requirements) for the Competence of Testing Laboratories.
5. **FCC – Registration No.: 282399**
SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 282399, May 31, 2002. With the above and NVLAP, SGS-CSTC is an authorized test laboratory for the DoC process.

4 Test Results

4.1 Test Instruments

Test Equipment	Manufacturer	Model	Asset No.	Cal. Due Date
Temperature, Humidity & Barometer	Oregon Scientific	BA-888	EMC0003	25-07-2003
3m Semi- Anechoic Chamber	Frankonia	N/A	EMC0501	04-11-2003
EMI Test Receiver	ROHDE & SCHWARZ	ESCS30	EMC0506	17-11-2003
Bilog Type Antenna	Schaffner Chase	CBL6143	EMC0519	01-12-2003
Coaxial cable	SGS	N/A	EMC0514	04-11-2003

4.2 E.U.T. Operation

Input voltage: 6V DC Recycled Battery (1 x 'Ni-MH' Battery)

Operating Environment:

Temperature: 24.0 °C

Humidity: 58 % RH

Atmospheric Pressure: 1010 mbar

EUT Operation:

Test the EUT in on mode.

4.3 Test Procedure & Measurement Data

4.3.1 Radiated Emissions

Test Requirement: FCC Part15 B
 Test Method: Based on FCC Part15 B Section 15.109
 Test Date: 14 March 2003
 Measurement Distance: 3m (Semi-Anechoic Chamber)
 Requirements: Emissions shall not exceed:
 40.0 dB μ V/m between 30MHz & 88MHz
 43.5 dB μ V/m between 88MHz & 216MHz
 46.0 dB μ V/m between 216MHz & 960MHz
 54.0 dB μ V/m above 960MHz

Detector: Peak Scan (120kHz resolution bandwidth)

Test Procedure: The procedure used was ANSI Standard C63.4-2000. Ansi Standard C63.4-2000

12.1.1.1 Superregenerative Receiver: A signal Generator was set to the unit under test operating frequency. An unmodulated continuous wave (CW) signal was radiated at the superregenerative receiver operating frequency to cohere the characteristic broadband emissions from the receiver.

The receiver was scanned from 30MHz to 1000MHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the horizontal and vertical polarities and the worst case emissions were reported.

The following measurements were performed on the EUT on 14 March 2003:

Test Frequency (MHz)	Test Polarization	Test Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
208.685	Vertical	30.5	43.5	13.0
243.312	Vertical	33.6	46.0	12.4
342.050	Vertical	34.8	46.0	11.2
516.620	Vertical	36.8	46.0	9.2
587.550	Vertical	38.4	46.0	7.6
643.875	Vertical	39.7	46.0	6.3
201.725	Horizontal	23.8	43.5	19.7
226.060	Horizontal	26.5	46.0	19.5
243.756	Horizontal	30.6	46.0	15.4
298.352	Horizontal	32.9	46.0	13.1
630.632	Horizontal	36.2	46.0	9.8
909.852	Horizontal	35.0	46.0	11.0

Test Results: The unit does meet the FCC Part 15 C requirements.