





FCC C2PC Test Report

FCC ID : JVPER-80

Equipment : Enhanced Wireless Receiver

Model No. : ER-80 Brand Name : ZOWIE

Applicant : BENQ CORPORATION

Address : 16 Jihu Road, Neihu, Taipei 114, Taiwan

Standard : 47 CFR FCC Part 15.249

Received Date : Aug. 23, 2022

Tested Date : Aug. 23 ~ Aug. 25, 2022

We, International Certification Corporation, would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by: Approved by:

Along Chen / Assistant Manager Gary Chang / Ma

Report No.: FR260609-01 Page : 1 of 16



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information	5
1.2	Local Support Equipment List	7
1.3	Test Setup Chart	
1.4	The Equipment List	
1.5	Test Standards	9
1.6	Deviation from Test Standard and Measurement Procedure	9
1.7	Measurement Uncertainty	g
2	TEST CONFIGURATION	10
2.1	Testing Facility	10
2.2	The Worst Test Modes and Channel Details	10
3	TRANSMITTER TEST RESULTS	11
3.1	Unwanted Emission	11
3.2	20dB and Occupied Bandwidth	14
3.3	AC Power Line Conducted Emissions	15
4	TEST LABORATORY INFORMATION	16

Appendix A. Unwanted Emission

Appendix B. 20dB and Occupied Bandwidth

Appendix C. AC Power Line Conducted Emissions



Release Record

Report No.	Version	Description	Issued Date
FR260609-01	Rev. 01	Initial issue	Sep. 06, 2022

Report No.: FR260609-01 Page: 3 of 16



Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	AC Power Line Conducted Emissions	[dBuV]: 0.546MHz 30.59 (Margin -15.41dB) - AV	Pass
15.249(a)	Field Strength of Fundamental	Meet the requirement of limit	Pass
15.249(a)(d)	Field Strength of Harmonics and Emissions Radiated outside of the Specified Frequency Bands	Meet the requirement of limit	Pass
15.215(c)	20dB bandwidth	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Report No.: FR260609-01 Page: 4 of 16



1 General Description

1.1 Information

This is a Class II Permissive Change report (C2PC).

This report is issued as a supplementary report to original report no. FR260609. The modifications are concerned with following items:

- Adding channels for 1Mbps data rate by software setting.
- To enable 2Mbps data rate by software setting.

In this report, only 2Mbps data was record in the following sections. No additional test results of 1Mbps data rate since L/M/H channel is not changed even if channels are adding.

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information							
Frequency Range (MHz)							
2400-2483.5	GFSK	2403-2475	1-73 [73]	1 Mbps			
2400-2483.5	GFSK	2403-2475	1-73 [73]	2 Mbps			

1.1.2 Antenna Details

Ant. No.	Brand	Model	Туре	Connector	Gain (dBi)
1	BENQ Corporation	ER-80 ANT	Patch Antenna	NA	5.69

1.1.3 Power Supply Type of Equipment under Test (EUT)

Dower Type	EV/da from hoot
Power Type	5Vdc from host

1.1.4 Accessories

No.	Equipment	Description
1	USB cable	Brand: Le Prestique Electronics Manufacturing Model: USB Type-C cable 2.05m non-shielded with one core

Report No.: FR260609-01 Page: 5 of 16



1.1.5 Channel List

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2403	20	2422	39	2441	58	2460
2	2404	21	2423	40	2442	59	2461
3	2405	22	2424	41	2443	60	2462
4	2406	23	2425	42	2444	61	2463
5	2407	24	2426	43	2445	62	2464
6	2408	25	2427	44	2446	63	2465
7	2409	26	2428	45	2447	64	2466
8	2410	27	2429	46	2448	65	2467
9	2411	28	2430	47	2449	66	2468
10	2412	29	2431	48	2450	67	2469
11	2413	30	2432	49	2451	68	2470
12	2414	31	2433	50	2452	69	2471
13	2415	32	2434	51	2453	70	2472
14	2416	33	2435	52	2454	71	2473
15	2417	34	2436	53	2455	72	2474
16	2418	35	2437	54	2456	73	2475
17	2419	36	2438	55	2457		
18	2420	37	2439	56	2458		
19	2421	38	2440	57	2459		

1.1.6 Test Tool and Duty Cycle

Test Tool	Bus Hound, Version: 7.00	
Duty Cycle and Duty Factor	Duty Cycle (%)	Duty Factor (dB)
Duty Cycle and Duty Factor	18.98	7.22

1.1.7 Power Index of Test Tool

Modulation Mode	Test Frequency (MHz)		
	2403	2440	2475
GFSK	Default	Default	Default


Report No.: FR260609-01 Page: 6 of 16



1.2 Local Support Equipment List

	Support Equipment List					
No.	No. Equipment Brand Model FCC ID Remarks					
1	Notebook	DELL	Latitude 5400	DoC		

1.3 Test Setup Chart



Report No.: FR260609-01 Page: 7 of 16



1.4 The Equipment List

Test Item	Conducted Emission							
Test Site	Conduction room 1 / (Conduction room 1 / (CO01-WS)						
Tested Date	Aug. 25, 2022	Aug. 25, 2022						
Instrument	Brand Model No. Serial No. Calibration Date Calibration Until							
Receiver	R&S	ESR3	101658	Feb. 16, 2022	Feb. 15, 2023			
LISN	R&S	ENV216	101579	Apr. 21, 2022	Apr. 20, 2023			
LISN (Support Unit)	SCHWARZBECK	Schwarzbeck 8127	8127667	Jan .07, 2022	Jan .06, 2023			
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Oct. 19, 2021	Oct. 18, 2022			
50 ohm terminal (Support Unit)	NA	50	01	May 10, 2022	May 09, 2023			
Measurement Software AUDIX e3 6.120210k NA NA								

Test Item	Radiated Emission				
Test Site	966 chamber1 / (03Cl	966 chamber1 / (03CH01-WS)			
Tested Date	Aug. 23 ~ Aug. 24, 2022				
Instrument	Brand	Model No.	Serial No.	Calibration Date	Calibration Until
Receiver	R&S	ESR3	101657	Mar. 15, 2022	Mar. 14, 2023
Spectrum Analyzer	R&S	FSV40	101498	Nov. 29, 2021	Nov. 28, 2022
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 08, 2021	Nov. 07, 2022
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Aug. 03, 2022	Aug. 02, 2023
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 03, 2021	Dec. 02, 2022
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 04, 2021	Nov. 03, 2022
Preamplifier	EMC	EMC02325	980225	Jun. 28, 2022	Jun. 27, 2023
Preamplifier	EMC	EMC118A45SE	980898	Jul. 16, 2022	Jul. 15, 2023
Preamplifier	EMC	EMC184045SE	980903	Jul. 16, 2022	Jul. 15, 2023
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Oct. 05, 2021	Oct. 04, 2022
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Oct. 05, 2021	Oct. 04, 2022
LF cable 11M	EMC	EMCCFD400-NW-N W-11000	200801	Oct. 05, 2021	Oct. 04, 2022
LF cable 1M	EMC	EMCCFD400-NM-N M-1000	160502	Oct. 05, 2021	Oct. 04, 2022
RF Cable	EMC	EMC104-35M-35M- 8000	210920	Oct. 05, 2021	Oct. 04, 2022
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Oct. 05, 2021	Oct. 04, 2022
Measurement Software	AUDIX	e3	6.120210g	NA	NA

Report No.: FR260609-01 Page: 8 of 16



1.5 Test Standards

47 CFR FCC Part 15.249 ANSI C63.10-2013

1.6 Deviation from Test Standard and Measurement Procedure

None

1.7 Measurement Uncertainty

The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)).

Measurement Uncertainty		
Parameters	Uncertainty	
Bandwidth	±34.130 Hz	
AC conducted emission	±2.92 dB	
Unwanted Emission ≤ 1GHz	±3.41 dB	
Unwanted Emission > 1GHz	±4.59 dB	

Report No.: FR260609-01 Page: 9 of 16



2 Test Configuration

2.1 Testing Facility

Test Laboratory	International Certification Corporation
Test Site	CO01-WS, 03CH01-WS
Address of Test Site	No.3-1, Lane 6, Wen San 3rd St., Kwei Shan Dist., Tao Yuan City 33381, Taiwan (R.O.C.)

FCC Designation No.: TW2732FCC site registration No.: 181692

➤ ISED#: 10807A

➤ CAB identifier: TW2732

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data Rate	Test Configuration
AC Power Line Conducted Emissions	GFSK	2440	2 Mbps	TX
Unwanted Emissions ≤ 1GHz	GFSK	2440	2 Mbps	TX
Field Strength of Fundamental Unwanted Emissions > 1GHz 20dB bandwidth	GFSK	2403 / 2440 / 2475	2 Mbps	TX

Report No.: FR260609-01 Page: 10 of 16



3 Transmitter Test Results

3.1 Unwanted Emission

This section includes field strength of fundamental, field strength of harmonics and emissions radiated outside of the operating frequency bands.

3.1.1 Limit of field strength of fundamental and field strength of harmonics

Fundamental Frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)	
2400-2483.5 MHz	50	500	

3.1.2 Limit of Unwanted Emissions

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in below table, whichever is the lesser attenuation.

Radiated emission limits				
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)	
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300	
0.490~1.705	24000/F(kHz)	33.8 - 23	30	
1.705~30.0	30	29	30	
30~88	100	40	3	
88~216	150	43.5	3	
216~960	200	46	3	
Above 960	500	54	3	

Note 1:

Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit **Note 2:**

Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

Report No.: FR260609-01 Page: 11 of 16



3.1.3 Test Procedures

- Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
- 2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
- 3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:

- Radiated emission below 1GHz
 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission
- Radiated emission above 1GHz / Peak value except fundamental RBW=1MHz, VBW=3MHz and Peak detector
- Radiated emission above 1GHz / Average value for field strength of fundamental and harmonics
 The average value is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:


20log (Duty cycle) = 20log
$$\frac{0.072464x13ms}{100 ms}$$
 = -40.52dB

- Radiated emission above 1GHz / Average value for other emissions RBW=1MHz, VBW=1/T and Peak detector
- Radiated emission Peak value for fundamental RBW=2MHz, VBW=10MHz and Peak detector

Report No.: FR260609-01 Page: 12 of 16



3.1.4 Test Setup



3.1.5 Test Results

Refer to Appendix A.

Report No.: FR260609-01 Page: 13 of 16



3.2 20dB and Occupied Bandwidth

3.2.1 Test Procedures

- 1. Set resolution bandwidth (RBW) = 20 kHz, Video bandwidth = 100 kHz.
- 2. Detector = Peak(20 dB bandwidth) / Sample(Occupied bandwidth), Trace mode = max hold
- 3. Sweep = auto couple, Allow the trace to stabilize.
- 4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 20dB relative to the maximum level measured in the fundamental emission.
- 5. Use the occupied measurement function of specturm analyzer to measure 99% occupied bandwidth.

3.2.2 Test Setup



3.2.3 Test Results

Ambient Condition	24°C / 63%	Tested By	Brad Wu

Refer to Appendix B.

Report No.: FR260609-01 Page: 14 of 16



3.3 AC Power Line Conducted Emissions


3.3.1 Limit of AC Power Line Conducted Emissions

Conducted Emissions Limit				
Frequency Emission (MHz)	Quasi-Peak	Average		
0.15-0.5	66 - 56 *	56 - 46 *		
0.5-5	56	46		
5-30	60	50		
Note 1: * Decreases with the logarithm of the frequency.				

3.3.2 Test Procedures

- 1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
- 2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
- 3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
- 4. This measurement was performed with AC 120V / 60Hz.

3.3.3 Test Setup



Note: 1. Support units were connected to second LISN.

Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.3.4 Test Results

Refer to Appendix C.

Report No.: FR260609-01 Page: 15 of 16



4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corporation (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website http://www.icertifi.com.tw.

Linkou

Tel: 886-2-2601-1640 No.30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan (R.O.C.)

Kwei Shan

Tel: 886-3-271-8666
No.3-1, Lane 6, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)
No.2-1, Lane 6, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)

Kwei Shan Site II

Tel: 886-3-271-8640 No.14-1, Lane 19, Wen San 3rd St., Kwei Shan Dist., Tao Yuan City 333, Taiwan (R.O.C.)

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666 Fax: 886-3-318-0345


Email: ICC Service@icertifi.com.tw

==END==

Report No.: FR260609-01 Page: 16 of 16



Unwanted Emissions (Below 1GHz)



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)


*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Page No. : 1 of 9






*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.



Unwanted Emissions (Above 1GHz)




Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

^{*}Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).






*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).






*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).






*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).






*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).






*Factor includes antenna factor, cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).








Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
2403.0	2.055	1.968
2440.0	2.048	1.961
2475.0	2.048	1.968








Page No. : 1 of :





Page No. : 2 of