

RF EXPOSURE TEST REPORT

Applicant	Belkin International, Inc.
Address	555 S. Aviation Blvd., Suite 180, El Segundo, CA 90245, USA

Manufacturer or Supplier	Belkin International, Inc.
Address	555 S. Aviation Blvd., Suite 180, El Segundo, CA 90245, USA
Product	BoostCharge 2-in-1 Convertible Magnetic Charging Stand
Brand Name	belkin
Model	WIZ035
Additional Model & Model Difference	N/A
Date of tests	Apr. 14, 2025

The submitted sample of the above equipment has been tested according to the requirements of the following standard:

- ☒ 47 CFR PART 1, Subpart I, Section 1.1310
- ☒ KDB 680106 D01

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Eric Fang Project Engineer / EMC Department	Approved by Glyn He Assistant Manager/ EMC Department
	 Date: May 15, 2025

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

RF EXPOSURE TEST REPORT	1
RELEASE CONTROL RECORD.....	3
1. GENERAL INFORMATION.....	4
1.1. GENERAL DESCRIPTION OF EUT	4
2. RF EXPOSURE MEASUREMENT	5
2.1 LIMITS	5
2.2 DESCRIPTION OF SUPPORT UNITS.....	6
2.3 CONFIGURATION OF SYSTEM UNDER TEST.....	7
2.4 TEST SETUP FOR WPC	8
2.5 EQUIPMENTS USED DURING TEST	8
2.6 TEST POINT DESCRIPTION	8
2.7 TEST RESULTS.....	9
3. PHOTOGRAPHS OF THE TEST CONFIGURATION.....	14



Test Report No.: FM2504WDG0089

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FM2504WDG0089	Original release	May 15, 2025

1. GENERAL INFORMATION

1.1. GENERAL DESCRIPTION OF EUT

FCC ID	K7SWIZ035
PRODUCT	BoostCharge 2-in-1 Convertible Magnetic Charging Stand
MODEL NO.	WIZ035
ADDITIONAL MODEL	N/A
POWER SUPPLY	DC 15V From Adapter
MODULATION TECHNOLOGY	FSK
OPERATING FREQUENCY RANGE	15W Qi2 Charging Coil (BPP/MPP):127.7kHz & 360kHz 5W Qi (BPP) Charging Coil:111-148kHz
ANTENNA TYPE	Coil Antenna*2
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	See section 2.2

NOTES:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- For the test results, the EUT had been tested with all conditions, but only the worst case was shown in test report.
- Please refer to the EUT photo document (Reference No.: 2504WDG0089-3) for detailed product photo.
- Adapter information as follows:

USB-C Power Adapter	
MODEL NO.:	CYPD30US
BRAND NAME:	belkin
INPUT:	100-240Vac, 50-60Hz 0.75A
OUTPUT:	5Vdc 3A, 9Vdc 3A, 15Vdc 2A
PLUG TYPE	US

2. RF EXPOSURE MEASUREMENT

2.1 LIMITS

§ 1.1310 The criteria listed in table 1 shall be used to evaluate the environmental impact of human exposure to radiofrequency(RF) radiation as specified in § 1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of § 2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

Reference KDB 680106 D01 RF Exposure Wireless Charging App v03

The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

2.2 DESCRIPTION OF SUPPORT UNITS


The EUT has been tested with associated equipment below

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	iPhone 16 Pro(1#)	Apple	A3083 (MYM93LL/A)	HY9H79YM6Y	BCG-E8666A	BV Lab.
B	iPhone 16 Pro(2#)	Apple	A3083 (MYM93LL/A)	C57JWWWYG0	BCG-E8666A	
C	iPhone 11 Pro	Apple	MWDD2CH/A	F17ZMCAMN6YL	N/A	
D	AirPods Pro Case	Apple	A2190	GXDGFE8W1059	N/A	


Description	Length (m)	Shielding (Y/N)	Remark
USB-C to USB-C cable	1.5	Y	Nen Oceans Precision Component (JiangXi) Co.,Ltd./ DB336/C-C/L=1.5m Black
USB-C to USB-C cable	1.5	Y	Nen Oceans Precision Component (JiangXi) Co.,Ltd./ DB337/C-C/L=1.5m White

2.3 CONFIGURATION OF SYSTEM UNDER TEST


Mode A: EUT Standby:




Mode B: EUT 15W Coil(iPhone 16 Pro)+ 5W Coil(iPhone 16 Pro):



Mode C: EUT 15W Coil(iPhone 11 Pro)+ 5W Coil(AirPods Pro Case):



2.4 TEST SETUP FOR WPC




Note: Measurements should be made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device.

2.5 EQUIPMENTS USED DURING TEST

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
E-Field probe	Narda	NBM-520	2403/01B	Apr. 05, 26
Electric and Magnetic Field Probe-Analyzer	Narda	EHP-200A	180ZX10216	Feb. 19, 26
3m Fully Anechoic Chamber	Chance Most	8m*4m*4m	D3040011DG	May 27, 25
Test Software	Narda	EHP200-TS	V1.94	N/A

NOTE: 1. The test was performed in RS chamber.
2. Equipment are calibrated by calibration laboratory accredited to ISO/IEC 17025 by a mutually recognized Accreditation and all tests are conducted within a valid calibration cycle.

2.6 TEST POINT DESCRIPTION



2.7 TEST RESULTS

Mode1: Standby for 15W Coil

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	0.2055	0.2985	0.2711	0.1624	0.1726
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-613.7945	-613.7015	-613.7289	-613.8376	-613.8274
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-306.7945	-306.7015	-306.7289	-306.8376	-306.8274

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (A/m)	0.0978	0.1019	0.0797	0.0416	0.0416
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.532	-1.528	-1.550	-1.588	-1.588
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.717	-0.713	-0.735	-0.773	-0.773

Mode1: Standby for 5W Coil

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	0.1881	0.2090	0.2013	0.1719	0.3808
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-613.8119	-613.791	-613.7987	-613.8281	-613.6192
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-306.8119	-306.791	-306.7987	-306.8281	-306.6192

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (A/m)	0.0528	0.0577	0.0590	0.0758	0.1964
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.577	-1.572	-1.571	-1.554	-1.434
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.762	-0.757	-0.756	-0.739	-0.619

Mode2: EUT+15W Coil (iPhone 16 Pro 10% Battery Charging)+ 5W Coil (iPhone 16 Pro 10% Battery Charging) For 15W Coil

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	1.0357	1.3337	0.6910	1.0254	0.4389
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-612.9643	-612.6663	-613.309	-612.9746	-613.5611
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-305.9643	-305.6663	-306.309	-305.9746	-306.5611

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (A/m)	0.1470	0.1373	0.2212	0.0736	0.0675
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.483	-1.493	-1.409	-1.556	-1.563
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.668	-0.678	-0.594	-0.741	-0.748

Mode2: EUT+15W Coil (iPhone 16 Pro 10% Battery Charging)+ 5W Coil (iPhone 16 Pro 10% Battery Charging) for 5W Coil

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	0.4125	0.9561	0.4163	0.2813	0.2817
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-613.5875	-613.0439	-613.5837	-613.7187	-613.7183
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-306.5875	-306.0439	-306.5837	-306.7187	-306.7183

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (A/m)	0.0360	0.1816	0.0409	0.0393	0.0236
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.594	-1.448	-1.589	-1.591	-1.606
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.779	-0.633	-0.774	-0.776	-0.791

Mode3:EUT+15W Coil (iPhone 16 Pro 90% Battery Charging)+ 5W Coil (iPhone 11 Pro 90% Battery Charging) For 15W Coil

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	0.5365	0.8548	0.6836	0.6454	0.4245
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-613.4635	-613.1452	-613.3164	-613.3546	-613.5755
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-306.4635	-306.1452	-306.3164	-306.3546	-306.5755

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (A/m)	0.1585	0.1409	0.2417	0.0913	0.0221
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.472	-1.489	-1.388	-1.539	-1.608
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.657	-0.674	-0.573	-0.724	-0.793

Mode3: EUT+15W Coil (iPhone 16 Pro 90% Battery Charging)+ 5W Coil (iPhone 16 Pro 90% Battery Charging) For 5W Coil

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	0.4201	0.7412	0.4310	0.2877	0.2940
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-613.5799	-613.2588	-613.569	-613.7123	-613.706
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-306.5799	-306.2588	-306.569	-306.7123	-306.706

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (A/m)	0.0560	0.0993	0.0577	0.0582	0.0244
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.574	-1.531	-1.572	-1.572	-1.606
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.759	-0.716	-0.757	-0.757	-0.791

Mode4: EUT+15W Coil(iPhone 11 Pro 10% Battery Charging)+ 5W Coil (AirPods Pro Case 10% Battery Charging) For 15W Coil

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	0.2799	0.3160	0.3912	0.4172	0.4389
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-613.7201	-613.684	-613.6088	-613.5828	-613.5611
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-306.7201	-306.684	-306.6088	-306.5828	-306.5611

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (A/m)	0.1453	0.1201	0.2484	0.0931	0.1592
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.485	-1.510	-1.382	-1.537	-1.471
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.670	-0.695	-0.567	-0.722	-0.656

Mode4: EUT+15W Coil(iPhone 11 Pro 10% Battery Charging)+ 5W Coil (AirPods Pro Case 10% Battery Charging) For 5W Coil

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	0.3594	0.4444	0.4110	0.2868	0.3644
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-613.6406	-613.5556	-613.589	-613.7132	-613.6356
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-306.6406	-306.5556	-306.589	-306.7132	-306.6356

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (A/m)	0.0711	0.0501	0.0777	0.0524	0.1235
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.559	-1.580	-1.552	-1.578	-1.507
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.744	-0.765	-0.737	-0.763	-0.692

Mode5: EUT+15W Coil(iPhone 11 Pro 90% Battery Charging)+ 5W Coil (AirPods Pro Case 90% Battery Charging) For 15W Coil

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	0.4110	0.4233	0.4175	0.4480	0.3865
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-613.589	-613.5767	-613.5825	-613.552	-613.6135
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-306.589	-306.5767	-306.5825	-306.552	-306.6135

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (A/m)	0.1477	0.1649	0.2036	0.1134	0.1206
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.482	-1.465	-1.426	-1.517	-1.509
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.667	-0.650	-0.611	-0.702	-0.694

Mode5: EUT+15W Coil(iPhone 11 Pro 90% Battery Charging)+ 5W Coil (AirPods Pro Case 90% Battery Charging) For 5W Coil

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	0.3584	0.4566	0.4066	0.2813	0.3752
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-613.6416	-613.5434	-613.5934	-613.7187	-613.6248
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-306.6416	-306.5434	-306.5934	-306.7187	-306.6248

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (A/m)	0.0736	0.5180	0.0762	0.0524	0.1211
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.556	-1.112	-1.554	-1.578	-1.509
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.741	-0.297	-0.739	-0.763	-0.694



Test Report No.: FM2504WDG0089

3. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

--- END ---