



TEST REPORT

Report No. : CHTEW21060127 Report Verification: 

Project No. : SHT2105083402EW

FCC ID : SIP-5787-V

Applicant's name : MegaGain International Ltd.

Address : Rm 904-905, Greenfield Tower, Concordia Plaza, 1 Science Museum Road, T.S.T. East. Kowloon. HongKong

Test item description : MARVEL 5.5" HULK / SPIDERMAN RC VEHICLE DELUXE CONTROLLER

Trade Mark : -

Model/Type reference : 18101(5787-W)-Vehicle

Listed Model(s) : 18100(5788-W)-Vehicle

Standard : FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of receipt of test sample : May.28, 2021

Date of testing : May.28, 2021- Jun.10, 2021

Date of issue : Jun.11, 2021

Result : PASS

Compiled by
(Position+Printed name+Signature): File administrator Fanghui Zhu

Fanghui Zhu

Supervised by
(Position+Printed name+Signature): Project Engineer Cheng Xiao

Cheng Xiao

Approved by
(Position+Printed name+Signature): RF Manager Hans Hu

Hans Hu

Testing Laboratory Name : Shenzhen Huatongwei International Inspection Co., Ltd.

Address : 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road,
Tianliao, Gongming, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely corresponds to the test sample.

Contents

1.	TEST STANDARDS AND REPORT VERSION	3
1.1.	Test Standards	3
1.2.	Report version	3
2.	TEST DESCRIPTION	4
3.	SUMMARY	5
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	Radio Specification Description	5
3.4.	Testing Laboratory Information	6
4.	TEST CONFIGURATION	7
4.1.	Test frequency list	7
4.2.	Test mode	7
4.3.	Support unit used in test configuration and system	7
4.4.	Testing environmental condition	8
4.5.	Measurement uncertainty	8
4.6.	Equipment Used during the Test	9
5.	TEST CONDITIONS AND RESULTS	11
5.1.	Antenna Requirement	11
5.2.	AC Conducted Emission	12
5.3.	Peak Output Power	13
5.4.	Power Spectral Density	14
5.5.	6dB bandwidth	15
5.6.	99% Occupied Bandwidth	16
5.7.	Duty Cycle	17
5.8.	Conducted Band edge and Spurious Emission	18
5.9.	Radiated Band edge Emission	20
5.10.	Radiated Spurious Emission	22
6.	TEST SETUP PHOTOS	27
7.	EXTERANAL AND INTERNAL PHOTOS	28
8.	APPENDIX REPORT	34

1. TEST STANDARDS AND REPORT VERSION

1.1. Test Standards

The tests were performed according to following standards:

- [FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz
- [ANSI C63.10:2013](#): American National Standard for Testing Unlicensed Wireless Devices
- [KDB 558074 D01 15.247 Meas Guidance v05r02](#): Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under Section 15.247 of The FCC Rules

1.2. Report version

Revision No.	Date of issue	Description
N/A	2021-06-11	Original

2. TEST DESCRIPTION

Report clause	Test Items	Standard Requirement	Result
5.1	Antenna Requirement	15.203/15.247(c)	PASS
5.2	AC Conducted Emission	15.207	N/A
5.3	Peak Output Power	15.247(b)(3)	PASS
5.4	Power Spectral Density	15.247(e)	PASS
5.5	6dB Bandwidth	15.247(a)(2)	PASS
5.6	99% Occupied Bandwidth	-	PASS ^{*1}
5.7	Duty cycle	-	PASS ^{*1}
5.8	Conducted Band Edge and Spurious Emission	15.247(d)/15.205	PASS
5.9	Radiated Band Edge Emission	15.205/15.209	PASS
5.10	Radiated Spurious Emission	15.247(d)/15.205/15.209	PASS

Note:

- The measurement uncertainty is not included in the test result.
- ^{*1}: No requirement on standard, only report these test data.

3. SUMMARY

3.1. Client Information

Applicant:	MegaGain International Ltd.
Address:	Rm 904-905, Greenfield Tower, Concordia Plaza,1 Science Museum Road, T.S.T. East. Kowloon. HongKong
Manufacturer:	MegaGain International Ltd.
Address:	Rm 904-905, Greenfield Tower, Concordia Plaza,1 Science Museum Road, T.S.T. East. Kowloon. HongKong

3.2. Product Description

Name of EUT:	MARVEL 5.5" HULK / SPIDERMAN RC VEHICLE DELUXE CONTROLLER
Trade Mark:	-
Model No.:	18101(5787-W)-Vehicle
Listed Model(s):	18100(5788-W)-Vehicle
Power supply:	DC 4.5V for battery
Battery Information:	DC 4.5V
Adapter Information:	-
Hardware version:	V1
Software version:	V1

3.3. Radio Specification Description

Modulation:	GFSK
Operation frequency:	2405MHz~2465MHz
Channel number:	61
Channel separation:	1MHz
Antenna type:	Monopole Antenna
Antenna gain:	0dBi

3.4. Testing Laboratory Information

Laboratory Name	Shenzhen Huatongwei International Inspection Co., Ltd.	
Laboratory Location	1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China	
Connect information:	Phone: 86-755-26715499 E-mail: cs@szhtw.com.cn http://www.szhtw.com.cn	
Qualifications	Type	Accreditation Number
	FCC	762235

4. TEST CONFIGURATION

4.1. Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channels which were tested. The Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the below blue front.

Channel	Frequency (MHz)
01	2405
02	2406
:	:
29	2433
:	:
60	2464
61	2465

4.2. Test mode

For RF test items
The engineering test program was provided and enabled to make EUT continuous transmit.
For Radiated spurious emissions test item:
The engineering test program was provided and enabled to make EUT continuous transmit. The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data Recorded in the report.

4.3. Support unit used in test configuration and system

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The following peripheral devices and interface cables were connected during the measurement:

Whether support unit is used?					
No					
Item	Equipement	Trade Name	Model No.	FCC ID	Power cord
1					
2					

4.4. Testing environmental condition

Type	Requirement	Actual
Temperature:	15~35°C	25°C
Relative Humidity:	25~75%	50%
Air Pressure:	860~1060mbar	1000mbar

4.5. Measurement uncertainty

Test Item	Measurement Uncertainty
AC Conducted Emission (150kHz~30MHz)	3.02 dB
Radiated Emission (30MHz~1000MHz)	4.90 dB
Radiated Emissions (1GHz~25GHz)	4.96 dB
Peak Output Power	0.51 dB
Power Spectral Density	0.51 dB
Conducted Spurious Emission	0.51 dB
6dB Bandwidth	70 Hz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.

4.6. Equipment Used during the Test

● Conducted Emission							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Shielded Room	Albatross projects	HTWE0114	N/A	N/A	2018/09/28	2023/09/27
●	EMI Test Receiver	R&S	HTWE0111	ESCI	101247	2020/10/19	2021/10/18
●	Artificial Mains	SCHWARZBECK	HTWE0113	NNLK 8121	573	2020/10/15	2021/10/14
●	Pulse Limiter	R&S	HTWE0033	ESH3-Z2	100499	2020/10/15	2021/10/14
●	RF Connection Cable	HUBER+SUHNER	HTWE0113-02	ENVIROFLEX_142	EF-NM-BNCM-2M	2020/10/15	2021/10/14
●	Test Software	R&S	N/A	ES-K1	N/A	N/A	N/A

● Radiated emission-6th test site							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0127	SAC-3m-02	C11121	2018/09/30	2021/09/29
●	EMI Test Receiver	R&S	HTWE0099	ESCI	100900	2020/10/19	2021/10/18
●	Loop Antenna	R&S	HTWE0170	HFH2-Z2	100020	2021/04/01	2024/03/31
●	Ultra-Broadband Antenna	SCHWARZBECK	HTWE0123	VULB9163	538	2021/04/01	2024/03/31
●	Pre-Amplifier	SCHWARZBECK	HTWE0295	BBV 9742	N/A	2020/11/13	2021/11/12
●	RF Connection Cable	HUBER+SUHNER	HTWE0062-01	N/A	N/A	2021/02/26	2022/02/25
●	RF Connection Cable	HUBER+SUHNER	HTWE0062-02	SUCOFLEX104	501184/4	2021/02/26	2022/02/25
●	Test Software	R&S	N/A	ES-K1	N/A	N/A	N/A

● Radiated emission-7th test site							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0122	SAC-3m-01	N/A	2018/09/27	2021/09/26
●	Spectrum Analyzer	R&S	HTWE0098	FSP40	100597	2020/10/20	2021/10/19
●	Horn Antenna	SCHWARZBECK	HTWE0126	9120D	1011	2020/04/01	2023/03/31
●	Broadband Horn Antenna	SCHWARZBECK	HTWE0103	BBHA9170	BBHA9170472	2018/10/11	2021/10/11
●	Pre-amplifier	CD	HTWE0071	PAP-0102	12004	2020/11/13	2021/11/12
●	Broadband Pre-amplifier	SCHWARZBECK	HTWE0201	BBV 9718	9718-248	2021/03/05	2022/03/04
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-01	6m 18GHz S Serisa	N/A	2021/05/08	2022/05/07
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-02	6m 3GHz RG Serisa	N/A	2021/05/08	2022/05/07
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-03	6m 3GHz RG Serisa	N/A	2021/05/08	2022/05/07
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-04	6m 3GHz RG Serisa	N/A	2021/05/08	2022/05/07
●	RF Connection Cable	HUBER+SUHNER	HTWE0121-01	6m 18GHz S Serisa	N/A	2021/05/08	2022/05/07
●	Test Software	Audix	N/A	E3	N/A	N/A	N/A

● RF Conducted Method						
Used	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Signal and spectrum Analyzer	R&S	FSV40	100048	2020/10/19	2021/10/18
●	Spectrum Analyzer	Agilent	N9020A	MY50510187	2020/10/19	2021/10/18
●	Power Meter	Anritsu	ML249A	N/A	2020/10/19	2021/10/18
○	Radio communication tester	R&S	CMW500	137688-Lv	2020/10/19	2021/10/18

5. TEST CONDITIONS AND RESULTS

5.1. Antenna Requirement

Requirement

FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.


FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

TEST RESULT

☒ Passed ☐ Not Applicable

The antenna type is a wire antenna, the directional gain of the antenna less than 6 dBi, please refer to the below antenna photo.



5.2. AC Conducted Emission


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT


☐ Passed ☒ Not Applicable

5.3. Peak Output Power

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3): 30dBm

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was tested according to ANSI C63.10 and KDB 558074 D01 requirements.
2. The maximum peak conducted output power may be measured using a broadband peak RF power meter.
3. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.
4. Record the measurement data.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

TEST Data

Please refer to appendix A on the appendix report


5.4. Power Spectral Density

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (e):

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input,
2. Configure the spectrum analyzer as shown below:
Center frequency=DTS channel center frequency
Span =1.5 times the DTS bandwidth
 $RBW = 3 \text{ kHz} \leq RBW \leq 100 \text{ kHz}$, $VBW \geq 3 \times RBW$
Sweep time = auto couple
Detector = peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter wave form on the spectrum analyzer.
4. Use the peak marker function to determine the maximum amplitude level within the RBW.
5. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

TEST Data

Please refer to appendix B on the appendix report


5.5. 6dB bandwidth

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(2):

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).
Center Frequency = DTS channel center frequency
Span = 2 x DTS bandwidth
RBW = 100 kHz, VBW $\geq$ 3 x RBW
Sweep time = auto couple
Detector = Peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission, and record the pertinent measurements.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

TEST Data


Please refer to appendix C on the appendix report

5.6. 99% Occupied Bandwidth

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).
Center Frequency = channel center frequency
Span $\geq 1.5 \times \text{OBW}$
RBW = 1%~5%OBW
VBW $\geq 3 \times \text{RBW}$
Sweep time = auto couple
Detector = Peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

TEST Data


Please refer to appendix D on the appendix report

5.7. Duty Cycle

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span=zero span, Frequency=centered channel, RBW= 1 MHz, VBW $\geq$ RBW
Sweep=as necessary to capture the entire dwell time,
Detector function = peak, Trigger mode
4. Measure and record the duty cycle data

TEST MODE:

Please refer to the clause 4.2

TEST Data


Please refer to appendix E on the appendix report

5.8. Conducted Band edge and Spurious Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Emission level measurement
Set the center frequency and span to encompass frequency range to be measured
RBW = 100 kHz, VBW $\geq 3 \times$ RBW
Detector = peak, Sweep time = auto couple, Trace mode = max hold
Allow trace to fully stabilize
Use the peak marker function to determine the maximum amplitude level.
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
4. Ensure that the amplitude of all unwanted emission outside of the authorized frequency band excluding restricted frequency bands) are attenuated by at least the minimum requirements specified (at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz). Report the three highest emission relative to the limit.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

TEST Data

Please refer to appendix F on the appendix report


5.9. Radiated Band edge Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, Radiated Emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the Radiated Emissions limits specified in §15.209(a) (see §15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10 .
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10 on radiated measurement.
5. Use the following spectrum analyzer settings:
 - a) Span shall wide enough to fully capture the emission being measured
 - b) Set RBW=100kHz for <1GHz, VBW=3*RBW, Sweep time=auto, Detector=peak, Trace=max hold
 - c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement

For average measurement:

 - VBW=10Hz, When duty cycle is no less than 98 percent
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clause 5.6 duty cycle.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

Note:

- 1) Level= Reading + Factor; Factor =Antenna Factor+ Cable Loss- Preamp Factor
- 2) Over Limit = Level– Limit
- 3) Average measurement was not performed if peak level is lower than average limit(54 dBuV/m).

Test channel		CH01			Polarity		Horizontal		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2310.00	32.72	27.96	7.30	37.56	30.42	74.00	-43.58	Peak
2	2373.21	43.63	27.75	7.63	37.49	41.52	74.00	-32.48	Peak
3	2389.96	37.35	27.72	7.72	37.45	35.34	74.00	-38.66	Peak

Test channel		CH01			Polarity		Vertical		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2310.00	33.42	27.96	7.30	37.56	31.12	74.00	-42.88	Peak
2	2373.21	46.47	27.75	7.63	37.49	44.36	74.00	-29.64	Peak
3	2389.96	38.46	27.72	7.72	37.45	36.45	74.00	-37.55	Peak

Test channel		CH61			Polarity		Horizontal		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2483.48	32.78	27.43	7.80	37.26	30.75	74.00	-43.25	Peak
2	2500.00	33.55	27.40	7.81	37.26	31.50	74.00	-42.50	Peak

Test channel		CH61			Polarity		Vertical		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2483.48	32.62	27.43	7.80	37.26	30.59	74.00	-43.41	Peak
2	2500.00	32.47	27.40	7.81	37.26	30.42	74.00	-43.58	Peak

5.10. Radiated Spurious Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209

Frequency	Limit (dBuV/m)	Value
0.009 MHz ~0.49 MHz	2400/F(kHz) @300m	Quasi-peak
0.49 MHz ~ 1.705 MHz	24000/F(kHz) @30m	Quasi-peak
1.705 MHz ~30 MHz	30 @30m	Quasi-peak


Note: Limit dBuV/m @3m = Limit dBuV/m @300m + $40 \cdot \log(300/3)$ = Limit dBuV/m @300m + 80,

Limit dBuV/m @3m = Limit dBuV/m @30m + $40 \cdot \log(30/3)$ = Limit dBuV/m @30m + 40.


Frequency	Limit (dBuV/m @3m)	Value
30MHz~88MHz	40.00	Quasi-peak
88MHz~216MHz	43.50	Quasi-peak
216MHz~960MHz	46.00	Quasi-peak
960MHz~1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION


- 9 kHz ~ 30 MHz



- 30 MHz ~ 1 GHz



- Above 1 GHz



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10 .
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
 - a) Span shall wide enough to fully capture the emission being measured;
 - b) Below 1 GHz:

RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;

If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement

For average measurement:

 - VBW=10Hz, When duty cycle is no less than 98 percent
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clause 5.6 duty cycle.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

Note:

- 1) Level= Reading + Factor/Transd; Factor/Transd =Antenna Factor+ Cable Loss- Preamp Factor
- 2) Over Limit = Level– Limit
- 3) Average measurement was not performed if peak level is lower than average limit(54 dBuV/m) for above 1GHz.

TEST DATA FOR 9 kHz ~ 30 MHz


The EUT was pre-scanned this frequency band, found the radiated level 20dB lower than the limit, so don't show data on this report.

TEST DATA FOR 30 MHz ~ 1000 MHz

Have pre-scan all test channel, found CH29 which it was worst case, so only show the worst case's data on this report.

Polarization:

Horizontal


**MEASUREMENT RESULT: "GM2106026039_red"**

6/2/2021 1:50PM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
47.460000	19.20	-8.6	40.0	20.8	QP	100.0	273.00	HORIZONTAL
59.100000	18.00	-9.8	40.0	22.0	QP	100.0	356.00	HORIZONTAL
109.540000	17.30	-10.9	43.5	26.2	QP	100.0	356.00	HORIZONTAL
301.600000	20.80	-7.1	46.0	25.2	QP	100.0	212.00	HORIZONTAL
555.740000	26.60	-0.3	46.0	19.4	QP	100.0	286.00	HORIZONTAL
934.040000	35.70	7.5	46.0	10.3	QP	100.0	126.00	HORIZONTAL

Polarization:

Vertical

**MEASUREMENT RESULT: "GM2106026038_red"**

6/2/2021 1:47PM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
45.520000	19.00	-8.9	40.0	21.0	QP	100.0	141.00	VERTICAL
55.220000	18.40	-9.1	40.0	21.6	QP	100.0	300.00	VERTICAL
107.600000	18.30	-10.7	43.5	25.2	QP	100.0	278.00	VERTICAL
288.020000	21.30	-7.5	46.0	24.7	QP	100.0	117.00	VERTICAL
546.040000	27.00	-0.7	46.0	19.0	QP	100.0	203.00	VERTICAL
875.840000	35.30	6.7	46.0	10.7	QP	100.0	335.00	VERTICAL

TEST DATA FOR 1 GHz ~ 25 GHz

Test channel		CH01			Polarity		Horizontal		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	1267.10	36.04	25.93	5.31	36.43	30.85	74.00	-43.15	Peak
2	3184.25	34.27	28.93	8.71	37.05	34.86	74.00	-39.14	Peak
3	4809.50	42.83	31.40	11.52	35.28	50.47	74.00	-23.53	Peak
4	7227.39	31.36	36.45	13.71	34.03	47.49	74.00	-26.51	Peak

Test channel		CH01			Polarity		Vertical		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	1182.94	36.86	25.53	5.07	36.67	30.79	74.00	-43.21	Peak
2	3588.94	33.21	29.38	10.03	36.90	35.72	74.00	-38.28	Peak
3	4809.50	42.20	31.40	11.52	35.28	49.84	74.00	-24.16	Peak
4	7961.43	30.70	36.95	14.41	33.32	48.74	74.00	-25.26	Peak

Test channel		CH29			Polarity		Horizontal		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	1283.34	36.03	25.97	5.37	36.36	31.01	74.00	-42.99	Peak
2	3176.16	34.28	28.95	8.70	37.09	34.84	74.00	-39.16	Peak
3	4871.10	43.34	31.40	11.51	35.16	51.09	74.00	-22.91	Peak
4	7301.36	32.27	36.40	13.63	34.12	48.18	74.00	-25.82	Peak

Test channel		CH29			Polarity		Vertical		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	1150.28	36.91	25.40	5.03	36.77	30.57	74.00	-43.43	Peak
2	3184.25	34.33	28.93	8.71	37.05	34.92	74.00	-39.08	Peak
3	4871.10	42.08	31.40	11.51	35.16	49.83	74.00	-24.17	Peak
4	8125.22	31.18	37.10	14.36	33.36	49.28	74.00	-24.72	Peak

Test channel		CH61			Polarity		Horizontal		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	1204.21	36.51	25.63	5.10	36.64	30.60	74.00	-43.40	Peak
2	3168.08	34.58	28.96	8.70	37.12	35.12	74.00	-38.88	Peak
3	4933.50	42.90	31.47	11.52	35.20	50.69	74.00	-23.31	Peak
4	7432.62	31.41	36.60	14.29	33.98	48.32	74.00	-25.68	Peak

Test channel		CH61			Polarity		Vertical		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	1270.33	35.43	25.94	5.32	36.42	30.27	74.00	-43.73	Peak
2	3700.26	35.40	29.40	9.79	37.05	37.54	74.00	-36.46	Peak
3	4933.50	42.36	31.47	11.52	35.20	50.15	74.00	-23.85	Peak
4	8002.06	29.85	37.10	14.29	33.31	47.93	74.00	-26.07	Peak


6. TEST SETUP PHOTOS


Radiated Emission




7. EXTERANAL AND INTERNAL PHOTOS

EXTERANAL PHOTOS
















INTERNAL PHOTOS





8. APPENDIX REPORT




APPENDIX REPORT

Project No.	SHT2105083402EW	Radio Specification	GFSK
Test sample No.	YPHT21050834006	Model No.	18101(5787-W)-Vehicle
Start test date	2021-06-03	Finish date	2021-06-03
Temperature	26.2°C	Humidity	53%
Test Engineer	Weiyang Xiang	Auditor	Xiaodong Zheo

Appendix clause	Test item	Result
A	Peak Output Power	PASS
B	Power Spectral Density	PASS
C	6 dB Bandwidth	PASS
D	99% Occupied Bandwidth	PASS
E	Duty cycle	PASS
F	Band edge and Spurious Emissions (conducted)	PASS




Appendix A: Peak Output Power

Type	Channel	Output power (dBm)	Average Output power (dBm)	Limit (dBm)	Result
GFSK	CH _L	-19.54	-19.56	≤ 30.00	Pass
	CH _M	-18.59	-18.66		
	CH _H	-17.82	-17.84		

CH _L	 Ref Level 10.50 dBm Offset 1.00 dB RBW 2 MHz Att 20 dB SWI 1.01 ms VBW 5 kHz Mode Auto Sweep Count 500/500 M1[1] -19.54 dBm 2.40560540 GHz CF 2.405 GHz 1001 pts 600.0 kHz/ Span 6.0 MHz Date: 3 JUN 2021 09:44:52
CH _M	 Ref Level 10.50 dBm Offset 1.00 dB RBW 2 MHz Att 20 dB SWI 1.01 ms VBW 5 kHz Mode Auto Sweep Count 500/500 M1[1] -18.59 dBm 2.43350450 GHz CF 2.433 GHz 1001 pts 500.0 kHz/ Span 5.0 MHz Date: 3 JUN 2021 09:48:55
CH _H	 Ref Level 10.50 dBm Offset 1.00 dB RBW 2 MHz Att 20 dB SWI 1.01 ms VBW 5 kHz Mode Auto Sweep Count 500/500 M1[1] -17.82 dBm 2.46495500 GHz CF 2.465 GHz 1001 pts 500.0 kHz/ Span 5.0 MHz Date: 3 JUN 2021 09:51:56




Appendix B: Power Spectral Density

Type	Channel	Power Spectral Density(dBm/3KHz)	Limit (dBm/3KHz)	Result
GFSK	CH _L	-34.97	≤8.00	Pass
	CH _M	-33.90		
	CH _H	-33.62		

CH _L	 Ref Level 5.00 dBm Offset 1.00 dB BW 3 kHz Att 10 dB SWF 1.4 ms (~13 ms) VBW 10 kHz Mode Auto FFT Count 100/100 M1[1] -34.97 dBm 2.40524580 GHz CF 2.405 GHz 1001 pts 300.0 kHz/ Span 3.0 MHz Date: 3 JUN 2021 09:45:52
CH _M	 Ref Level 10.50 dBm Offset 1.00 dB BW 3 kHz Att 10 dB SWF 1.4 ms (~13 ms) VBW 10 kHz Mode Auto FFT Count 100/100 M1[1] -33.90 dBm 2.43324880 GHz CF 2.433 GHz 1001 pts 300.0 kHz/ Span 3.0 MHz Date: 3 JUN 2021 09:49:00
CH _H	 Ref Level 10.50 dBm Offset 1.00 dB BW 3 kHz Att 10 dB SWF 1.4 ms (~13 ms) VBW 10 kHz Mode Auto FFT Count 100/100 M1[1] -33.62 dBm 2.46525170 GHz CF 2.465 GHz 1001 pts 300.0 kHz/ Span 3.0 MHz Date: 3 JUN 2021 09:52:05


Appendix C: 6dB bandwidth

Type	Channel	6dB Bandwidth(kHz)	Limit (kHz)	Result
GFSK	CH _L	861.00	≥500	Pass
	CH _M	783.00		
	CH _H	912.00		

CH_LCH_MCH_H


Appendix D: 99% Occupied Bandwidth

Type	Channel	99% Occupied Bandwidth(MHz)	Limit (kHz)	Result
GFSK	CH _L	1.17	-	Pass
	CH _M	1.17		
	CH _H	1.20		



Appendix E: Duty cycle

Test Frequency (MHz)	T _{on} time for single burst (ms)	T _{period} (ms)	Duty cycle	1/T _{on} time (kHz)
2433	0.15	0.53	28.3%	6.7



Appendix F: Band edge and Spurious Emissions (conducted)

Test Item:	Band edge
------------	-----------

CH_L

Ref Level 10.50 dBm Offset 1.00 dB BW 100 kHz
 ATT 20 dB SWT 1.09 ms VBW 300 kHz Mode Auto Sweep
 Count 300/300
 Frequency Sweep
 M1 [1] -20.77 dBm
 M2 [1] -65.50 dBm
 M3 [1] -73.88 dBm
 M4 [1] -72.04 dBm
 M5 [1] -53.27 dBm

Type	Ref	Trc	X-Value	Y-Value	Function	Function Result
M1	1		2.405192 GHz	-20.77 dBm		
M2	1		2.4 GHz	-65.50 dBm		
M3	1		2.39 GHz	-73.88 dBm		
M4	1		2.31 GHz	-72.04 dBm		
M5	1		2.373261 GHz	-53.27 dBm		




Date: 3 JUN 2021 09:46:02




CH_H




Ref Level 10.50 dBm Offset 1.00 dB BW 100 kHz
 ATT 20 dB SWT 1.09 ms VBW 300 kHz Mode Auto Sweep
 Count 100/100
 Frequency Sweep
 M1 [1] -19.03 dBm
 M2 [1] -72.04 dBm
 M3 [1] -73.30 dBm
 M4 [1] -51.49 dBm

Type	Ref	Trc	X-Value	Y-Value	Function	Function Result
M1	1		2.465246 GHz	-19.03 dBm		
M2	1		2.4855 GHz	-72.04 dBm		
M3	1		2.5 GHz	-73.30 dBm		
M4	1		2.49734 GHz	-51.49 dBm		

Date: 3 JUN 2021 09:52:45

Test Item:	SE
CH _L Reference level	 CH_L Reference level
CH _L 30MHz~1000MHz	 CH_L 30MHz~1000MHz
CH _L 1GHz~26GHz	 CH_L 1GHz~26GHz

CH_M Reference level	 The spectrum plot shows a frequency sweep from 2.433 GHz to 2.4332400 GHz. The y-axis represents power in dBm, ranging from -90 to 0. A prominent peak is visible at approximately 2.4331 GHz, reaching a level of -19.54 dBm. The plot includes parameters: Ref Level 5.00 dBm, Offset 1.00 dB, RBW 100 kHz, Att -10.25, SWI 1.04 ms, VBW 300 kHz, Mode Auto Sweep, Count 100/100, and Span 30.0 MHz.
CH_M 30MHz~1000MHz	 The spectrum plot shows a frequency sweep from 30.0 MHz to 1.0 GHz. The y-axis represents power in dBm, ranging from -90 to 0. A horizontal red line indicates a reference level at -39.540 dBm. The plot includes parameters: Ref Level 5.00 dBm, Offset 1.00 dB, RBW 100 kHz, Att -10.25, SWI 30.1 ms, VBW 300 kHz, Mode Auto Sweep, Count 10/10, and Span 30.0 MHz.
CH_M 1GHz~26GHz	 The spectrum plot shows a frequency sweep from 1.0 GHz to 26.0 GHz. The y-axis represents power in dBm, ranging from -90 to 0. A horizontal red line indicates a reference level at -39.540 dBm. The plot includes parameters: Ref Level 5.00 dBm, Offset 1.00 dB, RBW 100 kHz, Att -10.25, SWI 250 ms, VBW 300 kHz, Mode Auto Sweep, Count 10/10, and Span 25.0 GHz.

CH_H Reference level	 The spectrum plot shows a single peak at 2.465 GHz. The y-axis represents power in dBm, ranging from -90 to 0. The x-axis represents frequency in MHz, ranging from 2.45 to 2.48. The peak is labeled with a value of -18.96 dBm. The plot includes a grid and various measurement parameters such as Ref Level, Offset, RBW, and Span.
CH_H 30MHz~1000MHz	 The spectrum plot shows a wide range of frequencies from 30.0 MHz to 1.0 GHz. The y-axis represents power in dBm, ranging from -90 to 0. The x-axis represents frequency in MHz, ranging from 30.0 to 1000.0. The plot shows a noisy baseline with a small peak at 30.0 MHz. The plot includes a grid and various measurement parameters such as Ref Level, Offset, RBW, and Span.
CH_H 1GHz~26GHz	 The spectrum plot shows a wide range of frequencies from 1.0 GHz to 26.0 GHz. The y-axis represents power in dBm, ranging from -90 to 0. The x-axis represents frequency in GHz, ranging from 1.0 to 26.0. The plot shows a noisy baseline with a small peak at 1.0 GHz. The plot includes a grid and various measurement parameters such as Ref Level, Offset, RBW, and Span.

-----End of Report-----