

1. Maximum Permissible Exposure (MPE)

Standard Applicable

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

This is a Mobile device, the MPE is required.

According to §1.1310 and §2.1091 RF exposure is calculated.

Limits for Maximum Permissive Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-15000	/	/	1.0	30

F = frequency in MHz

* = Plane-wave equipment power density

Maximum Permissible Exposure (MPE) Evaluation

Frequency Band (MHz)	Conducted power (dBm)	Antenna gain (dBi)	Tune-Up Tolerance (dB)	EIRP (dBm)	MPE (mW/cm ²)	LIMIT (mW/cm ²)
2412 - 2462	24.19	2.7	1	27.890	0.122	1
5180 - 5240	14.09	6.63	1	21.720	0.030	1
5260 - 5320	13.85	6.63	1	21.480	0.028	1
5500 - 5720	14.2	5.78	1	20.980	0.025	1
5745 - 5825	13.85	5.55	1	20.400	0.022	1
2402 - 2480(BT)	6.53	2.7	1	10.230	0.002	1
2402 - 2480(BLE)	7.13	2.7	1	10.830	0.002	1

~ End of Report ~