

FCC Appendix RF Test Data

FCC ID : 2A6YS-WR303

Company: : Shenzhen Weier Technology Co., Ltd.

EUT : Bluetooth keyboard case

Model Number : WR303

Reviewed By : Eric Wang


Appendix A: DTS Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.644	2401.692	2402.336	0.5	PASS
		2440	0.644	2439.692	2440.336	0.5	PASS
		2480	0.644	2479.692	2480.336	0.5	PASS

Test Graphs






Appendix B: Occupied Channel Bandwidth

Test Result


TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	1.0028	2401.5166	2402.5194	---	---
		2440	1.0075	2439.5144	2440.5219	---	---
		2480	1.0036	2479.5166	2480.5202	---	---

Test Graphs


BLE_1M_Ant1_2402



BLE_1M_Ant1_2440



BLE_1M_Ant1_2480



Appendix C: Maximum conducted output power

Test Result Peak


TestMode	Antenna	Freq(MHz)	Conducted Peak Power[dBm]	Conducted Limit[dBm]	Verdict
BLE_1M	Ant1	2402	-3.36	≤30	PASS
		2440	-3.89	≤30	PASS
		2480	-4.16	≤30	PASS


Appendix D: Maximum power spectral density

Test Result

TestMode	Antenna	Freq(MHz)	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-19.19	≤8.00	PASS
		2440	-20.19	≤8.00	PASS
		2480	-20.05	≤8.00	PASS

Test Graphs






Appendix E: Band edge measurements

Test Result


TestMod e	Antenn a	ChNam e	Freq(MHz)	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdic t
BLE_1M	Ant1	Low	2402	-3.33	-55.07	≤-23.33	PASS
		High	2480	-4.14	-57.6	≤-24.14	PASS

Test Graphs

BLE_1M_Ant1_Low_2402



BLE_1M_Ant1_High_2480





Appendix F: Conducted Spurious Emission

Test Result

TestMode	Antenna	Freq(MHz)	FreqRange [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	Reference	-4.94	-4.94	---	PASS
			30~1000	-4.94	-69.35	≤-24.94	PASS
			1000~26500	-4.94	-47.94	≤-24.94	PASS
		2440	Reference	-5.42	-5.42	---	PASS
			30~1000	-5.42	-70.47	≤-25.42	PASS
			1000~26500	-5.42	-51.67	≤-25.42	PASS
		2480	Reference	-4.40	-4.40	---	PASS
			30~1000	-4.40	-69.19	≤-24.4	PASS
			1000~26500	-4.40	-49.34	≤-24.4	PASS

Test Graphs







BLE_1M_Ant1_2440_0~Reference



BLE_1M_Ant1_2440_30~1000




BLE_1M_Ant1_2440_1000~26500




BLE_1M_Ant1_2480_0~Reference



BLE_1M_Ant1_2480_30~1000



BLE_1M_Ant1_2480_1000~26500



Appendix G: Duty Cycle

Test Result

TestMode	Antenna	Freq(MHz)	ON Time [ms]	Period [ms]	X	DC [%]	xFactor	Limit	Verdict
BLE_1M	Ant1	2402	0.41	0.63	0.6508	65.08	1.87	---	---
		2440	0.41	0.63	0.6508	65.08	1.87	---	---
		2480	0.41	0.63	0.6508	65.08	1.87	---	---

Test Graphs

