



# FCC RADIO TEST REPORT

**FCC ID** : A4RG1008  
**Equipment** : Wireless Earphone  
**Model Name** : G1008  
**Applicant** : Google LLC  
1600 Amphitheatre Parkway,  
Mountain View, California, 94043 USA  
**Standard** : FCC Part 15 Subpart C §15.247

The product was received on Mar. 04, 2019 and testing was started from Aug. 16, 2019 and completed on Dec. 10, 2019. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

*Louis Wu*

Approved by: Louis Wu

**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



## Table of Contents

<b>History of this test report .....</b>	<b>3</b>
<b>Summary of Test Result .....</b>	<b>4</b>
<b>1 General Description .....</b>	<b>5</b>
1.1 Product Feature of Equipment Under Test .....	5
1.2 Product Specification of Equipment Under Test .....	5
1.3 Modification of EUT .....	5
1.4 Testing Location .....	6
1.5 Applicable Standards .....	6
<b>2 Test Configuration of Equipment Under Test .....</b>	<b>7</b>
2.1 Carrier Frequency Channel .....	7
2.2 Test Mode .....	8
2.3 Connection Diagram of Test System .....	9
2.4 EUT Operation Test Setup .....	9
2.5 Measurement Results Explanation Example .....	9
<b>3 Test Result .....</b>	<b>10</b>
3.1 6dB and 99% Bandwidth Measurement .....	10
3.2 Output Power Measurement .....	15
3.3 Power Spectral Density Measurement.....	16
3.4 Conducted Band Edges and Spurious Emission Measurement.....	21
3.5 Radiated Band Edges and Spurious Emission Measurement.....	26
3.6 Antenna Requirements .....	30
<b>4 List of Measuring Equipment .....</b>	<b>31</b>
<b>5 Uncertainty of Evaluation .....</b>	<b>32</b>
<b>Appendix A. Conducted Test Results</b>	
<b>Appendix B. Radiated Spurious Emission</b>	
<b>Appendix C. Radiated Spurious Emission Plots</b>	
<b>Appendix D. Duty Cycle Plots</b>	



## History of this test report

Report No.	Version	Description	Issued Date
FR921201-05B	01	Initial issue of report	Dec. 17, 2019

## Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.247(b)(3)	Peak Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	Under limit 2.02 dB at 7320.000 MHz
-	15.207	AC Conducted Emission	Not Required	
3.6	15.203 & 15.247(b)	Antenna Requirement	Pass	-

**Remark:** Not required means after assessing, test items are not necessary to carry out.

### Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

### Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

**Reviewed by: Wii Chang**

**Report Producer: Yvonne Cheng**

# 1 General Description

## 1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Wireless Earphone
Model Name	G1008
FCC ID	A4RG1008
EUT supports Radios application	Bluetooth BR/EDR/LE
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer.

## 1.2 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	Bluetooth LE (1Mbps) : 9.20 dBm (0.0083 W)
99% Occupied Bandwidth	Bluetooth LE (1Mbps) : 1.035MHz
Antenna Type / Gain	PCB Antenna type with gain -3.13 dBi
Type of Modulation	Bluetooth LE : GFSK

## 1.3 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.4 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sporton Site No.
	TH05-HY

**Note:** The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No.
	03CH12-HY

**Note:** The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW0007

## 1.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

### Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

### 2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-

## 2.2 Test Mode


- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth – LE / GFSK
Conducted Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
Radiated Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps



## 2.3 Connection Diagram of Test System



## 2.4 EUT Operation Test Setup

The RF test items, utility "CMD" was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

## 2.5 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

### 3 Test Result

#### 3.1 6dB and 99% Bandwidth Measurement

##### 3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


##### 3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

##### 3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW)  $\geq 3 * RBW$ .
6. Measure and record the results in the test report.

##### 3.1.4 Test Setup







### 3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

**6 dB Bandwidth Plot on Channel 00**




**6 dB Bandwidth Plot on Channel 19**





6 dB Bandwidth Plot on Channel 39






### 3.1.6 Test Result of 99% Occupied Bandwidth


Please refer to Appendix A.

#### 99% Bandwidth Plot on Channel 00



#### 99% Occupied Bandwidth Plot on Channel 19



**99% Occupied Bandwidth Plot on Channel 39**

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

## 3.2 Output Power Measurement

### 3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


### 3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

### 3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT was connected to the power meter by RF cable and attenuator.
3. The path loss was compensated to the results for each measurement.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Measure the conducted output power and record the results in the test report.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

### 3.3 Power Spectral Density Measurement

#### 3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


#### 3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

#### 3.3.4 Test Setup




#### 3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.




### 3.3.6 Test Result of Power Spectral Density Plots (100kHz)

### PSD 100kHz Plot on Channel 00




### PSD 100kHz Plot on Channel 19





PSD 100kHz Plot on Channel 39




Date: 21.AUG.2019 15:03:25




### 3.3.7 Test Result of Power Spectral Density Plots (3kHz)

PSD 3kHz Plot on Channel 00



Date: 21.AUG.2019 14:47:43


PSD 3kHz Plot on Channel 19



Date: 11.DEC.2019 19:20:01



PSD 3kHz Plot on Channel 39



Date: 21.AUG.2019 15:03:12

### 3.4 Conducted Band Edges and Spurious Emission Measurement

#### 3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


#### 3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.4.3 Test Procedure


1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

#### 3.4.4 Test Setup






### 3.4.5 Test Result of Conducted Band Edges Plots

**Low Band Edge Plot on Channel 00**

Date: 21.AUG.2019 14:54:51


**High Band Edge Plot on Channel 39**

Date: 21.AUG.2019 15:04:05




### 3.4.6 Test Result of Conducted Spurious Emission Plots

#### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00




Date: 12.DEC.2019 13:37:03

#### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00




Date: 12.DEC.2019 13:37:16

### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Date: 11.DEC.2019 19:23:23

### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19




Date: 11.DEC.2019 19:23:37






Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 39



Date: 21.AUG.2019 15:04:23

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 39



Date: 21.AUG.2019 15:04:35

### 3.5 Radiated Band Edges and Spurious Emission Measurement

#### 3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.5.2 Measuring Instruments


See list of measuring equipment of this test report.

### 3.5.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz;  $VBW \geq RBW$ ; Sweep = auto; Detector function = peak; Trace = max hold;
  - (3) Set RBW = 1 MHz, VBW= 3MHz for  $f \geq 1$  GHz for peak measurement.  
For average measurement:
    - $VBW = 10$  Hz, when duty cycle is no less than 98 percent.
    - $VBW \geq 1/T$ , when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

### 3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



### 3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

### 3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

### 3.5.7 Duty Cycle

Please refer to Appendix E.

### 3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.



## **3.6 Antenna Requirements**

### **3.6.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

### **3.6.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.6.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Sensor	DARE	RPR3006W	16I00054S NO10	10MHz~6GHz	Dec. 19, 2018	Aug. 16, 2019~ Dec. 12, 2019	Dec. 18 2019	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV40	101397	10Hz~40GHz	Nov. 13, 2018	Aug. 16, 2019~ Dec. 12, 2019	Nov. 12, 2019	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-058	EC120838 2	N/A	Mar. 27, 2019	Aug. 16, 2019~ Dec. 12, 2019	Mar. 26, 2020	Conducted (TH05-HY)
Hygrometer	Testo	DTM-303A	TP157075	N/A	Nov. 05, 2018	Aug. 16, 2019~ Dec. 12, 2019	Nov. 04, 2019	Conducted (TH05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Jan. 07, 2019	Dec. 09, 2019~ Dec. 10, 2019	Jan. 06, 2020	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	37059&01	30MHz~1GHz	Oct. 12, 2019	Dec. 09, 2019~ Dec. 10, 2019	Oct. 11, 2020	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120D	9120D-020 37	1GHz ~ 18GHz	Oct. 28, 2019	Dec. 09, 2019~ Dec. 10, 2019	Oct. 27, 2020	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120D	9120D-132 8	1GHz ~ 18GHz	Nov. 14, 2019	Dec. 09, 2019~ Dec. 10, 2019	Nov. 13, 2020	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170 251	18GHz ~ 40GHz	Dec. 06, 2019	Dec. 09, 2019~ Dec. 10, 2019	Dec. 06, 2020	Radiation (03CH12-HY)
Preamplifier	COM-POWER	PA-103	161075	10MHz~1GHz	Mar. 25, 2019	Dec. 09, 2019~ Dec. 10, 2019	Mar. 24, 2020	Radiation (03CH12-HY)
Preamplifier	Agilent	8449B	3008A023 75	1GHz~26.5GHz	May. 27, 2019	Dec. 09, 2019~ Dec. 10, 2019	May. 26, 2020	Radiation (03CH12-HY)
Preamplifier	Jet-Power	JPA0118-55-3 03K	171000180 0054002	1GHz~18GHz	Aug. 06, 2019	Dec. 09, 2019~ Dec. 10, 2019	Aug. 05, 2020	Radiation (03CH12-HY)
Spectrum Analyzer	Keysight	N9010A	MY553705 26	10Hz~44GHz	Mar. 19, 2019	Dec. 09, 2019~ Dec. 10, 2019	Mar. 18, 2020	Radiation (03CH12-HY)
Hygrometer	TECPEL	DTM-303B	TP140349	N/A	Oct. 25, 2019	Dec. 09, 2019~ Dec. 10, 2019	Oct. 24, 2020	Radiation (03CH12-HY)
Filter	Wainwright	WLKS1200-1 2SS	SN1	1.2 GHz Lowpass	Mar. 22, 2019	Dec. 09, 2019~ Dec. 10, 2019	Mar. 21, 2020	Radiation (03CH12-HY)
Filter	Wainwright	WHKX12-270 0-3000-18000 -60ST	SN2	3GHz High Pass	Jul. 15, 2019	Dec. 09, 2019~ Dec. 10, 2019	Jul. 14, 2020	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	505134/2	30M~40GHz	Feb. 26, 2019	Dec. 09, 2019~ Dec. 10, 2019	Feb. 25, 2020	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	800740/2	30M~40GHz	Feb. 26, 2019	Dec. 09, 2019~ Dec. 10, 2019	Feb. 25, 2020	Radiation (03CH12-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Dec. 09, 2019~ Dec. 10, 2019	N/A	Radiation (03CH12-HY)
Antenna Mast	EMEC	AM-BS-4500- B	N/A	1m~4m	N/A	Dec. 09, 2019~ Dec. 10, 2019	N/A	Radiation (03CH12-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Dec. 09, 2019~ Dec. 10, 2019	N/A	Radiation (03CH12-HY)
Software	Audix	E3 6.2009-8-24	RK-00098 9	N/A	N/A	Dec. 09, 2019~ Dec. 10, 2019	N/A	Radiation (03CH12-HY)

## 5 Uncertainty of Evaluation

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.1
--	-----

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.6
--	-----

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.0
--	-----



**Appendix A. Test Result of Conducted Test Items**

Test Engineer:	Luffy Lin/Richard Qiu/Kai Liao	Temperature:	21~25	°C
Test Date:	2019/8/16~2019/12/11	Relative Humidity:	51~54	%

**TEST RESULTS DATA**  
**6dB and 99% Occupied Bandwidth**

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.029	0.705	0.50	Pass
BLE	1Mbps	1	19	2440	1.035	0.701	0.50	Pass
BLE	1Mbps	1	39	2480	1.029	0.699	0.50	Pass

**TEST RESULTS DATA**  
**Average Power Table**

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	9.00	30.00	-3.13	5.87	36.00	Pass
BLE	1Mbps	1	19	2440	7.90	30.00	-3.13	4.77	36.00	Pass
BLE	1Mbps	1	39	2480	9.20	30.00	-3.13	6.07	36.00	Pass

**TEST RESULTS DATA**  
**Peak Power Density**

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	8.49	-6.63	-3.13	8.00	Pass
BLE	1Mbps	1	19	2440	7.94	-7.44	-3.13	8.00	Pass
BLE	1Mbps	1	39	2480	8.87	-6.23	-3.13	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.



## Appendix B. Radiated Spurious Emission

Test Engineer :	Jack Cheng, Lance Chiang, and Chuan Chu	Temperature :	22.5~24.7°C
		Relative Humidity :	59.3~68.5%

## 2.4GHz 2400~2483.5MHz

## BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BLE CH 00 2402MHz		2389.485	57.48	-16.52	74	46.49	27.52	16.63	33.16	333	241	P	H
		2331.42	45.19	-8.81	54	34.05	27.67	16.56	33.09	333	241	A	H
	*	2402	93.86	-	-	82.89	27.5	16.64	33.17	333	241	P	H
	*	2402	92.98	-	-	82.01	27.5	16.64	33.17	333	241	A	H
													H
		2389.485	56.39	-17.61	74	45.4	27.52	16.63	33.16	327	137	P	V
		2318.715	45.15	-8.85	54	33.95	27.73	16.54	33.07	327	137	A	V
	*	2402	92.23	-	-	81.26	27.5	16.64	33.17	327	137	P	V
	*	2402	91.3	-	-	80.33	27.5	16.64	33.17	327	137	A	V
													V
BLE CH 19 2440MHz		2362.78	56.89	-17.11	74	45.85	27.57	16.6	33.13	360	238	P	H
		2316.16	45.34	-8.66	54	34.13	27.74	16.54	33.07	360	238	A	H
	*	2440	95.33	-	-	84.46	27.42	16.67	33.22	360	238	P	H
	*	2440	94.45	-	-	83.58	27.42	16.67	33.22	360	238	A	H
		2498.52	55.31	-18.69	74	44.58	27.3	16.72	33.29	360	238	P	H
		2491.44	44.76	-9.24	54	34	27.32	16.72	33.28	360	238	A	H
		2341.36	55.8	-18.2	74	44.7	27.63	16.57	33.1	312	151	P	V
		2345.28	45.05	-8.95	54	33.96	27.62	16.57	33.1	312	151	A	V
	*	2440	92.54	-	-	81.67	27.42	16.67	33.22	312	151	P	V
	*	2440	91.65	-	-	80.78	27.42	16.67	33.22	312	151	A	V
		2495.52	55.1	-18.9	74	44.35	27.31	16.72	33.28	312	151	P	V
		2485.65	44.83	-9.17	54	34.06	27.33	16.71	33.27	312	151	A	V



<b>BLE CH 39 2480MHz</b>	*	2480	95.6	-	-	84.82	27.34	16.71	33.27	347	239	P	H
	*	2480	94.76	-	-	83.98	27.34	16.71	33.27	347	239	A	H
		2483.52	68.46	-5.54	74	57.69	27.33	16.71	33.27	347	239	P	H
		2483.56	47.58	-6.42	54	36.81	27.33	16.71	33.27	347	239	A	H
													H
													H
	*	2480	92.25	-	-	81.47	27.34	16.71	33.27	381	125	P	V
	*	2480	91.51	-	-	80.73	27.34	16.71	33.27	381	125	A	V
		2483.56	66.37	-7.63	74	55.6	27.33	16.71	33.27	381	125	P	V
		2483.52	46.6	-7.4	54	35.83	27.33	16.71	33.27	381	125	A	V
													V
													V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



## 2.4GHz 2400~2483.5MHz

## BLE (Harmonic @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BLE CH 00 2402MHz		4804	41.51	-32.49	74	62.9	31.1	10.07	62.56	128	0	P	H
		4804	33.8	-20.2	54	55.19	31.1	10.07	62.56	128	0	A	H
													H
													H
		4804	41.07	-32.93	74	62.46	31.1	10.07	62.56	100	126	P	V
		4804	31.89	-22.11	54	53.28	31.1	10.07	62.56	100	126	A	V
													V
													V
BLE CH 19 2440MHz		4880	41.54	-32.46	74	62.94	31.1	10.08	62.58	100	359	P	H
		4880	33.3	-20.7	54	54.7	31.1	10.08	62.58	100	359	A	H
		7320	49.21	-24.79	74	63.89	36.38	12.5	63.56	114	231	P	H
		7320	41.58	-12.42	54	56.26	36.38	12.5	63.56	114	231	A	H
		4880	39.92	-34.08	74	61.32	31.1	10.08	62.58	100	121	P	V
		4880	31.01	-22.99	54	52.41	31.1	10.08	62.58	100	121	A	V
		7320	56.54	-17.46	74	71.22	36.38	12.5	63.56	252	159	P	V
		7320	51.98	-2.02	54	66.66	36.38	12.5	63.56	252	159	A	V
BLE CH 39 2480MHz		4960	42.2	-31.8	74	63.47	31.24	10.08	62.59	100	342	P	H
		4960	34.99	-19.01	54	56.26	31.24	10.08	62.59	100	342	A	H
		7440	48.56	-25.44	74	63.14	36.4	12.61	63.59	124	122	P	H
		7440	41.89	-12.11	54	56.47	36.4	12.61	63.59	124	122	A	H
		4960	40.86	-33.14	74	62.13	31.24	10.08	62.59	100	85	P	V
		4960	32.73	-21.27	54	54	31.24	10.08	62.59	100	85	A	V
		7440	53.37	-20.63	74	67.95	36.4	12.61	63.59	100	138	P	V
		7440	48.75	-5.25	54	63.33	36.4	12.61	63.59	100	138	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

## Emission below 1GHz

## 2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	(dBμV)	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)
2.4GHz  BLE  LF		30	24.22	-15.78	40	29.25	24.31	0.84	30.18	-	-	P	H
		149.31	18.72	-24.78	43.5	30.39	17	1.71	30.38	-	-	P	H
		477.17	27.86	-18.14	46	30.91	23.59	3.19	29.83	-	-	P	H
		716.76	33.69	-12.31	46	32.47	26.76	3.94	29.48	-	-	P	H
		739.07	35.1	-10.9	46	32.59	27.93	4.01	29.43	-	-	P	H
		894.27	39.15	-6.85	46	34.81	29	4.49	29.15	100	0	P	H
													H
													H
													H
													H
													H
													H
													H
		30	30.03	-9.97	40	35.06	24.31	0.84	30.18	-	-	P	V
		99.84	24.25	-19.25	43.5	37.42	15.76	1.5	30.43	-	-	P	V
		406.36	25.02	-20.98	46	30.15	21.97	2.87	29.97	-	-	P	V
		563.5	29.67	-16.33	46	29.69	26.17	3.49	29.68	-	-	P	V
		720.64	37.93	-8.07	46	36.51	26.94	3.95	29.47	100	0	P	V
		973.81	37.22	-16.78	54	30.62	30.78	4.75	28.93	-	-	P	V
													V
												V	
												V	
												V	
												V	
												V	
												V	
Remark	1. No other spurious found.												
	2. All results are PASS against limit line.												



**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>P</b> eak or <b>A</b> verage
H/V	<b>H</b> orizontal or <b>V</b> ertical

**A calculation example for radiated spurious emission is shown as below:**

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
<b>BLE CH 00 2402MHz</b>		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =  
Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)  
= 55.45 (dBμV/m)
2. Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 55.45(dBμV/m) – 74(dBμV/m)  
= -18.55(dB)

**For Average Limit @ 2390MHz:**

1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)  
= 43.54 (dBμV/m)
2. Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 43.54(dBμV/m) – 54(dBμV/m)  
= -10.46(dB)

**Both peak and average measured complies with the limit line, so test result is “PASS”.**



## Appendix C. Radiated Spurious Emission Plots

Test Engineer :	Jack Cheng, Lance Chiang, and Chuan Chu	Temperature :	22.5~24.7°C
		Relative Humidity :	59.3~68.5%

### Note symbol





-L	Low channel location
-R	High channel location





2.4GHz 2400~2483.5MHz





BLE (Band Edge @ 3m)

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Fundamental
Peak	<div><p>Site : 03CH12-HY Condition : PEAK_BE_74 3m HORN_91200_1328 HORIZONTAL Detector : Peak Project : 921201-05 Mode : 4 Setting : 1</p></div>	<div><p>Site : 03CH12-HY Condition : PEAK_74 3m HORN_91200_1328 HORIZONTAL Detector : Peak Project : 921201-05 Mode : 4 Setting : 1</p></div>
Avg.	<div><p>Site : 03CH12-HY Condition : AVG_BE_54 3m HORN_91200_1328 HORIZONTAL Detector : Peak Project : 921201-05 Mode : 4 Setting : 1</p></div>	<div><p>Site : 03CH12-HY Condition : AVG_54 3m HORN_91200_1328 HORIZONTAL Detector : Peak Project : 921201-05 Mode : 4 Setting : 1</p></div>





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Vertical	Fundamental
Peak	<div><p>Site : 03CH12-HY Condition : PEAK_BE_74 3m HORN_91200_1328 VERTICAL Detector : Peak Project : 921201-05 Mode : 4 Setting : 1</p></div>	<div><p>Site : 03CH12-HY Condition : PEAK_74 3m HORN_91200_1328 VERTICAL Detector : Peak Project : 921201-05 Mode : 4 Setting : 1</p></div>
Avg	<div><p>Site : 03CH12-HY Condition : AV6_BE_54 3m HORN_91200_1328 VERTICAL Detector : Peak Project : 921201-05 Mode : 4 Setting : 1</p></div>	<div><p>Site : 03CH12-HY Condition : AV6_54 3m HORN_91200_1328 VERTICAL Detector : Peak Project : 921201-05 Mode : 4 Setting : 1</p></div>







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Horizontal	Fundamental
Peak	<div><p>Site : 03CH12-HY Condition : PEAK_9E_74 3m HORN_91200_1328 HORIZONTAL Detector : Peak Project : 921201-05 Mode : 5 Setting : 2</p></div>	<div><p>Site : 03CH12-HY Condition : PEAK_74 3m HORN_91200_1328 HORIZONTAL Detector : Peak Project : 921201-05 Mode : 5 Setting : 2</p></div>
Avg.	<div><p>Site : 03CH12-HY Condition : AVG_BE_54 3m HORN_91200_1328 HORIZONTAL Detector : Peak Project : 921201-05 Mode : 5 Setting : 2</p></div>	<div><p>Site : 03CH12-HY Condition : AVG_54 3m HORN_91200_1328 HORIZONTAL Detector : Peak Project : 921201-05 Mode : 5 Setting : 2</p></div>





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Horizontal	Fundamental
Peak	<div><p>Site : 03CH12-HY Condition : PEAK_BE_74 3m HORN_91200_1328 HORIZONTAL Detector : Peak Project : 921201-05 Mode : 5 Setting : 2</p></div>	Left blank
Avg.	<div><p>Site : 03CH12-HY Condition : AV6_BE_54 3m HORN_91200_1328 HORIZONTAL Detector : Peak Project : 921201-05 Mode : 5 Setting : 2</p></div>	Left blank







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Vertical	Fundamental
Peak	<div><p>Site : 03CH12-HY Condition : PEAK_BE_74 3m HORN_91200_1328 VERTICAL Detector : RBW:1000.0000Hz VBW:3000.0000Hz SWT:Auto Project : Peak Mode : 921201-05 Setting : 5 Setting : 2</p></div>	<div><p>Site : 03CH12-HY Condition : PEAK_74 3m HORN_91200_1328 VERTICAL Detector : RBW:1000.0000Hz VBW:3000.0000Hz SWT:Auto Project : Peak Mode : 921201-05 Setting : 5 Setting : 2</p></div>
Avg.	<div><p>Site : 03CH12-HY Condition : AV6_BE_54 3m HORN_91200_1328 VERTICAL Detector : RBW:1000.0000Hz VBW:1.0000Hz SWT:Auto Project : Peak Mode : 921201-05 Setting : 5 Setting : 2</p></div>	<div><p>Site : 03CH12-HY Condition : AV6_54 3m HORN_91200_1328 VERTICAL Detector : RBW:1000.0000Hz VBW:1.0000Hz SWT:Auto Project : Peak Mode : 921201-05 Setting : 5 Setting : 2</p></div>







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Vertical	Fundamental
Peak	<div><p>Site : 03CH12-HY Condition : PEAK_BE_74 3m HORN_91200_1328 VERTICAL Detector : Peak Project : 921201-05 Mode : 5 Setting : 2</p></div>	Left blank
Avg.	<div><p>Site : 03CH12-HY Condition : AVG_BE_54 3m HORN_91200_1328 VERTICAL Detector : Peak Project : 921201-05 Mode : 5 Setting : 2</p></div>	Left blank



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Fundamental
Peak	<div><p>Site : 03CH12-HY Condition : PEAK_BE_74 3m HORN_91200_1328 HORIZONTAL Detector : RBW:1000.0000Hz VBW:3000.0000Hz SWT:Auto Detector : Peak Project : 921201-05 Mode : 6 Setting : 1</p></div>	<div><p>Site : 03CH12-HY Condition : PEAK_74 3m HORN_91200_1328 HORIZONTAL Detector : RBW:1000.0000Hz VBW:3000.0000Hz SWT:Auto Detector : Peak Project : 921201-05 Mode : 6 Setting : 1</p></div>
Avg.	<div><p>Site : 03CH12-HY Condition : AVG_BE_54 3m HORN_91200_1328 HORIZONTAL Detector : RBW:1000.0000Hz VBW:1.0000Hz SWT:Auto Detector : Peak Project : 921201-05 Mode : 6 Setting : 1</p></div>	<div><p>Site : 03CH12-HY Condition : AVG_54 3m HORN_91200_1328 HORIZONTAL Detector : RBW:1000.0000Hz VBW:1.0000Hz SWT:Auto Detector : Peak Project : 921201-05 Mode : 6 Setting : 1</p></div>





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Vertical	Fundamental
Peak	<div><p>Site : 03CH12-HY Condition : PEAK_BE_74 3m HORN_91200_1328 VERTICAL Detector : Peak Project : 921201-05 Mode : 6 Setting : 1</p></div>	<div><p>Site : 03CH12-HY Condition : PEAK_74 3m HORN_91200_1328 VERTICAL Detector : Peak Project : 921201-05 Mode : 6 Setting : 1</p></div>
Avg.	<div><p>Site : 03CH12-HY Condition : AVG_BE_54 3m HORN_91200_1328 VERTICAL Detector : Peak Project : 921201-05 Mode : 6 Setting : 1</p></div>	<div><p>Site : 03CH12-HY Condition : AVG_54 3m HORN_91200_1328 VERTICAL Detector : Peak Project : 921201-05 Mode : 6 Setting : 1</p></div>







2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Vertical
Peak Avg.	<div><p>Site : 03CH12-HY Condition : PEAK_74 3m HORN_91200_1328 HORIZONTAL Detector : Peak Project : 921201-05 Mode : 4 Setting : 1</p></div>	<div><p>Site : 03CH12-HY Condition : PEAK_74 3m HORN_91200_1328 VERTICAL Detector : Peak Project : 921201-05 Mode : 4 Setting : 1</p></div>



BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m																									
	BLE CH19 2440MHz																									
	Horizontal	Vertical																								
Peak Avg.	<div><table><tr><td>Site</td><td>: 03CH12-HY</td></tr><tr><td>Condition</td><td>: PEAK_74 3m HORN_91200_1328 HORIZONTAL</td></tr><tr><td>Detector</td><td>: Peak</td></tr><tr><td>Project</td><td>: 921201-05</td></tr><tr><td>Mode</td><td>: 5</td></tr><tr><td>Setting</td><td>: 2</td></tr></table></div>	Site	: 03CH12-HY	Condition	: PEAK_74 3m HORN_91200_1328 HORIZONTAL	Detector	: Peak	Project	: 921201-05	Mode	: 5	Setting	: 2	<div><table><tr><td>Site</td><td>: 03CH12-HY</td></tr><tr><td>Condition</td><td>: PEAK_74 3m HORN_91200_1328 VERTICAL</td></tr><tr><td>Detector</td><td>: Peak</td></tr><tr><td>Project</td><td>: 921201-05</td></tr><tr><td>Mode</td><td>: 5</td></tr><tr><td>Setting</td><td>: 2</td></tr></table></div>	Site	: 03CH12-HY	Condition	: PEAK_74 3m HORN_91200_1328 VERTICAL	Detector	: Peak	Project	: 921201-05	Mode	: 5	Setting	: 2
Site	: 03CH12-HY																									
Condition	: PEAK_74 3m HORN_91200_1328 HORIZONTAL																									
Detector	: Peak																									
Project	: 921201-05																									
Mode	: 5																									
Setting	: 2																									
Site	: 03CH12-HY																									
Condition	: PEAK_74 3m HORN_91200_1328 VERTICAL																									
Detector	: Peak																									
Project	: 921201-05																									
Mode	: 5																									
Setting	: 2																									





BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Vertical
Peak	<div><p>140 Level (dBuV/m)</p><p>Date: 2019-12-09</p><p>Site : 03CH12-HY Condition : PEAK_74 3m HORN_91200_1328 HORIZONTAL Detector : Peak Project : 921201-05 Mode : G Setting : 1</p></div>	<div><p>140 Level (dBuV/m)</p><p>Date: 2019-12-09</p><p>Site : 03CH12-HY Condition : PEAK_74 3m HORN_91200_1328 VERTICAL Detector : Peak Project : 921201-05 Mode : G Setting : 1</p></div>



Emission below 1GHz

2.4GHz BLE (LF)


BLE	2.4GHz 2400~2483.5MHz	
	BLE LF	
	Horizontal	Vertical
QP / Peak	<div><p>Site : 03CH12-HY Condition : QP 3m 8ILO6_6111D_37059 HORIZONTAL Detector : Peak Project : 921201-05 Mode : 8 Setting : 2</p></div>	<div><p>Site : 03CH12-HY Condition : QP 3m 8ILO6_6111D_37059 VERTICAL Detector : Peak Project : 921201-05 Mode : 8 Setting : 2</p></div>



## Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
Bluetooth -LE	85.2	2130	0.47	1kHz	0.70

### Bluetooth - LE



—THE END—