

FCC Report

Applicant: Autel Intelligent Tech. Corp., Ltd.

Address of Applicant: 6th - 10th Floor, Bldg. B1, Zhiyuan, Xueyuan Rd., Xili, Nanshan, Shenzhen, China

Manufacturer/Factory: Autel Intelligent Tech. Corp., Ltd.

Address of Manufacturer/Factory: 6th - 10th Floor, Bldg. B1, Zhiyuan, Xueyuan Rd., Xili, Nanshan, Shenzhen, China

Equipment Under Test (EUT)

Product description: PROFESSIONAL SCAN TOOL(Model: MaxiCheck MX808TS),
AUTOMOTIVE DIAGNOSIS & ANALYSIS SYSTEM
(Model: MaxiCOM MK808TS),
AUTOMOTIVE DIAGNOSIS & ANALYSIS SYSTEM
(Model: MaxiDAS DS808TS),
AUTOMOTIVE DIAGNOSIS & ANALYSIS SYSTEM
(Model: MaxiPRO MP808TS),
COMPREHENSIVE TPMS TOOL(Model: MaxiTPMS TS608)

Trade Mark: AUTEL

FCC ID: WQ8MX808TS-17

Applicable standards: FCC CFR Title 47 Part 15 Subpart B:2016

Date of sample receipt: June 21, 2017

Date of Test: June 22-27, 2017

Date of report issue: June 28, 2017

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

A circular blue stamp with the text "GLOBAL UNITED TECHNOLOGY SERVICES CO., LTD." around the perimeter and "GTS" in the center. A handwritten signature in black ink is written over the stamp.

Robinson Lo

Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	June 28, 2017	Original

Prepared By:




Date:

June 28, 2017

Project Engineer

Check By:



Date:

June 28, 2017

Reviewer

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
4.1 MEASUREMENT UNCERTAINTY	4
5 GENERAL INFORMATION	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	5
5.3 TEST FACILITY	6
5.4 TEST LOCATION	6
5.5 DESCRIPTION OF SUPPORT UNITS	6
5.6 DEVIATION FROM STANDARDS	6
5.7 ABNORMALITIES FROM STANDARD CONDITIONS	6
5.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
6 TEST INSTRUMENTS LIST	7
7 TEST RESULTS AND MEASUREMENT DATA	8
7.1 CONDUCTED EMISSIONS	8
7.2 RADIATED EMISSION	13
8 TEST SETUP PHOTO	19
9 EUT CONSTRUCTIONAL DETAILS	20

4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part15.107	PASS
Radiated Emissions	Part15.109	PASS

PASS: The EUT complies with the essential requirements in the standard.

Remark : Test according to ANSI C63.4:2014.

4.1 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz ~ 30MHz	$\pm 4.34\text{dB}$	(1)
Radiated Emission	30MHz ~ 1000MHz	$\pm 4.24\text{dB}$	(1)
Radiated Emission	1GHz ~ 26.5GHz	$\pm 4.68\text{dB}$	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	$\pm 3.45\text{dB}$	(1)

Note (1): The measurement uncertainty is for coverage factor of $k=2$ and a level of confidence of 95%.

5 General Information

5.1 General Description of EUT

Product description:	PROFESSIONAL SCAN TOOL(Model: MaxiCheck MX808TS), AUTOMOTIVE DIAGNOSIS & ANALYSIS SYSTEM (Model: MaxiCOM MK808TS), AUTOMOTIVE DIAGNOSIS & ANALYSIS SYSTEM (Model: MaxiDAS DS808TS), AUTOMOTIVE DIAGNOSIS & ANALYSIS SYSTEM (Model: MaxiPRO MP808TS), COMPREHENSIVE TPMS TOOL(Model: MaxiTPMS TS608)
Test Model:	MaxiTPMS TS608
Remark:	<i>All above models are identical in the same PCB layout, interior structure and electrical circuits. The only difference is the model name for commercial purpose.</i>
Power Supply:	Adapter: Model:GME10C-050200FUu Input: AC 100-240V, 50-60Hz, 0.28A Output: DC 5V, 2A DC 3.7V 5000mAh Lithium Battery

5.2 Test mode

Test mode:	
Play with TF card mode	Keep the EUT in playing with TF card mode
Play with USB disk mode	Keep the EUT in playing with USB disk mode
Play with Int.memory mode	Keep the EUT in playing with Int.memory mode
Operation mode	Keep the EUT in operation mode
OTG mode	Keep the EUT in OTG mode
PC mode	Keep the EUT in PC status.
HDMI output mode	Keep the EUT in HDMI output mode.

5.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC —Registration No.: 600491**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 600491, June 22, 2016.

- **Industry Canada (IC) —Registration No.: 9079A-2**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, August 15, 2016

5.4 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102

Tel: 0755-27798480

Fax: 0755-27798960

5.5 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC Approval
Apple	PC	A1278	C1MN99ERDTY3	DoC
DELL	KEYBOARD	SK-8115	N/A	DoC
DELL	MOUSE	MOC5UO	N/A	DoC
Kingston	TF card	SD-C01G	N/A	DoC
Kingston	USB disk	4GB	N/A	DoC
PHILIPS	LCD TV	19PFL3120/T3	AU1A1212002906	DOC

5.6 Deviation from Standards

Biconical, log.per. antenna and horn antenna were used instead of dipole antenna. Semi-anechoic Chamber was used as alternation of open air test sites, and all test suites were performed with radiated method in it.

5.7 Abnormalities from Standard Conditions

None.

5.8 Other Information Requested by the Customer

None.

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.0(L)*6.0(W)* 6.0(H)	GTS250	July. 03 2015	July. 02 2020
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	ESU EMI Test Receiver	R&S	ESU26	GTS203	June 29 2016	June 28 2017
4	BiConiLog Antenna	SCHWARZBECK	VULB9163	GTS214	June 29 2016	June 28 2017
5	Double-ridged horn antenna	SCHWARZBECK	9120D	GTS208	June 29 2016	June 28 2017
6	RF Amplifier	HP	8347A	GTS204	June 29 2016	June 28 2017
7	Broadband Preamplifier	SCHWARZBECK	BBV9718	GTS535	June 29 2016	June 28 2017
8	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
9	Coaxial cable	GTS	N/A	GTS210	N/A	N/A
10	Coaxial Cable	GTS	N/A	GTS211	N/A	N/A
11	Thermo meter	N/A	N/A	GTS256	June 29 2016	June 28 2017

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May.16 2014	May.15 2019
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June 29 2016	June 28 2017
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June 29 2016	June 28 2017
4	Artificial Mains Network	SCHWARZBECK MESS	NSLK8127	GTS226	June 29 2016	June 28 2017
5	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	KTJ	TA328	GTS233	June 29 2016	June 28 2017

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	ChangChun	DYM3	GTS257	June 29 2016	June 28 2017

7 Test Results and Measurement Data


7.1 Conducted Emissions

Test Requirement:	FCC Part15 B Section 15.107		
Test Method:	ANSI C63.4:2014		
Test Frequency Range:	150KHz to 30MHz		
Class / Severity:	Class B		
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test setup:	<div><p style="text-align: center;">Reference Plane</p><p>Diagram Description: The diagram shows a test setup on a 'Test table/Insulation plane'. An 'E.U.T.' (Equipment Under Test) is connected to a 'LISN' (Line Impedance Stabilization Network) and an 'EMI Receiver'. The 'LISN' is connected to a 'Reference Plane' and 'AC power' through a 'Filter'. Dimensions of 40cm and 80cm are indicated between the equipment and the reference plane.</p><p><i>Remark</i> E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p></div>		
Test procedure:	<div><div>1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</div><div>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</div><div>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement.</div></div>		
Test Instruments:	Refer to section 6 for details		
Test mode:	Pre-scan all modes in section 5.2, only the data of worst mode was show on the test report.		
Test results:	Pass		

Measurement Data


Line:

PC Mode:



Freq MHz	Reading level dBuV	IISN/ISN factor dB	Cable loss dB	level dBuV	Limit level dBuV	Over limit dB	Remark
0.177	48.92	0.42	0.13	49.47	64.64	-15.17	QP
0.177	42.15	0.42	0.13	42.70	54.64	-11.94	Average
0.221	45.31	0.43	0.12	45.86	62.79	-16.93	QP
0.221	34.21	0.43	0.12	34.76	52.79	-18.03	Average
0.262	40.66	0.44	0.11	41.21	61.38	-20.17	QP
0.262	33.03	0.44	0.11	33.58	51.38	-17.80	Average
0.307	33.31	0.44	0.10	33.85	60.06	-26.21	QP
0.307	27.89	0.44	0.10	28.43	50.06	-21.63	Average
0.356	39.16	0.43	0.10	39.69	58.83	-19.14	QP
0.356	26.62	0.43	0.10	27.15	48.83	-21.68	Average
0.743	29.93	0.28	0.13	30.34	56.00	-25.66	QP
0.743	16.83	0.28	0.13	17.24	46.00	-28.76	Average


Neutral:



Freq MHz	Reading level dBuV	LIISN/ISN factor dB	Cable loss dB	level dBuV	Limit level dBuV	Over limit dB	Remark
0.156	50.93	0.41	0.12	51.46	65.65	-14.19	QP
0.156	41.58	0.41	0.12	42.11	55.65	-13.54	Average
0.184	42.58	0.41	0.13	43.12	64.28	-21.16	QP
0.184	36.85	0.41	0.13	37.39	54.28	-16.89	Average
0.223	43.76	0.42	0.12	44.30	62.70	-18.40	QP
0.223	34.37	0.42	0.12	34.91	52.70	-17.79	Average
0.283	35.72	0.42	0.10	36.24	60.72	-24.48	QP
0.283	27.88	0.42	0.10	28.40	50.72	-22.32	Average
0.346	30.52	0.41	0.10	31.03	59.05	-28.02	QP
0.346	21.66	0.41	0.10	22.17	49.05	-26.88	Average
0.474	33.59	0.36	0.11	34.06	56.45	-22.39	QP
0.474	26.10	0.36	0.11	26.57	46.45	-19.88	Average


Line:

Operation Mode:



Freq MHz	Reading level dBuV	11SN/ISN factor dB	Cable loss dB	level dBuV	Limit level dBuV	Over limit dB	Remark
0.156	42.05	0.42	0.12	42.59	65.65	-23.06	QP
0.156	27.58	0.42	0.12	28.12	55.65	-27.53	Average
0.172	42.18	0.42	0.12	42.72	64.86	-22.14	QP
0.172	28.01	0.42	0.12	28.55	54.86	-26.31	Average
0.228	34.15	0.43	0.12	34.70	62.52	-27.82	QP
0.228	19.74	0.43	0.12	20.29	52.52	-32.23	Average
0.270	31.50	0.44	0.11	32.05	61.12	-29.07	QP
0.270	17.07	0.44	0.11	17.62	51.12	-33.50	Average
0.315	28.17	0.44	0.10	28.71	59.84	-31.13	QP
0.315	17.42	0.44	0.10	17.96	49.84	-31.88	Average
0.505	32.88	0.38	0.11	33.37	56.00	-22.63	QP
0.505	22.63	0.38	0.11	23.12	46.00	-22.88	Average

Neutral:




Freq MHz	Reading level dBuV	LISN/ISN factor dB	Cable loss dB	level dBuV	Limit level dBuV	Over limit dB	Remark
0.150	42.48	0.41	0.12	43.01	66.00	-22.99	QP
0.150	29.17	0.41	0.12	29.70	56.00	-26.30	Average
0.170	40.71	0.41	0.12	41.24	64.94	-23.70	QP
0.170	26.77	0.41	0.12	27.30	54.94	-27.64	Average
0.226	34.54	0.42	0.12	35.08	62.61	-27.53	QP
0.226	19.58	0.42	0.12	20.12	52.61	-32.49	Average
0.272	30.19	0.42	0.11	30.72	61.07	-30.35	QP
0.272	16.71	0.42	0.11	17.24	51.07	-33.83	Average
0.320	27.81	0.42	0.10	28.33	59.71	-31.38	QP
0.320	17.74	0.42	0.10	18.26	49.71	-31.45	Average
0.505	29.31	0.35	0.11	29.77	56.00	-26.23	QP
0.505	18.77	0.35	0.11	19.23	46.00	-26.77	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.
5. Only the worst case shows above

7.2 Radiated Emission

Test Requirement:	FCC Part15 B Section 15.109																																					
Test Method:	ANSI C63.4:2014																																					
Test Frequency Range:	30MHz to 6GHz																																					
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)																																					
Receiver setup:	<table><tr><td>Frequency</td><td>Detector</td><td>RBW</td><td>VBW</td><td>Remark</td></tr><tr><td>30MHz-1GHz</td><td>Quasi-peak</td><td>120kHz</td><td>300kHz</td><td>Quasi-peak Value</td></tr><tr><td rowspan="2">Above 1GHz</td><td>Peak</td><td>1MHz</td><td>3MHz</td><td>Peak Value</td></tr><tr><td>Peak</td><td>1MHz</td><td>10Hz</td><td>Average Value</td></tr></table>					Frequency	Detector	RBW	VBW	Remark	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value	Above 1GHz	Peak	1MHz	3MHz	Peak Value	Peak	1MHz	10Hz	Average Value														
Frequency	Detector	RBW	VBW	Remark																																		
30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value																																		
Above 1GHz	Peak	1MHz	3MHz	Peak Value																																		
	Peak	1MHz	10Hz	Average Value																																		
Limit:	<table><tr><td colspan="2">Frequency</td><td>Limit (dBuV/m @3m)</td><td colspan="2">Remark</td></tr><tr><td colspan="2">30MHz-88MHz</td><td>40.00</td><td colspan="2">Quasi-peak Value</td></tr><tr><td colspan="2">88MHz-216MHz</td><td>43.50</td><td colspan="2">Quasi-peak Value</td></tr><tr><td colspan="2">216MHz-960MHz</td><td>46.00</td><td colspan="2">Quasi-peak Value</td></tr><tr><td colspan="2">960MHz-1GHz</td><td>54.00</td><td colspan="2">Quasi-peak Value</td></tr><tr><td colspan="2" rowspan="2">Above 1GHz</td><td>54.00</td><td colspan="2">Average Value</td></tr><tr><td>74.00</td><td colspan="2">Peak Value</td></tr></table>					Frequency		Limit (dBuV/m @3m)	Remark		30MHz-88MHz		40.00	Quasi-peak Value		88MHz-216MHz		43.50	Quasi-peak Value		216MHz-960MHz		46.00	Quasi-peak Value		960MHz-1GHz		54.00	Quasi-peak Value		Above 1GHz		54.00	Average Value		74.00	Peak Value	
Frequency		Limit (dBuV/m @3m)	Remark																																			
30MHz-88MHz		40.00	Quasi-peak Value																																			
88MHz-216MHz		43.50	Quasi-peak Value																																			
216MHz-960MHz		46.00	Quasi-peak Value																																			
960MHz-1GHz		54.00	Quasi-peak Value																																			
Above 1GHz		54.00	Average Value																																			
		74.00	Peak Value																																			
Test Procedure:	<div>1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</div> <div>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</div> <div>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</div> <div>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</div> <div>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</div> <div>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</div>																																					
Test setup:	Below 1GHz																																					

	 <p>Above 1GHz</p>
Test environment:	Temp.: 25 °C Humid.: 52% Press.: 1 012mbar
Measurement Record:	Uncertainty: ± 4.5dB
Test Instruments:	Refer to section 6 for details
Test mode:	Pre-scan all modes in section 5.2, only the data of worst mode was show on the test report.
Test results:	Pass

Note 1:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:


$$\text{Final Test Level} = \text{Receiver Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Preamplifier Factor}$$

Measurement Data

Below 1GHz


PC mode:

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
148.441	54.40	7.50	1.56	29.41	34.05	43.50	-9.45	QP
297.224	40.82	13.40	2.35	29.99	26.58	46.00	-19.42	QP
446.414	48.14	16.41	3.07	29.40	38.22	46.00	-7.78	QP
595.133	39.60	19.19	3.70	29.30	33.19	46.00	-12.81	QP
742.259	44.81	20.44	4.24	29.20	40.29	46.00	-5.71	QP
893.857	34.21	22.15	4.83	29.10	32.09	46.00	-13.91	QP

Vertical:




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
123.266	50.49	9.07	1.38	29.55	31.39	43.50	-12.11	QP
148.441	57.28	7.50	1.56	29.41	36.93	43.50	-6.57	QP
446.414	47.48	16.41	3.07	29.40	37.56	46.00	-8.44	QP
595.133	40.35	19.19	3.70	29.30	33.94	46.00	-12.06	QP
744.866	48.09	20.48	4.26	29.20	43.63	46.00	-2.37	QP
893.857	39.61	22.15	4.83	29.10	37.49	46.00	-8.51	QP

Above 1GHz


PC mode:

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
1555.000	39.92	25.08	4.72	33.71	36.01	74.00	-37.99	Peak
2385.000	35.86	27.61	5.38	34.03	34.82	74.00	-39.18	Peak
3205.000	34.30	28.71	6.37	33.08	36.30	74.00	-37.70	Peak
3750.000	32.02	29.30	7.42	32.46	36.28	74.00	-37.72	Peak
4720.000	28.89	31.68	8.53	32.05	37.05	74.00	-36.95	Peak
5375.000	30.23	31.77	9.33	32.36	38.97	74.00	-35.03	Peak


Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
1140.000	39.27	24.94	4.42	32.98	35.65	74.00	-38.35	Peak
1575.000	39.01	25.02	4.73	33.74	35.02	74.00	-38.98	Peak
3095.000	34.28	28.69	6.13	33.22	35.88	74.00	-38.12	Peak
3455.000	33.55	28.84	6.88	32.81	36.46	74.00	-37.54	Peak
4590.000	28.15	31.49	8.41	31.98	36.07	74.00	-37.93	Peak
5910.000	25.85	32.78	10.09	32.18	36.54	74.00	-37.46	Peak

8 Test Setup Photo

Radiated Emission



Conducted Emission



9 EUT Constructional Details

Reference to the test report No. GTS201708000145E01

----- End-----