客戶名称:	Shenzhe	Shenzhen I-Link Technology Co., Ltd				
客戶料号:		D.040.23				
我司型号:		DXD -G25-8.1UH-2800GS-55MM				
送样日期:	202	2024年8月26日				
供应方:	Donggua ————	Dongguan De Xinda electronic Technology Co., LTD				
绘制/draw		审 核/audit	批 准/ratify			
RAO		谢良	*			
客戶承认/CI	ustomer r	recognition:				
qualified	di squal i	fication	承 认			
备注						
	191, Qin gguan City	'an Road, Wei Town Commu	nity, Zhangmuou Town,			

我司型号

DXD-G25-8.1UH-2800GS-55MM

版本

Α0


日期


2024-8-26


客戶料号

客戶名称

一、平面结构图/Plane structure diagram: 单位/unit:MM







A	7. 65 ± 0.05
В	2.0 ± 0.05
С	2 ± 1
D	14 ± 0.2
Е	20.7 \pm 0.3
F	21 ± 0.2
G	7. 7 ± 0.05
Н	13.5 ± 0.2
1	23.5 ± 0.3
J	25 ± 0.2
K	2.5 ± 0.1
L	2.25±0.1 中柱高度
M	10 ± 1

二、产品参数/Product Parameter:

foot position	wire diameter	number of turns	remark
1 - 2	0.08*24P	14	Hot air stranding wire

- 三、技术要求/technical requirements:
- 1. Fix the end of the wire to prevent loose and broken wires
- 2. According to customer requirements, the over-long thread is cut, plated with tin, the tin plating depth is 2±1MM, and the back is affixed with 513-14mm round double-sided tape, and then packaged
- 3. Point the appropriate white glue on the soft magnetic sheet, paste the coil, and ensure that the product surface is clean and tidy in the process
- 4. The soft magnetic sheet used is with round holes, without damage
- 5.Additional process (according requirements) to customer Install 7.65x2.0mm magnet the middle round hole of the finished roduct the finished product and in

四、电性参数/electrical parameter

1.电感值, Q值/Inductance value, Q value:

PIN 1 - 2 = 8.1uH
$$\pm 0.5$$
UH

Q 值≥35/0 value ≥35

The above inductance values are based on Quanhua 1062A instrument, 10KHZ/0.3Vrms as the standard or equivalent instrument

Q value is based on Quanhua 1062A instrument, 100KHZ/0.3Vrms as standard or equivalent instrument

五、材料清单/bill of materials

	五、你们有一个biii bi liateriais						
序号	name:	texture					
1	Hot air stranding wire	0.08X24P					
2	magnetic sheet	G25 soft substrate material					
3	tin	High temperature environmental prote	ection				
4	white glues	BY882					
5	strong magnet	7.65*2.0(磁力 2800GS)					
6	double faced adhesive tape	513-14mm					