

# TEST REPORT

Applicant Name: Shenzhen Xin Yuan Electronic Technology Co., Ltd.  
Address: Room 801-803, Yousuowei Building, No.2000, JiaXian Road,  
Bantian Street, Longgang District, Shenzhen, Guangdong,  
China  
Report Number: 2401Z59114E-RF-00B  
FCC ID: 2ASYE-TDISS3-AMOLED

## Test Standard (s)

FCC PART 15.247

## Sample Description

Product Type: T-Display-S3-AMOLED  
Model No.: T-Display-S3-AMOLED 1.43  
Multiple Model(s) No.: T-Display-S3-AMOLED 1.75, T-Display-S3-AMOLED 1.75  
hemispherical  
Trade Mark: LILYGO  
Date Received: 2024-11-22  
Issue Date: 2025-03-14

Test Result:

Pass▲

▲ In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

GaLa Liu

GaLa Liu  
RF Engineer

Approved By:

Michelle Zeng

Michelle Zeng  
RF Supervisor

Note: The information marked<sup>#</sup> is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.

This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

**Bay Area Compliance Laboratories Corp. (Shenzhen)**

5F(B-West), 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China

Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

## **TABLE OF CONTENTS**

<b>DOCUMENT REVISION HISTORY .....</b>	<b>3</b>
<b>GENERAL INFORMATION.....</b>	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	4
OBJECTIVE .....	4
TEST METHODOLOGY .....	5
MEASUREMENT UNCERTAINTY .....	5
TEST FACILITY .....	5
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>6</b>
<b>SUMMARY OF TEST RESULTS .....</b>	<b>9</b>
<b>TEST EQUIPMENT LIST .....</b>	<b>10</b>
<b>REQUIREMENTS AND TEST PROCEDURES .....</b>	<b>12</b>
AC LINE CONDUCTED EMISSIONS.....	12
SPURIOUS EMISSIONS.....	14
6 dB EMISSION BANDWIDTH.....	17
MAXIMUM CONDUCTED OUTPUT POWER .....	18
100kHz BANDWIDTH OF FREQUENCY BAND EDGE .....	19
POWER SPECTRAL DENSITY .....	20
DUTY CYCLE .....	22
<b>ANTENNA REQUIREMENT .....</b>	<b>23</b>
<b>TEST DATA AND RESULTS.....</b>	<b>24</b>
AC LINE CONDUCTED EMISSIONS.....	24
SPURIOUS EMISSIONS.....	27
6dB EMISSION BANDWIDTH.....	88
99% OCCUPIED BANDWIDTH .....	91
MAXIMUM CONDUCTED OUTPUT POWER .....	94
POWER SPECTRAL DENSITY .....	95
100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	98
DUTY CYCLE .....	101
<b>RF EXPOSURE EVALUATION .....</b>	<b>103</b>
<b>EUT PHOTOGRAPHS .....</b>	<b>104</b>
<b>TEST SETUP PHOTOGRAPHS .....</b>	<b>105</b>

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	2401Z59114E-RF-00B	Original Report	2025-03-14

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

<b>Product</b>	T-Display-S3-AMOLED
<b>Tested Model</b>	T-Display-S3-AMOLED 1.43
<b>Multiple Model(s)</b>	T-Display-S3-AMOLED 1.75, T-Display-S3-AMOLED 1.75 hemispherical
<b>Frequency Range</b>	2412~2472MHz
<b>Maximum Conducted Output Peak Power</b>	20.0 dBm
<b>Modulation Technique</b>	DSSS, OFDM
<b>Antenna Specification<sup>#</sup></b>	4dBi (provided by the applicant)
<b>Voltage Range</b>	DC5.0V from type-c charging port
<b>Sample serial number</b>	Model: T-Display-S3-AMOLED 1.43 2UZL-2 for Conducted and Radiated Emissions Test 2UZL-1 for RF Conducted Test (Assigned by BACL, Shenzhen)  Model: T-Display-S3-AMOLED 1.75 2UZI-5 for Radiated Emissions Test  Model: T-Display-S3-AMOLED 1.75 hemispherical 2UZI-4 for Radiated Emissions Test
<b>Sample/EUT Status</b>	Good condition
<b>Adapter Information</b>	N/A

Note: The multiple models are electrically identical with the test model except for model name and screen size, model T-Display-S3-AMOLED 1.43 was selected for fully testing, other models were selected for “radiation emission below 1 GHz test”, please refer to the declaration letter<sup>#</sup> for more detail, which was provided by manufacturer.

### Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission’s rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

## Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

## Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		109.2kHz(k=2, 95% level of confidence)
RF output power, conducted		0.86dB(k=2, 95% level of confidence)
AC Power Lines Conducted Emissions	9kHz~150 kHz	3.63dB(k=2, 95% level of confidence)
	150 kHz ~30MHz	3.66dB(k=2, 95% level of confidence)
Radiated Emissions	0.009MHz~30MHz	3.60dB(k=2, 95% level of confidence)
	30MHz~200MHz (Horizontal)	5.32dB(k=2, 95% level of confidence)
	30MHz~200MHz (Vertical)	5.43dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Horizontal)	5.77dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Vertical)	5.73dB(k=2, 95% level of confidence)
	1GHz - 6GHz	5.34dB(k=2, 95% level of confidence)
	6GHz - 18GHz	5.40dB(k=2, 95% level of confidence)
	18GHz - 40GHz	5.64dB(k=2, 95% level of confidence)
Temperature		±1°C
Humidity		±1%
Supply voltages		±0.4%

*Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.*

## Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 715558, the FCC Designation No.: CN5045.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

For 2.4GHz Wi-Fi mode, total 13 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	12	2467
6	2437	13	2472
7	2442		

802.11b, 802.11g and 802.11n-HT20 mode was tested with Channel 1, 7 and 13.

802.11n-HT40 mode was tested with Channel 3, 7 and 11.

### EUT Exercise Software

Exercise Software <sup>#</sup>		EspRFTTestTool-V3.6-Manual.exe		
Mode	Data rate	Power Level <sup>#</sup>		
		Low Channel	Middle Channel	High Channel
802.11b	1Mbps	50	50	50
802.11g	6Mbps	25	25	35
802.11n20	MCS0	20	20	20
802.11n40	MCS0	20	20	20

Note: The worst-case data rates are determined to be as follows for each mode based upon investigation by measuring the power and PSD across all data rates bandwidths, and modulations.

### Special Accessories

No special accessory.

### Equipment Modifications

No modification was made to the EUT tested.

### Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
DELL	Notebook	Latitude E6410	11429208685
Unknown	Adapter	Unknown	Unknown
OUPU	Receptacle	PDU-OP1606K	6971041358020

**External I/O Cable**


Cable Description	Length (m)	From Port	To
Un-shielded Detachable USB Cable	1.5	EUT	Notebook
Unshielded Un-Detachable Cable	1.0	Receptacle	LISN/AC Main
Unshielded Detachable USB Cable	1.0	Adapter	EUT

**Block Diagram of Test Setup**


For Conducted Emissions:



For Radiated Emissions below 1GHz:



For Radiated Emissions above 1GHz:





**SUMMARY OF TEST RESULTS**

FCC Rules	Description of Test	Result
FCC §15.203	Antenna Requirement	Compliant
FCC §15.207(a)	AC Line Conducted Emissions	Compliant
FCC §15.205,§15.209,§15.247(d)	Radiated Spurious Emission	Compliant
FCC §15.207(a)(2)	6dB Emission Bandwidth& Occupied Bandwidth	Compliant
FCC §15.247(b)(1)	Maximum Conducted Output Power	Compliant
FCC §15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
FCC §15.247(d)	Conducted Spurious Emission	Compliant
FCC §15.247(e)	Power Spectral Density	Compliant
C63.10 §11.6	Duty Cycle	/
FCC § 15.247 (i), §1.1307 (b) (3) & §2.1091	Maximum Permissible Exposure(MPE)	Compliant

**TEST EQUIPMENT LIST**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
<b>Conducted Emission Test</b>					
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2024/12/04	2025/12/03
Rohde & Schwarz	LISN	ENV216	101613	2024/12/04	2025/12/03
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2024/05/21	2025/05/20
Unknown	CE Cable	Unknown	UF A210B-1-0720-504504	2024/05/21	2025/05/20
Audix	EMI Test software	E3	191218(V9)	NCR	NCR
<b>Radiated Emission Test</b>					
Rohde & Schwarz	EMI Test Receiver	ESR3	102455	2024/12/04	2025/12/03
Sonoma instrument	Pre-amplifier	310N	186238	2024/05/21	2025/05/20
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2023/07/20	2026/07/19
Unknown	Cable	Chamber Cable 1	F-03-EM236	2024/06/18	2025/06/17
Unknown	Cable	XH500C	J-10M-A	2024/06/18	2025/06/17
BACL	Active Loop Antenna	1313-1A	4031911	2024/05/14	2027/05/13
Audix	EMI Test software	E3	19821b(V9)	NCR	NCR
Rohde&Schwarz	Spectrum Analyzer	FSV40	101605	2024/03/27	2025/03/26
A.H.System	Preamplifier	PAM-0118P	489	2024/11/15	2025/11/14
Schwarzbeck	Horn Antenna	BBHA9120D(1201)	1143	2023/07/26	2026/07/25
Unknown	RF Cable	KMSE	0735	2024/12/04	2025/12/03
Unknown	RF Cable	UFA147	219661	2024/12/04	2025/12/03
A.H.System	Pre-amplifier	PAM-1840VH	190	2024/06/18	2025/06/17
Electro-Mechanics Co	Horn Antenna	3116	9510-2270	2023/09/18	2026/09/17
JD	Multiplex Switch Test Control Set	DT7220SCU	DS79903	2024/09/09	2025/09/08
JD	Filter Switch Unit	DT7220FSU	DS79906	2024/09/09	2025/09/08
UTIFLEX	RF Cable	NO. 13	232308-001	2024/06/18	2025/06/17
Audix	EMI Test software	E3	191218(V9)	NCR	NCR

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Unknown	10dB Attenuator	Unknown	F-03-EM190	2024/06/27	2025/06/26
Rohde&Schwarz	Spectrum Analyzer	FSV40-N	102259	2024/12/04	2025/12/03
ANRITSU	Microwave peak power sensor	MA24418A	12622	2024/05/21	2025/05/20

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).


## REQUIREMENTS AND TEST PROCEDURES

### AC Line Conducted Emissions

#### Applicable Standard

FCC§15.207

#### EUT Setup



Note: 1. Support units were connected to second LISN.  
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

#### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

FrequencyRange	IF B/W
150 kHz – 30 MHz	9 kHz

**Test Procedure**

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

**Factor & Over Limit Calculation**

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over limit of -7dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\begin{aligned} \text{Over Limit} &= \text{level} - \text{Limit} \\ \text{Level} &= \text{reading level} + \text{Factor} \end{aligned}$$

Note: The term "cable loss" refers to the combination of a cable and a 10dB transient limiter (attenuator).


## Spurious Emissions

### Applicable Standard


FCC §15.247 (d); §15.209; §15.205;


### EUT Setup

#### 9 kHz-30MHz:



#### 30MHz-1GHz:



**Above 1GHz:**

The radiated emission performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, FCC 15.247 limits.

**EMI Test Receiver & Spectrum Analyzer Setup**

The system was investigated from 9kHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

**9kHz-1GHz:**

Frequency Range	RBW	Video B/W	IF B/W	Measurement
9 kHz – 150 kHz	/	/	200Hz	QP
	300Hz	1 kHz	/	PK
150 kHz – 30 MHz	/	/	9 kHz	QP
	10 kHz	30 kHz	/	PK
30MHz – 1000 MHz	/	/	120kHz	QP
	100 kHz	300 kHz	/	PK

**1-25GHz:****Pre-scan**

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98%	1MHz	5 kHz
	<98%	1MHz	≥1/Ton, not less than 5 kHz

Final measurement for emission identified during pre-scan

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98%	1MHz	10 Hz
	<98%	1MHz	≥1/Ton

Note: Ton is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

### Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, average detection modes for frequency bands 9–90 kHz and 110–490 kHz, peak and average detection modes for frequencies above 1 GHz.

For 9 kHz-30MHz, the report shall list the six emissions with the smallest margin relative to the limit, for each of the three antenna orientations (parallel, perpendicular, and ground-parallel) unless the margin is greater than 20 dB.

All emissions under the average limit and under the noise floor have not recorded in the report.

### Factor & Over Limit/Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level/Corrected Amplitude} - \text{Limit} \\ \text{Level / Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$



## 6 dB Emission Bandwidth

### Applicable Standard

According to FCC §15.247(a) (2)

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.


### Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.8.1 & Clause 6.9.3

- a. Set RBW = 100 kHz.
- b. Set the VBW  $\geq [3 \times \text{RBW}]$ .
- c. Detector = peak.
- d. Trace mode = max hold.
- e. Sweep = auto couple.
- f. Allow the trace to stabilize.
- g. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. Procedure as below

- a. The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b. The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW (for RSS rules, VBW shall not be smaller than three times the RBW, unless otherwise specified by the applicable requirement).
- c. Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than  $[10 \log (\text{OBW}/\text{RBW})]$  below the reference level.
- d. Step a) through step c) might require iteration to adjust within the specified range.
- e. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- f. Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g. If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h. The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).



## Maximum Conducted Output Power


### Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

### Test Procedure

Test method: ANSI C63.10-2013 clause 11.9.1.3 for peak power method or clause 11.9.2.3.2 for average power method.

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Note: A short RF cable with low cable loss connected to the EUT antenna port, which was provided by client or lab, the cable loss was added with offset into test equipment, the total offset consists of attenuator and/or RF cable and/or power splitter loss

## 100kHz Bandwidth of Frequency Band Edge


### Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.11

1. Set the RBW=100 kHz.
  2. Set the VBW  $\geq 3 \times$  RBW.
  3. Detector = peak
  4. Sweep time = auto couple.
  5. Trace mode=max hold
  6. All trace to fully stabilize
  7. Use the peak marker function to determine the maximum amplitude level.
- Ensure that amplitude of all unwanted emissions outside of the authorized frequency band(excluding restricted frequency bands) is attenuated by at least the minimum requirement specified in 11.11.  
Report the three highest emissions relative to the limit.



## Power Spectral Density

### Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.10.2

Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.

1. Set the RBW to:  $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$ .
2. Set the VBW  $\geq 3 \times \text{RBW}$ .
3. Set the span to 1.5 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum amplitude level within the RBW.
9. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Method: ANSI C63.10-2013 Clause 11.10.3 Method AVGPSD-1


The following procedure may be used when the maximum (average) conducted output power was used to determine compliance to the fundamental output power limit. This is the baseline method for determining the maximum (average) conducted PSD level. If the instrument has a power averaging (rms) detector, then it must be used; otherwise, use the sample detector. The EUT must be configured to transmit continuously ( $D \geq 98\%$ ), or else sweep triggering/signal gating must be implemented to ensure that measurements are made only when the EUT is transmitting at its maximum power control level (no transmitter OFF time to be considered):

1. Set instrument center frequency to DTS channel center frequency.
2. Set span to at least 1.5 times the OBW.
3. Set the RBW to:  $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$ .
4. Set the VBW  $\geq 3 \times \text{BW}$ .
5. Detector = power averaging (rms) or sample detector (when rms not available)
6. Ensure that the number of measurement points in the sweep  $\geq [2 \times \text{span} / \text{RBW}]$ .
7. Sweep time = auto couple.
8. Employ trace averaging (rms) mode over a minimum of 100 traces.
9. Use the peak marker function to determine the maximum amplitude level.
10. If the measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).

## Test Method: ANSI C63.10-2013 Clause 11.10.5 Method AVGPSSD-2

The following procedure is applicable when the EUT cannot be configured to transmit continuously (i.e.,  $D < 98\%$ ), when sweep triggering/signal gating cannot be used to measure only when the EUT is transmitting at its maximum power control level, and when the transmission duty cycle is constant (i.e., duty cycle variations are less than  $\pm 2\%$ ):

1. Measure the duty cycle (D) of the transmitter output signal as described in 11.6.
2. Set instrument center frequency to DTS channel center frequency.
3. Set span to at least 1.5 times the OBW.
4. Set the RBW to:  $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$ .
5. Set the VBW  $\geq 3 \times \text{BW}$ .
6. Detector = power averaging (rms) or sample detector (when rms not available)
7. Ensure that the number of measurement points in the sweep  $\geq [2 \times \text{span} / \text{RBW}]$ .
8. Sweep time = auto couple.
9. Do not use sweep triggering; allow sweep to “free run.”
10. Employ trace averaging (rms) mode over a minimum of 100 traces.
11. Use the peak marker function to determine the maximum amplitude level.
12. If the measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).



Note: A short RF cable with low cable loss connected to the EUT antenna port, which was provided by client or lab, the cable loss was added with offset into test equipment, the total offset consists of attenuator and/or RF cable and/or power splitter loss


## Duty Cycle

### Test Procedure

According to ANSI C63.10-2013 Section 11.6

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set  $RBW \geq OBW$  if possible; otherwise, set RBW to the largest available value.
- 3) Set  $VBW \geq RBW$ . Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are  $> 50/T$  and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if  $T \leq 16.7 \mu s$ .)



## ANTENNA REQUIREMENT

---

### Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

### Antenna Connector Construction

The EUT has an internal antenna arrangement, which was permanently attached, the antenna gain<sup>#</sup> is 4dBi, fulfill the requirement of this section. Please refer to the EUT photos.

### Result: Compliant

TEST DATA AND RESULTS


AC Line Conducted Emissions

Environmental Conditions

Temperature (°C)	25.3	Relative Humidity (%)	50
ATM Pressure (kPa)	101.4	Test engineer	Macy Shi
Test date	2024.12.14		
EUT operation mode	Transmitting(Maximum output power mode, 802.11g, low channel)		



## AC 120V 60 Hz, Line



Condition: Line

Project : 2401Z59114E-RF


tester : Macy.shi

Note : Transmitting

Detector : RBW:9KHz VBW:Auto SWT:Auto

	Read Freq	Level dBuV	LISN Level dBuV	Cable Factor dB	Limit Loss dB	Over Line dBuV	Over Limit dB	Remark
1	0.155	3.42	24.43	10.89	10.12	55.74	-31.31	Average
2	0.155	11.20	32.21	10.89	10.12	65.74	-33.53	QP
3	0.206	3.56	24.44	10.79	10.09	53.36	-28.92	Average
4	0.206	10.16	31.04	10.79	10.09	63.36	-32.32	QP
5	0.502	7.89	28.53	10.50	10.14	46.00	-17.47	Average
6	0.502	12.35	32.99	10.50	10.14	56.00	-23.01	QP
7	0.614	15.49	36.11	10.50	10.12	46.00	-9.89	Average
8	0.614	20.92	41.54	10.50	10.12	56.00	-14.46	QP
9	2.285	1.23	21.95	10.54	10.18	46.00	-24.05	Average
10	2.285	8.84	29.56	10.54	10.18	56.00	-26.44	QP
11	5.805	1.48	22.09	10.43	10.18	50.00	-27.91	Average
12	5.805	8.40	29.01	10.43	10.18	60.00	-30.99	QP

## AC 120V 60 Hz, Neutral



Condition: Neutral

Project : 2401Z59114E-RF

tester : Macy.shi

Note : Transmitting

Detector : RBW:9KHz VBW:Auto SWT:Auto

	Freq	Read Level	LISN Level	Cable Factor	Limit Loss	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dB	dB
1	0.174	3.79	24.39	10.50	10.10	54.77	-30.38 Average
2	0.174	9.81	30.41	10.50	10.10	64.77	-34.36 QP
3	0.200	3.12	23.61	10.40	10.09	53.62	-30.01 Average
4	0.200	10.64	31.13	10.40	10.09	63.62	-32.49 QP
5	0.497	8.09	28.93	10.70	10.14	46.05	-17.12 Average
6	0.497	14.63	35.47	10.70	10.14	56.05	-20.58 QP
7	0.614	15.80	36.62	10.70	10.12	46.00	-9.38 Average
8	0.614	18.99	39.81	10.70	10.12	56.00	-16.19 QP
9	4.224	2.49	23.12	10.43	10.20	46.00	-22.88 Average
10	4.224	9.70	30.33	10.43	10.20	56.00	-25.67 QP
11	7.646	0.91	21.82	10.72	10.19	50.00	-28.18 Average
12	7.646	9.29	30.20	10.72	10.19	60.00	-29.80 QP

Spurious Emissions


Environmental Conditions

Temperature (°C)	24-27	Relative Humidity (%)	50-54
ATM Pressure (kPa):	101.0-101.2	Test engineer:	Anson Su & Alex Yan & Zenos Qiao
Test date:	2024.12.14-2025.3.14		
EUT operation mode:	Below 1GHz: Transmitting(Maximum output power mode, 802.11g, low channel) Above 1GHz: Transmitting		
Note:	1. For the radiated spurious emission below 30MHz, only the worst case (parallel) was recorded. 2. For the radiated spurious emission below 30MHz, When the test result of peak was less than the limit of QP/Average more than 6dB, just peak value were recorded. 3.After pre-scan in the X, Y and Z axes of orientation, the worst case z-axis of orientation were recorded.		

Below 1GHz:

For Model: T-Display-S3-AMOLED 1.43


9kHz-150kHz



Site : Chamber A  
Condition : 3m  
Project Number : 2401Z59114E-RF  
Test Mode : 2.4G WIFI Transmitting  
Detector QP RBW: 0.3KHz VBW:1KHz  
Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB/m	dBUV	dBUV/m	dBUV/m	dB	
1	0.01	32.00	27.32	59.32	126.33	-67.01	Peak
2	0.02	30.57	26.76	57.33	121.99	-64.66	Peak
3	0.03	28.60	21.69	50.29	118.22	-67.93	Peak
4	0.06	25.68	25.71	51.39	112.45	-61.06	Peak
5	0.07	24.66	25.32	49.98	111.03	-61.05	Peak
6	0.13	20.04	22.43	42.47	105.12	-62.65	Peak


## 150kHz-30MHz



Site : Chamber A  
Condition : 3m  
Project Number : 2401Z59114E-RF  
Test Mode : 2.4G WIFI Transmitting  
Detector QP RBW: 10KHz VBW:30KHz  
Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.63	4.75	42.55	47.30	71.52	-24.22	Peak
2	0.76	3.21	39.21	42.42	69.92	-27.50	Peak
3	0.95	1.59	43.00	44.59	67.95	-23.36	Peak
4	1.26	0.46	43.60	44.06	65.40	-21.34	Peak
5	1.58	-0.42	40.04	39.62	63.42	-23.80	Peak
6	1.89	-1.30	39.02	37.72	69.54	-31.82	Peak


30MHz-1GHz\_Horizontal



Site : Chamber A  
Condition : 3m Horizontal  
Project Number : 2401Z59114E-RF  
Test Mode : 2.4G WIFI Transmitting  
Detector QP RBW: 120KHz  
Tester : Anson Su

Freq Factor		Read Level	Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	Limit	
1	69.21 -17.87	50.60	32.73	40.00	-7.27 QP
2	71.99 -17.85	51.59	33.74	40.00	-6.26 QP
3	159.09 -12.73	50.00	37.27	43.50	-6.23 QP
4	165.63 -12.91	49.80	36.89	43.50	-6.61 QP
5	170.19 -13.12	50.33	37.21	43.50	-6.29 QP
6	197.72 -13.32	49.90	36.58	43.50	-6.92 QP
7	209.68 -13.99	54.30	40.31	43.50	-3.19 QP
8	218.98 -14.20	54.20	40.00	46.00	-6.00 QP

30MHz-1GHz\_Vertical




Site : Chamber A  
Condition : 3m Vertical  
Project Number : 2401Z59114E-RF  
Test Mode : 2.4G WIFI Transmitting  
Detector QP RBW: 120KHz  
Tester : Anson Su

	Freq		Read		Limit	Over	Remark
	Factor		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	40.42	-12.66	38.10	25.44	40.00	-14.56	QP
2	69.24	-17.87	49.50	31.63	40.00	-8.37	QP
3	72.02	-17.85	49.72	31.87	40.00	-8.13	QP
4	197.81	-13.31	43.31	30.00	43.50	-13.50	QP
5	218.98	-14.20	44.46	30.26	46.00	-15.74	QP
6	391.41	-8.81	41.83	33.02	46.00	-12.98	QP

**For Model: T-Display-S3-AMOLED 1.75**

9kHz-150kHz




Site : Chamber A  
Condition : 3m  
Project Number : 2401Z59114E-RF  
Test Mode : 2.4G WIFI Transmitting  
Detector: Peak RBW/VBW: 0.3/10kHz  
Tester : Alex Yan

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.01	31.84	24.34	56.18	125.71	-69.53	Peak
2	0.02	30.80	23.27	54.07	122.55	-68.48	Peak
3	0.06	25.61	25.09	50.70	112.36	-61.66	Peak
4	0.10	22.27	19.19	41.46	107.94	-66.48	Peak
5	0.11	21.39	18.60	39.99	106.75	-66.76	Peak
6	0.14	19.74	19.01	38.75	104.78	-66.03	Peak




150kHz-30MHz



Site : Chamber A  
Condition : 3m  
Project Number : 2401Z59114E-RF  
Test Mode : 2.4G WIFI Transmitting  
Detector: Peak RBW/VBW: 10/30kHz  
Tester : Alex Yan

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.61	5.06	41.83	46.89	71.88	-24.99	Peak
2	0.67	4.26	42.23	46.49	70.98	-24.49	Peak
3	0.87	2.15	41.08	43.23	68.67	-25.44	Peak
4	1.35	0.23	40.40	40.63	64.84	-24.21	Peak
5	1.47	-0.13	39.90	39.77	64.03	-24.26	Peak
6	1.65	-0.63	38.16	37.53	63.01	-25.48	Peak


## 30MHz-1GHz\_Horizontal



Site : Chamber A  
Condition : 3m Horizontal  
Project Number : 2401Z59114E-RF  
Test Mode : 2.4G WIFI Transmitting  
Detector: Peak RBW/VBW: 100/300kHz  
Tester : Alex Yan

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	111.49	-12.82	50.56	37.74	43.50	-5.76	QP
2	116.85	-11.82	50.70	38.88	43.50	-4.62	QP
3	122.03	-11.24	46.27	35.03	43.50	-8.47	QP
4	290.14	-11.22	49.56	38.34	46.00	-7.66	QP
5	387.14	-8.96	47.66	38.70	46.00	-7.30	QP
6	405.20	-8.24	44.86	36.62	46.00	-9.38	QP

## 30MHz-1GHz\_Vertical




Site : Chamber A  
Condition : 3m Vertical  
Project Number : 2401Z59114E-RF  
Test Mode : 2.4G WIFI Transmitting  
Detector: Peak RBW/VBW: 100/300kHz  
Tester : Alex Yan

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	111.49	-12.82	49.31	36.49	43.50	-7.01	QP
2	116.13	-11.97	48.12	36.15	43.50	-7.35	QP
3	122.14	-11.23	45.34	34.11	43.50	-9.39	QP
4	166.29	-12.94	46.67	33.73	43.50	-9.77	Peak
5	500.74	-5.76	38.27	32.51	46.00	-13.49	QP
6	796.88	-2.21	32.48	30.27	46.00	-15.73	QP

For Model: T-Display-S3-AMOLED 1.75 hemispherical


9kHz-150kHz



Site : Chamber A  
Condition : 3m  
Project Number : 2401Z59114E-RF  
Test Mode : 2.4G WIFI Transmitting  
Detector: Peak RBW/VBW: 0.3/10kHz  
Tester : Alex Yan

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.05	26.66	25.55	52.21	114.07	-61.86	Peak
2	0.06	25.61	25.33	50.94	112.35	-61.41	Peak
3	0.09	22.93	31.99	54.92	108.84	-53.92	Peak
4	0.10	21.98	32.68	54.66	107.57	-52.91	Peak
5	0.13	20.46	20.66	41.12	105.59	-64.47	Peak
6	0.14	19.85	20.47	40.32	104.91	-64.59	Peak


## 150kHz-30MHz



Site : Chamber A  
Condition : 3m  
Project Number : 2401Z59114E-RF  
Test Mode : 2.4G WIFI Transmitting  
Detector: Peak RBW/VBW: 10/30kHz  
Tester : Alex Yan

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.60	5.15	46.94	52.09	71.98	-19.89	Peak
2	0.71	3.87	38.72	42.59	70.57	-27.98	Peak
3	0.92	1.82	41.67	43.49	68.24	-24.75	Peak
4	1.21	0.61	43.40	44.01	65.78	-21.77	Peak
5	1.53	-0.28	39.08	38.80	63.72	-24.92	Peak
6	1.81	-1.07	42.92	41.85	69.54	-27.69	Peak


## 30MHz-1GHz\_Horizontal



Site : Chamber A  
Condition : 3m Horizontal  
Project Number : 2401Z59114E-RF  
Test Mode : 2.4G WIFI Transmitting  
Detector: Peak RBW/VBW: 100/300kHz  
Tester : Alex Yan

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	58.15	-18.22	42.06	23.84	40.00	-16.16	Peak
2	86.43	-18.08	44.40	26.32	40.00	-13.68	Peak
3	232.84	-13.68	53.23	39.55	46.00	-6.45	Peak
4	298.79	-11.20	46.06	34.86	46.00	-11.14	Peak
5	392.27	-8.78	42.17	33.39	46.00	-12.61	Peak
6	796.88	-2.21	34.56	32.35	46.00	-13.65	Peak

## 30MHz-1GHz\_Vertical



Site : Chamber A  
Condition : 3m Vertical  
Project Number : 2401Z59114E-RF  
Test Mode : 2.4G WIFI Transmitting  
Detector: Peak RBW/VBW: 100/300kHz  
Tester : Alex Yan

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	37.99	-10.98	42.71	31.73	40.00	-8.27	QP
2	47.97	-17.33	49.30	31.97	40.00	-8.03	QP
3	57.14	-18.31	51.51	33.20	40.00	-6.80	QP
4	58.08	-18.22	51.10	32.88	40.00	-7.12	QP
5	60.17	-18.12	50.70	32.58	40.00	-7.42	QP
6	61.43	-18.11	50.39	32.28	40.00	-7.72	QP
7	64.66	-18.00	50.63	32.63	40.00	-7.37	QP

**Above 1GHz:**

Frequency (MHz)	Reading (dBμV)	Detector (PK/Ave)	Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
<b>802.11b</b>							
Low Channel							
4824	62.29	PK	H	-7.75	54.54	74	-19.46
4824	58.75	AV	H	-7.75	51	54	-3
4824	60.93	PK	V	-7.75	53.18	74	-20.82
4824	57.88	AV	V	-7.75	50.13	54	-3.87
Middle Channel							
4884	60.35	PK	H	-7.57	52.78	74	-21.22
4884	58.1	AV	H	-7.57	50.53	54	-3.47
4884	59.02	PK	V	-7.57	51.45	74	-22.55
4884	57.28	AV	V	-7.57	49.71	54	-4.29
High Channel							
4944	58.54	PK	H	-7.61	50.93	74	-23.07
4944	56.71	AV	H	-7.61	49.1	54	-4.9
4944	57.25	PK	V	-7.61	49.64	74	-24.36
4944	55.86	AV	V	-7.61	48.25	54	-5.75
<b>802.11g</b>							
Low Channel							
4824	71.19	PK	H	-7.75	63.44	74	-10.56
4824	58.71	AV	H	-7.75	50.96	54	-3.04
4824	69.86	PK	V	-7.75	62.11	74	-11.89
4824	57.94	AV	V	-7.75	50.19	54	-3.81
Middle Channel							
4884	70.41	PK	H	-7.57	62.84	74	-11.16
4884	58.25	AV	H	-7.57	50.68	54	-3.32
4884	69.07	PK	V	-7.57	61.5	74	-12.5
4884	57.38	AV	V	-7.57	49.81	54	-4.19
High Channel							
4944	69.02	PK	H	-7.61	61.41	74	-12.59
4944	57.4	AV	H	-7.61	49.79	54	-4.21
4944	67.66	PK	V	-7.61	60.05	74	-13.95
4944	56.57	AV	V	-7.61	48.96	54	-5.04



Frequency (MHz)	Reading (dBμV)	Detector (PK/Ave)	Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
<b>802.11n20</b>							
Low Channel							
4824	70.52	PK	H	-7.75	62.77	74	-11.23
4824	58.37	AV	H	-7.75	50.62	54	-3.38
4824	69.18	PK	V	-7.75	61.43	74	-12.57
4824	57.56	AV	V	-7.75	49.81	54	-4.19
Middle Channel							
4884	69.49	PK	H	-7.57	61.92	74	-12.08
4884	57.84	AV	H	-7.57	50.27	54	-3.73
4884	68.05	PK	V	-7.57	60.48	74	-13.52
4884	57.01	AV	V	-7.57	49.44	54	-4.56
High Channel							
4944	68.17	PK	H	-7.61	60.56	74	-13.44
4944	56.76	AV	H	-7.61	49.15	54	-4.85
4944	66.88	PK	V	-7.61	59.27	74	-14.73
4944	55.93	AV	V	-7.61	48.32	54	-5.68
<b>802.11n40</b>							
Low Channel							
4844	68.8	PK	H	-7.72	61.08	74	-12.92
4844	56.18	AV	H	-7.72	48.46	54	-5.54
4844	67.49	PK	V	-7.72	59.77	74	-14.23
4844	55.36	AV	V	-7.72	47.64	54	-6.36
Middle Channel							
4884	67.97	PK	H	-7.57	60.4	74	-13.6
4884	55.76	AV	H	-7.57	48.19	54	-5.81
4884	66.64	PK	V	-7.57	59.07	74	-14.93
4884	55.03	AV	V	-7.57	47.46	54	-6.54
High Channel							
4924	67.32	PK	H	-7.57	59.75	74	-14.25
4924	55.05	AV	H	-7.57	47.48	54	-6.52
4924	66.13	PK	V	-7.57	58.56	74	-15.44
4924	54.27	AV	V	-7.57	46.7	54	-7.3

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor


Corrected Amplitude/Level = Corrected Factor + Reading

Margin = Corrected Amplitude/Level - Limit

The other spurious emission which is in the noise floor level was not recorded.

Test plots


Left Band edge\_Horizontal\_Peak\_802.11b



Condition : Horizontal  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 2.4GWiFi-b-2412

Freq Factor		Read	Limit	Over	Remark	
MHz	dB/m	Level	Level	Line		
		dBuV	dBuV/m	dBuV/m	dB	
1	2373.352	-10.95	62.63	51.68	74.00	-22.32 Peak
2	2390.000	-10.98	61.50	50.52	74.00	-23.48 Peak


Left Band edge\_Vertical\_Peak\_802.11b



Condition : Vertical  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 2.4GWiFi-b-2412

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2388.354	-10.98	63.26	52.28	74.00	-21.72	Peak
2	2390.000	-10.98	60.38	49.40	74.00	-24.60	Peak


Right Band edge\_Horizontal\_Peak\_802.11b



Condition : Horizontal  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 2.4GWiFi-b-2472

	Freq Factor		Read Level		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	61.29	50.32	74.00	-23.68	Peak
2	2490.849	-10.98	63.28	52.30	74.00	-21.70	Peak


Right Band edge\_Vertical\_Peak\_802.11b



Condition : Vertical  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 2.4GWiFi-b-2472

	Freq Factor		Read Level		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	60.94	49.97	74.00	-24.03	Peak
2	2498.825	-11.00	63.43	52.43	74.00	-21.57	Peak


Left Band edge\_Horizontal\_Peak\_802.11g



Condition : Horizontal  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 2.4GWiFi-g-2412

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2382.056	-10.97	63.94	52.97	74.00	-21.03	Peak
2	2390.000	-10.98	61.70	50.72	74.00	-23.28	Peak


Left Band edge\_Vertical\_Peak\_802.11g



Condition : Vertical  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 2.4GWiFi-g-2412

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2381.306	-10.96	63.65	52.69	74.00	-21.31 Peak
2	2390.000	-10.98	61.44	50.46	74.00	-23.54 Peak

Right Band edge\_Horizontal\_Peak\_802.11g




Condition : Horizontal  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 2.4GWiFi-g-2472

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	63.37	52.40	74.00	-21.60	Peak
2	2483.849	-10.97	65.81	54.84	74.00	-19.16	Peak




Right Band edge\_Horizontal\_Average\_802.11g



Condition : Horizontal  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:2kHz Detector:Peak  
Note : 2.4GWiFi-g-2472

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	51.41	40.44	54.00	-13.56	Average
2	2484.631	-10.97	51.86	40.89	54.00	-13.11	Average


Right Band edge\_Vertical\_Peak\_802.11g



Condition : Vertical  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 2.4GWiFi-g-2472

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	62.31	51.34	74.00	-22.66 Peak
2	2486.684	-10.97	65.23	54.26	74.00	-19.74 Peak


Right Band edge\_Vertical\_Average\_802.11g



Condition : Vertical  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:2kHz Detector:Peak  
Note : 2.4GWiFi-g-2472

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	50.96	39.99	54.00	-14.01	Average
2	2483.759	-10.97	51.32	40.35	54.00	-13.65	Average


Left Band edge\_Horizontal\_Peak\_802.11n20



Condition : Horizontal  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 2.4GWiFi-n20-2412

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2370.679	-10.94	63.64	52.70	74.00	-21.30	Peak
2	2390.000	-10.98	61.54	50.56	74.00	-23.44	Peak


Left Band edge\_Vertical\_Peak\_802.11n20



Condition : Vertical  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 2.4GWiFi-n20-2412

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2351.927	-10.88	62.68	51.80	74.00	-22.20 Peak
2	2390.000	-10.98	60.31	49.33	74.00	-24.67 Peak


Right Band edge\_Horizontal\_802.11n20



Condition : Horizontal  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 2.4GWiFi-n20-2472

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	61.62	50.65	74.00	-23.35	Peak
2	2483.562	-10.97	64.29	53.32	74.00	-20.68	Peak


Right Band edge\_Vertical\_802.11n20



Condition : Vertical  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 2.4GWiFi-n20-2472

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	61.80	50.83	74.00	-23.17	Peak
2	2483.595	-10.97	63.66	52.69	74.00	-21.31	Peak

Left Band edge\_Horizontal\_802.11n40




Condition : Horizontal  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 2.4GWiFi-n40-2422

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2385.066	-10.97	63.98	53.01	74.00	-20.99 Peak
2	2390.000	-10.98	61.79	50.81	74.00	-23.19 Peak




Left Band edge\_Vertical\_802.11n40



Condition : Vertical  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 2.4GWiFi-n40-2422

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2382.271	-10.97	63.67	52.70	74.00	-21.30	Peak
2	2390.000	-10.98	61.11	50.13	74.00	-23.87	Peak


Right Band edge\_Horizontal\_Peak\_802.11n40



Condition : Horizontal  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 2.4GWiFi-n40-2462

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	63.51	52.54	74.00	-21.46	Peak
2	2483.537	-10.97	65.72	54.75	74.00	-19.25	Peak


## Right Band edge\_Horizontal\_Average\_802.11n40



Condition : Horizontal  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:2kHz Detector:Peak  
Note : 2.4GWiFi-n40-2462

	Freq Factor		Read Level		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	51.05	40.08	54.00	-13.92	Average
2	2483.935	-10.97	51.13	40.16	54.00	-13.84	Average


Right Band edge\_Vertical\_Peak\_802.11n40



Condition : Vertical  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 2.4GWiFi-n40-2462

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	62.87	51.90	74.00	-22.10	Peak
2	2483.561	-10.97	65.28	54.31	74.00	-19.69	Peak


Right Band edge\_Vertical\_Average\_802.11n40



Condition : Vertical  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:2kHz Detector:Peak  
Note : 2.4GWiFi-n40-2462

	Freq Factor		Read Level		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	50.40	39.43	54.00	-14.57	Average
2	2483.716	-10.97	51.00	40.03	54.00	-13.97	Average


1-18G (Listed with the worst harmonic margin test plot)  
1-4GHz\_Horizontal\_802.11b



Condition : Horizontal  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
: Average reading:RBW:1MHz VBW:2kHz Detector:Peak  
Note : 2.4GWiFi-b-2412

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	3810.976	-9.84	43.67	33.83	54.00	-20.17 Average
2	3810.976	-9.84	57.13	47.29	74.00	-26.71 Peak


1-4GHz\_Vertical\_802.11b



Condition : Vertical  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
: Average reading:RBW:1MHz VBW:2kHz Detector:Peak  
Note : 2.4GWiFi-b-2412

Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	3645.956	-9.81	43.44	33.63	54.00	-20.37	Average
2	3645.956	-9.81	57.31	47.50	74.00	-26.50	Peak

4-18GHz\_Horizontal\_Peak\_802.11b




Condition : Horizontal  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 2.4GWiFi-b-2412

Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4824.000	-7.75	62.29	54.54	74.00	-19.46	Peak
2	17972.000	13.06	48.82	61.88	74.00	-12.12	Peak




4-18GHz\_Horizontal\_Average\_802.11b



Condition : Horizontal  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:2kHz Detector:Peak  
Note : 2.4GWiFi-b-2412

		Read		Limit	Over	Remark
Freq Factor		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 4824.000	-7.75	58.75	51.00	54.00	-3.00	Average
2 17991.250	13.16	34.21	47.37	54.00	-6.63	Average


4-18GHz\_Vertical\_Peak\_802.11b



Condition : Vertical  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 2.4GWiFi-b-2412

Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4824.000	-7.75	60.93	53.18	74.00	-20.82	Peak
2	17961.500	13.01	49.05	62.06	74.00	-11.94	Peak


4-18GHz\_Vertical\_Average\_802.11b



Condition : Vertical  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:2kHz Detector:Peak  
Note : 2.4GWiFi-b-2412

Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4824.000	-7.75	57.88	50.13	54.00	-3.87	Average
2	17998.250	13.19	34.05	47.24	54.00	-6.76	Average


## 1-4GHz\_Horizontal\_802.11g



Condition : Horizontal  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
: Average reading:RBW:1MHz VBW:2kHz Detector:Peak  
Note : 2.4GWiFi-g-2412

	Freq	Factor	Read		Limit	Over	Remark
			Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	3956.870	-9.31	43.56	34.25	54.00	-19.75	Average
2	3956.870	-9.31	56.80	47.49	74.00	-26.51	Peak


1-4GHz\_Vertical\_802.11g



Condition : Vertical  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
: Average reading:RBW:1MHz VBW:2kHz Detector:Peak  
Note : 2.4GWiFi-g-2412

Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	3954.994	-9.32	43.39	34.07	54.00	-19.93	Average
2	3954.994	-9.32	57.14	47.82	74.00	-26.18	Peak


4-18GHz\_Horizontal\_Peak\_802.11g



Condition : Horizontal  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 2.4GWiFi-g-2412

Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4824.000	-7.75	71.19	63.44	74.00	-10.56	Peak
2	17954.490	12.97	48.66	61.63	74.00	-12.37	Peak


4-18GHz\_Horizontal\_Average\_802.11g



Condition : Horizontal  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:2kHz Detector:Peak  
Note : 2.4GWiFi-g-2412

		Read		Limit	Over	Remark
Freq Factor		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 4824.000	-7.75	58.71	50.96	54.00	-3.04	Average
2 17996.500	13.19	34.36	47.55	54.00	-6.45	Average

4-18GHz\_Vertical\_Peak\_802.11g




Condition : Vertical  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 2.4GWiFi-g-2412

		Read		Limit	Over	Remark
Freq Factor		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 4824.000	-7.75	69.86	62.11	74.00	-11.89	Peak
2 17998.250	13.19	48.52	61.71	74.00	-12.29	Peak




4-18GHz\_Vertical\_Average\_802.11g



Condition : Vertical  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:2kHz Detector:Peak  
Note : 2.4GWiFi-g-2412

Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4824.000	-7.75	57.94	50.19	54.00	-3.81	Average
2	17998.630	13.20	34.11	47.31	54.00	-6.69	Average


1-4GHz\_Horizontal\_802.11n-HT20



Condition : Horizontal  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
: Average reading:RBW:1MHz VBW:2kHz Detector:Peak  
Note : 2.4GWiFi-n20-2412

Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	3917.115	-9.67	43.85	34.18	54.00	-19.82	Average
2	3917.115	-9.67	57.27	47.60	74.00	-26.40	Peak


1-4GHz\_Vertical\_802.11n-HT20



Condition : Vertical  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
: Average reading:RBW:1MHz VBW:2kHz Detector:Peak  
Note : 2.4GWiFi-n20-2412

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	3952.744	-9.33	43.42	34.09	54.00	-19.91 Average
2	3952.744	-9.33	56.89	47.56	74.00	-26.44 Peak


4-18GHz\_Horizontal\_Peak\_802.11n-HT20



Condition : Horizontal  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 2.4GWiFi-n20-2412

Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4824.000	-7.75	70.52	62.77	74.00	-11.23	Peak
2	17989.500	13.16	48.63	61.79	74.00	-12.21	Peak


4-18GHz\_Horizontal\_Average\_802.11n-HT20



Condition : Horizontal  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:2kHz Detector:Peak  
Note : 2.4GWiFi-n20-2412

Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4824.000	-7.75	58.37	50.62	54.00	-3.38	Average
2	17996.500	13.19	34.27	47.46	54.00	-6.54	Average


4-18GHz\_Vertical\_Peak\_802.11n-HT20



Condition : Vertical  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 2.4GWiFi-n20-2412

Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4824.000	-7.75	69.18	61.43	74.00	-12.57	Peak
2	17968.500	13.05	47.73	60.78	74.00	-13.22	Peak


4-18GHz\_Vertical\_Average\_802.11n-HT20



Condition : Vertical  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:2kHz Detector:Peak  
Note : 2.4GWiFi-n20-2412

		Read		Limit	Over	Remark
Freq Factor		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 4824.000	-7.75	57.56	49.81	54.00	-4.19	Average
2 17993.000	13.17	34.13	47.30	54.00	-6.70	Average

1-4GHz\_Horizontal\_802.11n-HT40




Condition : Horizontal  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
: Average reading:RBW:1MHz VBW:2kHz Detector:Peak  
Note : 2.4GWiFi-n40-2422

Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	3951.244	-9.32	43.24	33.92	54.00	-20.08	Average
2	3951.244	-9.32	56.52	47.20	74.00	-26.80	Peak




1-4GHz\_Vertical\_802.11n-HT40



Condition : Vertical  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
: Average reading:RBW:1MHz VBW:2kHz Detector:Peak  
Note : 2.4GWiFi-n40-2422

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	3882.235	-9.88	43.72	33.84	54.00	-20.16 Average
2	3882.235	-9.88	57.03	47.15	74.00	-26.85 Peak


4-18GHz\_Horizontal\_Peak\_802.11n-HT40



Condition : Horizontal  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 2.4GWiFi-n40-2422

Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4844.000	-7.72	68.80	61.08	74.00	-12.92	Peak
2	17984.250	13.12	48.51	61.63	74.00	-12.37	Peak


4-18GHz\_Horizontal\_Average\_802.11n-HT40



Condition : Horizontal  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:2kHz Detector:Peak  
Note : 2.4GWiFi-n40-2422

Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4844.000	-7.72	56.18	48.46	54.00	-5.54	Average
2	17995.750	13.20	34.31	47.51	54.00	-6.49	Average


4-18GHz\_Vertical\_Peak\_802.11n-HT40



Condition : Vertical  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 2.4GWiFi-n40-2422

Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4844.000	-7.72	67.49	59.77	74.00	-14.23	Peak
2	17954.490	12.97	48.28	61.25	74.00	-12.75	Peak

4-18GHz\_Vertical\_Average\_802.11n-HT40




Condition : Vertical  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:2kHz Detector:Peak  
Note : 2.4GWiFi-n40-2422

Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4844.000	-7.72	55.36	47.64	54.00	-6.36	Average
2	17996.500	13.19	34.09	47.28	54.00	-6.72	Average

18-25 (Only with worst case margin mode plot)


18-25GHz\_Horizontal



Condition : Horizontal  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
: Average reading:RBW:1MHz VBW:2kHz Detector:Peak  
Note : 2.4GWiFi-b-2412

Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	19382.670	15.11	28.74	43.85	54.00	-10.15	Average
2	19382.670	15.11	37.59	52.70	74.00	-21.30	Peak

18-25GHz\_Vertical



Condition : Vertical  
Project No. : 2401Z59114E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
: Average reading:RBW:1MHz VBW:2kHz Detector:Peak  
Note : 2.4GWiFi-b-2412

Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	19410.680	15.10	28.98	44.08	54.00	-9.92	Average
2	19410.680	15.10	37.82	52.92	74.00	-21.08	Peak

6dB Emission Bandwidth

Test Information:

Sample No.:	2UZI-1	Test Date:	2024/12/04
Test Site:	RF	Test Mode:	Transmitting
Tester:	Cheeb Huang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C):	25.7	Relative Humidity: (%)	45	ATM Pressure: (kPa)	101
-----------------------	------	------------------------------	----	------------------------	-----


Test Data:

Mode	Antenna	Test Frequency (MHz)	Result (MHz)	Limit (MHz)	Verdict
802.11b	Chain 0	2412	9.169	≥0.5	Pass
		2442	9.169	≥0.5	Pass
		2472	9.169	≥0.5	Pass
802.11g	Chain 0	2412	16.376	≥0.5	Pass
		2442	15.976	≥0.5	Pass
		2472	15.816	≥0.5	Pass
802.11n20	Chain 0	2412	15.576	≥0.5	Pass
		2442	15.816	≥0.5	Pass
		2472	15.616	≥0.5	Pass
802.11n40	Chain 0	2422	32.833	≥0.5	Pass
		2442	34.034	≥0.5	Pass
		2462	32.833	≥0.5	Pass




2412~2472

802.11b\_2412MHz 9.169MHz




ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 13:10:21

802.11b\_2442MHz 9.169MHz




ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 13:17:20

802.11b\_2472MHz 9.169MHz




ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 13:20:26

802.11g\_2412MHz 16.376MHz




ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 13:23:42

802.11g\_2442MHz 15.976MHz




ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 13:30:21

802.11g\_2472MHz 15.816MHz




ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 13:34:32

802.11n20\_2412MHz 15.576MHz




ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 13:38:14

802.11n20\_2442MHz 15.816MHz




ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 13:47:17

802.11n20\_2472MHz 15.616MHz




ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 13:53:32

802.11n40\_2422MHz 32.833MHz




ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 13:56:43

802.11n40\_2442MHz 34.034MHz



ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 13:59:28

802.11n40\_2462MHz 32.833MHz



ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 14:03:23

99% Occupied Bandwidth

Test Information:

Sample No.:	2UZI-1	Test Date:	2024/12/04
Test Site:	RF	Test Mode:	Transmitting
Tester:	Cheeb Huang	Test Result:	N/A

Environmental Conditions:


Temperature: (°C):	25.7	Relative Humidity: (%)	45	ATM Pressure: (kPa)	101
-----------------------	------	---------------------------	----	------------------------	-----

Test Data:

Mode	Antenna	Test Frequency (MHz)	99% OBW (MHz)
802.11b	Chain 0	2412	12.840
		2442	12.880
		2472	12.960
802.11g	Chain 0	2412	16.320
		2442	16.360
		2472	16.320
802.11n20	Chain 0	2412	17.160
		2442	17.160
		2472	17.160
802.11n40	Chain 0	2422	35.360
		2442	35.360
		2462	35.360


2412~2472

802.11b\_2412MHz 12.840MHz




ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 13:10:44

802.11b\_2442MHz 12.880MHz




ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 13:17:42

802.11b\_2472MHz 12.960MHz




ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 13:20:49

802.11g\_2412MHz 16.320MHz




ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 13:21:06

802.11g\_2442MHz 16.360MHz




ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 13:30:45

802.11g\_2472MHz 16.320MHz




ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 13:35:06

802.11n20\_2412MHz 17.160MHz




ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 13:38:45

802.11n20\_2442MHz 17.160MHz




ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 13:47:59

802.11n20\_2472MHz 17.160MHz




ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 13:53:56

802.11n40\_2422MHz 35.360MHz




ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 13:56:55

802.11n40\_2442MHz 35.360MHz



ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 13:59:41

802.11n40\_2462MHz 35.360MHz



ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 14:03:35

Maximum Conducted Output Power

Test Information:

Sample No.:	2UZI-1	Test Date:	2024/12/04
Test Site:	RF	Test Mode:	Transmitting
Tester:	Cheeb Huang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C):	25.7	Relative Humidity: (%)	45	ATM Pressure: (kPa)	101
-----------------------	------	---------------------------	----	------------------------	-----

Test Data:

Mode	Antenna	Test Frequency (MHz)	Peak Output Power(dBm)	Average Output Power(dBm)	Limit (dBm)	Verdict
802.11b	Chain 0	2412	17.26	13.96	30	Pass
		2442	16.04	12.17	30	Pass
		2472	14.94	12.25	30	Pass
802.11g	Chain 0	2412	20.00	12.75	30	Pass
		2442	18.99	12.84	30	Pass
		2472	17.83	10.93	30	Pass
802.11n20	Chain 0	2412	18.62	11.70	30	Pass
		2442	17.81	10.91	30	Pass
		2472	16.44	10.19	30	Pass
802.11n40	Chain 0	2422	18.28	12.04	30	Pass
		2442	17.27	10.98	30	Pass
		2462	16.81	10.46	30	Pass

Power Spectral Density

Test Information:

Sample No.:	2UZI-1	Test Date:	2024/12/04
Test Site:	RF	Test Mode:	Transmitting
Tester:	Cheeb Huang	Test Result:	Pass

Environmental Conditions:


Temperature: (°C):	25.7	Relative Humidity: (%)	45	ATM Pressure: (kPa)	101
-----------------------	------	------------------------------	----	------------------------	-----

Test Data:

Mode	Antenna	Test Frequency (MHz)	Result (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
802.11b	Chain 0	2412	-10.09	8	Pass
		2442	-11.16	8	Pass
		2472	-12.25	8	Pass
802.11g	Chain 0	2412	-12.58	8	Pass
		2442	-13.52	8	Pass
		2472	-13.34	8	Pass
802.11n20	Chain 0	2412	-13.61	8	Pass
		2442	-14.27	8	Pass
		2472	-14.23	8	Pass
802.11n40	Chain 0	2422	-13.77	8	Pass
		2442	-14.69	8	Pass
		2462	-13.86	8	Pass


2412~2472

802.11b\_2412MHz -10.09dBm/3kHz




ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 13:15:11

802.11b\_2442MHz -11.16dBm/3kHz




ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 13:18:50

802.11b\_2472MHz -12.25dBm/3kHz




ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 13:22:19

802.11g\_2412MHz -12.58dBm/3kHz




ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 13:27:40

802.11g\_2442MHz -13.52dBm/3kHz



ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 13:31:48


802.11g\_2472MHz -13.34dBm/3kHz




ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 13:36:41




802.11n20\_2412MHz -13.61dBm/3kHz




802.11n20\_2442MHz -14.27dBm/3kHz




802.11n20\_2472MHz -14.23dBm/3kHz




802.11n40\_2422MHz -13.77dBm/3kHz



802.11n40\_2442MHz -14.69dBm/3kHz



802.11n40\_2462MHz -13.86dBm/3kHz



100 kHz Bandwidth of Frequency Band Edge

Test Information:

Sample No.:	2UZI-1	Test Date:	2024/12/04
Test Site:	RF	Test Mode:	Transmitting
Tester:	Cheeb Huang	Test Result:	Pass


Environmental Conditions:

Temperature: (°C):	25.7	Relative Humidity: (%)	45	ATM Pressure: (kPa)	101
-----------------------	------	------------------------------	----	------------------------	-----


Test Data:

2412~2472


802.11b\_2412MHz




802.11b\_2472MHz




802.11g\_2412MHz




802.11g\_2472MHz




802.11n20\_2412MHz




802.11n20\_2472MHz



802.11n40\_2422MHz



802.11n40\_2462MHz



Duty Cycle

Test Information:

Sample No.:	2UZI-1	Test Date:	2024/12/04~2024/12/21
Test Site:	RF	Test Mode:	Transmitting
Tester:	Cheeb Huang	Test Result:	N/A

Environmental Conditions:

Temperature: (°C):	25.7~26.0	Relative Humidity: (%)	45~50	ATM Pressure: (kPa)	101
-----------------------	-----------	------------------------------	-------	------------------------	-----


Test Data:

Mode	Antenna	Test Frequency (MHz)	Ton (ms)	Ton+Toff (ms)	Duty Cycle (%)	Duty Cycle Factor(dB)	1/Ton (Hz)	VBW Setting (kHz)
802.11b	Chain 0	2442	0.587	1.810	32.43	4.89	1704	2.0
802.11g	Chain 0	2442	0.578	1.795	32.20	4.92	1730	2.0
802.11n20	Chain 0	2442	0.557	1.782	31.26	5.05	1795	2.0
802.11n40	Chain 0	2442	0.578	1.809	31.95	4.96	1730	2.0

Duty Cycle = Ton/(Ton+Toff)\*100%


2412~2472

802.11b\_2442MHz  
0.587ms,1.810ms




ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 21.DEC.2024 14:16:55

802.11g\_2442MHz  
0.578ms,1.795ms




ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 21.DEC.2024 14:23:08

802.11n20\_2442MHz  
0.557ms,1.782ms



ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 12:03:14

802.11n40\_2442MHz  
0.578ms,1.809ms



ProjectNo.:2401Z59114E-RF Tester:Cheeb Huang  
Date: 4.DEC.2024 12:05:37

## RF EXPOSURE EVALUATION

### MAXIMUM PERMISSIBLE EXPOSURE (MPE)

#### Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 Interim General RF Exposure Guidance v01

MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power(ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(3)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$ .
1.34-30	$3,450 R^2/f^2$ .
30-300	$3.83 R^2$ .
300-1,500	$0.0128 R^2 f$ .
1,500-100,000	$19.2 R^2$ .

R is the minimum separation distance in meters

f = frequency in MHz

#### Measurement Result

Mode	Frequency (MHz)	Tune up conducted power <sup>#</sup> (dBm)	Antenna Gain <sup>#</sup>		ERP		Evaluation Distance (m)	ERP Limit (W)
			(dBi)	(dBd)	(dBm)	(W)		
BLE	2402-2480	6.50	4	1.85	8.35	0.007	0.2	0.768
2.4G Wi-Fi	2412-2472	20.5	4	1.85	22.35	0.172	0.2	0.768

Note: The tune up conducted power<sup>#</sup> and antenna gain<sup>#</sup> was declared by the applicant.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

#### Result: Compliant

## **EUT PHOTOGRAPHS**

---

Please refer to the attachment 2401Z59114E-RF External photo and 2401Z59114E-RF Internal photo.



## TEST SETUP PHOTOGRAPHS

---

Please refer to the attachment 2401Z59114E-RF Test Setup photo.

\*\*\*\*\* END OF REPORT \*\*\*\*\*