FCC ID: ZHW-8062738

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]·[$\sqrt{f}(GHZ)$] \leq 3.0 for 1-g SAR and \leq 7.5 for 10-g extremity SAR, where:

- f(GHZ) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BT:

Modulatior	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculatio n	1g SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	2.14	1.637	2±1	3	1.995	<5	0.61847	3.00	YES
	2.441	2.68	1.854	2±1	3	1.995	<5	0.62347	3.00	YES
	2.480	2.48	1.770	2±1	3	1.995	<5	0.62843	3.00	YES
π/4- DQPSK	2.402	1.7	1.479	2±1	3	1.995	<5	0.61847	3.00	YES
	2.441	2.22	1.667	2±1	3	1.995	<5	0.62347	3.00	YES
	2.480	1.96	1.570	2±1	3	1.995	<5	0.62843	3.00	YES
8DPSK	2.402	2.06	1.607	2±1	3	1.995	<5	0.61847	3.00	YES
	2.441	2.71	1.866	2±1	3	1.995	<5	0.62347	3.00	YES
	2.480	2.43	1.750	2±1	3	1.995	<5	0.62843	3.00	YES

Conclusion:

For the max result : 0.62847≤ 3.0 for 1-g SAR, No SAR is required.

Jason chen

Signature:

Date: 2017-02-17

NAME AND TITLE (Please print or type): Jason Chen /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.