



Maximum Permissible Exposure (MPE) & Exposure evaluation

Report identification number: 1-6428/18-01-06 MPE (FCC_ISED)

Certification numbers and labeling requirements	
FCC ID	ROJ-3723A
ISED number	6200B-3723A
HVIN (Hardware Version Identification Number)	TT-3723A
PMN (Product Marketing Name)	EXPLORER 323
FVIN (Firmware Version Identification Number)	-/-
HMN (Host Marketing Name)	-/-

This report is electronically signed and valid without handwriting signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Document authorised:



Thomas Vogler
Lab Manager
Radio Communications & EMC



Marco Scigliano
Testing Manager
Radio Communications & EMC

EUT technologies:

Technologies:	Max. measured power conducted:	Max. antenna gain:	Max. declared EIRP
WLAN 2450 MHz*	17.0 (802.11b) 16.7 (802.11g)	< 0 dBi	18 dBm
Inmarsat Satellite-Terminal** 1626.5 to 1606.5 MHz 1668.0 to 1675.0 MHz	Side Panels: 34.5 dBm Top Panel: 32.0 dBm	Side Panels: 8.7 dBi Top Panel: 11.2 dBm	43.2 dBm

)* for detailed test results see CTC advanced test report 1-6428/18-01-03

)** for detailed test results see CTC advanced test report 1-6428/18-01-02

NOTE:

Maximum declared values for the Inmarsat Satellite-Terminal are taken from customer document: 99-171635-A MPE Calculation – T3723A, Explorer 323_v1.pdf

Prediction of MPE limit at given distance - FCC

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

where: S = Power density
 P = Power input to the antenna
 G = Antenna gain
 R = Distance to the center of radiation of the antenna
 PG = Output Power including antenna gain

The table below is excerpted from Table 1B of 47 CFR 1.1310 titled "Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure"

Frequency Range (MHz)	Power Density (mW/cm ²)	Averaging Time (minutes)
300 -1500	f/1500	30
1500 - 100000	1.0	30

where f = Frequency (MHz)

Prediction: worst case

Technologies:	SRD	WLAN	
Frequency (MHz)	1675	2450	
PG Declared max power (EIRP)	43.2	18	dBm
R Distance	70	70	cm
S MPE limit for uncontrolled exposure	1	1	mW/cm ²
Calculated Power density:	0.3395	0.0010	mW/cm ²
Calculated percentage of Limit:	33.95%	0.10%	

This prediction demonstrates the following:

The power density levels for FCC at a distance of 70 cm are below the maximum levels allowed by regulations.

Prediction of MPE limit at given distance - ISED

RSS-102, general limitations for E- and H- Field

Reference levels for general public (uncontrolled environment) exposure to time-varying electric and magnetic fields

According to: RSS 102-ISSUE 05		
Frequency Range (MHz)	Power density (W/m ²)	Reference Period (minutes)
0.003-10	--	Instantaneous*
0.1-10	--	6**
1.1-10	--	6**
10-20	2	6
20-48	$8.944 / f^{0.5}$	6
48-300	1.291	6
300-6000	$0.02619 \times f^{0.6834}$	6
6000-15000	10	6
15000-150000	10	$616000 / f^{1.2}$
150000-300000	$6.67 \times 10^{-5} \times f$	$616000 / f^{1.2}$
Note: f is frequency in MHz. * Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).		

NOTE:

The resulting Limit for 1675MHz is 4.18W/m²

The resulting Limit for 2450MHz is 5.42W/m²

Prediction: worst case

		Inmarsat	WLAN	
	Frequency	1675	2450	MHz
R	Distance	70	70	cm
PG	Maximum EIRP	43.2	18	dBm
PG	Maximum EIRP	20893.0	63.1	mW
S	Power density	3.4	0.01025	W/m ²
	Exclusion Limit from above:	4.18	5.42	W/m ²
	Calculated percentage of Limit:	81.17%	0.19%	