

RF Exposure Evaluation Declaration

Product Name : CS-3152C: Wireless HD Day/Night Cloud Camera ;
CS-3152: Wireless HD Day/Night Network Camera
Model No. : CS-3152C, CS-3152
FCC ID. : RRK-CS3152

Applicant : Alpha Networks Inc.

Address : No.8 Li-shing 7th Rd., Science-based Industrial Park,
Hsinchu, Taiwan, R.O.C.

Date of Receipt : 2014/05/02

Date of Declaration : 2014/06/24

Report No. : 1450137R-RF-US-Exp

Report Version : V1.0



The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of Quietek Corporation.

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product	Wireless HD Day/Night Cloud Camera
Test Mode	Transmit
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.3dBi or 1.35 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11b			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412	90.9913	0.0244
6	2437	72.4436	0.0194
11	2462	71.4496	0.0192

IEEE 802.11g			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412	224.9055	0.0604
6	2437	255.2701	0.0685
11	2462	226.4644	0.0608

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

Product	Wireless HD Day/Night Cloud Camera
Test Mode	Transmit
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.3dBi or 1.35 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11n (20MHz) ANT 0			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412	234.9633	0.0631
6	2437	262.4219	0.0704
11	2462	238.7811	0.0641

IEEE 802.11n (40MHz) ANT 0			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
3	2422	248.3133	0.0666
6	2437	260.6154	0.0699
9	2452	244.9063	0.0657

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².